

# Additional License Authorizations

for HP Network Node Manager i Software products



## Product use authorizations

This document provides Additional License Authorizations for the following HP Business Technology Optimization Software products:

- HP Network Node Manager i (NNMi)
- HP Network Node Manager i Advanced (NNMi Advanced)
- HP Network Node Manager i Software Developer Toolkit (NNMi SDK)
- HP Network Node Manager i Integration Enablement License (NNMi IEL)
  
- HP Network Node Manager i Smart Plug-in for IP Telephony (iSPI IP Telephony)
- HP Network Node Manager i Smart Plug-in for MPLS (iSPI MPLS)
- HP Network Node Manager i Smart Plug-in for IP Multicast (iSPI IP Multicast)
- HP Network Node Manager i Smart Plug-in for Network Engineering Toolset (iSPI NET)
- HP Network Node Manager i Smart Plug-in Performance for Metrics (iSPI Perf for Metrics)
- HP Network Node Manager i Smart Plug-in Performance for Traffic (iSPI Perf for Traffic)
- HP Network Node Manager i Smart Plug-in Performance for Quality Assurance (iSPI Perf for QA)
- HP Network Node Manager i Smart Plug-in for Performance (iSPI Performance)
- HP Network Node Manager i Integration Module for NetCool (IM for NetCool)

## Definitions

Capitalized terms not otherwise defined in this Additional License Authorizations document are defined in the governing Agreement.

Term	Definition
<i>Base Template</i>	means an amount of NNM iSPI Points required for specific NNM iSPIs to be operational at a basic level. The specific amount varies depending on the specific NNM iSPI. More NNM iSPI Points are required for these NNM iSPIs to be fully functional to provide services such as data collection and analysis.
<i>Clustered Computer</i>	means a group of servers or other resources that act like a single system and enable high availability and in some cases, load balancing and parallel processing.
<i>E-LTU and E-Media</i>	means products which are electronically delivered only, and as such any references to FOB Destination or delivery methods that are stated on Your purchase order other than electronic shall be null and void with respect to these E-LTU or E-Media products.
<i>Instance</i>	means each implementation of the application installed on a Server.



<b>Term</b>	<b>Definition</b>
<i>LTU</i>	means License To Use.
<i>NNM Cold Standby System</i>	means a Non-Production standby system which has the HP Network Node Manager i Software Product installed, but is either shutdown or is not concurrently running any of the product's processes.
<i>NNM Development and Test System</i>	means a Non-Production system which has the HP Network Node Manager i Software Product installed, and is concurrently running some or all of the product's processes for the purpose of a) developing Licensee add-on applications; b) migration testing; or c) pre-production staging.
<i>NNM Hot Standby System</i>	means a Non-Production standby system which has the HP Network Node i Manager Software Product installed, and is concurrently running some or all of the product's processes.
<i>NNM iSPI Points</i>	means the Base Templates and metrics a Licensee is authorized to use or monitor.
<i>NNM Management Station</i>	means the software component of the HP Network Node Manager i Software Product that constitutes the central entity, where all messages are received, processed, stored and forwarded to the operator GUI.
<i>Nodes</i>	means a collection of network interfaces that the Management Station software can pragmatically associate together.
<i>NNM Node Pack</i>	means a predetermined number of manageable Nodes.
<i>Non-Production or NP</i>	means internal use which is limited to Use on Development and Test Systems and Hot and/or Cold Standby Systems. This NP license requires the previous purchase of the equivalent or greater production licenses. Support for NP licenses is restricted to the period of and current status of the equivalent production license.
<i>NNM Production System</i>	means a system which has a HP Network Node Manager i Software Product installed and is running some or all of the product's processes to be used for collecting data, executing product logic, or sending/receiving messages.
<i>QA Probe</i>	means an agent based probe which generates specific type of network traffic in a continuous, reliable, and predictable manner for measuring end to end network performance like jitter, latency and , packet loss.
<i>Server</i>	means any designated computer system in which an Instance or Instances of the Software is installed.
<i>Suite</i>	means two or more software products combined into a single license offering. The specific software products included in a Suite are specified in the Software Specific License Terms below. Software products included in a Suite are governed by the individual authorizations and use restrictions associated with each Software Product.
<i>Traffic Collector Connection</i>	means the association of an Instance of HP Network Node Manager I Smart Plug-in Performance for traffic with a remote Instance of a flow collector for the purpose of receiving flow data from the flow collector
<i>Unlimited NNM Nodes</i>	means that the NNM Management System software does not programmatically limit to the number of Nodes that can be managed from that Instance of the Management Station software; however, there are practical limits based on overall system resources, system performance, and constraints of the operating system.
<i>Unlimited NNM iSPI Points</i>	means that the NNM Management System software does not programmatically limit to the number of NNM iSPI Points that can be managed from that Instance of the Management Station software; however, there are practical limits based on overall system resources, system performance, and constraints of the operating system.

## Software specific license terms

An HP Network Node Manager i Software Product is licensed for use on a single computer or Clustered Computer. Depending on the implementation and use, an appropriate license is required for:

- NNM Production System: HP Network Node Manager i Software Product LTU is required.  
For clarification only, installing an HP Network Node Manager i Software Product on a Clustered Computer only requires the Production LTU; a separate Non-Production LTU is not required.
- NNM Cold Standby System: HP Network Node Manager i Software Product Non-Production LTU is required.
- NNM Development and Test System: HP Network Node Manager i Software Product Non-Production LTU is required.
- NNM Hot Standby System: HP Network Node Manager i Software Product Non-Production LTU is required.

## HP Network Node Manager i and HP Network Node Manager i Advanced

An HP Network Node Manager i Software Product Node Pack License-To-Use (LTU) consists of two components: Management System and Nodes. The reference to Node Packs reflects the number of Nodes that the Licensee may concurrently monitor from the Management System and comes in various counts, including, but not limited to: 50 and Unlimited Nodes.

## HP Network Node manager i Smart Plug-Ins

An HP Network Node Manager i Smart Plug-ins Software Product NNM iSPI Node Pack License-To-Use (LTU) consists of two components: Management System and Nodes. The reference to Node Packs reflects the number of Nodes that the Licensee may concurrently monitor from the Management System and comes in various counts, including, but not limited to: 50 and Unlimited Nodes.

An HP Network Node Manager i Smart Plug-ins Software Product NNM iSPI Point Pack License-To-Use (LTU) consists of NNM iSPI Points. The reference to Point Packs reflects the number of NNM iSPI Points the Licensee may use to concurrently enable NNM iSPI Base Templates and monitor metrics from the Management System and comes in various counts, including, but not limited to: 100 and Unlimited NNM iSPI Points.

NNM iSPI Nodes and NNM iSPI Points may be used to enable monitoring of the following network technologies, as per below:

Smart Plug-In	Covers
<i>NNM iSPI Telephony</i>	
Each NNM iSPI Telephony Base Template	1,000 NNM iSPI Points
Each IP Phone Node	1 NNM iSPI Point
Each IP Gateway Node	3 NNM iSPI Points
Each IP PBX/System Node	7 NNM iSPI Points
<i>NNM iSPI MPLS</i>	
Each NNM iSPI MPLS Base Template	5,000 NNM iSPI Points
Each Label Switch Router (LSR) Node	4 NNM iSPI Points
Each OSI Layer-3 VRF Interface	4 NNM iSPI Points
Each OSI Layer-2 Forwarding Interfaces	5 NNM iSPI Points
<i>NNM iSPI IP Multicast</i>	
Each NNM iSPI IP Multicast Base Template	1,500 NNM iSPI Points
Each IP Multicast Node	5 NNM iSPI Points
Each IP Multicast Source Group, N(S,G)	4 NNM iSPI Points
<i>NNM iSPI NET</i>	
Each Node	1 NNM iSPI Node
<i>NNM iSPI Performance for Metrics</i>	
Each Node	1 NNM iSPI Node
<i>NNM iSPI Performance for QA</i>	
Each QA Probe	1 NNM iSPI Point
<i>NNM iSPI Performance for Traffic</i>	
Each sFlow Interface	1 NNM iSPI Point
Each NetFlow Interface	5 NNM iSPI Points
<i>NNM iSPI for Performance</i>	
Each Node	1 NNM iSPI Node

## HP Network Node Manager i Suite offerings

Suite	Offering includes
<i>HP Network Node Manager i + HP Network Node Manager i Smart Plug-In Performance for Metrics</i>	<ul style="list-style-type: none"><li>▪ 1 HP Network Node Manager i 50 Node pack</li><li>▪ 1 HP Network Node Manager i Smart Plug-In Performance for Metrics 50 Node Pack</li></ul>
<i>HP Network Node Manager i + HP Network Node Manager i Smart Plug-In Performance for Metrics + HP Network Node Manager i Smart Plug-In Network Engineering Toolset</i>	<ul style="list-style-type: none"><li>▪ 1 HP Network Node Manager i 50 Node pack</li><li>▪ 1 HP Network Node Manager i Smart Plug-In Performance for Metrics 50 Node Pack</li><li>▪ 1 HP Network Node Manager i Smart Plug-In Network Engineering Toolset 50 Node pack</li></ul>

## Technology for better business outcomes

© 2009-2010 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services or in your mutually executed license and/or consulting services agreement(s) with HP. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

5014-0335, (March 2010, rev. B April 2010), replaces 5014-0294 (September 2009)

