

# HP Data Protector A.06.11

## Integration guide for VMware Virtual Infrastructure, Sybase, Network Node Manager, and Network Data Management Protocol Server



B 6 9 6 0 - 9 0 1 6 0

Part number: B6960-90160  
First edition: September 2009



## **Legal and notice information**

© Copyright 2004, 2009 Hewlett-Packard Development Company, L.P.

Confidential computer software. Valid license from HP required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel®, Itanium®, Pentium®, Intel Inside®, and the Intel Inside logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Microsoft®, Windows®, Windows XP®, and Windows NT® are U.S. registered trademarks of Microsoft Corporation.

Adobe and Acrobat are trademarks of Adobe Systems Incorporated.

Java is a US trademark of Sun Microsystems, Inc.

Oracle® is a registered US trademark of Oracle Corporation, Redwood City, California.

UNIX® is a registered trademark of The Open Group.

Printed in the US

---

# Contents

Publication history .....	15
About this guide .....	17
Intended audience .....	17
Documentation set .....	17
Guides .....	17
Online Help .....	20
Documentation map .....	21
Abbreviations .....	21
Map .....	22
Integrations .....	23
Document conventions and symbols .....	25
Data Protector graphical user interface .....	26
General information .....	27
HP technical support .....	27
Subscription service .....	28
HP websites .....	28
Documentation feedback .....	28
1 Integrating VMware Virtual Infrastructure and Data Protector .....	29
Introduction .....	29
Integration concepts .....	30
Supported environments .....	30
VirtualCenter environment .....	31
Standalone ESX Server environment .....	35
Data Protector components .....	36
Data Protector Cell Manager .....	36
Data Protector VMware Integration component .....	36
Data Protector Media Agents .....	36
Configuring the integration .....	37
Prerequisites .....	37
Before you begin .....	37

Configuring VMware users .....	38
Configuring clusters .....	38
ESX Server systems in a cluster .....	38
Configuring backup proxy systems .....	39
Configuring VMware management clients .....	39
Using the Data Protector GUI .....	40
Using the Data Protector CLI .....	42
Configuring virtual machines .....	43
Using the Data Protector GUI .....	43
Using the Data Protector CLI .....	46
Checking the configuration of VMware clients .....	47
Using the Data Protector GUI .....	47
Using the Data Protector CLI .....	47
Backup .....	48
What is backed up? .....	48
Virtual machines .....	49
Filesystems .....	49
Backup methods .....	49
Snapshot method .....	50
Suspend method .....	60
VCBimage method .....	61
VCBfile method .....	63
Backup types .....	65
Considerations .....	66
Creating backup specifications .....	68
Modifying backup specifications .....	72
Scheduling backup specifications .....	72
Scheduling example .....	72
Previewing backup sessions .....	73
Using the Data Protector GUI .....	73
Using the Data Protector CLI .....	74
What happens during the preview? .....	74
Starting backup sessions .....	74
Using the Data Protector GUI .....	74
Using the Data Protector CLI .....	75
Preparing for disaster recovery .....	76
Restore .....	77
Restore of virtual machines .....	77
Application database: Datacenter .....	77
Application database: None (restore files to client) .....	78
Restore of filesystems .....	78
Considerations .....	79
Finding information for restore .....	79

Using the Data Protector GUI .....	79
Using the Data Protector CLI .....	80
Restoring using the Data Protector GUI .....	81
Restoring using the Data Protector CLI .....	89
Recovering virtual machines manually .....	92
Recovery after restoring outside of a datacenter .....	92
Recovery after restoring to a datacenter .....	100
Restoring using another device .....	108
Disaster recovery .....	108
Monitoring sessions .....	109
Troubleshooting .....	109
Before you begin .....	109
Checks and verifications .....	110
Problems .....	110

## 2 Integrating Sybase Server and Data Protector ..... 113

Introduction .....	113
Integration concepts .....	113
Data Protector CLI commands .....	115
Configuring the integration .....	115
Prerequisites .....	116
Before you begin .....	116
Cluster-aware clients .....	116
Configuring Sybase users .....	116
Configuring Sybase instances .....	117
Before you begin .....	117
Using the Data Protector GUI .....	117
Using the Data Protector CLI .....	120
Checking the configuration .....	121
Using the Data Protector GUI .....	121
Using the Data Protector CLI .....	122
Backup .....	122
Creating backup specifications .....	122
Modifying backup specifications .....	127
Scheduling backup specifications .....	127
Previewing backup sessions .....	128
Using the Data Protector GUI .....	128
Using the Data Protector CLI .....	129
What happens during the preview? .....	129
Starting backup sessions .....	130
Using the Data Protector GUI .....	130
Using the Data Protector CLI .....	130

Using Sybase commands .....	131
Restore .....	131
Localized database names .....	132
Finding information for restore .....	132
Using the Data Protector GUI .....	132
Using the Data Protector CLI .....	132
Restoring using the Sybase isql command .....	139
Restore examples .....	142
Restoring using another device .....	145
Monitoring sessions .....	145
Troubleshooting .....	145
Before you begin .....	146
Checks and verifications .....	146

### 3 Integrating HP Network Node Manager and Data Protector ..... 149

Introduction .....	149
Integration concept .....	150
Configuring the integration .....	150
Prerequisites .....	150
Before you begin .....	151
Tasks for the NNM administrator .....	151
Backup .....	151
Creating backup specifications .....	152
Modifying backup specifications .....	153
Scheduling backup specifications .....	153
Starting backup sessions .....	154
Restore .....	155
Monitoring sessions .....	155
Acceptable warnings on Windows .....	155
Troubleshooting .....	156
Before you begin .....	157
Problems .....	157

### 4 Integrating NDMP Server and Data Protector ..... 163

Introduction .....	163
Integration concept .....	163
Configuring the integration .....	166
Prerequisites .....	166
Importing NDMP Server systems .....	166
Creating media pools .....	168

Configuring NDMP devices .....	169
Configuring tape libraries .....	171
Configuring standalone devices .....	174
Network appliance configuration .....	176
EMC Celerra configuration .....	177
Block size .....	178
Backup .....	179
Before you begin .....	180
Creating backup specifications .....	180
Modifying backup specifications .....	185
Starting backup sessions .....	185
Restore .....	185
Restoring using the Data Protector GUI .....	186
Direct access restore .....	187
Restoring using another device .....	189
NDMP environment variables .....	189
The NDMP specific omnirc file variables .....	190
Media management .....	192
Troubleshooting .....	193
Before you begin .....	193
Problems .....	193

## A Integrating Citrix XenServer and HP Data Protector ..... 195

Introduction .....	195
Integration concepts .....	195
Types of backup .....	195
Online backup .....	195
Offline backup .....	196
Disaster recovery .....	196
Backup processes .....	196
Online backup .....	196
Offline backup .....	197
Types of restore .....	197
Restore processes .....	198
Restore from online backup .....	198
Restore from offline backup .....	198
Restore considerations .....	199
Main integration components .....	200
Installation of the integration .....	201
Prerequisites .....	201
Installation of the integration scripts .....	202
Integration script functions .....	204

Backup using the integration .....	204
Updating configuration script DPxen_config.py for backup .....	205
Example backup configurations .....	206
Creating a backup specification .....	207
Restore using the integration .....	209
Updating configuration script DPxen_config.py for restore .....	209
Example restore configurations .....	210
Specifying a restore .....	212
Notes on restore .....	214
Special considerations .....	214
Further information .....	215
Glossary .....	217
Index .....	275

---

# Figures

1 Data Protector graphical user interface .....	27
2 VirtualCenter environment .....	32
3 Migration of virtual machines .....	34
4 Standalone ESX Server environment .....	35
5 Configuring a VirtualCenter Server system .....	41
6 Configuring virtual machines .....	44
7 Snapshot tree .....	51
8 Full backup (disabled mode) .....	53
9 Differential backup (single mode) .....	55
10 Incremental backup (single mode) .....	57
11 Incremental backup (mixed mode) .....	59
12 Incremental backup (mixed mode) .....	60
13 Snapshot and Suspend backup methods .....	61
14 VCBimage backup method .....	63
15 VCBfile method .....	65
16 Selecting VMware objects (Snapshot, Suspend, VCBimage) .....	69
17 Selecting VMware objects (VCBfile) .....	70
18 Application specific options .....	71
19 Scheduling a backup specification .....	73
20 Backup object information .....	80
21 Selecting VMware objects for restore (Snapshot, Suspend, VCBimage) .....	82
22 Selecting VMware objects for restore (VCBfile) .....	83
23 Restore options (Snapshot, Suspend, VCBimage) .....	84

24	Restore options (VCBfile) .....	85
25	Conversion – Specify Source .....	95
26	Conversion – Specify Destination 1 .....	96
27	Conversion – Specify Destination 2 .....	97
28	Conversion – View/Edit Options .....	98
29	Conversion – Ready to Complete .....	99
30	Recovery completed .....	100
31	Virtual Infrastructure Client .....	105
32	Virtual machine properties .....	106
33	Browsing datastores .....	107
34	Add hardware summary .....	108
35	Sybase integration architecture .....	114
36	Specifying the Sybase instance .....	118
37	Configuring a Sybase instance (Windows) .....	119
38	Configuring a Sybase instance (UNIX) .....	120
39	Selecting backup objects .....	123
40	Pre- and post-exec commands (Windows) .....	124
41	Pre- and post-exec commands (UNIX) .....	125
42	Specifying the number of concurrent streams .....	126
43	Scheduling a backup specification .....	128
44	Example of previewing a backup .....	129
45	Running the syb_tool command .....	134
46	Running the syb_tool command with the -file and -media options .....	134
47	The load command for restore to a different database .....	135
48	The load command for restore to a different server .....	136
49	Loading transaction logs from multiple backups .....	137
50	Example of a list of backed up Sybase databases .....	138
51	Example of a list of backup sessions for a specific object .....	139
52	Example of finding media needed for restore .....	139

53	Example of a list of Sybase databases .....	142
54	Restoring a database from a specific session .....	143
55	Creating a database device .....	144
56	Creating an empty database .....	144
57	Scheduling a backup specification .....	154
58	Data Protector NDMP Server integration architecture .....	164
59	The NDMP environment configuration .....	165
60	Specifying an NDMP Server system .....	167
61	Specifying an NDMP Server system .....	168
62	Library configuration—I .....	170
63	Library configuration—II .....	171
64	Configuring a library .....	172
65	Configuring a standalone device .....	175
66	Selecting a backup template .....	181
67	Specifying the NDMP Server mountpoints for backup (UNIX) .....	182
68	Specifying advanced NetApp options .....	184
69	NDMP advanced restore options .....	186
70	Selecting NDMP Server Data for direct access restore .....	188
71	Example backup and restore .....	199
72	Example layout .....	201
73	Obtaining the names of the virtual machines .....	206
74	Temporary backup folder selection .....	208
75	Available storage repositories .....	212
76	Selection of files to restore .....	213

---

# Tables

1	Edition history .....	15
2	Document conventions .....	25
3	VMware users .....	38
4	Virtual machine options .....	44
5	Backup method overview .....	50
6	Legend .....	53
7	Backup types .....	66
8	Disk space requirements .....	67
9	VMware backup options .....	72
10	What must be backed up .....	76
11	VMware restore options .....	86
12	Virtual machine information .....	101
13	Backup types .....	113
14	Legend .....	114
15	Backup types .....	122
16	Sybase backup options .....	127
17	Backup types .....	149
18	Data Protector NNM integration components .....	150
19	Backup types .....	151
20	Backup modes .....	151
21	Analyzing the drive's SCSI address .....	176
22	Analyzing the library Robotics' SCSI address .....	177
23	Example of a list of SCSI devices .....	178
24	Supported block sizes .....	178

25 NDMP variables for NetApp NAS device .....	189
26 NDMP variables for Celerra NAS device .....	189
27 Approximate disk consumption by file history swap files .....	192



---

# Publication history

Guide updates may be issued between editions to correct errors or document product changes. To ensure that you receive updated or new editions, subscribe to the appropriate product support service. See your HP sales representative for details.

**Table 1 Edition history**

<b>Part number</b>	<b>Guide edition</b>	<b>Product</b>
B6960-90111	October 2004	Data Protector Release A.05.50
B6960-96010	July 2006	Data Protector Release A.06.00
B6960-96044	November 2008	Data Protector Release A.06.10
B6960-90160	September 2009	Data Protector Release A.06.11



---

# About this guide

This guide describes how to configure and use Data Protector with Sybase, Network Node Manager, Network Data Management Protocol, and VMware.

## Intended audience

This guide is intended for backup administrators responsible for planning, setting up, and maintaining network backups. It assumes you are familiar with:

- Basic Data Protector functionality
- Administration of the respective application

Conceptual information can be found in the *HP Data Protector concepts guide*, which is recommended to fully understand the fundamentals and the model of Data Protector.

## Documentation set

Other documents and online Help provide related information.

## Guides

Data Protector guides are available in printed format and in PDF format. Install the PDF files during the Data Protector setup procedure by selecting the *English Documentation & Help* component on Windows or the *OB2-DOCS* component on UNIX. Once installed, the guides reside in the *Data\_Protector\_home\docs* directory on Windows and in the */opt/omni/doc/C* directory on UNIX.

You can find these documents from the *Manuals* page of the HP Business Support Center website:

<http://www.hp.com/support/manuals>

In the *Storage* section, click **Storage Software** and then select your product.

- *HP Data Protector concepts guide*

This guide describes Data Protector concepts and provides background information on how Data Protector works. It is intended to be used with the task-oriented online Help.

- *HP Data Protector installation and licensing guide*

This guide describes how to install the Data Protector software, taking into account the operating system and architecture of your environment. This guide also gives details on how to upgrade Data Protector, as well as how to obtain the proper licenses for your environment.

- *HP Data Protector troubleshooting guide*

This guide describes how to troubleshoot problems you may encounter when using Data Protector.

- *HP Data Protector disaster recovery guide*

This guide describes how to plan, prepare for, test and perform a disaster recovery.

- *HP Data Protector integration guides*

These guides describe how to configure and use Data Protector to back up and restore various databases and applications. They are intended for backup administrators or operators. There are four guides:

- *HP Data Protector integration guide for Microsoft applications: SQL Server, SharePoint Portal Server, Exchange Server, and Volume Shadow Copy Service*

This guide describes the integrations of Data Protector with the following Microsoft applications: Microsoft Exchange Server, Microsoft SQL Server, and Volume Shadow Copy Service.

- *HP Data Protector integration guide for Oracle and SAP*

This guide describes the integrations of Data Protector with Oracle, SAP R/3, and SAP DB/MaxDB.

- *HP Data Protector integration guide for IBM applications: Informix, DB2, and Lotus Notes/Domino*

This guide describes the integrations of Data Protector with the following IBM applications: Informix Server, IBM DB2, and Lotus Notes/Domino Server.

- *HP Data Protector integration guide for VMware Virtual Infrastructure, Sybase, Network Node Manager, and Network Data Management Protocol Server*

This guide describes the integrations of Data Protector with VMware Virtual Infrastructure, Sybase, Network Node Manager, Network Data Management Protocol Server, and Citrix XenServer.

- *HP Data Protector integration guide for HP Service Information Portal*

This guide describes how to install, configure, and use the integration of Data Protector with HP Service Information Portal. It is intended for backup administrators. It discusses how to use the application for Data Protector service management.

- *HP Data Protector integration guide for HP Reporter*  
This manual describes how to install, configure, and use the integration of Data Protector with HP Reporter. It is intended for backup administrators. It discusses how to use the application for Data Protector service management.
- *HP Data Protector integration guide for HP Operations Manager for UNIX*  
This guide describes how to monitor and manage the health and performance of the Data Protector environment with HP Operations Manager and HP Service Navigator on UNIX.
- *HP Data Protector integration guide for HP Operations Manager for Windows*  
This guide describes how to monitor and manage the health and performance of the Data Protector environment with HP Operations Manager and HP Service Navigator on Windows.
- *HP Data Protector integration guide for HP Performance Manager and HP Performance Agent*  
This guide provides information about how to monitor and manage the health and performance of the Data Protector environment with HP Performance Manager (PM) and HP Performance Agent (PA) on Windows, HP-UX, Solaris, and Linux.
- *HP Data Protector zero downtime backup concepts guide*  
This guide describes Data Protector zero downtime backup and instant recovery concepts and provides background information on how Data Protector works in a zero downtime backup environment. It is intended to be used with the task-oriented *HP Data Protector zero downtime backup administrator's guide* and the *HP Data Protector zero downtime backup integration guide*.
- *HP Data Protector zero downtime backup administrator's guide*  
This guide describes how to configure and use the integration of Data Protector with HP StorageWorks Virtual Array, HP StorageWorks Enterprise Virtual Array, EMC Symmetrix Remote Data Facility and TimeFinder, and HP StorageWorks Disk Array XP. It is intended for backup administrators or operators. It covers the zero downtime backup, instant recovery, and the restore of filesystems and disk images.
- *HP Data Protector zero downtime backup integration guide*  
This guide describes how to configure and use Data Protector to perform zero downtime backup, instant recovery, and standard restore of Oracle, SAP R/3, Microsoft Exchange Server, and Microsoft SQL Server databases. The guide also

describes how to configure and use Data Protector to perform backup and restore using the Microsoft Volume Shadow Copy Service.

- *HP Data Protector MPE/iX system user guide*  
This guide describes how to configure MPE/iX clients and how to back up and restore MPE/iX data.
- *HP Data Protector Media Operations user guide*  
This guide provides tracking and management of offline storage media. It describes the tasks of installing and configuring the application, performing daily media operations and producing reports.
- *HP Data Protector product announcements, software notes, and references*  
This guide gives a description of new features of HP Data Protector A.06.11. It also provides information on installation requirements, required patches, and limitations, as well as known issues and workarounds.
- *HP Data Protector product announcements, software notes, and references for integrations to HP Operations Manager, HP Reporter, HP Performance Manager, HP Performance Agent, and HP Service Information Portal*  
This guide fulfills a similar function for the listed integrations.
- *HP Data Protector Media Operations product announcements, software notes, and references*  
This guide fulfills a similar function for Media Operations.
- *HP Data Protector command line interface reference*  
This guide describes the Data Protector command-line interface, command options and their usage as well as provides some basic command-line examples.

## Online Help

Data Protector provides context-sensitive (F1) Help and Help Topics for Windows and UNIX platforms.

You can access the online Help from the top-level directory on the installation DVD-ROM without installing Data Protector:

- **Windows:** Unzip `DP_help.zip` and open `DP_help.chm`.
- **UNIX:** Unpack the zipped tar file `DP_help.tar.gz`, and access the online Help system through `DP_help.htm`.

# Documentation map

## Abbreviations

Abbreviations in the documentation map that follows are explained below. The guide titles are all preceded by the words “HP Data Protector”.

<b>Abbreviation</b>	<b>Guide</b>
CLI	Command line interface reference
Concepts	Concepts guide
DR	Disaster recovery guide
GS	Getting started guide
Help	Online Help
IG-IBM	Integration guide for IBM applications: Informix, DB2, and Lotus Notes/Domino
IG-MS	Integration guide for Microsoft applications: SQL Server, SharePoint Portal Server, Exchange Server, and Volume Shadow Copy Service
IG-O/S	Integration guide for Oracle and SAP
IG-OMU	Integration guide for HP Operations Manager for UNIX
IG-OMW	Integration guide for HP Operations Manager for Windows
IG-PM/PA	Integration guide for HP Performance Manager and HP Performance Agent
IG-Report	Integration guide for HP Reporter
IG-SIP	Integration guide for HP Service Information Portal
IG-Var	Integration guide for VMware Virtual Infrastructure, Sybase, Network Node Manager, Network Data Management Protocol Server, and Citrix XenServer.

<b>Abbreviation</b>	<b>Guide</b>
Install	Installation and licensing guide
MO GS	Media Operations getting started guide
MO RN	Media Operations product announcements, software notes, and references
MO UG	Media Operations user guide
MPE/iX	MPE/iX system user guide
PA	Product announcements, software notes, and references
Trouble	Troubleshooting guide
ZDB Admin	ZDB administrator's guide
ZDB Concept	ZDB concepts guide
ZDB IG	ZDB integration guide

## Map

The following table shows where to find information of different kinds. Shaded squares are a good place to look first.

	Help	GS	Concepts	Install	Trouble	DR	PA	Integration Guides						ZDB			MO			MPE/iX	CLI		
								MS	O/S	IBM	Var	OV	OVOU	OVOW	Concept	Admin	IG	GS	User			PA	
Backup	X	X	X					X	X	X	X				X	X	X					X	
CLI																							X
Concepts/ Techniques	X		X					X	X	X	X	X	X	X	X	X	X						X
Disaster Recovery	X		X			X																	
Installation/ Upgrade	X	X		X			X					X	X	X				X	X				X
Instant Recovery	X		X												X	X	X						
Licensing	X			X			X												X				
Limitations	X				X		X	X	X	X			X				X					X	
New features	X						X																
Planning strategy	X		X								X				X								
Procedures/ Tasks	X			X	X	X		X	X	X	X	X	X	X		X	X			X			
Recommendations			X				X								X							X	
Requirements				X			X	X	X	X			X					X	X	X			
Restore	X	X	X					X	X	X	X					X	X						X
Supported configurations															X								
Troubleshooting	X			X	X			X	X	X	X	X				X	X						

## Integrations

Look in these guides for details of the following integrations:

Integration	Guide
HP Operations Manager for UNIX/for Windows	IG-OMU, IG-OMW
HP Performance Manager	IG-PM/PA
HP Performance Agent	IG-PM/PA

<b>Integration</b>	<b>Guide</b>
HP Reporter	IG-R
HP Service Information Portal	IG-SIP
HP StorageWorks Disk Array XP	all ZDB
HP StorageWorks Enterprise Virtual Array (EVA)	all ZDB
HP StorageWorks Virtual Array (VA)	all ZDB
IBM DB2 UDB	IG-IBM
Informix	IG-IBM
Lotus Notes/Domino	IG-IBM
Media Operations	MO User
MPE/iX system	MPE/iX
Microsoft Exchange Server	IG-MS, ZDB IG
Microsoft Exchange Single Mailbox	IG-MS
Microsoft SQL Server	IG-MS, ZDB IG
Microsoft Volume Shadow Copy Service (VSS)	IG-MS, ZDB IG
NDMP Server	IG-Var
Network Node Manager (NNM)	IG-Var
Oracle	IG-O/S
Oracle ZDB	ZDB IG
SAP DB	IG-O/S
SAP R/3	IG-O/S, ZDB IG

Integration	Guide
Sybase	IG-Var
EMC Symmetrix	all ZDB
VMware	IG-Var

## Document conventions and symbols

**Table 2 Document conventions**

Convention	Element
Blue text: <a href="#">Table 2</a> on page 25	Cross-reference links and e-mail addresses
Blue, underlined text: <a href="http://www.hp.com">http://www.hp.com</a>	Website addresses
<i>Italic text</i>	Text emphasis
Monospace text	<ul style="list-style-type: none"> <li>• File and directory names</li> <li>• System output</li> <li>• Code</li> <li>• Commands, their arguments, and argument values</li> </ul>
<i>Monospace, italic text</i>	<ul style="list-style-type: none"> <li>• Code variables</li> <li>• Command variables</li> </ul>
Monospace, bold text	Emphasized monospace text

---

**CAUTION:**

Indicates that failure to follow directions could result in damage to equipment or data.

---



---

**IMPORTANT:**

Provides clarifying information or specific instructions.

---



**NOTE:**

Provides additional information.

---




**TIP:**

Provides helpful hints and shortcuts.

---

## Data Protector graphical user interface

Data Protector provides a cross-platform (Windows and UNIX) graphical user interface. You can use the original Data Protector GUI (Windows only) or the Data Protector Java GUI. For information about the Data Protector graphical user interface, see the online Help.



**Figure 1 Data Protector graphical user interface**

## General information

General information about Data Protector can be found at <http://www.hp.com/go/dataprotector>.

## HP technical support

For worldwide technical support information, see the HP support website:

<http://www.hp.com/support>

Before contacting HP, collect the following information:

- Product model names and numbers
- Technical support registration number (if applicable)
- Product serial numbers
- Error messages
- Operating system type and revision level
- Detailed questions

## Subscription service

HP recommends that you register your product at the Subscriber's Choice for Business website:

<http://www.hp.com/go/e-updates>

After registering, you will receive e-mail notification of product enhancements, new driver versions, firmware updates, and other product resources.

## HP websites

For additional information, see the following HP websites:

- <http://www.hp.com>
- <http://www.hp.com/go/software>
- <http://www.hp.com/support/manuals>
- <http://h20230.www2.hp.com/selfsolve/manuals>
- <http://www.hp.com/support/downloads>

## Documentation feedback

HP welcomes your feedback.

To make comments and suggestions about product documentation, please send a message to [DP.DocFeedback@hp.com](mailto:DP.DocFeedback@hp.com). All submissions become the property of HP.

---

# 1 Integrating VMware Virtual Infrastructure and Data Protector

## Introduction

This chapter explains how to configure and use the Data Protector VMware Virtual Infrastructure integration (**VMware integration**). Data Protector integrates with VMware Virtual Infrastructure, including ESX Server and ESXi Server<sup>1</sup> systems, and VirtualCenter Server systems, to back up and restore the following **VMware objects**:

- Virtual machines
- Filesystems of virtual machines<sup>2</sup>

The following backup methods are available:

- Snapshot<sup>3</sup>
- Suspend<sup>3</sup>
- VCBimage<sup>4</sup>
- VCBfile<sup>4</sup>

During backup, virtual machines can be powered off (**offline backup**) or actively used (**online backup**). The **Suspend** backup method supports only offline backup.

<sup>1</sup>Since Data Protector components cannot be installed on ESXi Server systems, not all backup and restore functionality is available for virtual machines running on ESXi Server systems. For details, see the following sections.

<sup>2</sup>Currently, you can back up only filesystems of virtual machines running Windows. For a detailed list of guest operating systems supported for the VCBfile backup method, see the latest support matrices at <http://www.hp.com/support/manuals>.

<sup>3</sup>This method is not supported for virtual machines running on ESXi Server systems.

<sup>4</sup>This method requires a Windows system with the VMware Consolidated Backup software installed (backup proxy system).

The **Snapshot**, **Suspend**, and **VCBimage** methods are used to back up virtual machines. The **VCBfile** method is used to back up filesystems of virtual machines.

For details, see “[Backup methods](#)” on page 49.

Data Protector offers interactive and scheduled backups of the following types:

- Full
- Incremental
- Differential

For details on the backup types see, [Table 7](#) on page 66.

Virtual machines can be restored:

- To the original ESX Server and/or ESXi Server systems
- To any Data Protector client with the `VMware Integration` component installed. After such a restore, you need to manually move the restored virtual machine images to an ESX Server or ESXi Server system, using the VMware Converter.

Filesystems of virtual machines can be restored to any Windows system (physical or virtual) that has the `VMware Integration` component installed.

This chapter provides information specific to the VMware Virtual Infrastructure integration. For limitations, see the *HP Data Protector product announcements, software notes, and references*. For general Data Protector procedures and options, see the online Help.

## Integration concepts

Data Protector integrates with VMware Virtual Infrastructure through the Data Protector VMware integration agent, which channels communication between the Data Protector Session Manager and the clients in the VMware environment. The Data Protector VMware integration agent communicates with the Virtual Infrastructure through VI SDK, a web-service API.

## Supported environments


Data Protector supports environments where ESX Server and/or ESXi Server systems are managed through a VirtualCenter Server system (**VirtualCenter environments**) as well as environments with standalone ESX Server systems (**standalone ESX Server environments**). Mixed environments, in which some of the ESX Server and/or ESXi Server systems are managed through a VirtualCenter Server system and some are standalone, are also supported. You can even have multiple VirtualCenter Server

systems in your environment, each managing its own set of ESX Server and/or ESXi Server systems.

## VirtualCenter environment

In a VirtualCenter environment, Data Protector communicates with the VMware Virtual Infrastructure through the VirtualCenter Server system. All backup and restore requests are sent there.

In one session, you can back up virtual machines from only one datacenter.




**Figure 2 VirtualCenter environment**

ESX Server or ESXi Server system	VMware platform capable of hosting multiple virtual machines.
VM	Virtual machine. Virtualized x86 or x64 PC environment, in which a guest operating system and associated application software can run.
Datacenter	An organizational unit that consists of one or more ESX Server and/or ESXi Server systems and the related storage for virtual machines (datastores). Datastores can reside on local disks/RAID, iSCSI or SAN storage.

## Migration of virtual machines

In a VirtualCenter environment, Data Protector supports migration of virtual machines between ESX Server and/or ESXi Server systems that belong to the same datacenter. Virtual machines migrate from one ESX Server or ESXi Server system to another for various reasons:

- If ESX Server and/or ESXi Server systems are configured in a **VMware high availability cluster**, virtual machines automatically migrate when the original ESX Server or ESXi Server system fails.
- If ESX Server and/or ESXi Server systems are configured in a **VMware load balancing cluster**, virtual machines automatically migrate to ESX Server or ESXi Server systems with less workload.
- You can start a migration of a virtual machine manually, using the Virtual Infrastructure client.



**Figure 3 Migration of virtual machines**

Whatever the reason for the migration, you do not need to create a new backup specification afterwards. Data Protector will automatically find the migrated virtual machines and back them up.

Data Protector does not support migration of virtual machines between ESX Server and/or ESXi Server systems that belong to different datacenters.


### VirtualCenter Server system in a cluster

Data Protector also supports environments with a VirtualCenter Server system in a Microsoft Cluster Service cluster. After a failover in such a cluster, you do not need to change the backup specification. However, if the failover occurs during a backup or restore session, the session fails and has to be restarted.

## Standalone ESX Server environment

In a standalone ESX Server environment, Data Protector communicates with the VMware Virtual Infrastructure through an ESX Server system. All backup and restore requests are sent there.

In one session, you can back up virtual machines from only one datacenter (ESX Server system).



**Figure 4 Standalone ESX Server environment**

---

 **NOTE:**

ESXi Server systems are not supported in standalone environments.

---

## Data Protector components

### Data Protector Cell Manager

The Data Protector Cell Manager can be installed on a virtual machine, VirtualCenter Server system, backup proxy system, or a separate system outside the VMware Virtual Infrastructure environment.

### Data Protector VMware Integration component

The Data Protector `VMware Integration` component must be installed on the following clients:

- All ESX Server systems from which you plan to back up virtual machines
- VirtualCenter Server systems (if they exist)
- Backup proxy systems (if you plan to use the **VCBfile** and **VCBimage** backup methods)
- Windows systems (physical or virtual) to which you plan to restore filesystems of virtual machines

---

 **NOTE:**

The Data Protector `VMware Integration` component (or any other) cannot be installed on ESXi Server systems.

---

The component consists of the following parts:

- `vmware_bar.exe`, activated during backup and restore
- `util_vmware.exe`, activated during configuration and mounting on backup proxy systems

### Data Protector Media Agents

Data Protector Media Agents can be installed on ESX Server systems, VirtualCenter Server systems, backup proxy systems, or separate systems outside the VMware Virtual Infrastructure environment.

# Configuring the integration

Configure the integration as follows:

- Configure users as described in “[Configuring VMware users](#)” on page 38.
- Provide Data Protector with login information to VMware management clients as described in “[Configuring VMware management clients](#)” on page 39.
- If your ESX Server systems are configured in a cluster, check the cluster settings as described in “[Configuring clusters](#)” on page 38.
- For each virtual machine, specify details on how to perform various backup methods as described in “[Configuring virtual machines](#)” on page 43.

## Prerequisites

- Ensure that you have a correctly installed and configured VMware environment.
  - For supported versions, platforms, devices, and other information, see the latest support matrices at <http://www.hp.com/support/manuals>.
  - For information on installing, configuring, and using the VMware Virtual Infrastructure, see the VMware documentation.

For the **VCBfile** and **VCBimage** backup methods, ensure that you have at least one backup proxy system configured in your environment. For details, see the VMware documentation.
- Ensure that you have correctly installed Data Protector. On how to install Data Protector in various architectures, see the *HP Data Protector installation and licensing guide*.
- For limitations, see “Limitations and recommendations” in the *HP Data Protector product announcements, software notes, and references*.

## Before you begin

- Configure devices and media for use with Data Protector.
- To test whether the VMware Virtual Infrastructure and the Cell Manager communicate properly, configure and run a Data Protector filesystem backup and restore on every VMware client (ESX Server system, VirtualCenter Server system, backup proxy system) in your environment.

## Configuring VMware users

1. Identify or configure the following users:

**Table 3 VMware users**

VirtualCenter users (VirtualCenter environment)	For each VirtualCenter Server system, identify the Windows operating system user who administers the VirtualCenter Server.
ESX Server users (standalone ESX Server environment)	For each standalone ESX Server system, identify an operating system user who has read, write, and execute permissions on the related datastores.

2. Add all these users to the Data Protector `admin` or `operator` user group.  
For details on adding users, see the online Help index: "adding users".



**NOTE:**

If your VirtualCenter Server system is in a cluster, add the users from both nodes to the Data Protector `admin` or `operator` user group.

---

## Configuring clusters

### ESX Server systems in a cluster

If your ESX Server systems are configured in a high availability cluster, open the cluster settings dialog box in the Virtual Infrastructure client and select the option **Allow virtual machines to be powered on even if they violate availability constraints**.



**NOTE:**

This option is applicable only for the **Suspend** backup method. Therefore, it is not applicable for ESXi Server systems.

If the option is not selected, you may encounter problems when trying to back up virtual machines that have migrated to other ESX Server systems after a failover. More specifically, Data Protector may not be able to power on the virtual machines at the end of the session.

---

## Configuring backup proxy systems

If your virtual machines reside on **iSCSI datastores**, restart the Data Protector `Inet` service on the related backup proxy system under a network domain user account that has read-write permissions for the following directories:

- `C:\Program Files`
- `C:\Windows\Temp\vmware-system` (this directory is created when you run the `vcbMounter` for the first time)

---

 **NOTE:**

If the Data Protector `Inet` service on the backup proxy system runs under the Local System account, **VCBimage** and **VCBfile** backup sessions fail because this account does not have permissions to use network, which is needed to access iSCSI datastores.

---

For information on changing the Data Protector `Inet` account, see the online Help index: “Inet, changing account”.

## Configuring VMware management clients

In VirtualCenter environments, Data Protector communicates with the VMware Virtual Infrastructure through a VirtualCenter Server system and in standalone ESX Server environments, through an ESX Server system. From now on, this client will be called the **VMware management client**.

For each VMware management client, you need to provide the following login information:

- Username
- Password
- Web root (optional)
- Port (optional)

For details on the parameters, see the following section.

You can provide the information in two different ways:

- Specify the login information manually (**Standard security**). In this case, the information is saved in the VMware management client specific configuration file

on the Cell Manager. The file is named  
`VMwareManagementClient%_OB2_GLOBAL`.

---

 **NOTE:**

Before the information is saved, Data Protector first tests the connection. If the connection fails, the information is not saved in the configuration file, leaving the previous login information (if it exists) in the configuration file intact.


---

- Instruct Data Protector to use the login information contained in a local file on the VMware management client (**Integrated security**). At the beginning of a backup session, the Session Manager starts the VMware integration agent on the VMware management client and the agent provides the information from the file.

To configure VMware management clients, use the Data Protector GUI or CLI.

## Using the Data Protector GUI

You specify the login information in the Configure VMware dialog box. The dialog box is displayed automatically when you create the first backup specification. To change or check the parameters later, open any backup specification for this VMware management client, go to the Source page, right-click the client at the top, and click **Configure**.



**Figure 5 Configuring a VirtualCenter Server system**

Select either **Integrated security** or **Standard security**.

If you select **Standard security**, specify the following:

- **Username** and **Password**: Specify an operating system user account that has the following VMware Virtual Infrastructure privileges:
  - System.View
  - System.Anonymous
  - Folder.Create
  - VirtualMachine.State.CreateSnapshot
  - VirtualMachine.State.RemoveSnapshot
  - VirtualMachine.Interact.Suspend
  - VirtualMachine.Interact.PowerOff
  - VirtualMachine.Interact.PowerOn
  - VirtualMachine.Inventory.Create
  - VirtualMachine.Inventory.Delete
- **Web service**: Optionally, change the web service entry point URI. Default: /sdk

- **Port:** Optionally, change the TCP port number of the Virtual Infrastructure web service server.  
Default: 443 (SSL-encrypted HTTP), 80 (unencrypted HTTP).  
By default, the HTTP/S (SSL-encrypted HTTP) is used. To switch to unencrypted HTTP, configure the VMware management client to allow HTTP connections and set the Data Protector `omnirc` variable `OB2_VMWARE_HTTP` to 1. On how to set the `omnirc` variable, see the online Help index: “omnirc options”.  
If you leave the **Port** option empty, the value is read from the following file, depending on your VMware management client:  
**VirtualCenter Server system:** Windows registry:  
`HKEY_LOCAL_MACHINE\SOFTWARE\VMware, Inc.\VMware VirtualCenter\`  
**ESX Server system:** `/etc/vmware/hostd/config.xml`

If you select **Integrated security**, ensure that the `backuptools.conf` file on the VMware management client contains the required data. The file location depends on your VMware management client:

**VirtualCenter Server system:** `C:\Documents and Settings\All Users\Application Data\VMware\VMware VirtualCenter\backuptools.conf`.

**Standalone ESX Server system:** `/etc/vmware/backuptools.conf`.

On the VirtualCenter Server system, the file does not exist by default. It has to be created manually at the specified location. The file content should be similar to the following:

```
USERNAME="Administrator"
PASSWORD="vnm46578"
```

## Using the Data Protector CLI

1. Log in to the VMware management client under a user account that is configured as described in “[Configuring VMware users](#)” on page 38.
2. Go to the following directory:  
**VirtualCenter Server system:** `Data_Protector_home\bin`  
**Standalone ESX Server system:** `/opt/omni/lbin`

### 3. Run:

For **Integrated security**:

```
util_vmware.exe
-config
-security 1
```

For **Standard security**:

```
util_vmware.exe
-config
-security 0
-user Username
-password Password
[-webroot WebServiceRoot]
[-port WebServicePort]
```

The message `*RETVAL*0` indicates successful configuration.

For option description, see the `util_vmware.exe` man page or the *HP Data Protector command line interface reference*.

## Configuring virtual machines

For each virtual machine, specify details on how to perform various backup methods:

- For the **Snapshot** method, specify how to handle virtual machine snapshots that are created during backup. Note that not all snapshot handling modes support incremental and differential backups.
- For the **VCBfile** and **VCBimage** backup methods, specify which backup proxy system and mount points should be used to back up virtual machines or filesystems.
- The **Suspend** backup method has no specifics.


You can configure each virtual machine separately or all together. Configuration settings for virtual machines of the same datacenter are saved in a separate configuration file on the Cell Manager. The file is named `VMwareManagementClient%DatacenterPath`. It is used for all backup sessions involving this particular datacenter.

To configure virtual machines, use the Data Protector GUI or CLI.

## Using the Data Protector GUI

You can specify details on how a virtual machine backup should be performed when you create or modify a backup specification. In the Source page of a backup

specification, right-click the client system at the top or any of the virtual machines listed below and click **Configure Virtual Machines**.



**Figure 6 Configuring virtual machines**

In the Configure Virtual Machine(s) dialog box, specify the following options:

**Table 4 Virtual machine options**

<b>Configure virtual machine</b>	Select whether you want to specify common virtual machine settings ( <b>Common VM Settings</b> ) or settings for a specific virtual machine. Virtual machine specific settings override the common virtual machine settings.
----------------------------------	--

	<b>Use common settings for selected VM</b>	Available only if a virtual machine is selected. Select this option to apply the common virtual machine settings for the selected virtual machine. Default: ON
	<b>Use default settings</b>	Available only if <b>Common VM Settings</b> is selected. Select this option to set default values for the common virtual machine settings. Default: ON
<b>Snapshot handling</b>	<b>Disabled (default)</b>	This mode supports only full backups. The virtual machine snapshot that is created during backup is removed at the end of the session. For details, see <a href="#">“Snapshot mode: disabled”</a> on page 52.
	<b>Single</b>	This mode supports full, incremental, and differential backups. However, you cannot mix incremental and differential backups within the same backup chain. Data Protector keeps one DP snapshot for backup purposes. For details, see <a href="#">“Snapshot mode: single”</a> on page 54.
	<b>Mixed</b>	This mode supports full, incremental, and differential backups, in all combinations. Data Protector keeps up to two DP snapshots for backup purposes. For details, see <a href="#">“Snapshot mode: mixed”</a> on page 58.
<b>Backup proxy configuration</b>	<b>Backup proxy</b>	Select a backup proxy system to be used for the <b>VCBfile</b> and <b>VCBimage</b> backup methods. Note that Data Protector lists all the systems that have the <code>VMware Integration</code> component installed, including those that may not be backup proxy systems.

<p><b>Specify mountpoint</b></p>	<p>During a VCB backup session, virtual machine disks are mounted on a backup proxy system. Select this option to specify a different mount point directory on the backup proxy system. This is particularly useful for the <b>VCBimage</b> backup method, during which the virtual machine disks are copied to a local disk on the backup proxy system. This option enables you to specify a mount point where you have enough disk space. It also enables you to mount virtual machines on different disks, which improves backup performance.</p> <p>Default: <i>Data_Protector_home\tmp</i></p>
----------------------------------	---

## Using the Data Protector CLI

1. Log in to the VMware management client under a user account that is configured as described in “Configuring VMware users” on page 38.

2. Go to the following directory:

**VirtualCenter Server system:** *Data\_Protector\_home\bin*

**Standalone ESX Server system:** */opt/omni/lbin*

3. Run:

```
util_vmware.exe
-config
-instance DatacenterPath
-vm VMpath VM_OPTIONS [-vm VMpath VM_OPTIONS...]
```

```
VM_OPTIONS
-snapshots { 0 | 1 | 2}
-proxy BackupProxy
-mount ProxyMountPoint
-default
```

The values { 0 | 1 | 2} represent **Disabled**, **Single**, and **Mixed** snapshot handling modes respectively. For details, see the `util_vmware.exe` man page or the *HP Data Protector command line interface reference*.

To change virtual machine specific settings back to common virtual machine settings, run:

```
util_vmware.exe -config -instance DatacenterPath -vm VMpath
-default [-vm VMpath -default ...]
```

The message `*RETVAL*0` indicates successful configuration.

---

 **TIP:**

You can join the options for configuring virtual machines and the options for configuring the VMware management client in the same command line.

---

### Example

Suppose you want to set **Integrated security** for the VirtualCenter Server system `virtualcenter2.company.com`. In addition, you want to specify **Single** snapshot handling mode and use the backup proxy system `proxy2.company.com` for the virtual machine `/vm/myfolder/myvm` that belongs to the `datacenter/Mydatacenters/Datacenter1`.

To achieve all this, log in to the VirtualCenter Server system `virtualcenter2.company.com`, go to the directory `Data_Protector_home\bin`, and run:

```
util_vmware.exe -config -security 1 -instance  
/Mydatacenters/Datacenter1 -vm /vm/myfolder/myvm -snapshots  
1 -proxy proxy2.company.com
```

## Checking the configuration of VMware clients

To verify the connection, use the Data Protector GUI or CLI.

### Using the Data Protector GUI

You can verify the connection to the VMware management client after you have created at least one backup specification.

1. In the Context List, select **Backup**.
2. In the Scoping Pane, expand **Backup Specifications** and then **VMware**. Click the backup specification for the VMware management client to be checked.
3. Right-click the VMware management client and click **Check configuration**.

### Using the Data Protector CLI

1. Log in to the VMware management client under a user account that is configured as described in “[Configuring VMware users](#)” on page 38.

2. Go to the following directory:

**VirtualCenter Server system:** `Data_Protector_home\bin`

**Standalone ESX Server system:** `/opt/omni/lbin`

3. Run:

```
util_vmware.exe -chkconf [-instance DatacenterPath]
```

For option description, see the `util_vmware.exe` man page or the *HP Data Protector command line interface reference*.

## Backup

Using the Data Protector VMware integration, you can back up the following VMware objects:

- Virtual machines
- Filesystems of virtual machines

## What is backed up?

Data Protector identifies datacenters and virtual machines by their Virtual Infrastructure inventory path. A standalone ESX Server system has only one datacenter `/ha-datacenter` and only one folder `/vm`, which stores all the virtual machines.

Example:

Datacenter: `/ha-datacenter`

Virtual machine: `/vm/myvm1`

In a VirtualCenter environment, you can organize virtual machines and datacenters within folders that you create yourself. However, once you move a datacenter or a virtual machine to another folder, you need to create a new backup specification because Data Protector no longer finds the datacenter or virtual machine under the specified path.

Example:

Virtual machine: `/vm/myfolder1/myfolder2/.../myvm2`

Datacenter: `/myfolder/mydatacenter`

Depending on the backup method that you select, you can back up either a virtual machine or a filesystem of a virtual machine.

## Virtual machines

Virtual machines can be backed up using the **Snapshot**, **Suspend**, or **VCBimage** backup method. A virtual machine backup contains the following files:

vmx

Virtual machine configuration file.

vmdk

Virtual machine disk files. There are two types: metadata files and binary extent files. When you create a snapshot of a virtual machine, all the subsequent changes made to the virtual machine are recorded to new metadata and binary extent delta files. A separate metadata and binary extent delta file is created for each virtual machine disk.

vmsn/vmss

Snapshot or suspend memory file (not applicable for the **VCBimage** backup method).

vmsd

Snapshot description file (not applicable for the **VCBimage** backup method).

nvram

Non-volatile RAM file, describing the BIOS of the virtual machine.

## Virtual machine disks

Data Protector supports backup of individual virtual machine disks. In this case, all the virtual machine files are backed up, except the vmdk files of virtual machine disks that are excluded from backup. You can run full, incremental, and differential backups. However, after you restore individual virtual machine disks, you may need to follow additional steps to fully recover the virtual machine. For details, see [“Recovering virtual machines manually”](#) on page 92.

## Filesystems

Filesystems of virtual machines can be backed up using the **VCBfile** backup method. Currently, you can back up filesystems of virtual machines running Windows. This backup type is similar to the common filesystem backup, enabling you to select individual files and folders.

## Backup methods

Data Protector offers four different backup methods:

- **Snapshot** (see “[Snapshot method](#)” on page 50)
- **Suspend** (see “[Suspend method](#)” on page 60)
- **VCBimage** (see “[VCBimage method](#)” on page 61)
- **VCBfile** (see “[VCBfile method](#)” on page 63)

**Table 5 Backup method overview**

Backup method	How is backup consistency achieved?	Needs a backup proxy system	Supported backup types			Backs up all snapshot branches (including user created)
			Full	Diff	Incr	
Snapshot <sup>1</sup>	Data Protector creates a virtual machine snapshot.		✓	✓	✓	✓
Suspend <sup>1</sup>	Data Protector suspends the virtual machine.		✓	✓	✓	✓
VCBimage	The backup proxy system that is involved in the backup creates a virtual machine snapshot.	✓	✓			
VCBfile		✓	✓	✓	✓	

<sup>1</sup>This method is not supported for virtual machines running on ESXi Server systems.


For details on the supported backup types, see [Table 7](#) on page 66.

## Snapshot method

A virtual machine snapshot is an operation that puts the virtual machine into a consistent state. As a result, all subsequent changes made to the virtual machine disks are recorded to separate files. Note that the snapshot operation is not supported by all virtual machine disks. For details, see the VMware documentation.

During a **Snapshot** backup, Data Protector first creates a snapshot and then copies the consistent state to Data Protector media. Snapshots created by Data Protector (**DP snapshots**) are distinguished from other snapshots by the label `_DP_SNAP_` and

a description that contains the product name and a timestamp. Therefore, avoid using this label for snapshots that you create for other purposes.



**Figure 7 Snapshot tree**

Existing virtual machine snapshots reduce the overall performance of a virtual machine. For this reason, Data Protector removes DP snapshots once they are no longer needed. The number of DP snapshots that remain on the snapshot tree depends on the selected snapshot handling mode and backup type. The following snapshot handling modes are available:

- **Disabled:** This mode supports only full backups. The snapshot that is made at the beginning of a backup session is used only to create a consistent state. After the data transfer completes, the snapshot is removed. For details, see [“Snapshot mode: disabled”](#) on page 52.
- **Single:** This mode supports full, differential, and incremental backups. The following backup chains are supported:  
Full, differential, differential, differential,...  
Full, incremental, incremental, incremental,...  
It means that you cannot mix incremental and differential backups within the same backup chain. The snapshot that is made at the beginning of a backup session is used to create a consistent state. After the backup completes, one DP snapshot remains on the snapshot tree. It is needed to track changes made since the last full or incremental backup. For details, see [“Snapshot mode: single”](#) on page 54.
- **Mixed:** This mode supports full, differential, and incremental backups. All backup chains are supported. For example:  
Full, incremental, incremental, differential, incremental, differential,...  
The snapshot that is made at the beginning of a backup session is used to create a consistent state. After the backup completes, up to two DP snapshots remain on the snapshot tree. One is needed to track changes made since the last full backup and the other to track changes made since the last backup (incremental or differential). For details, see [“Snapshot mode: mixed”](#) on page 58.

---

 **IMPORTANT:**

A backup chain gets broken if you do any of the following operations:


- Delete a snapshot
- Revert to a snapshot
- Create a non-Data Protector snapshot
- Change snapshot handling mode
- Add a new virtual machine disk or rename an existing one
- Restore the virtual machine

After you make such changes, you must run a full backup again to start a new backup chain. Otherwise, subsequent incremental and differential sessions fail.

---

### Snapshot mode: disabled

A full backup in **Disabled** mode progresses as shown in the following figure.



START

1. All DP snapshots (if they exist) are removed (virtual machine delta files created by the DP snapshots are committed to the virtual machine base or to the latest preceding non-Data Protector created virtual machine delta file).

2. A new snapshot is created (DP snapshot1).
3. All the virtual machine files, including the complete snapshot tree, are backed up.
4. DP snapshot1 is removed (the active state VM<sub>Δ</sub>1 is committed to the parent file).

END

**Figure 8 Full backup (disabled mode)**

**Table 6 Legend**


T <sub>i</sub>	Boxes denoted by T <sub>i</sub> show how the virtual machine snapshot tree changes in time.
Virtual machine base	The rectangle denoted by Virtual machine base represents the virtual machine base or the last non-Data Protector created virtual machine delta file on the active branch.
VM <sub>Δ</sub>	A rectangle denoted by VM <sub>Δ</sub> represents a virtual machine delta file created by a Data Protector snapshot.

DP snapshot

A rectangle denoted by DP snapshot represents a process (snapshot operation triggered by Data Protector). This process closes the current active state to become a read-only file. At the same time, it creates a new delta file, which becomes the active state. The active state is denoted by round corners.

### Snapshot mode: single

A full backup in the **Single** mode progresses in the same way as a full backup in the **Disabled** mode, with the exception that the DP snapshot is not removed at the end (you end up with one DP snapshot). A subsequent differential backup is shown in the following figure.




**Figure 9 Differential backup (single mode)**

DP snapshot1 remains on the snapshot tree to track changes made since the last full

backup.

A backup chain consisting of a full backup that is followed by incremental sessions progresses in the same way, with the exception that, at the end of an incremental session, DP snapshot1 is removed instead of DP Snapshot2 (see [Figure 10](#)).



**Figure 10 Incremental backup (single mode)**


DP snapshot2 remains on the snapshot tree to track changes made since the last

incremental backup.


### Snapshot mode: mixed

A full backup in the **Mixed** mode progresses in the same way as a full backup in the **Single** mode (you end up with one DP snapshot). A subsequent differential or incremental backup progresses in the same way as a differential or incremental backup in the **Single** mode, with the exception that no DP snapshot is removed at the end (you end up with two DP snapshots).

The progress of a subsequent incremental backup is shown below.



**Figure 11 Incremental backup (mixed mode)**



**Figure 12 Incremental backup (mixed mode)**

DP snapshot1 and DP snapshot3 remain on the snapshot tree to track changes made since the last full and the last backup respectively.

A subsequent differential backup progresses in the same way as an incremental session described in [Figure 11](#) on page 59, with the following exceptions:


- DP snapshot2 is removed before DP snapshot3 is created.
- Instead of changes made between DP snapshot2 and DP snapshot3, changes made between DP snapshot1 and DP snapshot3 are backed up.

## Suspend method

The suspend operation saves the current memory state of a virtual machine to a file and puts the virtual machine offline. This functionality is similar to the Hibernate power mode in Windows operating systems. Note that the suspend operation is supported by all virtual machines. Therefore, this is the only backup method that can be used if your virtual machines do not support the snapshot operation.

During a **Suspend** backup, Data Protector suspends the virtual machine (if it is online) and then copies the virtual machine files to Data Protector media. If specified, the memory state is also backed up. After the backup, the virtual machine is powered on (if it was online), the memory is read from the memory file, and the virtual machine resumes the original state.

Using this method, you can run full, incremental, and differential backups. Data Protector uses the file modification time as an incremental or differential backup criterion. It means that only the files with the modification time changed since the last (full) backup are backed up.



**Figure 13 Snapshot and Suspend backup methods**

## VCBimage method

For the **VCBimage** backup method, you need to have at least one backup proxy system configured in your environment. A backup proxy system is a Windows system that has the VMware Consolidated Backup (**VCB**) software installed. For details on the VCB software, see the VMware documentation.

During a **VCBimage** backup, Data Protector invokes VCB to mount virtual machines on a backup proxy host. Before a virtual machine is mounted, VCB creates a virtual

machine snapshot to put the virtual machine into a consistent state. Once mounted, the virtual machine is copied (exported) to the backup proxy local disk.

---


 **NOTE:**

Depending on virtual machine disk sizes, the copy operation can be very time-consuming. It may take longer than the default Data Protector Session Manager timeout, which is 10 minutes. If the timeout is reached, the session is automatically aborted. To solve the problem, extend the timeout by resetting the Data Protector `SmWaitForFirstBackupClient` global options variable. For details, on how to set the variable, see the online Help index: “global options”.

---

After the virtual machine copy is created, it is transferred to Data Protector media. At the end, the virtual machine is unmounted. Consequently, the virtual machine copy is removed from the backup proxy. The virtual machine snapshot is removed as well.

The **VCBimage** backup method backs up only the current state of a virtual machine. Information about the snapshot tree and the changes made on non-active snapshot branches are not included in the backup.




**Figure 14 VCBimage backup method**

## VCBfile method

For the **VCBfile** backup method, you need to have at least one backup proxy system configured in your environment. A backup proxy system is a Windows system that has the VMware Consolidated Backup (VCB) software installed. For details on the VCB software, see the VMware documentation.

During a **VCBfile** backup, Data Protector invokes VCB to mount NTFS filesystems of Windows virtual machines on a backup proxy host. Before a filesystem is mounted, VCB creates a virtual machine snapshot to put the files into a consistent state. Once the filesystem is mounted, the files are transferred directly to Data Protector media while the backup proxy is only referencing them. At the end, the filesystem is unmounted and the virtual machine snapshot is removed.

The **VCBfile** backup method enables you to back up NTFS filesystems of virtual machines running Windows. Filesystems of other guest operating systems cannot be backed up.



**Figure 15 VCBfile method**

## Backup types

The integration provides the following backup types:

**Table 7 Backup types**

Full	<p><b>Snapshot and Suspend:</b> Backs up the complete virtual machine, including the virtual machine snapshot tree and the virtual machine memory file (if specified).</p> <p><b>VCBimage:</b> Backs up the complete virtual machine. The virtual machine snapshot tree and the virtual machine memory file are not included.</p> <p><b>VCBfile:</b> Backs up all selected files and folders.</p>
Incr	<p><b>Snapshot and Suspend:</b> Backs up changes made to the virtual machines since the last backup of any type.</p> <p><b>VCBimage:</b> Not available.</p> <p><b>VCBfile:</b> Backs up only those files and folders that have changed since the last backup of any type.</p>
Differential	<p><b>Snapshot and Suspend:</b> Backs up changes made to virtual machines since the last full backup.</p> <p><b>VCBimage:</b> Not available.</p> <p><b>VCBfile:</b> Backs up only those files and folders that have changed since the last full backup.</p>

How Data Protector identifies what to back up during incremental and differential backups depends on the selected backup method:

- **Snapshot:** Data Protector uses DP snapshots to identify the changes.
- **Suspend and VCBfile:** Data Protector checks file modification time to identify the changes.

## Considerations

- **Disk space:** Virtual machine operations that are performed during backup require additional disk space on the datastores. Data Protector checks for each virtual machine or filesystem separately whether the required virtual machine operation

can be safely performed (whether enough disk space is available). If not, the backup of that particular virtual machine or filesystem is skipped.

**Table 8 Disk space requirements**

Backup method	Required disk space on datastores	Explanation
Snapshot	The sum of the sizes of all the virtual machine disks, plus the size of the virtual machine RAM if specified.	After a snapshot is created, changes made to the virtual machine disks are recorded to separate files (one delta file is created for each virtual machine disk). A delta file can grow up to the total size of the virtual machine disk.
Suspend	The size of the virtual machine RAM.	The Suspend method does not create any delta files. However, a copy of the memory state is always made, even if the memory file is not selected for backup.
VCBimage	The sum of the sizes of all the virtual machine disks.	Same as for the Snapshot method.
VCBfile		

For the **VCBimage** and **VCBfile** backup methods, disk space is needed also on the backup proxy system for mounting virtual machines and filesystems. VCB checks whether enough disks space is available and informs Data Protector of it. If not, Data Protector skips the backup of that particular virtual machine or filesystem.

To disable the check for available disk space that is performed during backup of a particular datacenter, set the Data Protector environment variable `OB2_VMWARE_SKIPSPACECHECK` in the datacenter configuration file to 1.

To set the `OB2_VMWARE_SKIPSPACECHECK` variable using the Data Protector GUI, perform the following:

1. In the Context List, click **Backup**.
2. In the Scoping Pane, expand **Backup Specifications** and then **VMware**. Click a backup specification for your VMware datacenter.
3. In the Source property page, right-click the VMware datacenter and select **Set Environment Variables...**
4. In the Advanced dialog box, add the `OB2_VMWARE_SKIPSPACECHECK` variable and set its value to 1. Apply the change by clicking **OK**.

- **Concurrent sessions:** Backup sessions that use the same devices or back up the same datacenter cannot run concurrently. If multiple sessions are started, one session waits for the other to complete.

## Creating backup specifications

Create a backup specification using the Data Protector Manager.

1. In the Context List, click **Backup**.
2. In the Scoping Pane, expand **Backup Specifications**, right-click **VMware**, and click **Add Backup**.
3. In the Create New Backup dialog box, click **OK**.
4. In **Client**, select a VMware management client. Note that the **Client** drop-down list offers all clients that have the `VMware Integration` component installed. If your VMware management client is a VirtualCenter Server system that is configured in a Microsoft Cluster Service cluster, select its virtual hostname.

If the selected VMware management client is not configured for use with Data Protector, a warning is displayed that the configuration check failed. Click **OK** to open the Configure VMware dialog box and provide the connection parameters as described in “[Configuring VMware management clients](#)” on page 39.

In **Application database**, select a datacenter that you want to back up from (standalone ESX Server system has only one datacenter (`/ha-datacenter`)).

In **Backup method**, select a backup method.


Specify the **User and group/domain** options, which are available if an ESX Server or Windows Server 2008 VirtualCenter Server system is selected:

- **Specify OS:** On ESX Server clients, it is mandatory to specify the **Username** and **Group/Domain name** options. On Windows Server 2008 VirtualCenter Server systems, it is not mandatory to specify these options and if they are not specified, the backup runs under the Local System Account.
- **Username, Group/Domain name:** Specify the operating system user account under which you want the backup session to run (for example, the user name `root`, group `root`, or user name `Administrator`, domain `DP`). Ensure that this user has been added to the Data Protector `admin` or `operator` user group. This user becomes the backup owner.

If you selected an ESX Server client, ensure that this user also has the read, write, and execute permissions on the ESX Server datastores.


Click **Next**.

5. **Snapshot, Suspend, and VCBimage** backup methods: Select virtual machines or individual virtual machine disks that you want to back up.



**Figure 16 Selecting VMware objects (Snapshot, Suspend, VCBimage)**

**VCBfile** backup method: Right-click a virtual machine and click **Mount filesystem** to mount virtual machine filesystems. This may take some time. Then, select the files and folders that you want to back up.



**Figure 17 Selecting VMware objects (VCBfile)**

 **NOTE:**

The following note applies to all backup methods: if you select the client system at the top, all virtual machines in the datacenter will be selected for backup, including the virtual machines that you create after the backup specification is saved.

If your virtual machines are not configured yet, right-click the client system at the top or any of the virtual machines listed below, and click **Configure Virtual Machines**. For details, see “[Configuring virtual machines](#)” on page 43.

Click **Next**.


6. Select devices to use for the backup.

To specify device options, right-click the device and click **Properties**. Specify the number of parallel backup streams in the **Concurrency** tab and the media pool you will use.

Click **Next**.

7. Set backup options.

For information on application specific backup options, see [Table 9](#) on page 72.



**Figure 18 Application specific options**

Click **Next**.

8. Optionally, schedule the backup. See “[Scheduling backup specifications](#)” on page 72.

Click **Next**.

9. Save the backup specification, specifying a name and a backup specification group.

**TIP:**

Preview your backup specification before using it for real. See “[Previewing backup sessions](#)” on page 73.

**Table 9 VMware backup options**

Options	Description
<b>Pre-exec, Post-exec</b>	<p>The command specified here is run by <code>vmware_bar.exe</code> on the VMware management client before the backup (<code>pre-exec</code>) or after it (<code>post-exec</code>).</p> <p>Do not use double quotes. Type only the name of the command and ensure that the command resides in the following directory:</p> <p><b>VirtualCenter Server system:</b> <code>Data_Protector_home\bin</code></p> <p><b>Standalone ESX Server system:</b> <code>/opt/omni/bin</code></p>
<b>Backup memory file</b>	<p>Available only for the <b>Snapshot</b> and <b>Suspend</b> backup methods.</p> <p>If this option is selected, the memory of a running virtual machine is saved into a file and backed up. Note that the backup takes considerably longer if this option is selected.</p>

## Modifying backup specifications

To modify your backup specification, click its name in the Scoping Pane of the Backup context, then click the appropriate tab, and apply the changes.

## Scheduling backup specifications


You can run unattended backups at specific times or periodically. For details on scheduling, see the online Help index: “scheduled backups”.

### Scheduling example

To schedule differential backups at 8:00, 13:00, and 18:00 during week days:

1. In the **Schedule** property page of the backup specification, select the starting date in the calendar and click **Add** to open the **Schedule Backup** dialog box.

- Under **Recurring**, select **Weekly**. Under **Time options**, select **8:00**. Under **Recurring Options**, select **Mon, Tue, Wed, Thu, and Fri**. See [Figure 19](#) on page 73. Under **Session options**, select **Differential** from the **Backup type** drop-down list.  
Click **OK**.
- Repeat [Step 1](#) and [Step 2](#) to schedule differential backups at 13:00 and 18:00.
- Click **Apply** to save the changes.



**Figure 19 Scheduling a backup specification**

## Previewing backup sessions

Preview the backup session to test it. You can use the Data Protector GUI or CLI.

### Using the Data Protector GUI

- In the Context List, click **Backup**.
- In the Scoping Pane, expand **Backup Specifications** and then **VMware**. Right-click the backup specification you want to preview and click **Preview Backup**.

3. Specify the **Backup type** and **Network load**. Click **OK**.

The message `Session completed successfully` is displayed at the end of a successful preview.

## Using the Data Protector CLI

1. Log in to the VMware management client under a user account that is configured as described in “[Configuring VMware users](#)” on page 38.
2. Go to the following directory:

**VirtualCenter Server system:** `Data_Protector_home\bin`

**Standalone ESX Server system:** `/opt/omni/lbin`

3. Run:

```
omnib -vmware_list BackupSpecificationName -test_bar
```

## What happens during the preview?

The following is tested:

- Communication between the VMware management client and Data Protector
- The syntax of the backup specification
- If devices are correctly specified
- If the necessary media are in the devices

## Starting backup sessions

Interactive backups are run on demand. They are useful for urgent backups or restarting failed backups.

To start a backup, use the Data Protector GUI or CLI.

## Using the Data Protector GUI

1. In the Context List, click **Backup**.
2. In the Scoping Pane, expand **Backup Specifications**, and then **VMware**. Right-click the backup specification you want to start and click **Start Backup**.
3. Specify **Backup type** and **Network load**. Click **OK**.

The message `Session completed successfully` is displayed at the end of a successful backup session.

## Using the Data Protector CLI

1. Log in to the VMware management client under a user account that is configured as described in “[Configuring VMware users](#)” on page 38.
2. Go to the following directory:

**VirtualCenter Server system:** `Data_Protector_home\bin`

**Standalone ESX Server system:** `/opt/omni/lbin`

3. Run:

```
omnib -vmware_list BackupSpecificationName [-barmode VMwareMode] [ListOptions]
```

where `VMwareMode` is one of the following backup types:

```
full|incr|diff
```

The default is `full`.

For `ListOptions`, see the `omnib` man page or the *HP Data Protector command line interface reference*.

## Examples

To start a full backup using the backup specification `snapshot2`, run:

```
omnib -vmware_list snapshot2 -barmode full
```

To start a differential backup using the same backup specification, run:

```
omnib -vmware_list snapshot2 -barmode diff
```

## Preparing for disaster recovery

To do a disaster recovery, you need backups of the following VMware objects:

**Table 10 What must be backed up**

VMware objects	How to back up
ESX Server console	<ol style="list-style-type: none"><li>1. Ensure that the Data Protector <code>Disk Agent</code> component is installed on all the ESX Server systems.</li><li>2. In the Backup context of the Data Protector GUI, right-click <b>Filesystem</b> and click <b>Add backup</b> to create a backup specification of the filesystem type. In the Source page of the backup specification, select ESX Server consoles of all ESX Server systems.  For details on what to back up, see the topic “ESX Server Configuration Backup and Restore procedure” at <a href="http://kb.vmware.com/selfservice/microsites/microsite.do">http://kb.vmware.com/selfservice/microsites/microsite.do</a>.</li><li>3. Start a backup using the newly created backup specification.</li></ol>
VirtualCenter configuration database (applicable only for VirtualCenter environments)	<p>The VirtualCenter configuration database can be an Oracle database or Microsoft SQL Server database. To back up the database, use the corresponding Data Protector integration. For example, if it is an Oracle database, follow these steps:</p> <ol style="list-style-type: none"><li>1. Ensure that the Data Protector <code>Oracle Integration</code> component is installed on the VirtualCenter Server system.</li><li>2. In the Backup context of the Data Protector GUI, right-click <b>Oracle Server</b> and click <b>Add backup</b> to create a backup specification of the Oracle type. In <b>Application database</b>, type the name of the VirtualCenter configuration database.  Continue with the backup specification creation as described in the <i>HP Data Protector integration guide for Oracle and SAP</i>.</li><li>3. Start a backup using the newly created backup specification.</li></ol>
VMware virtual machines	Back up the virtual machines as described in this chapter.

# Restore

You can restore virtual machines and filesystems of virtual machines using the Data Protector GUI or CLI.

## Restore of virtual machines

Virtual machines backed up with the **Snapshot**, **Suspend**, or **VCBimage** method can be restored in two ways, depending on what you select in the **Application database** restore option. You can select a datacenter or **None (restore files to client)**.

### Application database: Datacenter

If you select a datacenter in the **Application database** option, virtual machines are restored to the original ESX Server and/or ESXi Server systems. For the restore, you can also specify the following:

- Whether existing virtual machine files should be overwritten with files from the backup or left intact
- Whether the restored virtual machine files should be consolidated when the restore completes
- Whether the restored virtual machines should be registered in the datacenter, and powered on

Usually, you specify the original datacenter in the **Application database** option. Specifying a different datacenter is allowed only in the case of a disaster recovery when the new datacenter has a different name from the original one. Do not restore a virtual machine to a different datacenter in order to clone the virtual machine because this leads to licensing and network problems (mostly because the virtual machine UUID gets duplicated).

---

 **IMPORTANT:**

Since the Data Protector `VMware Integration` component cannot be installed on ESXi Server systems, virtual machines backed up from ESXi Server systems can be restored back to the original ESXi Server systems only if there is an ESX Server system (with the `VMware Integration` component installed) in the same datacenter, having access to the virtual machine datastores.

If the connection with the target ESX Server or ESXi Server system cannot be established, the virtual machines are automatically restored to the client specified in the **Restore client** option as if **None (restore files to client)** had been selected in the **Application database** option (see [Application database: None \(restore files to client\)](#)). However, if the `omnirc` variable `OB2_VMWARE_PATH` on the restore client has not been set, the restore fails.

---

## Application database: None (restore files to client)

If you select **None (restore files to client)** in the **Application database** option, virtual machines are restored to the client specified in the **Restore client** option. This destination client can be any client with the `VMware Integration` component installed, but typically it is a VCB proxy system. During such a restore, the virtual machine files are restored to the directory specified in the destination client `omnirc` variable `OB2_VMWARE_PATH` (for example, `C:\tmp`). Therefore, before you start the restore session, ensure that the `omnirc` variable `OB2_VMWARE_PATH` is set. For details, on how to set `omnirc` variables, see the online Help index: "omnirc option".

After such a restore (**restore outside of a datacenter**), the virtual machines are not functional. You need to manually move the restored virtual machine images to an ESX Server or ESXi Server system, using the VMware Converter as described in "[Recovery after restoring outside of a datacenter](#)" on page 92.

## Restore of filesystems

Filesystems of virtual machines backed up with the **VCBfile** method can be restored to the original virtual machine or to any Windows system (physical or virtual) that has the `VMware Integration` component installed. You can also specify what to do if the files to be restored already exist on the destination client: you may keep or overwrite them.

## Considerations

- **Restore chain:** When you restore a virtual machine from an incremental or differential **Snapshot** or **Suspend** session, Data Protector automatically restores the complete backup chain, starting with the last full backup, which is then followed by the last differential and all subsequent incremental backups (if they exist) up to the selected session.
- **Backup proxy:** A restore session from a **VCBfile** or **VCBimage** backup does not involve a backup proxy system. VMware objects are restored directly to specified clients.
- **Concurrent sessions:** Restore sessions that use the same devices or restore the same datacenter cannot run concurrently.
- **Different backup methods:** VMware objects that were created using different backup methods cannot be restored in the same session.

## Finding information for restore

You can find information about backup objects in the Data Protector IDB, such as which backup type and media were used, and which messages were displayed during the backup. To retrieve this information, use the Data Protector GUI or CLI.


## Using the Data Protector GUI

In the Internal Database context, expand **Objects** or **Sessions**.

If you expand **Objects**, backup objects are sorted according to the virtual machine for which they were created. For example, backup objects for the virtual machine /vm/mach1 from the datacenter ELDatacentro are listed under /%2FE1datacentro/0/%2Fvm%2Fmach1.

If you expand **Sessions**, backup objects are sorted according to the session in which they were created. For example, backup objects created in the session 2008/08/15-7 are listed under 2008/08/15-7.

To view details on a backup object, right-click the backup object and click **Properties**.



**Figure 20 Backup object information**



**TIP:**

To view the messages displayed during the session, click the **Messages** tab.

## Using the Data Protector CLI

1. Log in to the VMware management client under a user account that is configured as described in “Configuring VMware users” on page 38.

2. Go to the following directory:

**VirtualCenter Server system:** `Data_Protector_home\bin`

**Standalone ESX Server system:** `/opt/omni/sbin`

3. Get a list of VMware backup objects created in a particular backup session:

```
omnidb -session SessionID
```

4. Get details on a particular backup object:

```
omnidb -vmware BackupObjectName -session SessionID -catalog
```

Here is one example of a backup object name:

```
gabriel.company.com::/%2FE1Datacentro/0/%2Fvm%2Fharbour
```

For details, see the omnidb man page or the *HP Data Protector command line interface reference*.

## Restoring using the Data Protector GUI

1. In the Context List, click **Restore**.
2. In the Scoping Pane, expand **VMware**, expand the VMware management client and click the datacenter you want to restore.

3. In the Source page, Data Protector displays VMware objects that were backed up with the method specified in **Backup method**. To display VMware objects that were backed up with a different method, change **Backup method**.

---

 **NOTE:**

VMware objects that were created using different backup methods cannot be restored in the same session.

---

By using the **From** and **To** options, you narrow the scope of displayed virtual machines to those backed up within the specified time interval.


Select the VMware objects that you want to restore.

---


 **NOTE:**

Data Protector restores each selected VMware object from the last backup session performed during the specified time interval.

---




**Figure 21 Selecting VMware objects for restore (Snapshot, Suspend, VCBimage)**




**Figure 22 Selecting VMware objects for restore (VCBfile)**

4. In the **Options** page, specify the VMware restore options. For details, see [Table 11](#) on page 86.



**Figure 23 Restore options (Snapshot, Suspend, VCBImage)**



**Figure 24 Restore options (VCBfile)**

**IMPORTANT:**

If you restore from a **Snapshot** backup in which individual virtual machine disks were backed up, clear the option **Register virtual machines if needed**. Otherwise, the restore fails.

Whenever you restore with the option **Register virtual machines if needed** cleared, you need to manually recover the virtual machine after the session completes. For details, see [“Recovery after restoring to a datacenter”](#) on page 100.

5. In the **Devices** page, select devices to use for restore.
6. Click **Restore**.

7. In the **Start Restore Session** dialog box, click **Next**.
8. Specify **Report level** and **Network load**.

Click **Finish** to start the restore.

The message `Session completed successfully` is displayed at the end of a successful session.

**Table 11 VMware restore options**

GUI/CLI option	Description
<b>Restore client/</b> -destination	<p>Specifies the client that the restore session is started on. By default, the session is started on the same client on which the backup was started.</p> <p>Change the default only in the case of a disaster recovery when you restore from a <b>Suspend, Snapshot</b>, or <b>VCBimage</b> backup and the new VMware management client does not have the same name as the original one. Ensure that the new client has access to all the required datastores.</p> <p>You can also change the default if you want to restore the virtual machines outside of a datacenter, in which case you must specify the client to restore to.</p> <p>If you select a client that has not been configured for use with the Data Protector VMware Virtual Infrastructure integration, a warning is displayed. Click <b>OK</b> and configure the client as described in <a href="#">“Configuring VMware management clients”</a> on page 39. However, to restore outside of a datacenter, you do not need to configure the destination client, just click <b>Cancel</b>.</p> <p>To change the configuration of the selected client, click the <b>Connection</b> button.</p>

GUI/CLI option	Description
<b>Application database/ -newinstance</b>	<p>Specifies the datacenter that the virtual machines are restored to. By default, the virtual machines are restored to the original datacenter. Change the default only in the case of a disaster recovery when the new datacenter does not have the same name as the original one.</p> <p>You can also change the default if you want to restore the virtual machines outside of a datacenter, in which case you should select <b>None (restore files to client)</b>. Consequently, the virtual machines are restored to the client specified in <b>Restore client</b>, to the directory specified in the client <code>omnirc</code> variable <code>OB2_VMWARE_PATH</code>.</p> <p>This option is not applicable if you restore from a <b>VCBfile</b> backup.</p>
<b>Restore memory state if available/ -memory</b>	<p>Select this option to restore the virtual machine memory file as well if it was backed up.</p> <p>This option is not available if <b>None (restore files to client)</b> is selected in <b>Application database</b> or if you restore from a <b>VCBfile</b> backup.</p> <p>Default: OFF</p>
<b>Register virtual machines if needed/ -register</b>	<p>Select this option to register restored virtual machines. Clear this option if you restore from a <b>Snapshot</b> backup in which individual virtual machine disks were backed up. Otherwise, the restore fails.</p> <p>If this option is not selected, you need to manually recover the restored virtual machines as described in <a href="#">"Recovering virtual machines manually"</a> on page 92.</p> <p>This option is not available if <b>None (restore files to client)</b> is selected in <b>Application database</b> or if you restore from a <b>VCBfile</b> backup.</p> <p>Default: OFF</p>
<b>Consolidate snapshots to single file/ -consolidate</b>	<p>This option is applicable only if <b>Register virtual machines if needed</b> is selected. Select this option to commit all existing snapshots (including non-Data Protector ones) to the virtual machine base when the restore completes.</p> <p>This option is not available if <b>None (restore files to client)</b> is selected in <b>Application database</b> or if you restore from a <b>VCBfile</b> backup.</p> <p>Default: OFF</p>

GUI/CLI option	Description						
<b>Power-on virtual machines after restore/</b> -poweron	<p>This option is applicable only if <b>Register virtual machines if needed</b> is selected. Select this option to put the newly-restored virtual machines online when the session completes.</p> <p>This option is not available if <b>None (restore files to client)</b> is selected in <b>Application database</b> or if you restore from a <b>VCBfile</b> backup.</p> <p>Default: OFF</p>						
<b>File conflict handling/</b> -overwrite [older]	<p>Specifies Data Protector's behavior if virtual machines or files to be restored already exist in the destination. The file handling options have different meanings, depending on whether you restore from a <b>Snapshot</b>, <b>Suspend</b>, <b>VCBimage</b>, or <b>VCBfile</b> backup.</p> <p>Note that if you restore from a <b>Snapshot</b>, <b>Suspend</b>, or <b>VCBimage</b> backup and at the same time you select <b>None (restore files to client)</b> in <b>Application database</b>, the same description applies as if you restored from a <b>VCBfile</b> backup.</p> <table border="1" data-bbox="451 725 1165 1315"> <tbody> <tr> <td data-bbox="451 725 562 913"><b>Overwrite</b> (default)</td> <td data-bbox="562 725 1165 913"> <p><b>Snapshot, Suspend, VCBimage:</b> Data Protector unregisters such virtual machines, deletes their files, and then restores them from the backup.</p> <p><b>VCBfile:</b> Data Protector overwrites such files with those from the backup.</p> </td> </tr> <tr> <td data-bbox="451 913 562 1130"><b>Keep latest</b></td> <td data-bbox="562 913 1165 1130"> <p><b>Snapshot, Suspend, VCBimage:</b> Data Protector leaves such virtual machines intact. They are not restored from the backup.</p> <p><b>VCBfile:</b> Data Protector leaves such files intact only if they are more recent than those from the backup. Otherwise, such files are overwritten with those from the backup.</p> </td> </tr> <tr> <td data-bbox="451 1130 562 1315"><b>Skip</b></td> <td data-bbox="562 1130 1165 1315"> <p><b>Snapshot, Suspend, VCBimage:</b> Data Protector leaves such virtual machines intact. They are not restored from the backup.</p> <p><b>VCBfile:</b> Data Protector leaves such files intact. They are not restored from the backup.</p> </td> </tr> </tbody> </table>	<b>Overwrite</b> (default)	<p><b>Snapshot, Suspend, VCBimage:</b> Data Protector unregisters such virtual machines, deletes their files, and then restores them from the backup.</p> <p><b>VCBfile:</b> Data Protector overwrites such files with those from the backup.</p>	<b>Keep latest</b>	<p><b>Snapshot, Suspend, VCBimage:</b> Data Protector leaves such virtual machines intact. They are not restored from the backup.</p> <p><b>VCBfile:</b> Data Protector leaves such files intact only if they are more recent than those from the backup. Otherwise, such files are overwritten with those from the backup.</p>	<b>Skip</b>	<p><b>Snapshot, Suspend, VCBimage:</b> Data Protector leaves such virtual machines intact. They are not restored from the backup.</p> <p><b>VCBfile:</b> Data Protector leaves such files intact. They are not restored from the backup.</p>
<b>Overwrite</b> (default)	<p><b>Snapshot, Suspend, VCBimage:</b> Data Protector unregisters such virtual machines, deletes their files, and then restores them from the backup.</p> <p><b>VCBfile:</b> Data Protector overwrites such files with those from the backup.</p>						
<b>Keep latest</b>	<p><b>Snapshot, Suspend, VCBimage:</b> Data Protector leaves such virtual machines intact. They are not restored from the backup.</p> <p><b>VCBfile:</b> Data Protector leaves such files intact only if they are more recent than those from the backup. Otherwise, such files are overwritten with those from the backup.</p>						
<b>Skip</b>	<p><b>Snapshot, Suspend, VCBimage:</b> Data Protector leaves such virtual machines intact. They are not restored from the backup.</p> <p><b>VCBfile:</b> Data Protector leaves such files intact. They are not restored from the backup.</p>						

GUI/CLI option	Description
<b>Target hosts for restore/</b> -target	This option is available only if you restore from a <b>VCBfile</b> backup. Specifies where to restore filesystems of virtual machines. The target system can be any Windows system (physical or virtual).

## Restoring using the Data Protector CLI

1. Log in to the VMware management client under a user account that is configured as described in “[Configuring VMware users](#)” on page 38.

2. Go to the following directory:

**VirtualCenter Server system:** `Data_Protector_home\bin`

**Standalone ESX Server system:** `/opt/omni/lbin`

### 3. Run:

#### ***Restore of virtual machines:***

```
omnir -vmware
-barhost OriginalVMwareManagementClient
-instance OriginalDatacenter
-method {Snapshot | Suspend | VCBimage}
[-session SessionID]
VirtualMachines [-disk Disk [-disk Disk...]]
[VirtualMachines [-disk Disk [-disk Disk...]]...]
[-destination RestoreClient]
[-newinstance TargetDatacenter]
[-consolidate]
[-memory]
[-register]
[-poweron]
[-overwrite [older]]
```

#### ***Restore of filesystems:***

```
omnir -vmware
-barhost OriginalVMwareManagementClient
-instance OriginalDatacenter
-method VCBfile
[-session SessionID]
VirtualMachines -target TargetClient [-file File [-file File...]]
[VirtualMachines -target TargetClient [-file File [-file File...]]...]
[-destination RestoreClient]
[-overwrite [older]]
```

where *VirtualMachines* must be specified in one of the following ways:

```
{
-all [-exclude VMFolder [-exclude VMFolder...]] |
-vmfolder VMFolder [-exclude VMFolder [-exclude VMFolder...]] |
-vm VM
}
```

For description of all the options, see the `omnir` man page or the *HP Data Protector command line interface reference*.

### Example (Restoring virtual machines to a datacenter)

Suppose you want to restore the virtual machine `/vm/machineA` and the individual disks (`scsi0:0` and `scsi0:1`) of the virtual machine `/vm/machineB`. At the time of backup, the virtual machines were running on the ESX Server systems that belonged

to the datacenter /MyDatacenter managed by the VirtualCenter Server system Virtualcenter.company.com. The virtual machines were backed up with the Suspend backup method.

You want to restore them to the original location, using the backup session 2008/07/14-1. If, in this session, virtual machine memory files were also backed up, you want to restore them as well. You also want to ensure that the newly restored virtual machines are put online when the session completes.

Run:

```
omnir -vmware -barhost Virtualcenter.company.com -instance /MyDatacenter -method Suspend -session 2008/7/14-1 -vm /vm/machineA -vm /vm/machineB -disk scsi0:0 -disk scsi0:1 -memory -poweron
```

### Example (Restoring virtual machines outside of a datacenter)

Suppose the virtual machines /MyVirtualMachines/machineA and /MyVirtualMachines/machineB were backed up in the session 2009/8/14-5 from the datacenter /MyDatacenter that is managed by the VirtualCenter Server system VirtualCenter.company.com, using the VCBimage backup method. To restore the virtual machines outside of the datacenter, to the directory C:\tmp on the VCB proxy system proxy.company.com:

1. Log in to the VCB proxy system.
2. Set the omnirc variable OB2\_VMWARE\_PATH to C:\tmp.
3. Run:

```
omnir -vmware -barhost VirtualCenter.company.com -instance /MyDatacenter -method VCBimage -session 2009/8/14-5 -vm /MyVirtualMachines/machineA -vm /MyVirtualMachines/machineB -destination proxy.company.com -newinstance "None"
```

### Example (Restoring filesystems of virtual machines)

Suppose you want to restore all filesystems of all the virtual machines contained in the Virtual Infrastructure inventory folder /MyVirtualMachines, except the filesystems of the virtual machine /MyVirtualMachines/MachineA. The restore destination is the Windows client computer1.company.com.

In addition, you want to restore the C:\Documents and Settings folder and the file C:\Test\Schedule.txt of the virtual machine /MyVirtualMachines2/MachineB back to the same virtual machine

MachineB.company.com. The virtual machines were backed up from the datacenter /MyDatacenter that was managed by the VirtualCenter Server system VirtualCenter.company.com. You want to restore from the last backup session.

Run:

```
omnir -vmware -barhost VirtualCenter.company.com -instance /MyDatacenter -method VCBfile -vmfolder /MyVirtualMachines -exclude /MyVirtualMachines/MachineA -target computer1.company.com -vm /MyVirtualMachines2/MachineB -target MachineB.company.com -file "C/Documents and Settings" -file C/Test/Schedule.txt
```

## Recovering virtual machines manually

There are two different scenarios when you need to manually recover virtual machines after they have been restored with Data Protector:

- If you have restored the virtual machine files to a directory on a Data Protector client due to one of the following reasons:
  - You selected **None (restore files to client)** in the **Application database** restore option.
  - You selected a datacenter in the **Application database** restore option but the connection with the target ESX Server or ESXi Server system could not be established.

See [“Recovery after restoring outside of a datacenter”](#) on page 92.

- If you have restored the virtual machine files to the original ESX Server and/or ESXi Server systems by selecting a datacenter in the **Application database** restore option, however, without selecting the restore option **Register virtual machines if needed** (see [“Recovery after restoring to a datacenter”](#) on page 100).

## Recovery after restoring outside of a datacenter

Suppose the virtual machine FreeBSD 8.0 beta2 i386 was backed up in the **VCBimage** backup session 2009/07/07-2 and you have restored the virtual machine to the directory C:\tmp on the VCB proxy system droid.company.com.

To manually move the restored virtual machine image to the ESXi Server system srsen.company.com managed by the VirtualCenter Server system volk.company.com, using the VMware Converter:

1. Display the content of the restored directory C:\tmp\FreeBSD 8.0 beta2 i386:

```
catalog_2009_07_17_0002
FreeBSD 8.0 beta2 i386.vmdk_2009_07_17_0002
FreeBSD 8.0 beta2 i386.vmx_2009_07_17_0002
scsi0-0-0-FreeBSD 8.0 beta2 i386-flat.vmdk_2009_07_17_0002
```

2. Delete the backup session IDs appended at the end of the filenames:

```
catalog
FreeBSD 8.0 beta2 i386.vmdk
FreeBSD 8.0 beta2 i386.vmx
scsi0-0-0-FreeBSD 8.0 beta2 i386-flat.vmdk
```

3. Open the catalog file with a text editor:


```
catalog
version= esx-3.0
state= poweredOn
display_name= "FreeBSD 8.0 beta2 i386"
uuid= "503d98d9-cad4-5c0e-9132-b35de35b900d"
disk.scsi0:0.filename= "scsi0-0-0-FreeBSD 8.0 beta2 i386.vmdk"
disk.scsi0:0.diskname= "[Storage_VmWare_all] FreeBSD 8.0 beta2
i386/FreeBSD 8.0 beta2 i386.vmdk"
config.vmx= "[Storage_VmWare_all] FreeBSD 8.0 beta2 i386/FreeBSD
8.0 beta2 i386.vmx"
host= srsen.company.com
timestamp= "Fri Jul 17 05:52:17 2009"
config.suspenddir= "[Storage_VmWare_all] FreeBSD 8.0 beta2 i386/"
config.snapshotdir= "[Storage_VmWare_all] FreeBSD 8.0 beta2 i386/"
config.file0= "FreeBSD 8.0 beta2 i386.vmsd"
config.file1= "FreeBSD 8.0 beta2 i386.vmx"
config.file2= "FreeBSD 8.0 beta2 i386.nvram"
config.logdir= "[Storage_VmWare_all] FreeBSD 8.0 beta2 i386/"
config.log0= "vmware.log"
folderpath= "/Datacenters/europa/vm"
resourcepool= "/Datacenters/europa/host/srsen.company.com/Resources"
```

The name specified in the `disk.scsi0:0.filename` catalog variable and the name of the base metadata file residing in the folder must match. Therefore, rename the base metadata file `FreeBSD 8.0 beta2 i386.vmdk` to `scsi0-0-0-FreeBSD 8.0 beta2 i386.vmdk`:

```
catalog
scsi0-0-0-FreeBSD 8.0 beta2 i386.vmdk
FreeBSD 8.0 beta2 i386.vmx
scsi0-0-0-FreeBSD 8.0 beta2 i386-flat.vmdk
```

4. Share the folder `C:\tmp\FreeBSD 8.0 beta2 i386` so that it is accessible from the VirtualCenter Server system.
5. Log in to the VirtualCenter Server system and open the VMware Converter user interface.
6. Click the **Convert Machine** button to open the **Conversion** wizard.

7. In the **Specify Source** page, select **Backup image or third-party virtual machine** for the source type and `\\droid\tmp\FreeBSD 8.0 beta2 i386\FreeBSD 8.0 beta2 i386.vmx` for the virtual machine.



**Figure 25 Conversion – Specify Source**

Click **Next**.

8. In the **Specify Destination (Destination Type)** page, provide the login information for the VirtualCenter Server system.

**Conversion**

1 Specify Source    2 **Specify Destination**    3 View/Edit Options    4 Ready to Complete

**Destination Type**    Host/Resource

**Source:** \\droid\tmp\FreeBSD...0 beta2 i386\FreeBSD 8.0 beta2 i386.vmx    **Destination:** none

Select destination type: VMware Infrastructure virtual machine

Creates a new virtual machine for use on a VMware Infrastructure product.

— VMware Infrastructure server details —

Server:


User name:

Password:

**Figure 26 Conversion – Specify Destination 1**

Click **Next**.


9. In the **Specify Destination (Host/Resource)** page, specify the destination ESXi Server system `srsen.company.com`.



**Figure 27 Conversion – Specify Destination 2**

Click **Next**.


10. In the **View/Edit Options** page, modify the options (optional).



**Figure 28 Conversion – View/Edit Options**

Click **Next**.

11. In the **Ready to Complete** page, review your selection and click **Finish**.



**Figure 29 Conversion – Ready to Complete**

12. After a while, the VMware Converter informs you about the successful recovery.




Figure 30 Recovery completed

## Recovery after restoring to a datacenter

The following procedure enables you to import restored virtual machine disks into a new or an existing virtual machine. Use this procedure if you have restored individual virtual machine disks or virtual machines to the original ESX Server or ESXi Server system (**Application database**: datacenter), however, without selecting the option **Register virtual machines if needed**. Note that after such a restore, the original virtual machines are no longer registered. So in case you decide to import the disks into new virtual machines, the new virtual machines can have the same names as the original ones.

However, before you import the disks, you have to prepare the disks first, depending on the backup you restored from:

- **Snapshot**: Link and consolidate virtual machine disk files.
- **Suspend**: Consolidate virtual machine disk files.

- **VCBimage:** No preparatory steps are required.

### Linking virtual machine disk files

The procedure for linking virtual machine disk files is described using the following example:

**Table 12 Virtual machine information**

Virtual machine	helios
Virtual machine disks	<ul style="list-style-type: none"> <li>• scsi0:0 (1.2 GB) base metadata file: helios.vmdk base extent file: helios-flat.vmdk</li> <li>• scsi1:2 (1.0 GB) base metadata file: helios_1.vmdk base extent file: helios_1-flat.vmdk</li> </ul>
Datstore	storage2

Suppose you backed up the virtual machine disk `scsi1:2` in the following **Snapshot** backup sessions:

1. **Full** (2008/09/10-1)
2. **Incr** (2008/09/10-2)
3. **Differential** (2008/09/10-3)
4. **Incr** (2008/09/10-4)

When you restore the virtual machine disk `scsi1:2` from the session 2008/09/10-4, Data Protector automatically restores the complete restore chain:

1. 2008/09/10-1 (full backup)
2. 2008/09/10-3 (differential backup)
3. 2008/09/10-4 (incremental backup)

After the restore, you need to manually update the content of `scsi1:2` metadata files by correcting the extent file names and metadata parent file names:

## 1. Display the content of the restored directory

/vmfs/volumes/storage2/helios/:

```
.  
..  
helios_1-000001-delta.vmdk.2008_09_10_0003  
helios_1-000001.vmdk.2008_09_10_0003  
helios_1-000002-delta.vmdk.2008_09_10_0004  
helios_1-000002.vmdk.2008_09_10_0004  
helios_1-flat.vmdk.2008_09_10_0001  
helios_1.vmdk.2008_09_10_0001  
helios.nvram.2008_09_10_0001  
helios.nvram.2008_09_10_0003  
helios.nvram.2008_09_10_0004  
helios-Snapshot1.vmsn.2008_09_10_0001  
helios-Snapshot4.vmsn.2008_09_10_0003  
helios-Snapshot5.vmsn.2008_09_10_0004  
helios.vmsd.2008_09_10_0001  
helios.vmsd.2008_09_10_0003  
helios.vmsd.2008_09_10_0004  
helios.vmx.2008_09_10_0001  
helios.vmx.2008_09_10_0003  
helios.vmx.2008_09_10_0004  
helios.vmx.2008_09_10_0004  
helios.vmx.2008_09_10_0001  
helios.vmx.2008_09_10_0003  
helios.vmx.2008_09_10_0004
```

## 2. Identify the scsi1:2 metadata files:

```
helios_1.vmdk.2008_09_10_0001  
helios_1-000001.vmdk.2008_09_10_0003  
helios_1-000002.vmdk.2008_09_10_0004
```

Identify the corresponding extent files:

```
helios_1-flat.vmdk.2008_09_10_0001  
helios_1-000001-delta.vmdk.2008_09_10_0003  
helios_1-000002-delta.vmdk.2008_09_10_0004
```

The correct sequence in which the metadata files should be linked is determined from timestamps appended at the end of filenames. The metadata file `helios_1.vmdk.2008_09_10_0001` is the parent of `helios_1-000001.vmdk.2008_09_10_0003`, which is the parent of `helios_1-000002.vmdk.2008_09_10_0004`.

**3. Open the base metadata file `helios_1.vmdk.2008_09_10_0001`:**

```
# Disk DescriptorFile
version=1
CID=d0fb6c81
parentCID=ffffffff
createType="vmfs"

# Extent description
RW 2097152 VMFS "helios_1-flat.vmdk"
# The Disk Data Base
#DDB
ddb.virtualHWVersion = "4"
ddb.geometry.cylinders = "512"
ddb.geometry.heads = "128"
ddb.geometry.sectors = "32"
ddb.adapterType = "lsilogic"
```

Change the extent file name `helios_1-flat.vmdk` to `helios_1-flat.vmdk.2008_09_10_0001`.

**4. Open the snapshot metadata file `helios_1-000001.vmdk.2008_09_10_0003`:**

```
# Disk DescriptorFile
version=1
CID=d0fb6c81
parentCID=d0fb6c81
createType="vmfsSparse"
parentFileNameHint="helios_1.vmdk"
# Extent description
RW 2097152 VMFSSPARSE "helios_1-000001-delta.vmdk"
# The Disk Data Base
#DDB
```

Change the parent metadata file name `helios_1.vmdk` to `helios_1.vmdk.2008_09_10_0001`. Change the extent file name `helios_1-000001-delta.vmdk` to `helios_1-000001-delta.vmdk.2008_09_10_0003`.

## 5. Open the snapshot metadata file

helios\_1-000002.vmdk.2008\_09\_10\_0004:

```
# Disk DescriptorFile
version=1
CID=d0fb6c81
parentCID=d0fb6c81
createType="vmfsSparse"
parentFileNameHint="helios_1-000001.vmdk"
# Extent description
RW 2097152 VMFSSPARSE "helios_1-000002-delta.vmdk"
# The Disk Data Base
#DDB
```

Change the parent metadata file name `helios_1-000001.vmdk` to `helios_1-000001.vmdk.2008_09_10_0003`. Change the extent file name `helios_1-000002-delta.vmdk` to `helios_1-000002-delta.vmdk.2008_09_10_0004`.

## Consolidating virtual machine disks

1. Connect to the ESX Server system to which the virtual machine was restored.
2. Run:

```
vmkfstools --clonevirtualdisk LastMetadataFile
RecoveredDisk
```

For example:


```
vmkfstools --clonevirtualdisk
helios_1-000002.vmdk.2008_09_10_0004
helios_1_recovered.vmdk
```

As a result, the file `helios_1_recovered.vmdk` is created in the directory `/vmfs/volumes/storage2/helios/`.

## Importing virtual machine disks

To import the virtual machine disk `helios_1_recovered.vmdk` into the virtual machine `galaxy`:


1. Open the Virtual Infrastructure Client.



**Figure 31 Virtual Infrastructure Client**

Right-click the virtual machine `galaxy` and click **Edit Settings**.


2. In the Virtual Machine Properties dialog box, select **Hard Disk 1** and click **Add**.



**Figure 32 Virtual machine properties**

3. In the Select Device Type page of the Add Hardware wizard, select **Hard disk** and click **Next**.
4. In the Select a Disk page of the Add Hardware wizard, select **Use an existing virtual disk** and click **Next**.
5. In the Select Existing Disk page of the Add Hardware wizard, click **Browse**.


6. In the Browse Datastores dialog box, browse to /vmfs/volumes/storage2/helios, select helios\_1\_recovered.vmdk and click **Open**.



**Figure 33 Browsing datastores**

7. In the Advanced Options page of the Add Hardware wizard, select a Virtual Device Node for the new disk and click **Next**.

8. In the Ready to Complete page of the Add Hardware wizard, review your selection and click **Finish**.



**Figure 34** Add hardware summary

## Restoring using another device

You can restore using a device other than that used for backup. For details, see the online Help index: “restore, selecting devices for”.

## Disaster recovery

Disaster recovery is very complex, involving different products from different vendors. Check the instructions from the guest operating systems and VMware on how to prepare for it.

The following are the main steps needed to recover a virtual machine after a disaster:

1. Reinstall the VMware environment. The configuration should be the same as during the backup. Although the new VMware management client and datacenters may have different names, ensure that the datastores have the same names as the original ones. Otherwise, the restore fails.
2. Install Data Protector in the newly configured environment.

3. Restore the service console of the ESX Server system on which the virtual machine was running to the newly configured ESX Server system from a Data Protector filesystem backup.

For details on what to restore, see the topic “ESX Server Configuration Backup and Restore procedure” at <http://kb.vmware.com/selfservice/microsites/microsite.do>.

For details on how to restore from a filesystem backup, see the online Help.

4. Restore the original VirtualCenter database (if needed). For details, see the Data Protector integration that was used to back up the database.
5. Restore the virtual machine from a Data Protector VMware backup as described in “Restore” on page 77.

## Monitoring sessions

You can monitor currently running sessions in the Data Protector GUI. When you run a backup or restore session, a monitor window shows the progress of the session. Closing the GUI does not affect the session.

You can also monitor sessions from any Data Protector client with the `User Interface` component installed, using the `Monitor` context.

To monitor a session, see the online Help index: “viewing currently running sessions”.

## Troubleshooting

This section lists general checks and verifications, plus problems you might encounter when using the VMware integration.

For general Data Protector troubleshooting information, see the *HP Data Protector troubleshooting guide*.

## Before you begin

- Ensure that the latest official Data Protector patches are installed. See the online Help index: “patches” on how to verify this.
- See the *HP Data Protector product announcements, software notes, and references* for general Data Protector limitations, as well as recognized issues and workarounds.
- See <http://www.hp.com/support/manuals> for an up-to-date list of supported versions, platforms, and other information.

## Checks and verifications

If your configuration, backup, or restore failed:

- Examine system errors reported in the `debug.log` located in:  
**VirtualCenter Server system:** `Data_Protector_home\log`.  
**Standalone ESX Server system:** `/opt/omni/log`.
- Check if you can do a filesystem backup and restore on the problematic client. For information, see the online Help.

Additionally, if your backup failed:

- Check the configuration of the VirtualCenter Server or standalone ESX Server system as described in “[Configuring VMware management clients](#)” on page 39.

## Problems

### Problem

#### **Suspend backup fails with the error “IPC Cannot Connect”**

A **Suspend** backup of virtual machines running on ESX Server systems that are configured in a VirtualCenter environment fails with the `IPC Cannot Connect` error.

### Action

Ensure that the Data Protector VMware Integration agent is not blocked by the ESX Server firewall. For information on how to limit the range of port numbers from which dynamically allocated ports are selected, see the online Help index: “firewall support”.

### Problem

#### **Creation of a VCBfile backup specification fails with the error “IPC Cannot Connect”**

When you create a backup specification for a VCBfile backup and you try to mount filesystems of virtual machines in the Source page, Data Protector displays the `IPC Cannot Connect` error.

### Action

Ensure that the Data Protector VMware Integration agent is not blocked by the ESX Server firewall. For information on how to limit the range of port numbers from which dynamically allocated ports are selected, see the online Help index: “firewall support”.

## Problem

### Suspend backup fails with the error “insufficient resources to satisfy failover level”

This error may occur if your ESX Server systems are configured in a high availability cluster and one of the ESX Server systems fails. Consequently, the virtual machines from the failed system migrate elsewhere. If you start a **Suspend** backup of such virtual machines, the power-on operation at the end of the backup fails with an error similar to the following:

```
[Critical] From: OB2BAR_VMWARE_BAR@gabriel.company.com
"/ClusterDatacenter" Time: 7.4.2008 16:13:50 Virtual machine
'/vm/vmsan1': operation failed: Error: {
localizedMessage='Insufficient resources to satisfy configured
failover level for HA.';
```

## Action

1. Open the cluster settings dialog box in the Virtual Infrastructure client and select the option **Allow virtual machines to be powered on even if they violate availability constraints**.
2. Power on the virtual machines and restart the backup (if needed).

## Problem

### Orphaned virtual machines

When you open the Virtual Infrastructure client while the restore session is in progress, the virtual machines that are being restored are shaded and the note (orphaned) is added next to them.

This happens if you back up virtual machines from a datacenter that is managed by a VirtualCenter Server system and, then, restore the virtual machines, specifying a different client on which to start the restore. Specifically, you change the restore option **Restore client** from the VirtualCenter Server system to the ESX Server system on which the virtual machines were running. Consequently, the restore option **Application database** automatically changes to the datacenter `/ha-datacenter`. As a result, during restore, the virtual machines are unregistered inside the datacenter `/ha-datacenter`, but not inside the VirtualCenter Server datacenter from which they were backed up.

## Action

Do not change the restore destination. Changes are allowed only in case of a disaster recovery when the newly configured VirtualCenter systems, ESX Server systems, or datacenters have different names than the original ones.

## Problem

### **Backup fails if a VM filesystem is still mounted**

If not enough time passes between unmounting and mounting of a VM (mount point), the vcbMounter will report that it cannot create a directory, although the directory has been removed:

```
[2009-08-04 12:13:05.218 'vcbMounter' 712 error] Error: Cannot  
create directory c:\mount-p\26752.3
```

```
[2009-08-04 12:13:05.218 'vcbMounter' 712 error] An error  
occurred, cleaning up...
```

The issue appears only with interactive backups.

## Action

Restart the backup. The previous failed backup resulted in unmounted VMs, so the issue will not appear.

---

# 2 Integrating Sybase Server and Data Protector

## Introduction

This chapter explains how to configure and use the Data Protector Sybase Adaptive Server (**Sybase Server**) integration. It describes concepts and methods you need to understand to back up and restore Sybase databases.

Data Protector offers interactive and scheduled backups of the following types:

**Table 13 Backup types**

Full	Backs up all selected Sybase databases and transaction logs.
Trans	Backs up changes made to the transaction logs since the last backup of any type.

During backup, the database is online and actively used.

Sybase databases are restored using the `isql` utility. You can restore a database:


- To a specific point in time
- To a new database
- To another Sybase instance

This chapter provides information specific to the Data Protector Sybase Server integration. For general Data Protector procedures and options, see online Help.

## Integration concepts

Data Protector integrates with Sybase Backup Server through the Data Protector Database Library based on a common library called Data Protector **BAR** (Backup And Restore). The Data Protector Database Library channels communication between the Data Protector Session Manager, and, via the **Sybase Backup Server API**, the

Sybase Server **isql** utility. Figure 35 on page 114 shows the architecture of the Data Protector Sybase integration.



**Figure 35 Sybase integration architecture**

**Table 14 Legend**

SM	Data Protector Session Manager: Backup Session Manager during backup and Restore Session Manager during restore.
API	Sybase Backup Server Application Programming Interface.
Database Library	A set of Data Protector executables that enable data transfer between the Sybase Backup Server and Data Protector.
MA	Data Protector General Media Agent.
Backup Specification	A list of objects to be backed up, backup devices, and options to be used.
IDB	The Data Protector Internal Database.

The `isql` utility sends backup and restore commands (issued through the Data Protector GUI or CLI, or the Sybase `isql` command line interface) to Sybase Backup Server, initiating data transfer between Sybase databases and Data Protector media.

While Sybase Backup Server is responsible for read/write operations to disk, Data Protector manages devices and media used for backup and restore.

## Data Protector CLI commands

Run the Data Protector CLI commands from the following directories:

**Windows:** `Data_Protector_home\bin`

**UNIX:**

Command	Directory
<code>omnib</code>	<code>opt/omni/bin</code>
<code>omnidb</code>	
<code>syb_tool</code>	
<code>testbar</code>	
<code>omnigetmsg</code>	<code>opt/omni/lbin</code>
<code>util_cmd</code>	
<code>util_sybase.pl</code>	

To run the commands, you must have appropriate Data Protector user rights. For information, see the online Help index: “user groups” and “adding users”.

If the names of the database or database instances are in a non-ASCII encoding, set the `OB2_CLI_UTF8` environment variable to 1 to enable unicode output of the Data Protector Sybase CLI utilities. The terminal application must also use a UTF-8 locale.

## Configuring the integration

You need to configure Sybase users and every Sybase Adaptive Server instance (**Sybase instance**) you intend to back up from or restore to.

## Prerequisites

- Ensure that you have correctly installed and configured Sybase Server.
  - For supported versions, platforms, devices, and other information, see the *HP Data Protector product announcements, software notes, and references* or <http://www.hp.com/support/manuals>.
  - For information on the Sybase Server, see the *Adaptive Server Enterprise System Administration Guide* and *Adaptive Server Enterprise Installation and Configuration Guide*.

Every Sybase instance and its default Sybase Backup Server must be configured on the same system.

- Ensure that you have correctly installed Data Protector. On how to install the Data Protector Sybase integration in various architectures, see the *HP Data Protector installation and licensing guide*.

Every Sybase Server system you intend to back up from or restore to must have the Data Protector `Sybase Integration` component installed.

## Before you begin

- Configure devices and media for use with Data Protector.
- To test whether the Sybase Server system and the Cell Manager communicate properly, configure and run a Data Protector filesystem backup and restore on the Sybase Server system.

## Cluster-aware clients

Configure Sybase instances only on one cluster node, since the configuration files reside on the Cell Manager.

If you intend to use the Data Protector CLI, set the Data Protector environment variable `OB2BARHOSTNAME` to the virtual server name.

## Configuring Sybase users

On UNIX, add user `root` and the Sybase Server administrator (the owner of the `isql` utility) to the Data Protector `admin` or `operator` user group. For information, see the online Help index: “adding users”.

This chapter assumes that the Sybase Server administrator is user `sybase` in the group `sybase`.

## Configuring Sybase instances

Provide Data Protector with Sybase instance configuration parameters:

- Pathname of the Sybase Server home directory
- Pathname of the Sybase `isql` utility
- Sybase instance name
- Sybase instance user
- Password of the Sybase instance user
- Name of the Sybase `SYBASE_ASE` directory
- Name of the Sybase `SYBASE_OCS` directory

Data Protector then creates the Sybase instance configuration file on the Cell Manager and verifies the connection to the Sybase Backup Server.

To configure a Sybase instance, use the Data Protector GUI. On UNIX, you also use the Data Protector CLI.

### Before you begin

- Ensure that the default Sybase Backup Server of the Sybase instance is online.


### Using the Data Protector GUI

1. In the Context List, click **Backup**.
2. In the Scoping Pane, expand **Backup Specifications**, right-click **Sybase Server**, and click **Add Backup**.
3. In the **Create New Backup** dialog box, click **OK**.

4. In **Client**, select the Sybase Server system. In a cluster environment, select the virtual server.

In **Application database**, type the Sybase instance name.


**UNIX only:** Type `sybase` in both **Username** and **Group/Domain name**. This user becomes the backup owner.




**Figure 36** Specifying the Sybase instance

Click **Next**.

5. In the **Configure Sybase** dialog box, review and, if necessary, correct the configuration parameters that are filled in automatically. On Windows, all configuration parameters are determined automatically. On UNIX, you need to set the Sybase Server home directory, and username and password of the Sybase instance user that has the Sybase rights to back up and restore databases. See [Figure 37](#) on page 119 and [Figure 38](#) on page 120.



**Figure 37 Configuring a Sybase instance (Windows)**



**Figure 38 Configuring a Sybase instance (UNIX)**

Click **OK**.

6. The Sybase instance is configured. Exit the GUI or proceed with creating the backup specification at [Step 6](#) on page 123.

## Using the Data Protector CLI

Run:

**Windows:** `perl -I..\lib\perl util_sybase.pl -CONFIG  
Sybase_instance Sybase_home isql_path Sybase_user  
Sybase_password Sybase_ASE Sybase_OCS`

**UNIX:** `util_sybase.pl -CONFIG Sybase_instance Sybase_home  
isql_path Sybase_user Sybase_password Sybase_ASE  
Sybase_OCS`

### Parameter description

<i>Sybase_instance</i>	Name of the Sybase instance.
<i>Sybase_home</i>	Pathname of the Sybase Server home directory.
<i>isql_path</i>	Pathname of the Sybase <code>isql</code> command.
<i>Sybase_user</i>	Sybase instance user with the Sybase right to back up and restore databases.
<i>Sybase_password</i>	Password of the Sybase instance user.
<i>Sybase_ASE</i>	Name of the Sybase <i>Sybase_ASE</i> directory.
<i>Sybase_OCS</i>	Name of the Sybase <i>Sybase_OCS</i> directory.

The message `*RETVAl*0` indicates successful configuration. Otherwise, you receive `*RETVAl*error_number`. To get the error description, run:  
`omnigetmsg 12 error_number`.

### Example 1

To configure the Sybase instance `mysybase`, run:

```
util_sybase.pl -CONFIG mysybase /applications/sybase.12/
/applications/sybase.12/OCS-12_0/bin/isql sa " " ASE-12_0
OCS-12_0
```

## Checking the configuration

You can check the configuration of a Sybase instance after you have created at least one backup specification for the Sybase instance. Use the Data Protector GUI. On UNIX, you can also use the Data Protector CLI.

### Using the Data Protector GUI

1. In the Context List, select **Backup**.
2. In the Scoping Pane, expand **Backup Specifications** and then **Sybase Server**. Click the backup specification to display the Sybase instance to be checked.
3. Right-click the instance and click **Check configuration**.

## Using the Data Protector CLI

Run:

**Windows:** `perl -I..\lib\perl util_sybase.pl -CHKCONF  
Sybase_instance_name`

**UNIX:** `util_sybase.pl -CHKCONF Sybase_instance_name`

## Backup

The Data Protector Sybase integration provides online backup of the following types:

**Table 15 Backup types**

Full	Backs up all selected Sybase databases and transaction logs.
Trans <sup>1</sup>	Backs up changes made to the transaction logs since the last backup of any type.

<sup>1</sup>For this backup type, the transaction logs must be placed on a separate Sybase database device. Otherwise, the backup fails. For details on how to place transaction logs on a separate Sybase database device, see the Sybase documentation.

To be prepared for hardware or software failures on your system:

- Regularly back up Sybase system databases.  
Back up the `master` database every time you create, alter, or delete a device or database. Back up the `model` database and `system procedure` database every time you change them.
- Keep a copy of the following system tables:
  - `sysusages`
  - `sysdatabases`
  - `sysdevices`
  - `sysloginroles`
  - `syslogins`

## Creating backup specifications

Create a backup specification using the Data Protector GUI.

1. In the Context List, click **Backup**.


2. In the Scoping Pane, expand **Backup Specifications**, right-click **Sybase Server**, and click **Add Backup**.
3. In the **Create New Backup** dialog box, click **OK**.
4. In **Client**, select the Sybase Server system. In a cluster environment, select the virtual server.

In **Application database**, type the Sybase instance name.

**UNIX only:** Type `sybase` in both **Username** and **Group/Domain name**. This user becomes the backup owner.

Click **Next**.

5. If the Sybase instance is not configured for use with Data Protector, the **Configure Sybase** dialog box is displayed. Configure it as described in “[Configuring Sybase instances](#)” on page 117.
6. Select the databases you want to back up.



**Figure 39** Selecting backup objects


Click **Next**.

7. Select devices to use for the backup.


To specify device options, right-click the device and click **Properties**.

Click **Next**.

8. Set backup options. For information on application specific options, see [Table 16](#) on page 127.



**Figure 40 Pre- and post-exec commands (Windows)**



**Figure 41 Pre- and post-exec commands (UNIX)**


Click **Next**.

9. Optionally, schedule the backup. For more information, see “[Scheduling backup specifications](#)” on page 127.

Click **Next**.

10. View the properties of objects selected for backup. If you have selected only specific databases, not the whole instance, you can specify the number of concurrent data streams for backing up a particular database: right-click the database and click **Properties**.

This option is equivalent to Sybase *dump striping*.



**Figure 42 Specifying the number of concurrent streams**

The Sybase Backup Server then splits the database into approximately equal parts and sends the parts concurrently to devices according to device concurrency values.

If the total sum of device concurrencies is big enough, two or more databases can be backed up simultaneously.

Click **Next**.

11. Save the backup specification, specifying a name and a backup specification group.

**TIP:**

Preview your backup specification before using it for real. See “[Previewing backup sessions](#)” on page 128.

**Table 16 Sybase backup options**

Pre-exec, Post-exec	<p>Specify a command that will be started by <code>ob2sybase.exe</code> (Windows) or <code>ob2sybase.pl</code> (UNIX) on the Sybase Server system before the backup of every selected database (<code>pre-exec</code>) or after it (<code>post-exec</code>). Do not use double quotes.</p> <p><b>Windows:</b> Provide only the name of the command. The command must reside in the <code>Data_Protector_home\bin</code> directory. See <a href="#">Figure 40</a> on page 124.</p> <p><b>UNIX:</b> Provide the pathname of the command. See <a href="#">Figure 41</a> on page 125.</p>
------------------------	---

## Modifying backup specifications

To modify your backup specification, click its name in the Scoping Pane of the Backup context, then click the appropriate tab, and apply the changes.


## Scheduling backup specifications

You can run unattended backups at specific times or periodically. For details on scheduling, see the online Help index: “scheduled backups”.

### Example

To schedule `Full` backups at 8:00, 13:00, and 18:00 during week days:

1. In the **Schedule** property page, select the starting date in the calendar and click **Add** to open the **Schedule Backup** dialog box.
2. Under **Recurring**, select **Weekly**. Under **Time options**, select **8:00**. Under **Recurring Options**, select **Mon, Tue, Wed, Thu, and Fri**. Under **Session options**, select the **Full** backup type. See [Figure 43](#) on page 128. Click **OK**.
3. Repeat [Step 1](#) on page 127 and [Step 2](#) on page 127 to schedule another backup at 13:00, and another one at 18:00.
4. Click **Apply** to save the changes.



**Figure 43 Scheduling a backup specification**

## Previewing backup sessions

Preview the backup session to test it. Use the Data Protector GUI or CLI.

### Using the Data Protector GUI


1. In the Context List, click **Backup**.
2. In the Scoping Pane, expand **Backup Specifications** and then **Sybase Server**. Right-click the backup specification you want to preview and click **Preview Backup**.
3. Specify the **Backup type** and **Network load**. Click **OK**.

The message `Session completed successfully` is displayed at the end of a successful preview.

## Using the Data Protector CLI

Run:

```
omnib -sybase_list backup_specification_name -test_bar
```



```
dtterm
Window Edit Options Help
$ omnib -sybase_list BLAS92 -test_bar
[Normal] From: BSM@audi.hermes "BLAS92" Time: 06/28/99 10:43:55
OB2BAR application on "audi.hermes" successfully started.

[Report] Initializing ...
[Report] Initializing succeeded.

[Report] Creating backup set...
[Normal] From: BMA@audi.hermes "SYBASE" Time: 06/28/99 10:44:07
STARTING Medium Agent "SYBASE"

[Normal] From: OB2BAR@audi.hermes "audi" Time: 06/28/99 10:44:08
Starting OB2BAR Backup: sybdb1_27641:SYBASE_TST<1:0>

[Report] Creating backup set succeeded.

[Report] Creating backup object...
[Report] Creating backup object succeeded.

[Report] Writing backup object ...
[Report] Writing backup object succeeded.

[Report] Completing backup object ...
[Report] Completing backup object succeeded.

[Report] Completing backup set ...
[Normal] From: OB2BAR@audi.hermes "audi" Time: 06/28/99 10:44:15
Completed OB2BAR Backup: sybdb1_27641:SYBASE_TST<1:0>

[Report] Completing backup set succeeded.

[Report] -----
[Report] OmniBackII/Sybase integration test PASSED.
```

**Figure 44** Example of previewing a backup

### What happens during the preview?

The following are tested:

- Communication between the Sybase instance and Data Protector
- The syntax of the backup specification
- If devices are correctly specified
- If the necessary media are in the devices
- Configuration of the Sybase instance

## Starting backup sessions

Interactive backups are run on demand. They are useful for urgent backups or for restarting failed backups.

Start a backup in any of the following ways:

- Use the Data Protector GUI.
- Use the Data Protector CLI.
- Use the Sybase `isql` utility.

## Using the Data Protector GUI

1. In the Context List, click **Backup**.
2. In the Scoping Pane, expand **Backup Specifications** and then **Sybase Server**. Right-click the backup specification you want to start and click Start Backup.
3. Select the **Backup type** and **Network load**. Click **OK**.

Successful backup displays the message `Session completed successfully`.

## Using the Data Protector CLI

Run:

```
omnib -sybase_list backup_specification [-barmode sybase_mode]  
[options]
```

### Parameter description

<i>backup_specification</i>	Name of the Data Protector Sybase backup specification.
<i>sybase_mode</i>	Backup type. Select among {full   trans}.
<i>options</i>	For information, see the omnib man page.

## Example

To perform a full backup using the backup specification `FullSybase`, run:

```
omnib -sybase_list FullSybase -barmode full
```

## Using Sybase commands

To start a database backup from the client where the database is located, using the Sybase `isql` utility:

1. Check if the devices to be used contain formatted (initialized) media with enough free space.
2. Verify the backup options in the Data Protector Sybase backup specification.
3. Log in to the Sybase Server system as user `sybase`.
4. Run the Sybase `isql` command:

```
isql -SSybase_instance -USybase_user -PSybase_password  
dump database database to "ob2syb::backup_specification"
```

### Parameter description

<i>Sybase_instance</i>	Sybase instance name.
<i>Sybase_user</i>	Sybase instance user.
<i>Sybase_password</i>	Password of the Sybase instance user.
<i>database</i>	Name of the database to be backed up.
<i>backup_specification</i>	Name of the Data Protector Sybase backup specification.

## Restore

Restore Sybase databases using the Sybase `isql` utility.

To restore a Sybase database:

1. Restore a full backup of the Sybase database.
2. Restore subsequent transaction backups (if they exist).

## Localized database names

If the names of backed up objects contain characters that cannot be displayed using the current language group (on Windows) or code page (on UNIX):

1. Set the encoding used on the terminal to UTF-8.
2. **Windows only:** Set the environment variable `OB2_CLI_UTF8` to 1.
3. When gathering information for restore, redirect the output of the `syb_tool` or `omnidb` command to a text file.

If you need to edit the file containing the load command, use a UTF-8 aware editor that does not set the first byte ("BOM"), since such a file is not supported by `isql`. Note that the Windows Notepad editor cannot be used.

For details, see “[Finding information for restore](#)” on page 132.

4. When restoring the objects, add the `-i file_name -J utf8` options to the `isql` command, where `file_name` is the file with the load command.

For details, see “[Restoring using the Sybase isql command](#)” on page 139.

## Finding information for restore

To restore a corrupted database, first find the necessary media and the session ID of the last full backup. If you have backed up the database using several streams, also determine the number of streams.

Use the Data Protector GUI or CLI.

### Using the Data Protector GUI

In the Internal Database context, expand `Objects` or `Sessions`. To view details on a session, right-click the session and click `Properties`.

### Using the Data Protector CLI

Use the Data Protector `syb_tool` command or the standard Data Protector CLI commands.

## Using the Data Protector `syb_tool` command

The Data Protector `syb_tool` command returns the exact Sybase `load` command needed for restore.

The syntax of the `syb_tool` command is:

```
syb_tool database Sybase_instance
-date YYYY/MM/DD.hh:mm:ss
  [ -new_db new_database ]
  [ -new_server new_Sybase_instance ]
  [ -file file ]
  [ -media ]
```

### Parameter description

<code>database</code>	Database to be restored.
<code>Sybase_instance</code>	Sybase instance from which the database to be restored was backed up.
<code>date</code>	Point in time. The first backup version created after this point in time is restored. Use the 0-24h time format.
<code>new_database</code>	Target database to which to restore.
<code>new_Sybase_instance</code>	Target Sybase instance to which to restore.
<code>file</code>	Pathname of a file to which the <code>load</code> command or command sequence is recorded.
<code>-media</code>	Lists media needed for the restore.


To define the time interval between the closure of transaction logs and the start of a backup session, set the global variable `OB2SybaseTransLogDelay`. The default value is 20 seconds.

### Example 1

To get the `load` command that restores `database1` of the Sybase instance `audi` from the first backup performed after 12.00 noon on June 1, 1999, and to get the necessary media, run:

```
syb_tool database1 audi -date 1999/06/01.12:00:00 -media
```

See [Figure 45](#) on page 134.




```
Terminal
Window Edit Options Help
$ syb_tool database1 audi -date 199/06/01.12:00:00 -media
-----
ISQL command to be executed:
    load DATABASE database1 from "ob2syb::1999/06/24-0001"
Needed media:
    Media ID   :0a110154:3771e46d:2d74:0001
    Media Label:Default File_17
$
```

**Figure 45** Running the `syb_tool` command

### Example 2

To get the load command that restores `database1` of the Sybase instance `sherlock` from the first backup performed after 12.00 noon on June 1, 1999, to get the necessary media, and to record the load command to the file `c:/tmp/isqlfile` (Windows), run:

```
syb_tool database1 sherlock -date 1999/06/01.12:00:00 -file
c:\tmp\isqlfile -media
```



```
C:\WINNT\System32\cmd.exe
C:\Program Files\OmniBack\bin>syb_tool database1 SHERLOCK -date 1999/08/12.12:00:00 -file c
-----
ISQL command to be executed:
    load DATABASE database1 from "ob2syb::1999/08/12-0004"
Needed media:
    Media ID   :6d05110a:37b2df50:01a5:0001
    Media Label:Default QIC_4
C:\Program Files\OmniBack\bin>type c:\temp\isqlfile
load DATABASE database1 from "ob2syb::1999/08/12-0004"
go
C:\Program Files\OmniBack\bin>
```

**Figure 46** Running the `syb_tool` command with the `-file` and `-media` options

### Example 3

To get the load command that restores `database1` to `database2` from the first backup performed after 12.00 noon on June 1, 1999, run:

```
syb_tool database1 audi -date 1999/06/01.12:00:00 -new_db
database2 -media
```



```
dtterm
Window Edit Options Help
$ syb_tool database1 audi -date 1999/06/01.12:00:00 -new_db database2 -media
-----
SQL command to be executed:

    load DATABASE database2 from "ob2syb::1999/06/08-0003::database1"

Needed media:

    Media ID      :0a110154:375cef5a:6a0e:0001
    Media Label:Default File_8
$
```

**Figure 47 The load command for restore to a different database**

#### Example 4

To get the load command that restores database1 of the Sybase instance audi to the Sybase instance toplarna, run:

```
syb_tool database1 audi -date 1999/06/01.12:00:00 -new_server
toplarna -file /tmp/isql -media
```

A screenshot of a terminal window titled "dtterm". The window has a menu bar with "Window", "Edit", "Options", and "Help". The terminal shows a command being executed: "\$ syb\_tool database1 audi -date 1999/06/01.12:00:00 -new\_server toplarna -fil>". The output shows the ISQL command to be executed: "load DATABASE database1 from \"ob2syb::1999/06/08-0003::database1::audi\"". Below this, it lists "Needed media:" with "Media ID :0a110154:375cef5a:6a0e:0001" and "Media Label:Default File\_8". The user then enters "\$ cat /tmp/isqlfile1", which outputs "load DATABASE database1 from \"ob2syb::1999/06/08-0003::database1::audi\"". The user then enters "go" and "\$" again, with a cursor at the end of the second "\$".

```
dtterm
Window Edit Options Help
$ syb_tool database1 audi -date 1999/06/01.12:00:00 -new_server toplarna -fil>
-----
ISQL command to be executed:
    load DATABASE database1 from "ob2syb::1999/06/08-0003::database1::audi"
Needed media:
    Media ID :0a110154:375cef5a:6a0e:0001
    Media Label:Default File_8
$ cat /tmp/isqlfile1
load DATABASE database1 from "ob2syb::1999/06/08-0003::database1::audi"
go
$
```


**Figure 48** The load command for restore to a different server

### Example 5

To get the load command that restores database1 of the Sybase instance audi from the first backup performed after 14:28 on July 7, 1999, and to record the load command to the file /tmp/dudule, run:

```
syb_tool database1 audi -date 1999/07/07.14:28:00 -file
/tmp/dudule
```

You see in [Figure 49](#) on page 137 that you need to restore one full backup and four transaction log backups, the last one backed up with concurrency 3.



```
dtterm
Window Edit Options Help
$ syb_tool database1 audi -date 1999/07/07.14:28:00 -file /tmp/dudule

-----
ISQL command to be executed:

  load DATABASE database1 from "ob2syb::1999/07/07-0027"

-----
ISQL command to be executed:

  load TRAN database1 from "ob2syb::1999/07/07-0028"

-----
ISQL command to be executed:

  load TRAN database1 from "ob2syb::1999/07/07-0029"

-----
ISQL command to be executed:

  load TRAN database1 from "ob2syb::1999/07/07-0030"

-----
ISQL command to be executed:


  load TRAN database1 from "ob2syb::1999/07/07-0031"
  stripe on "ob2syb::1999/07/07-0031"
  stripe on "ob2syb::1999/07/07-0031"
$ cat /tmp/dudule
load DATABASE database1 from "ob2syb::1999/07/07-0027"
go
load TRAN database1 from "ob2syb::1999/07/07-0028"
go
load TRAN database1 from "ob2syb::1999/07/07-0029"
go
load TRAN database1 from "ob2syb::1999/07/07-0030"
go
load TRAN database1 from "ob2syb::1999/07/07-0031"
  stripe on "ob2syb::1999/07/07-0031"
  stripe on "ob2syb::1999/07/07-0031"
go
$
```

**Figure 49 Loading transaction logs from multiple backups**

Using the standard Data Protector CLI commands

1. Get a list of backed up Sybase databases:

```
omnidb -sybase
```




```
Terminal
Window Edit Options Help
$ pwd
/opt/omni/bin
$ omnidb -sybase
Object Name                                     Object type
-----
=
audi.hermes  :database1:audi<1:0> [DATABASE]      Sybase
audi.hermes  :database1:audi<3:0> [DATABASE]      Sybase
audi.hermes  :database1:audi<3:1> [DATABASE]      Sybase
audi.hermes  :database1:audi<3:2> [DATABASE]      Sybase
audi.hermes  :database2:audi<1:0> [DATABASE]      Sybase
audi.hermes  :database3:audi<1:0> [DATABASE]      Sybase
audi.hermes  :database4:audi<1:0> [DATABASE]      Sybase
audi.hermes  :database5:audi<1:0> [DATABASE]      Sybase
audi.hermes  :master:audi<1:0> [DATABASE]       Sybase
```

**Figure 50** Example of a list of backed up Sybase databases

2. Get a list of backup sessions for a specific object, including the session ID:

```
omnidb -sybase "object_name"
```



```
Terminal
Window Edit Options Help
$ omnidb -sybase "audi.hermes:database1:audi<1:0> [DATABASE]"
SessionID      Started      Duration    Object      Status      Size [KB]    NumberOfEr
-----
1999/06/09-2   12:33:36    00:00:11    Completed   288         0
1999/06/08-3   12:25:52    00:00:07    Completed   288         0
1999/06/02-4   09:07:30    00:00:07    Completed   288         0
1999/06/02-3   09:04:53    00:00:07    Completed   288         0
1999/06/02-2   09:03:48    00:00:07    Completed   288         0
1999/05/31-3   14:24:25    00:00:07    Completed   288         0
1999/05/28-7   16:51:02    00:00:08    Completed   288         0
$
```

**Figure 51 Example of a list of backup sessions for a specific object**

 **IMPORTANT:**

For object copies, use the object's backup ID (which equals the object's backup session ID). Do not use the object's copy session ID.

3. Get a list of media needed for restore:

```
omnidb -session session_id -media
```



```
Terminal
Window Edit Options Help
$ omnidb -session 1999/06/09-2 -media
Medium Label      Medium ID      Free Block
-----
Default File_14   0a110154:375e3de9:34c4:0001   9889
Default QIC_1     0a110154:375e2996:2e13:0001   416816
$
```

**Figure 52 Example of finding media needed for restore**

For details on the `omnidb` command, see the `omnidb` man page.

## Restoring using the Sybase `isql` command

1. On UNIX, log in to the Sybase Server system as user `sybase`.

**2.** Run the Sybase `isql` utility:

```
isql -SSybase_instance -USybase_user -PSybase_password [-i  
input_file -J utf8]
```

**Parameter description**

<i>Sybase_instance</i>	Sybase instance name.
<i>Sybase_user</i>	Sybase instance user.
<i>Sybase_password</i>	Password of the Sybase instance user.
<i>input_file</i>	The file to which the <code>load</code> parameter was saved. See also " <a href="#">Localized database names</a> " on page 132.

3. If you did not provide the load command in a file, type the desired `load` command in the first line. To run the command(s), type `go` in the last line and press **Enter**.

The syntax of the Sybase `load` command is:

```
load {database|transaction} new_database from
"ob2syb::version[::database[::Sybase_instance]]"
stripe on
"ob2syb::version[::database[::Sybase_instance]]"
```

## Parameter description

<code>{database transaction}</code>	Defines whether databases or transaction logs are to be restored.
<code>version</code>	Session ID of the backup version to restore from. You can also type <code>latest version</code> to restore from the latest backup.
<code>new_database</code>	Target database to which to restore.
<code>database</code>	Database to be restored.
<code>Sybase_instance</code>	Sybase instance from which the database to be restored was backed up.

The `stripe` part is needed only when restoring a database backed up with several streams. The number of streams used for backup is displayed in the `Data Protector Monitor` during the backup session.

---

### **IMPORTANT:**

To restore a database to a new database, first create a new database. The new database should have the same structure as the database to be restored.

---

For details on the Sybase `load` command, see the *Adaptive Server Enterprise System Administration Guide*.

---

 **TIP:**


To list all Sybase databases of a particular Sybase instance, run:

**Windows:**

```
perl -I..\lib\perl util_sybase.pl -OBSO Sybase_instance_name
```

**UNIX:** util\_sybase.pl -OBSO Sybase\_instance\_name

---



```
Terminal
Window Edit Options Help
$ /opt/omni/lbin/util_sybase.exe -OBSO audi
database1
database2
database3
database4
database5
master
model
sybserverprocs
tempdb
*RETVL *0
```

**Figure 53 Example of a list of Sybase databases**

## Restore examples

### Example 1

To restore the database `database2` from the backup session `1999/06/09-2`, run:

```
1>load database database2 from "ob2syb::1999/06/09-2"
2>go
```

A terminal window titled "Terminal" with a menu bar containing "Window", "Edit", "Options", and "Help". The terminal displays the following text:


```
$ isql -Usa -P" " -Saudi
1> load database database2 from "ob2syb::1999/06/09-2"
2> go
Backup Server session id is: 9. Use this value when executing the
'sp_volchanged' system stored procedure after fulfilling any volume change
request from the Backup Server.
Backup Server: 4.132.1.1: Attempting to open byte stream device:
'ob2syb::1999/06/09-2::00'
Backup Server: 6.28.1.1: Dumpfile name 'tabase2991600B096' section number 0001
mounted on byte stream 'ob2syb::1999/06/09-2::00'
Backup Server: 4.58.1.1: Database database2: 3588 kilobytes LOADED.
Backup Server: 4.58.1.1: Database database2: 3596 kilobytes LOADED.
Backup Server: 3.42.1.1: LOAD is complete (database database2).
Use the ONLINE DATABASE command to bring this database online; SQL Server will
not bring it online automatically.
1> █
```

**Figure 54 Restoring a database from a specific session**

### Example 2

To restore the latest version of the database Sybdata to a new database, named Sybdata1:


1. Create a database device. See [Figure 55](#) on page 144.



```
Terminal
Window Edit Options Help
$ isql -Usa -P"" -Sandi
1> disk init name = "SYB_DISK",
2> physname = "/applications/sybase92/data/Sybackup1",
3> vdevno = 8,
4> size = 5000
5> go
1>
```

**Figure 55** Creating a database device

2. Create an empty database, named Sybdata1. See [Figure 56](#) on page 144.



```
Terminal
Window Edit Options Help
1> create database
2> Sybdata1 on SYB_DISK = 5000
3> go
CREATE DATABASE: allocating 4864 pages on disk 'SYB_DISK'
1>
```

**Figure 56** Creating an empty database

3. Restore Sybdata to Sybdata1 by running:

```
1>load database Sybdata1 from "ob2syb::latest version::Sybdata"
2>go
```

### Example 3

To restore the latest version of the database database3 backed up with three streams, run:

```
1>load database database3 from "ob2syb::latest version"
2>stripe on "ob2syb::latest version"
3>stripe on "ob2syb::latest version"
4>go
```

### Example 4

To start a restore a database from the instance "instance1", which name contains Cyrilic and Latin charaters, and for which the load command was saved in the file restore\_20050609-2.txt, run :

```
isql -S instance1 -U admin -PSybase_password -J utf8 -i
restore_20050609-2.txt
```

## Restoring using another device

You can restore using a device other than that used for backup.

Specify the new device in the file:

**Windows:** `Data_Protector_home\Config\server\Cell\restoredev`

**UNIX:** `/etc/opt/omni/server/cell/restoredev`

Use the format:

`"DEV 1" "DEV 2"`

where `DEV 1` is the original device and `DEV 2` the new device.



### IMPORTANT:

Delete this file after use.

---

On Windows, use the Unicode format for the file.

## Monitoring sessions

You can monitor currently running sessions in the Data Protector GUI. When you run an interactive backup or restore session, a monitor window shows you the progress of the session. Closing the GUI does not affect the session.

You can also monitor sessions from any Data Protector client with the `User Interface` component installed, using the `Monitor` context.

On how to monitor a session, see the online Help index: "viewing currently running sessions".

## Troubleshooting

This section lists general checks and verifications.

For general Data Protector troubleshooting information, see the HP Data Protector troubleshooting guide.

## Before you begin

- Ensure that the latest official Data Protector patches are installed. See the online Help index: “patches” on how to verify this.
- See the *HP Data Protector product announcements, software notes, and references* for general Data Protector limitations, as well as recognized issues and workarounds.
- See <http://www.hp.com/support/manuals> for an up-to-date list of supported versions, platforms, and other information.

## Checks and verifications

If your configuration, backup, or restore failed:

- Examine system errors written to `debug.log`, located on the Sybase Server system in:  
**Windows:** `Data_Protector_home\log`  
**UNIX:** `/var/opt/omni/log`
- Make a test backup and restore of any filesystem on the problematic client. For information, see online Help.
- In a cluster environment, before performing procedures from the Data Protector CLI, ensure that the environment variable `OB2BARHOSTNAME` is set to the virtual server name. When the Data Protector GUI is used, this is not required.
- Ensure that the Sybase instance and its default Sybase Backup Server are online.
- **UNIX only:** Ensure that user `root` and user `sybase` are added to the Data Protector `admin` or `operator` user group.

Additionally, if your configuration or backup failed:

- If you use non-default Sybase settings, ensure that they are registered in:  
**Windows:** The `System Properties` dialog box, which you access by double-clicking `System` in the `Control Panel`.  
**UNIX:** The Data Protector Sybase configuration file.

Additionally, if your backup failed:

- Check the configuration of the Sybase instance described in “[Checking the configuration](#)” on page 121.
- Test the backup specification as described in “[Previewing backup sessions](#)” on page 128.

If the Data Protector part of the test fails:

1. **UNIX only:** Ensure that the owner of the backup specification is user `sybase` and that it is added to the Data Protector `operator` or `admin` user groups.
2. Create a Sybase backup specification to back up to a null or file device. If the backup succeeds, then the problem is probably related to devices. For information on troubleshooting devices, see the HP Data Protector troubleshooting guide.

If the test succeeds, start a backup directly from the Sybase Server. See “Using Sybase commands” on page 131.

Additionally, if your backup or restore failed:

- Test Data Protector data transfer using the `testbar` utility. Log in to the Sybase Server system as user `sybase` and run:
  - If your backup failed:

```
testbar -type:Sybase -appname:Sybase_instance_name
-bar:backup_specification_name -perform:backup
```
  - If your restore failed:

```
testbar -type:Sybase -appname:Sybase_instance_name
-bar:backup_specification_name -perform:restore
-object:object_name -version:object_version
```

where `object_name` is the name of the object to be restored.

If the test fails:

- Troubleshoot errors. See the text file `Trouble.txt` located on the Cell Manager in:
  - Windows:** `Data_Protector_home\help\enu`
  - UNIX:** `/opt/omni/gui/help/C`
- On the Sybase Server system, examine system errors, reported in:
  - Windows:** `Data_Protector_home\log\debug.log`
  - UNIX:** `/var/opt/omni/log/debug.log`

Additionally, if your restore failed:

- Ensure that the Data Protector `operator` user group has the `See private objects` user right selected. On how to change user rights, see the online Help index: “changing user rights”.



---

# 3 Integrating HP Network Node Manager and Data Protector

## Introduction

This chapter explains how to configure and use the Data Protector HP Network Node Manager (NNM) integration. It describes concepts and methods you need to understand to back up and restore the NNM database.

You can back up or restore NNM objects: the whole database or only parts of it.

Data Protector offers interactive and scheduled backups of the following types:

**Table 17 Backup types**

Full	Backs up the selected NNM objects.
Incremental	Backs up changes made to the selected NNM objects since the last full backup.

This chapter provides information specific to the Data Protector HP Network Node Manager integration. For general Data Protector procedures and options, see online Help.

## Integration concept

The basic components of the Data Protector NNM integration are the following Perl scripts:

**Table 18 Data Protector NNM integration components**

NNMpre.ovpl	A script without arguments that: <ol style="list-style-type: none"><li>1. Initiates a special NNM backup, instructing the NNM database to make a direct copy of itself to a location specified in the <code>solid.ini</code> file, from which Data Protector backs it up later.</li><li>2. Pauses the eight NNM processes, so that Data Protector can actually back up the NNM data.</li></ol>
NNMpost.ovpl	A script without arguments that restarts the NNM processes after the backup completes.
NNMScript.exe (Windows only)	A script with a pre- and post- argument that locates the NNM Perl compiler and NNM <code>pre.ovpl</code> or <code>NNMpost.ovpl</code> , and starts the script.

---

 **NOTE:**

Files created by the embedded database remain on the disk and are overwritten by future backups. Remove the files manually to free the disk space.

---

The NNM Perl compiler is used for `NNMpre.ovpl` and `NNMpost.ovpl`.

While HP Network Node Manager is responsible for read/write operations to disk, Data Protector reads from and writes to devices and manages media.

## Configuring the integration

### Prerequisites

- Ensure that you have correctly installed and configured NNM.
- For supported versions, platforms, devices, and other information, see the *HP Data Protector product announcements, software notes, and references* or <http://www.hp.com/support/manuals>.

- For information on backup and recovery strategies and NNM concepts, see the HP Network Node Manager documentation.
- Ensure that you have correctly installed Data Protector. On how to install the Data Protector NNM integration in various architectures, see the *HP Data Protector installation and licensing guide*.  
Every NNM system you intend to back up from or restore to must have the Data Protector HP Network Node Manager Backup Integration and Disk Agent components installed.

## Before you begin

- Configure devices and media for use with Data Protector. For information, see online Help.
- To test whether the NNM system and the Cell Manager communicate properly, configure and run a Data Protector filesystem backup and restore on the NNM system.

## Tasks for the NNM administrator

- Communicate the location of the NNM backup directory, specified in the NNM embedded database file `solid.ini`.
- In `solid.ini`, comment out the line beginning with `At=` that schedules a nightly backup of the NNM embedded database.

## Backup

The Data Protector NNM integration provides two backup types and two backup modes.

**Table 19 Backup types**

Full	Backs up all selected NNM objects.
Incremental	Backs up changes made to the selected NNM objects since the last full backup.

**Table 20 Backup modes**

Offline	The database is taken offline. Consequently, no changes can be made to the database during the backup process, leaving it in a consistent state.
---------	--

Online

The database is in a paused state and the changes made to the database during the backup process are recorded to temporary files. When the backup completes, the database resumes its normal state and the changes from the temporary files are applied to the database, bringing it to a consistent state.

To perform an offline backup:

1. On the NNM system, take the NNM database offline by running:

```
ovstop
```

2. Back up the complete NNM directory using Data Protector.

3. On the NNM system, bring the NNM database online by running:

```
ovstart
```

## Creating backup specifications

Create a backup specification using the Data Protector Manager.

1. In the Context List, click **Backup**.
2. In the Scoping Pane, expand Backup Specifications, right-click **Filesystem**, and click **Add Backup**.
3. Select a template:

**Windows:** NT\_NNM\_template

**UNIX:** Unix\_NNM\_template

You can also select the Blank Filesystem Backup template or any other template.

Click **OK**.

4. Select the appropriate client and directories to be backed up from the client.

Click **Next**.

5. Select devices to use for the backup.

To specify device options, right-click the device and click **Properties**.

Click **Next**.

6. Set backup options.



---

**IMPORTANT:**

If you have selected the NNM template, do not change the default pre- and post-exec options. If you have selected a different template, specify exactly the same pre-exec and post-exec scripts as specified in the NNM template.

---

Click **Next**.

7. Optionally, schedule the backup. For more information, see “[Scheduling backup specifications](#)” on page 127.

Click **Next**.

8. Save the backup specification, specifying a name and a backup specification group.



---

**TIP:**

Preview backup session for your backup specification before using it. For details, see the online Help index: “[previewing a backup](#)”. Note that the backup preview does not run pre-exec and post-exec scripts.

---

## Modifying backup specifications

To modify your backup specification, click its name in the Scoping Pane of the Backup context, then click the appropriate tab, and apply the changes.

## Scheduling backup specifications


You can run unattended backups at specific times or periodically. For details on scheduling, see the online Help index: “[scheduled backups](#)”.

### Example

To schedule backups at 8:00, 13:00, and 18:00 during week days:

1. In the Schedule property page, select the starting date in the calendar and click **Add** to open the Schedule Backup dialog box.

2. Under Recurring, select **Weekly**. Under Time options, select **8:00**. Under Recurring Options, select **Mon, Tue, Wed, Thu,** and **Fri**. See [Figure 57](#) on page 154.  
Click **OK**.
3. Repeat [Step 1](#) on page 153 and [Step 2](#) on page 154 to schedule another backup at 13:00, and another one at 18:00.
4. Click **Apply** to save the changes.



**Figure 57 Scheduling a backup specification**

## Starting backup sessions

Interactive backups are run on demand. They are useful for urgent backups or for restarting failed backups. Use the Data Protector GUI.

1. In the Context List, click **Backup**.
2. In the Scoping Pane, expand Backup Specifications and then Filesystem. Right-click the backup specification you want to start and click **Start Backup**.

3. Specify Backup type and Network load. Click **OK**.

The message `Session completed successfully` is displayed at the end of a successful backup session.

## Restore

To restore NNM objects:

1. Stop all NNM processes.
2. Restore the NNM objects using the Data Protector GUI.
3. Perform the NNM recovery procedures.
4. Restart the NNM processes.

For details, see the online Help index: “standard restore procedure” and the *NNM reporting and data analysis* manual.

## Monitoring sessions

You can monitor currently running sessions in the Data Protector GUI. When you run an interactive backup or restore session, a monitor window shows you the progress of the session. Closing the GUI does not affect the session.

You can also monitor sessions from any Data Protector client with the `User Interface` component installed, using the Monitor context.

On how to monitor a session, see the online Help index: “viewing currently running sessions”.

Messages generated by scripts, NNM, and Data Protector are logged to the IDB.

## Acceptable warnings on Windows

The following warnings, which are likely to occur during an NNM backup, have no impact on the validity of the backup. They are only informational.

### Message

```
[Warning] From: session_owner Time: mm/dd/yy hr:mn:sc  
[error code] path\HP OpenView\NNM\bin\tcl7.5.dll  
Cannot preserve time attributes: ([5] Access is denied.).
```

## Description

The file `tc17.5.dll` is backed up, but the time attributes, which are not significant to Data Protector, are not preserved.

## Message

```
[Warning] From: session_owner Time: mm/dd/yy hr:mn:sc  
[error code] path\HP  
OpenView\NNM\databases\analysis\default\solid.db Cannot open:  
([33] The process cannot access the file ....).
```

## Description

The embedded database file referenced in this message has already been backed up as part of the pre-exec script. Its default location is in the `path\HP` `OpenView\NNM\databases\analysis\default\backup` directory, which is specified in the `solid.ini` file. After the restore, copy the backed up `solid.db` file from that directory to the active `path\HP` `OpenView\NNM\databases\analysis\default` directory.

## Message

```
[Warning] From: session_owner Time: mm/dd/yy hr:mn:sc  
[error code] path\HP  
OpenView\NNM\databases\openview\topo\netmon.lock Cannot open:  
([33] The process cannot access the file ....).
```

## Message

```
[Warning] From: session_owner Time: mm/dd/yy hr:mn:sc  
[error code] path\HP OpenView\NNM\databases\snmpCollect\dblock  
Cannot open: ([33] The process cannot access the file ....).
```

## Description

These files are not significant to Data Protector.

# Troubleshooting

This section lists problems you might encounter when using the Data Protector NNM integration.

For general Data Protector troubleshooting information, see the *HP Data Protector troubleshooting guide*.

## Before you begin

- Ensure that the latest official Data Protector patches are installed. See the online Help index: “patches” on how to verify this.
- See the *HP Data Protector product announcements, software notes, and references* for general Data Protector limitations, as well as recognized issues and workarounds.
- See <http://www.hp.com/support/manuals> for an up-to-date list of supported versions, platforms, and other information.

## Problems

### Problem

#### **The system is already in a paused state**

NNM reports:

```
The system is already in a paused state. 'ovpause' cannot
continue, If a synchronization error has occurred, try
removing the file e:Program Files\HP OpenView\tmp\ovpause.lock
(Windows system) or /var/opt/OV/tmp/ovpause.lock (UNIX system)
and then retrying the 'ovpause' command.
```

### Action

Ensure that the NNM processes are not paused manually before the Data Protector NNM session starts. Otherwise, the pre-exec script `NNNpre.ovpl` fails.

### Problem

#### **The system is not in a paused state**

NNM reports:

```
The system is not in a paused state. 'ovresume' cannot
continue. If a synchronization error has occurred, try
creating the empty file e:Program Files\HP
OpenView\tmp\ovpause.lock (Windows systems) or
/var/opt/OV/tmp/ovpause.lock (UNIX systems) and then retrying
the 'ovresume' command.
```

## Action

Ensure that the NNM processes are not resumed manually during the Data Protector NNM session. Otherwise, the post-exec script `NNMpost.ovpl` fails and Data Protector displays the message Backup completed with errors.

## Problem

### **ODBC Error: SQLSTATE=HY000**

Data Protector reports:

```
ODBC Error:SQLSTATE=HY000 NATIVE ERROR=21306 SOLID
Communication Error 21306: Server 'tcpip 2690' not found,
connection failed Connect to ODBC data Source "ovdbrun"
failed.
```

## Action

Ensure that no NNM processes are paused manually before the Data Protector NNM session starts. Otherwise, the pre-exec script `NNMpre.ovpl` fails because it cannot connect to the NNM embedded database.

## Problem

### **Embedded database is currently in the backup process**

NNM reports:

```
Embedded database is currently in the backup process.
Aborting Data Protector backup.
```

## Action

Ensure that the default scheduled backup in the `solid.ini` file is commented out. A Data Protector NNM backup and an active backup of the NNM embedded database cannot be performed simultaneously.

## Problem

### **Wrong number of arguments**

On Windows, Data Protector reports:

```
Wrong number of arguments. Please specify pre or post backup.
"NNMScript.exe pre" for pre-exec script "NNMScript.exe post"
for post-backup script.
```

## Action

Correct the number of arguments for `NNMScript.exe`, as specified in the pre-exec and post-exec backup options.

## Problem

### Couldn't find HP Network Node Manager key

On Windows, Data Protector reports:

Couldn't find HP Network Node Manager key in registry.

## Action

Ensure that NNM is installed on the target client and that the registry key `HP Network Node Manager` exists under `HKEY_LOCAL_MACHINE\SOFTWARE\Hewlett-Packard\OpenView`.

## Problem

### Couldn't find the HP Network Node Manager PathName

On Windows, Data Protector reports:

Couldn't find the HP Network Node Manager PathName in registry.

## Action

Ensure that a registry entry with the name `PathName` exists under `HKEY_LOCAL_MACHINE\SOFTWARE\Hewlett-Packard\OpenView\HP Network Node Manager` and has a string value.

## Problem

### Couldn't find OmniBack II key

On Windows, NNM reports:

Couldn't find OmniBack II key in registry.

## Action

Ensure that Data Protector with a Disk Agent is installed on the target client and that the registry key `OmniBack II` exists under `HKEY_LOCAL_MACHINE\SOFTWARE\Hewlett-Packard\OpenView`. Any other name causes problems, potentially requiring reinstallation of the Disk Agent.

## Problem

### Couldn't find the Data Protector HomeDir

On Windows, NNM reports:

```
Couldn't find the Data Protector HomeDir in registry.
```

## Action

Ensure that a registry entry with the name `HomeDir` exists under `HKEY_LOCAL_MACHINE\SOFTWARE\Hewlett-Packard\OpenView\OmniBackII\Common`, having a string value for the Data Protector path. Otherwise, create it or reinstall the Disk Agent.

## Problem

### Incorrect argument

On Windows, Data Protector reports:

```
Incorrect arguments. Use "pre" or "post".
```

## Action

Ensure that `NNMScript.exe` has correct arguments, as specified in the pre- and post-exec backup options. The arguments are not case-sensitive.

## Problem

### Failure starting `NNM_perl_compiler_path Data_Protector_home\bin\*.ovpl`.

On Windows, Data Protector reports:

```
Failure starting NNM_perl_compiler_path  
Data_Protector_home\bin\*.ovpl.
```

## Action

Ensure that the NNM Perl compiler has not been removed and paths for Data Protector and NNM in the registry are correct.

## Problem

### Execution of `NNM_perl_compiler_path Data_Protector_home\bin\*.ovpl` failed

On Windows, NNM reports:

```
Execution of NNM_perl_compiler_path  
Data_Protector_home\bin\*.ovpl failed.
```

### Action

Ensure that *path\HP OpenView\NNM\bin* is in the PATH and scripts are in the *Data\_Protector\_home\bin* directory. Otherwise, the command that starts NNMpre.ovpl or NNMpost.ovpl fails.



---

# 4 Integrating NDMP Server and Data Protector

## Introduction

This chapter explains how to configure and use the Data Protector Network Data Management Protocol Server integration (**NDMP Server integration**). It describes concepts and methods you need to understand to perform filesystem backups and restores on a Network Attached Storage device.

Network Data Management Protocol (**NDMP**) is a protocol used to manage backup and restore operations on a Network Attached Storage device. NDMP uses a client server model, where the Data Protector NDMP Media Agent client controls the backup, while the NDMP Server performs the actual backup operations.

The Data Protector NDMP Server integration offers interactive and scheduled filesystem backups of the following types:

- Full
- Inc1

For information on these backup types, see the *HP Data Protector concepts guide*.

The Data Protector NDMP Server integration offers two restore types:


- Standard filesystem restore
- Direct access restore

This chapter provides information specific to the Data Protector NDMP Server integration. For general Data Protector procedures and options, see online Help.

## Integration concept

Data Protector integrates with NDMP Server through the Data Protector NDMP library and the NDMP Media Agent. The Data Protector NDMP library channels communication between the Data Protector Session Manager, and, via the NDMP

interfaces, the NDMP Server. [Figure 58](#) on page 164 shows the architecture of the integration.



**Figure 58 Data Protector NDMP Server integration architecture**


Legend	
Session Manager	Data Protector Session Manager: Backup Session Manager during backup and Restore Session Manager during restore. No Data Protector Disk Agents are involved in the session because the whole functionality is already implemented within the NDMP Media Agent.
NDMP Media Agent	The NDMP client, which contains a layer called the NDMP library. The library enables the NDMP Media Agent to communicate with the NDMP Server through the NDMP interfaces.

For more information on the NDMP protocol and NDMP interfaces, see the NDMP documentation.

Data Protector supports two different NDMP Server types:

- NetApp NAS device (**NetApp**)
- Celerra NAS device (**Celerra**)

In a typical environment (Figure 59 on page 165), the NDMP Server system and the Data Protector client with the NDMP Media Agent installed (**NDMP client**) are connected to the LAN. However, data from the NDMP Server disks does not flow through the LAN, it is backed up to a tape device connected to the NDMP Server system. The NDMP client initiates, monitors, and controls data management and the NDMP Server executes these operations, having a direct control over devices connected to it and over the backup and restore speed.



**Figure 59 The NDMP environment configuration**

Due to the NDMP catalog handling design, Data Protector caches the entire catalog on the NDMP client before storing it to the Data Protector internal database (IDB). Since the catalog can increase in size significantly, the NDMP client caches parts of the catalog into **file history swap files**, located in the following directory:

**Windows:** `Data_Protector_home\tmp`

**UNIX:** `/var/opt/omni/tmp`

For more information on file history swap files, see “[The NDMP specific omnirc file variables](#)” on page 190.

## Configuring the integration

To configure the Data Protector NDMP Server integration:

1. Import the NDMP Server system into the Data Protector cell.
2. Create a media pool for NDMP media.
3. Configure NDMP devices.

### Prerequisites

- Ensure that you have correctly installed and configured NDMP Server.
  - For supported versions, platforms, devices, and other information, see the *HP Data Protector product announcements, software notes, and references* or <http://www.hp.com/support/manuals>.
  - For information on installing, configuring, and using NDMP Server, see the NDMP Server documentation.
- Ensure that you have correctly installed Data Protector. On how to install Data Protector in various architectures, see the *HP Data Protector installation and licensing guide*.


Every NDMP client (Data Protector client that controls the NDMP Server backup) must have the Data Protector `NDMP Media Agent` component installed.

### Importing NDMP Server systems

Import the NDMP Server system using the Data Protector GUI:

1. In the Context List, click **Clients**.
2. In the Scoping Pane, right-click **Clients** and click **Import Client**.

3. In **Name**, type the name of the NDMP Server system you want to import and select **NDMP Server**.



**Figure 60** Specifying an NDMP Server system


Click **Next**.

4. In **NDMP Type**, select the NAS device type.

In **Port**, specify the TCP/IP port number of the NDMP Server. The default number is 10000.

Provide the NDMP Server system user account that will be used by Data Protector to connect to the NDMP Server system. This user must have permission to read from and write to the NDMP media.

The Data Protector NDMP integration supports the “none”, “text”, and “MD5” NDMP authentication methods. Data Protector automatically detects and uses the method supported by your NDMP Server.



**Figure 61 Specifying an NDMP Server system**

Click **Finish**.

## Creating media pools

Create a special media pool for NDMP media. For information, see the online Help index: “creating media pools”.

The NDMP media pool can only be used by devices using the NDMP data format (**NDMP devices**).

### Limitations

- A medium cannot be used by different NDMP Server types. Consequently, data that was backed up from one NDMP Server type cannot be restored to another NDMP Server type.

## Configuring NDMP devices

Configure NDMP devices using the Data Protector GUI.


### Prerequisites

- The NDMP Server system must have a tape drive connected to it. The drive must be supported by both NDMP Server and Data Protector.


Library robotics can be connected to:

- NDMP Server system ([Figure 62](#) on page 170).
- NDMP client ([Figure 63](#) on page 171).
- Data Protector client with the general Media Agent installed (**general Media Agent client**) ([Figure 63](#) on page 171).

If it is connected to the NDMP Server system, the library robotics must be supported by both NDMP Server and Data Protector.



**Figure 62 Library configuration—I**



**Figure 63 Library configuration—II**

Several drives can be connected to the NDMP Server system.

If library robotics or drives are connected to the NDMP Server system, they can be controlled only by an NDMP client.

Library drives can be shared between multiple NDMP Server systems and general Media Agent clients, and with other applications. For more information, see the *HP Data Protector concepts guide*.

### Limitations

- NDMP devices can only use NDMP media pools.

### Configuring tape libraries

To configure a tape library with robotics connected to the NDMP Server system:

1. In the Context list, click **Devices & Media**.
2. In the Scoping Pane, right-click **Devices**, and then click **Add Device**.

3. Type a name for the device. Optionally, describe the device. See [Figure 64](#) on page 172.


In **Device Type**, select **SCSI Library**.

In **Interface Type**, select the NAS device used.

In **Client**, select the NDMP client that will control the library through the NDMP Server.

In **NDMP Server**, select the NDMP Server system with the library robotics connected to it.

Optionally, in **Management Console URL**, type a valid URL of the library management console. It will enable you to invoke a web browser and load the management console interface directly from the Data Protector GUI.



**Figure 64** Configuring a library

Click **Next**.

4. Specify library robotics' SCSI address and drive handling. For information, see ["Network appliance configuration"](#) on page 176 and ["EMC Celerra configuration"](#) on page 177.

Click **Next**.

5. Specify slots to be used by Data Protector.

Click **Next**.

6. Select the media type used in the library.

Click **Next**.

7. Click **Finish** and then click **Yes** to configure drives in the library.

8. Type a name for the drive. Optionally, describe the drive.

In **Client**, select the NDMP client that will control the library through the NDMP Server.

In **NDMP Server**, select the NDMP Server system with the library robotics connected to it.

In **Data Format**, select the NAS device used.

Click **Next**.

9. Specify the drive's NDMP SCSI address. For information, see ["Network appliance configuration"](#) on page 176 and ["EMC Celerra configuration"](#) on page 177.

Do not change the drive index number.

Click **Next**.

10. Specify the media pool.

To specify advanced device options, click **Advanced**. For information on supported block sizes, see [Table 24](#) on page 178.

---

 **NOTE:**

Multiplexing data streams is not supported by NDMP Server, limiting device concurrency to 1.

---

11. Click **Yes** to create another drive or **NO** to finish.

On how to configure a tape library with robotics connected to a Data Protector NDMP or General Media Agent client and drives connected to the NDMP Server system, see the online Help index: "configuring SCSI libraries". Then configure the drives as described in [Step 8](#) on page 173 through [Step 11](#) on page 174 in [Step 8](#) on page 173.

## Configuring standalone devices

To configure a standalone device:

1. In the Context List, click **Devices & Media**.
2. In the Scoping Pane, right-click **Devices**, and then click **Add Device**.


3. Type a name for the device. Optionally, describe the device.

In **Device Type**, select **Standalone**.

In **Data Format**, select the NAS device used.

In **Client**, select the NDMP client that will control the device through the NDMP Server.

In **NDMP Server**, select the NDMP Server system to which the standalone device is connected.



**Figure 65 Configuring a standalone device**

Click **Next**.

4. Provide the SCSI address of the device. For information, see “[Network appliance configuration](#)” on page 176 and “[EMC Celerra configuration](#)” on page 177.

Click **Next**.

**5.** Specify the media pool.

To specify advanced device options, click **Advanced**. For information on supported block sizes, see [Table 24](#) on page 178.



**NOTE:**

Multiplexing data streams is not supported by NDMP Server, limiting device concurrency to 1.

**6.** Click **Finish**.

## Network appliance configuration

### Before you begin

- Ensure that the NDMP Server is online.

### Standalone tape devices and drives in a tape library

To get information about standalone tape devices (or drives in a tape library) connected to the NDMP Server system, run:

```
sysconfig -t
```

on the NDMP Server system. The SCSI address is written at the beginning of the output and consists of four parts. See [Table 21](#) on page 176.

**Table 21 Analyzing the drive's SCSI address**

Parts	Description
{n u}	no rewind and unload/reload respectively. <sup>1</sup>
rst	Raw SCSI tape (always present).
{0   1   2   ...}	Device number.
{1 m h a}	Data density and compression.

<sup>1</sup>Data Protector supports only the no rewind devices.

## Example

The output for a DLT 4000 drive is:

```
nrst0m - no rewind device, format is:42500 bpi 6.0GB
```

## Library robotics

To get the SCSI address of the library robotics connected to the NDMP Server system, run:

```
sysconfig -m
```

on the NDMP Server system. The SCSI address consists of two parts. See [Table 22](#) on page 177.

**Table 22 Analyzing the library Robotics' SCSI address**

Parts	Description
mc	Media changer device (always present).
{0   1   2   ...}	Device number.

## Example

The output for a DLT 4000 library is:

```
mc0
```

## EMC Celerra configuration

### Before you begin

- Ensure that the NDMP Server is online.

### SCSI devices

To get information about SCSI devices (tape drives and library robotics) connected to the EMC Celerra NAS device:

1. Log in to the Celerra control station.
2. Run:

```
server_devconfig server_name -list -scsi -all
```

## Example

See [Table 23](#) on page 178 for an example list of SCSI devices. `c2t210` and `c2t310` are the SCSI addresses of the drives in the tape library and `c2t010` is the SCSI address of the library robotics.

**Table 23 Example of a list of SCSI devices**

Name	SCSI address	Device type	Information
jbox1	c2t010	jbox	ATL P1000 62200001.03
tape2	c2t310	tape	QUANTUM DLT7000 1624q\$
ttape2	c2t210	tape	QUANTUM DLT7000 1624q\$

## Block size

The integration supports variable tape block sizes. For limitations, see [Table 24](#) on page 178.

**Table 24 Supported block sizes**

NAS device	Block size range (KB)
ONTAP < 6.5.3	64
ONTAP ≥ 6.5.3	$64 \leq \textit{Size} \leq 256$
Celerra	$64 \leq \textit{Size} \leq 256$

## Prerequisites

- Ensure that the NDMP Server is configured to support variable block size.

The recommended (default) block size is 64 KB. You can set any value between 64 KB and 1024 KB. If the set block size is not supported by the NAS device, and you start a backup, Data Protector displays an error and aborts the session.

---

 **NOTE:**

Although the Data Protector media formatting completes successfully, that does not guarantee that the NAS device supports the set block size, and backup may still fail.

---

### Limitations

- The device used for restore must have the same or greater block size than the one that was used for backup.
- **Celerra only:** Block size value should not be greater than the Celerra `readWriteBlockSizeInKB` parameter.

---

 **TIP:**

To get the current value of the `readWriteBlockSizeInKB` parameter, run:

```
server_param server_3 -facility PAX -info  
readWriteBlockSizeInKB -verbose
```

---

## Backup

### Limitations

- Only filesystem backup is supported.
- You cannot store an NDMP backup and a standard Data Protector backup on the same medium.
- Load balancing is not supported.
- Device concurrency is limited to 1.
- You cannot browse devices and filesystems.
- Only `Full` and `Inc1` backup types are supported.
- Object copying, object mirroring, and media copying are not supported.
- By default, you cannot select more than 5 million files for backup.

To enable higher values (up to 20 millions), set the `OB2NDMPMEMONLY omnirc` file variable to 0. For more information, see [“The NDMP specific omnirc file variables”](#) on page 190.

- Once you have selected a directory, you cannot exclude any subdirectories or files from backup. Specifically, the following options are not supported:
  - Data Protector GUI: the `Trees/Filters` set of options: `Trees`, `Excludes`, `Skips`, and `Onlys`.
  - Data Protector omnib command: `-trees`, `-exclude`, `-skip`, and `-only`.

## Before you begin


- Ensure that media to be used are formatted.
- **NetApp only:** Get information about filesystems exported from the NDMP Server system by running `exportfs`.

## Creating backup specifications

Create a backup specification using the Data Protector Manager.

1. In the Context List, click **Backup**.
2. In the Scoping Pane, expand **Backup Specifications**, right-click **Filesystem**, and click **Add Backup**.

3. Select a template. In Backup type, select **Data mover backup**. In Sub type, select **NDMP-NetApp** or **NDMP-Celerra**. See [Figure 66](#) on page 181.




**Figure 66** Selecting a backup template

Click **OK**.

4. Select the NDMP Server system you want to back up and click **Add/Remove**.

In the Add/Remove Disk Mount Points dialog box, specify the filesystem mountpoints you want to back up: type the pathname of each directory in New mount point and click **Add**. See [Figure 67](#) on page 182.

Click **OK**.



**Figure 67 Specifying the NDMP Server mountpoints for backup (UNIX)**

Click **Next**.

5. Select devices to use for the backup.

To specify device options, right-click the device and click **Properties**.

Click **Next**.


6. Set backup options.  
Click **Next**.
7. Optionally, schedule the backup.  
Click **Next**.

**8.** Review the summary of the backup specification

To specify the NDMP NetApp options for a specific backup object, right-click the object, click **Properties**, and click the **NDMP** tab.

For each object, you can specify a new user account that will override the user account specified in the Import NDMP Host dialog box, provided that the access rights are properly set on the NetApp or Celerra NAS device system.

To set the NDMP environment variables, click **Advanced**. See [Figure 68](#) on page 184. For more information, see “[NDMP environment variables](#)” on page 189.



**Figure 68** Specifying advanced NetApp options

Click **Next**.

9. Save the backup specification, specifying a name and a backup specification group.

---

 **TIP:**

Preview backup session for your backup specification before using it. For details, see the online Help index: “previewing a backup”.

---

## Modifying backup specifications

To modify your backup specification, click its name in the Scoping Pane of the Backup context, then click the appropriate tab, and apply the changes.

## Starting backup sessions

Interactive backups are run on demand. They are useful for urgent backups or for restarting failed backups. Use the Data Protector GUI.

1. In the Context List, click **Backup**.
2. In the Scoping Pane, expand Backup Specifications and then Filesystem. Right-click the backup specification you want to start and click **Start Backup**.
3. Select a Backup type and Network load. Click **OK**.

## Restore

Restore filesystems using the Data Protector GUI or CLI.


### Limitations

- Once you have selected a directory, you cannot exclude any subdirectories or files from restore. Specifically, the following options are not supported:
  - Data Protector GUI options: `Restore only` and `Skip`.
  - Data Protector CLI `omnir` command: `-only`, `-skip` and `-exclude`.
- Restore preview is not supported.
- Data that was located on an NDMP server can only be restored to the same NDMP server.

## Restoring using the Data Protector GUI

1. In the Context List, select **Restore**.
2. In the Scoping Pane, expand **Filesystem**, expand the client with the data you want to restore, and then click the object that has the data.
3. In the Source page, browse for and select the objects you want to restore.
4. In the Destination page, specify restore destination for every selected object.
5. In the Options page, specify the NDMP Server system user account that will be used by Data Protector to connect to the NDMP Server system. This user must have permission to read from and write to the NDMP media.

To specify the NDMP environment variables, click **Advanced** (Figure 69 on page 186). For more information, see “[NDMP environment variables](#)” on page 189.



**Figure 69 NDMP advanced restore options**

6. In the Devices page, select devices you want to use for the restore.
7. Optionally, in the Media page, specify the media allocation priority.
8. Optionally, in the Copies page, specify the media set to restore from.
9. Click **Restore**.
10. In the Start Restore Session dialog box, click **Next**.
11. Specify **Report level** and **Network load**.

12. Click **Finish** to start the restore.

## Direct access restore

Direct access restore is an optimized data recovery operation. Backed up data is accessed directly, in the middle of a tape.


This is achieved by partitioning backed up data into segments during backup and recording their start addresses.

During restore, Data Protector first computes which segment contains the requested file or directory, then locates the segment, and finally starts reading through it to locate the beginning of the file or directory.

### Prerequisites

File history tracking must be turned on during the backup. On how to enable file history tracking, see “[NDMP environment variables](#)” on page 189.

To enable direct access restore, set the NDMP environmental variable `DIRECT` to `Y`. The procedure for the direct access restore is the same as for standard restore. The only difference is that you can browse for and select individual files and directories for restore. See [Figure 70](#) on page 188.



**Figure 70** Selecting NDMP Server Data for direct access restore

## Limitations

- **NetApp:**
  - Direct access restore of files is supported on ONTAP v6.1.x and higher.
  - Direct access restore of directories is supported on ONTAP v6.4.x and higher.

If you select both a directory and individual files from another directory and start the restore, only the selected files are restored. To restore both, use standard restore (set the NDMP environment variable `DIRECT` to `N`).
- **Celerra:** Direct access restore of directories is not supported. If you select a directory and start the restore, only the directory without its contents is restored. To restore the whole directory, use standard restore (set the NDMP environment variable `DIRECT` to `N`).

## Restoring using another device

You can restore using a device other than that used for backup. For more information, see online Help.

## NDMP environment variables

Set the NDMP environment variables for NetApp and Celerra NAS devices using the Data Protector GUI. See [Figure 68](#) on page 184 and [Figure 69](#) on page 186.

The following tables show the supported NDMP environment variables:

**Table 25 NDMP variables for NetApp NAS device**

Variable	Value	Function
HIST	y/n	Turns on/off file history tracking.
DIRECT	y/n	Enables direct access restore.
LEVEL	0, 1, 2, ... 9	Backup level (0=full).

**Table 26 NDMP variables for Celerra NAS device**

Variable	Value	Function
HIST	y/n	Turns on/off file history tracking.
DIRECT	y/n	Enables direct access restore.
LEVEL	0, 1, 2, ... 9	Backup level (0=full)
BASE_DATE	<i>32bit level 32bit date</i>	Incremental backup based on a specific date.
OPTIONS	LK	Follow symbolic links.
	AT	Preserve access time.
	NT	Save NT attributes.

Variable	Value	Function
	MI/MD/MM	Restore collision policy for localization.

---

 **NOTE:**

You can also set some NDMP environment variables using the `omnirc` file. For more information, see [“The NDMP specific omnirc file variables”](#) on page 190.

---

## The NDMP specific omnirc file variables

On how to set the `omnirc` variables, see the online Help index: [“omnirc options”](#).

---

 **NOTE:**

You can also set some variables using the Data Protector GUI. On how to do this, see [Figure 67](#) on page 182, [Figure 68](#) on page 184, and [“NDMP environment variables”](#) on page 189.

The GUI setting overrides the setting in the `omnirc` file.

---

The NDMP specific `omnirc` file variables are:

- **OB2NDMPFH** (Y/N)  
Default value: Y  
When set to Y, the NDMP Server file history tracking is turned on, which is a prerequisite for browsing and restoring individual files. However, this impacts the time needed for such a backup.  
This setting overrides the file history setting on the NDMP Server every time a backup is started.
- **OB2NDMPDIRECT** (Y/N)  
Default value: Y  
When set to Y, Data Protector uses the direct access restore functionality, provided that the NDMP Server file history tracking was turned on during the backup.
- **OB2NDMPMEMONLY** (0/1)  
Default value: 1  
This variable defines how the NDMP Media Agent uses system resources.

When set to 1, the NDMP Media Agent uses system physical memory only.

When set to 0, the NDMP Media Agent stores part of the catalog in file history swap files. Set the variable to 0 whenever the number of files in the backup specification exceeds 5 millions. Consequently, the NDMP Media Agent can handle backups of up to 20 million files (in one backup specification), provided the system has enough resources.

For example, to back up 20 million files, where 10% of the total number of backed up files are directories, with the average directory name consisting of 25 characters, and average filename consisting of 10 characters, you need approximately 1.9 GB of system memory and 2.8 GB of disk space.

For optimal performance, select 10 million files and directories for backup.

For more information on file history swap files, see the OB2NDMPFHFILEOPT variable description.

- **OB2NDMPCATQESIZE**

Default value: 5

This variable sets the number of internal buffers that hold catalog information before storing it to file history swap files. By fine tuning the value, you can increase, to a certain extent, NDMP backup performance.

When set to 5, the NDMP Media Agent can process up to 20 million files (in one backup specification), provided that enough system resources are available (approximately 1.9 GB of system memory and 2.8 GB of disk space).

Set the variable to higher values if the number of files in the backup specification is less than 20 millions and enough system memory is available.

To calculate memory allocation overhead in kilobytes, multiply the variable value by 512.

- **OB2NDMPFHFILEOPT**

Default values:

**Windows:** *Data\_Protector\_home\tmp, 32, 1024*

**UNIX:** */var/opt/omni/tmp, 32, 1024*

This variable fine tunes file history swap files usage. It has three parameters that define the following:

1. Pathname of the directory where the file history swap files are stored.
2. Maximum number of file history swap files, created by Data Protector on the NDMP client's disk.
3. Maximum size of a file history swap file (in MB).

The parameters are separated by commas. You can specify several sets of parameters. Use a semicolon to separate them.

## Example

**Windows:** C:\tmp, 32, 1024; D:\tmp\tmp\_1, 10, 1024

**UNIX:** /tmp, 10, 1024; /var/tmp, 5, 60

When the files in the first directory are full, the integration writes data to the files in the next specified directory. If the allocated disk space is used up during the backup, the backup fails.

File history swap files can increase in size significantly. Use the following formula to calculate approximate disk consumption:

$$EstConsumption = (NumOfFiles + NumOfDirs) \times (136 + AverageFileNameSize)$$

where `NumOfFiles` is the number of backed up files and `NumOfDirs` is the number of backed up directories.

See the calculations in [Table 27](#) on page 192 that presume that the number of directories is up to 10% of the total number of files, the average directory name length is 25 characters, and the average file name length is 10 characters.

**Table 27 Approximate disk consumption by file history swap files**

Number of backed up files and directories	Approximate disk consumption by file history swap files
5 Millions	0.7 GB
10 Millions	1.4 GB
20 Millions	2.8 GB

## Media management

Data Protector media management is limited because data is backed up by NDMP Server in its specific data format.

Data Protector supports the following media management functionalities:

- Import and export of media.
- Media scan.
- Media initialization.
- Dirty drive detection.

Data Protector does not support the following media management functionalities:

- Verification of backed up data.
- Media copy.

For more information, see online Help.

## Troubleshooting

This section lists problems you might encounter when using the Data Protector NDMP Server integration.

For general Data Protector troubleshooting information, see the *HP Data Protector troubleshooting guide*.

### Before you begin

- Ensure that the latest official Data Protector patches are installed. See the online Help index: “patches” on how to verify this.
- See the *HP Data Protector product announcements, software notes, and references* for general Data Protector limitations, as well as recognized issues and workarounds.
- See <http://www.hp.com/support/manuals> for an up-to-date list of supported versions, platforms, and other information.

## Problems

### Problem

#### **End of media**

At the end of the backup, Data Protector starts storing the catalog to the media. The catalog size increases with the number of files backed up. Since Data Protector has no control over how much free space is left on the media, the `End of Media` error may occur during the writing of the catalog. This has no impact on future restore because the catalog is still stored in the IDB. However, the medium cannot be imported anymore.

### Problem

#### **Import of NDMP media failed**

## Action

Ensure that the drive used for importing NDMP media is connected to an NDMP Server system.

## Problem

### **A tape remains in the drive after a successful drive scan**

## Action

Eject the tape manually and set the `OB2SCTLMOVETIMEOUT` `omnirc` file variable on the NDMP client to a higher value (for example, 360000 or higher).

On how to set the `omnirc` file variables, see the online Help index: "omnirc options".

## Problem

### **Data Protector was unable to set NDMP record size**

Data Protector reports:

```
DP was unable to set NDMP record size. Reason for this might
be that NDMP server doesn't support specified record size.
Please check the release notes in order to determine which
record size is supported for your NDMP server.
```

## Action

See "[Block size](#)" on page 178.

---

# A Integrating Citrix XenServer and HP Data Protector

## Introduction

This appendix describes a script based solution that, when used together with standard Data Protector functionality, enables online and offline backup and restore of **Virtual Machines** hosted on a **Citrix XenServer**. For the supported version of Citrix XenServer for your version of Data Protector, refer to the *HP Data Protector A.06.1x Virtualization support matrix*.

## Integration concepts

### Types of backup

Using this integration, you can perform both online and offline backups. In both cases, only full backups of virtual machines are available.

### Online backup

Online backups are performed without stopping the virtual machines concerned, using the snapshot functionality available on the Citrix XenServer. By creating a snapshot of a virtual machine, a copy of the whole virtual machine is created, using the capabilities of the underlying storage repository and is saved as a template virtual machine. This template can subsequently be used to restore the disks of the original virtual machine, or to create new virtual machines as exact copies of the original at the time of the snapshot.

- **online.** The user selects which virtual machine, or virtual machines, Data Protector should back up without disturbing their power state(s).
- **allOnline.** Data Protector backs up all virtual machines present in the XenServer without disturbing their power states.

---

 **NOTE:**

The types of storage repositories for which online backup is supported is dependent on the version of XenServer that you are using. Refer to “[Special considerations](#)” on page 214

---

Online backup is available for Virtual Hard Disk (VHD), Netapp and EqualLogic storage repositories.

## Offline backup

Offline backups are performed after first shutting down the virtual machines concerned. The complete virtual machine is then saved as an `.xva` file using the Citrix export functionality. This file can subsequently be imported into any XenServer to create a new machine equivalent to the one exported.

- **offline.** The user selects which virtual machine, or virtual machines, should be suspended and backed up.
- **allOffline.** All the virtual machines present in the XenServer are sequentially suspended and backed up.

## Disaster recovery

For disaster recovery, you need a backup of the disks that a virtual machine uses plus the metadata for the virtual machine. With this integration, this is only possible with offline backup.

## Backup processes

### Online backup

The process used by the integration script for an online backup is as follows:

1. Check that snapshot operation is allowed for all the disks of the virtual machine.
2. Snapshot the virtual machine.
3. Export the snapshot to the temporary backup folder as an `.xva` file.
4. Delete the snapshot.

After the script has finished, the contents of the temporary backup folder are backed up to the backup device using standard Data Protector functionality.

## Offline backup

The process used by the integration script for an offline backup is as follows:

1. If the virtual machine to be backed up is running, stop it.
2. Export the virtual machine to the temporary backup folder as an `.xva` file.
3. If the virtual machine was running before the backup, restart it.

After the script has finished, the contents of the temporary backup folder are backed up to the backup device using standard Data Protector functionality.

---

 **NOTE:**

The file type of the exported file for offline backup is the same as that for online backup, but it is possible to differentiate between offline and online backups from the filename. Refer to “[Specifying a restore](#)” on page 212

---

## Types of restore

The type of restore that can be performed is dependent on the type of backup that was performed: Restore from online backup requires a different process to restore from offline backup.

The following restore possibilities are available:

- **Restore from online backup.** In a similar way to online backup, this has two options available:
  - **online.** This mode allows a user to restore the disks of selected virtual machines that were backed up in a session using backup mode `online` or `allOnline`.
  - **allOnline.** This mode allows a user to restore the disks of all the virtual machines backed up in a session using backup mode `online` or `allOnline`.
- **Restore from offline backup.** In a similar way to offline backup, this has two options available:
  - **offline.** This mode allows a user to restore selected virtual machines that were backed up in a session using backup mode `offline` or `allOffline`.
  - **allOffline.** This mode allows a user to restore all virtual machines that were backed up in a session using backup mode `offline` or `allOffline`.

---

 **NOTE:**

The disks or virtual machines available for restore can be influenced by selections made within the Data Protector GUI. See [Figure 76](#).

---

## Restore processes

### Restore from online backup

First, Data Protector restores the selected contents from the relevant backup session to the temporary backup folder.

Then, the integration script uses the following process to perform the restore from online backup:

1. Ensure that the virtual machine is present and stopped.
2. Delete the old disks of the virtual machine.
3. Import the `.xva` file containing the snapshot from the temporary backup directory.
4. Restore the disks of the virtual machine using the disks from the snapshot.

### Restore from offline backup

First, Data Protector restores the selected contents from the relevant backup session to the temporary backup folder.

Then, the integration script uses the following process to perform the restore from offline backup:

1. If present, ensure that the virtual machine is stopped.
2. Delete the old virtual machine.
3. Import the `.xva` file from the temporary backup directory, activating the restore option.


The import operation of XenServer converts the `.xva` file into a virtual machine and sets the virtual machine in the same power state as it was during the export. When the restore option is set to true, the MAC of the old virtual machine is preserved

 **NOTE:**

The file type of the backup file for offline backup is the same as that for online backup, but it is possible to differentiate between offline and online backups from the filename. Refer to “[Specifying a restore](#)” on page 212

## Restore considerations

When a restore is performed, the original storage repositories used by the virtual machine are not known, so the user must specify in which storage repository the restore should be performed. If no storage repository is specified, the virtual machine will be restored in the default storage repository. Consider [Figure 71](#).



**Figure 71 Example backup and restore**

On the left side is a virtual machine with two disks: One disk uses the shared storage repository and the other the default storage repository.

When this virtual machine is backed up, an .xva file is produced.

When the virtual machine is subsequently restored, two options are available:

- A storage repository is not specified. In this case, both disks are restored into the default storage repository.
- A storage repository is specified. In this case, both disks are restored into the specified storage repository. For example, if the Shared Storage repository is specified, both disks are restored into the Shared Storage repository.

This means that the virtual machine can be restored successfully, but it is only possible to restore the disks to a single storage repository, regardless of the original configuration.

## Main integration components


To function, this integration requires the following components:

- Supported Citrix XenServer
- HP Data Protector client(s) with:
  - Disk Agent
  - Media Agent
- Integration scripts

A simple example layout for these components (with both Disk Agent and Media Agent on the same Data Protector client) is shown in [Figure 72](#).

No scripts are installed on the Citrix XenServer, but its export facility is used by the integration scripts. The integration scripts themselves are all installed on the Data Protector client with the Disk Agent installed.

During backup, virtual machines, or virtual machine disks, are exported to the Disk Agent host and backed up using Data Protector. The device used for the backup can be any device supported by Data Protector for file-system backup.



**Figure 72 Example layout**

## Installation of the integration

This section gives detailed instructions for the installation of the XenServer integration.

### Prerequisites

The machine on which the integration is to be installed must be a Data Protector client (shown as DP Client in [Figure 72](#)) with the Data Protector Disk Agent installed and must be a member of a Data Protector Cell. For further details, refer to the *HP Data Protector installation and licensing guide*.

The Data Protector Disk Agent must be installed first, since other software must be installed in specific Data Protector directories.

The following software must then be installed on the Disk Agent host:

- Python version 2.5.x or 2.6.x (available from <http://www.python.org/download>). This must be installed first. (Also, see the note regarding Pycurl below).

Install the software in the following directories:

- On Windows: `Data_Protector_home\bin`
- On Linux: `/opt/omni/bin`

- Curl with libcurl version 7.18.x or 7.19.x (available from <http://curl.haxx.se/download.html>).

Note that the package installed must contain libcurl.

- Pycurl (available from <http://pycurl.sourceforge.net/>).

If you prefer there are some compiled versions available from:

- For Windows: <http://pycurl.sourceforge.net/download/>
- For Linux: <http://rpm.pbone.net/index.php3>

---

 **NOTE:**

The installers may require a Python version earlier than the latest available, so it is best to check the situation before installing Python. For example, the fact that the `pycurl-ssl-7.18.2.win32-py2.5.exe` contains the string `py2.5` implies that python 2.5 is required.

---

- `xenAPI.py` for the version of XenServer that you are using (available from <http://community.citrix.com/display/xs/Download+SDKs>)

---

 **TIP:**

Note the full installation directory of python. You will need this later when calling the Data Protector Pre-exec and Post-exec scripts. For this documentation it is assumed to be:

- On Windows: `Data_Protector_home\bin\Python25\`
  - On Linux: `/opt/omni/bin/Python25/`
- 

## Installation of the integration scripts

The following scripts are supplied for the integration:

- `DPxen_config.py`
- `DPxen_operations.py`
- `DPxen_backup.py`
- `DPxen_restore.py`
- `DPxen_postbackup.py`

They are available as follows:

- For Data Protector A.06.11, on the Data Protector A.06.11 DVD-ROM in directory:
  - For Windows: `DP611_WIN_OTHER\Windows_other\Xen_sup`
  - For Linux: `DP611_SOL_LINUX/Xen_sup`
- For other versions of Data Protector for which the integration is supported, as a download package:
  1. Go to <http://www.hp.com/go/dataprotector>

2. Click **Patches and utilities**.
3. Select the Data Protector version with which you will be using the integration.
4. Select **Cross operating system (BIOS, Firmware, Diagnostics, etc.)**
5. In the Software-Solutions section, click **Data Protector Release x.xx / Xen Server integration packet** and download the package from the subsequent page.

When you have obtained the scripts, install them as follows:

1. If you have downloaded the package, unzip `xenServer_backup_solution.zip`.
2. Copy all of the scripts to your preferred location on the Data Protector Disk Agent host. For security reasons, the following locations are recommended:
  - On Windows: `Data_Protector_home\bin`
  - On Linux: `/opt/omni/bin`Make a note of this location: You will need it later.
3. If you do not already have the `xenAPI.py` file:
  - a. Go to <http://community.citrix.com/display/xs/Download+SDKs>.
  - b. Go to the download section for the version of XenServer that you are using.
  - c. Download the `XenAPI.py`.
4. Copy `XenAPI.py` to the same location as the integration scripts.
5. Create a folder with read and write permissions, for temporary use during backup. Create the folder as follows:
  - On Windows: `C:\tmp\backup\`
  - On Linux: `/tmp/backup/`

---

 **IMPORTANT:**

It is the contents of this directory that will actually be backed up to the backup device by Data Protector. It must therefore have enough space available to cope with your largest likely backup. For instance, if you want to be able to backup all the virtual machines on your XenServer in one operation, there must be enough space for all of them. The folder will be referred to as the temporary backup folder in these instructions.

---

## Integration script functions

The integration components, supplied in the `xenServer_backup_solution.zip` file, and their purposes are described below:

- **DPxen\_config.py.** This is the default configuration file for backup and restore operations using the integration. It is the only file that should be changed by the user, to match particular work scenarios. For details of setting up its contents, refer to “[Updating configuration script DPxen\\_config.py for backup](#)” on page 205 and “[Updating configuration script DPxen\\_config.py for restore](#)” on page 209.  
For convenience, you can create your own versions of this file, with your own names, for instance `myBackupConfig` and `myRestoreConfig`, and specify these when calling the main scripts `DPxen_backup.py` and `DPxen_restore.py`.
- **DPxen\_operations.py.** This contains same auxiliary functions that are used during backup and restore, for example, functions to import or export a virtual machine, to find a virtual machine by name, and so on.
- **DPxen\_backup.py.** This controls obtaining the files to backup from the XenServer, according to the parameters specified in the configuration file, and writing them to the temporary backup folder ready for backup by Data Protector. If snapshots are created during the backup process it also deletes them afterwards.  
This script can be called with the name of the configuration file as an argument, which allows you to use your own configuration file. If called without an argument, the default configuration file, `DPxen_config.py` is used.
- **DPxen\_restore.py.** This restores the files saved during the backup in the XenServer. It also deletes all the auxiliary elements created during a restore in the XenServer. The files restored by Data Protector to the temporary backup folder are not deleted by this script. This script also accepts as an argument the name of the configuration file to use.
- **DPxen\_postbackup.py.** This can be used to delete the contents of the temporary backup folder. It should be run after completion of a backup session as a cleanup operation. Alternatively, it could be used to delete the contents of the temporary backup folder before a restore session.

## Backup using the integration

To produce a backup using the integration, you need to perform the following operations:

1. Update the configuration script `DPxen_config.py`, or your own equivalent.
2. Ensure that the temporary backup directory is empty.

3. Set up a Data Protector backup specification.
4. Run the backup specification (or schedule it in the specification).

These operations are described in this section.

## Updating configuration script `DPxen_config.py` for backup

In the configuration file `DPxen_config.py`, or a configuration file with a name of your own, you can specify the following parameters required to perform the backup:

### *Mode*

The type of backup to be used and whether all, or only specified virtual machines are to be backed up. Valid options are: `online`, `allOnline`, `offline`, and `allOffline`. For explanations of these options, refer to “[Integration concepts](#)” on page 195

### *url*

The URL of the XenServer containing the virtual machines to be backed up.

### *username*

The username of a user with the required access rights to the Xen Server.

### *password*

The password of the user specified in *username*.

### *vmName*

A list containing the names of the virtual machines to be backed up. If you specify `online` or `offline` for the *Mode* parameter, you must specify the names of the individual virtual machines that you want to backup. The format of the list is:

```
["name1", "name2", ...]
```

The names can be obtained from the command line interface on the XenServer (running the `xe vm-list` command) or from the XenCenter interface, as shown in [Figure 73](#).


If you specify `allOnline` or `allOffline` for the *Mode* parameter, this parameter will be ignored.

### *debug*

A Boolean value that should be set to `True` if you want to create a debug file during the backup.

### *sr*

This parameter is used for restore only. It is ignored during backup operations and can be left out for backup, if preferred.



**Figure 73** Obtaining the names of the virtual machines

Once you have all the information for those parameters you can proceed to change the `DPxen_config.py` file or create a new configuration file.

## Example backup configurations

- Suspend and backup the Debian virtual machine, without creating a debug file.

```
Mode = "offline"
url = "http://tpc227.company.com"
username = "user"
password = "myPassword"
vmName = ["Debian"]
debug = False
sr = ""
```

- Suspend and backup all the virtual machines present in the XenServer and create a debug file. The debug file will be created in `/tmp/` or `C:/tmp/`.

```
Mode = "allOffline"
url = "http://tpc227.company.com"
username = "user"
password = "myPassword"
vmName = []
debug = True
sr = ""
```

- Backup the virtual machines Debian and vm2 in hot mode, creating a debug file.

```
Mode = "online"
url = "http://tpc227.company.com"
username = "user"
password = "myPassword"
```

```
vmName = ["Debian", "vm2"]
debug = True
sr = ""
```


- Backup all the virtual machines present in the XenServer, without changing their power state. When the *Mode* selected is `allOnline` or `allOffline`, the value of the *vmName* parameter is ignored so its value is not important. In this example a debug file will not be created.

```
Mode = "allOnline"
url = "http://tpc227.company.com"
username = "user"
password = "myPassword"
vmName = []
debug = False
sr = ""
```

## Creating a backup specification

In the Data Protector GUI, create a filesystem backup specification:

1. Select the **Backup** context and expand **Backup Specifications**.
2. Right click on **Filesystem** and select **Add Backup**.
3. Select a **Blank Filesystem Backup** template and click **OK**.
4. Select the item to be backed up. In this case, you must select the temporary backup folder that was created during the installation process:
  - On Windows: `C:\tmp\backup`
  - On Linux: `/tmp/backup`



**Figure 74 Temporary backup folder selection**

5. Click **Next**.
6. Select the backup device on which the backup will be performed and click **Next**.
7. In Backup Specification Options, click **Advanced**.
8. In the Backup Options window, make the following entries in the Pre-exec and Post-exec sections:

**Pre-exec:** *PythonDirectory*\python.exe  
*ScriptPath*\DPxen\_backup.py [*ConfigFile*]

**On client:** myDPCClient.com

**Post-exec:** *PythonDirectory*\python.exe  
*ScriptPath*\DPxen\_postbackup.py

**On client:** myDPCClient.com

where:

- *PythonDirectory* is the name of the directory containing the python interpreter, for example, Python25. Python must be installed in the correct location, as described in “Prerequisites” on page 201.

---

 **NOTE:**

If the integration scripts have been installed on the Cell Manager, the *full* path must be given. For example,  
*Data\_Protector\_home*\bin\Python25.

---

- *ScriptPath* is the full path of the integration scripts, for example, `Data_Protector_home\bin`
  - *ConfigFile* is an optional parameter for specifying a configuration file with a name of your own. If this is omitted, the default configuration file `DPxen_config.py` is used.
9. Click **OK** and then **Next**.
  10. Schedule the backup in the normal way for a Data Protector backup. Select a backup type of **Full**. Even though incremental backups are shown as available, only full backups are supported for this integration.
  11. Click **Next**
  12. After reviewing the specification, click **Next**. Note that if you click **Properties** on the review panel, the options tab contains object options, not backup options, so your pre-exec and post-exec entries are not displayed.
  13. Click **Save as...**, enter a name for the specification and click **OK**

## Restore using the integration

To restore a backup using the integration, you need to perform the following operations:

1. Update the configuration file `DPxen_config.py`, or your own equivalent.
2. Ensure that the temporary backup directory is empty.
3. Specify a Data Protector restore.
4. Perform the restore.

These operations are described in this section.

## Updating configuration script `DPxen_config.py` for restore

In a similar way to with backup, the configuration file `DPxen_config.py`, or a configuration file with a name of your own, must be used to specify the parameters required to perform a restore:

*Mode*

: The type of restore to be performed and whether all, or only specified virtual machines are restored. Valid options are: `online`, `allOnline`, `offline`, and `allOffline`. For explanations of these options, refer to “[Integration concepts](#)” on page 195.

*url*

The URL of the XenServer to which virtual machines are to be restored.

*username*

The username of a user with the required access rights to the XenServer.

*password*

The password of the user specified in *Username*.

*vmName*

A list containing the names of the virtual machines to be restored. If you specify *online* or *offline* for the *Mode* parameter, you must specify the names of the individual virtual machines that you want to restore. The format of the list is:

```
["name1", "name2", ..]
```

If you specify *allOnline* or *allOffline* for the *Mode* parameter, the *vmName* parameter is ignored.

*debug*

A Boolean value that should be set to *True* if you want to create a debug file during the restore.

*sr*

The name of the storage repository to which you want to restore the virtual machine(s) specified in the *vmName* parameter. This does not have to be the same storage repository as the one in use when the virtual machine was backed up. If the specified value is blank (*sr* = "") the restore is performed to the default storage repository.



#### IMPORTANT:

You must have a default storage repository defined if you leave this parameter blank for a restore, otherwise the restore will fail.

---

## Example restore configurations

- Restore the Debian virtual machine, which was backed up using *offline* mode, into the default storage repository. Create a debug file.

```
Mode = "offline"  
url = "http://tpc227.company.com"  
username = "user"  
password = "myPassword"  
vmName = ["Debian"]  
debug = False  
sr = ""
```

- Restore all the files backed up in the selected session into the default storage repository. The backup was performed in `offline` mode. Create a debug file.

```
Mode = "allOffline"
url = "http://tpc227.company.com"
username = "user"
password = "myPassword"
vmName = []
debug = True
sr = ""
```

- Restore the virtual machines Debian and vm2, which were backed up in `online` mode, into the default storage repository and create a debug file.


```
Mode = "online"
url = "http://tpc227.company.com"
username = "user"
password = "myPassword"
vmName = ["Debian", "vm2"]
debug = True
sr = ""
```

- Restore all the virtual machines present in the XenServer, without changing their power state. Create a debug file.

```
Mode = "allOnline"
url = "http://tpc227.company.com"
username = "user"
password = "myPassword"
vmName = []
debug = False
sr = ""
```

- Restore the Debian and vm2 virtual machines, which were backed up using the `offline` mode, into storage repository "Shared Storage" (See [Figure 75](#)) . Create a debug file.

```
Mode = "offline"
url = "http://tpc227.company.com"
username = "user"
password = "myPassword"
vmName = ["Debian", "vm2"]
debug = True
sr = "Shared Storage"
```



**Figure 75 Available storage repositories**

- Restore the Debian virtual machine, which was originally backed up using the online mode, into the "Removable storage" storage repository. Do not create a debug file.


```
Mode = "online"
url = "http://tpc227.company.com"
username = "user"
password = "myPassword"
vmName = ["Debian"]
debug = False
sr = "Removable storage"
```

## Specifying a restore

1. In the Context List, click **Restore**.
2. In the Scoping Pane, expand **Restore Sessions** to display clients and then the object backed up on those clients (The mount point containing the temporary backup directory you created during the installation process).
3. Click the object to open the property pages.
4. In the Source tab, select the temporary backup directory to view the files available for restore. Note that the filename formats indicate the mode of the backups in the folder, as follows:

- offline or allOffline: *servername\_vmName.xva*
- online or allOnline: *servername\_vmName\_Snapshot.xva*

Check the file format, to decide the mode of restore required, (it must be equivalent to the type of backup). See [Figure 76](#).



**Figure 76 Selection of files to restore**



**IMPORTANT:**

The Source tab shows the contents of the temporary backup folder when the backup session was performed. It does not show the current contents of the folder. It is important to ensure that the temporary backup folder is empty before performing a restore.

During a restore, the files selected in this tab are first restored to the temporary backup folder. Only files selected here are subsequently available for the restore of virtual machines using the `DPxen_restore.py` script (provided the temporary backup folder was empty beforehand).

5. In the Options tab, in the **Post-exec** field, specify the `DPxen_restore.py` script as follows:

```
PythonPath\python.exe ScriptPath\DPxen_restore.py
[ConfigFile]
```

where:

- *PythonPath* is the *full* path of the python interpreter, for example, `Data_Protector_home\bin\Python25`

- *ScriptPath* is the full path of the integration scripts, for example, `Data_Protector_home\bin`
- *ConfigFile* is an optional parameter for specifying a configuration file with a name of your own. If this is omitted, the default configuration file `DPxen_config.py` is used.



#### NOTE:

The restore mode specified in the configuration file must be suitable for the filename format of the files in the folder. See the previous point.

---

6. Click **Restore** and check that the conditions for the restore, summarized in the **Start Restore Session** panel, are correct.
7. When you are sure that the restore is correctly specified, click **Finish** to start the restore.

## Notes on restore

- It is possible to perform the restore without specifying a post-exec. In this case, the `.xva` file is restored to the temporary backup folder only. You can then run the script independently.
- After the restore has completed, the files in the temporary backup folder are not deleted automatically. If you don't require them for any other purpose, it is advisable to delete them.
- When you restore a virtual machine, its UUID changes.

## Special considerations

- The online backup performs a snapshot of the virtual machine, but this operation is not always allowed. For XenServer 5.0, at the time of writing, snapshots were supported with VHD, Netapp, or EqualLogic storage repositories only. Any attempt to perform an online backup of a virtual machine that uses a different storage repository will fail and the error message, `At least one sr used by vmName does not support snapshot`, will be displayed in the monitor. If you are performing a backup of multiple virtual machines, only the virtual machines that allow snapshot operation will be backed up.

For the latest snapshot support with your XenServer version, refer to the XenServer documentation.

If you want to convert your default storage repository to file-based VHD-on-EXT3, follow the instructions given in the Citrix forum at <http://support.citrix.com/article/ctx116324>.

- When you perform an online backup, only the disks of the virtual machines are available for restore, not the metadata. To be able to restore the disks and the metadata, you need to perform an offline backup. The best practice is to perform an offline backup after the metadata of a virtual machine has changed, for example after installing a new application. The rest of the time it is sufficient to perform online backups.

If only the disks of a virtual machine have been corrupted you only need to restore your latest online backup. If the metadata is corrupted you need to first restore your latest offline backup and then your latest online backup, if newer.

- Before performing a backup, ensure that there is enough space on the Disk Agent host. If there is not enough space, the backup will fail.

## Further information

For further information, refer to <http://www.hp.com/go/dataprotector>.



---

# Glossary

<b>access rights</b>	See <a href="#">user rights</a> .
<b>ACSL</b>	<i>(StorageTek specific term)</i> The Automated Cartridge System Library Server (ACSL) software that manages the Automated Cartridge System (ACS).
<b>Active Directory</b>	<i>(Windows specific term)</i> The directory service in a Windows network. It contains information about resources on the network and makes them accessible to users and applications. The directory services provide a consistent way to name, describe, locate, access and manage resources regardless of the physical system they reside on.
<b>AES 256-bit encryption</b>	Data Protector software encryption, based on the AES-CTR (Advanced Encryption Standard in Counter Mode) encryption algorithm that uses random keys of 256-bit length. The same key is used for both encryption and decryption. With AES 256-bit encryption, data is encrypted before it is transferred over a network and before it is written to media.
<b>AML</b>	<i>(EMASS/GRAU specific term)</i> Automated Mixed-Media library.
<b>application agent</b>	A component needed on a client to back up or restore online database integrations. See also <a href="#">Disk Agent</a> .
<b>application system</b>	<i>(ZDB specific term)</i> A system the application or database runs on. The application or database data is located on source volumes. See also <a href="#">backup system</a> and <a href="#">source volume</a> .
<b>archived redo log</b>	<i>(Oracle specific term)</i> Also called offline redo log. If the Oracle database operates in the ARCHIVELOG mode, as each online redo log is filled, it is copied to an archived log destination. This copy is the archived redo log. The presence or absence of

an archived redo log is determined by the mode the database is using:

- ARCHIVELOG - The filled online redo log files are archived before they are reused. The database can be recovered if an instance or a disk fails. A “hot” backup can be performed only when the database is running in this mode.
- NOARCHIVELOG - The filled online redo log files are not archived.

See also [online redo log](#).

**archive logging**

(*Lotus Domino Server specific term*) Lotus Domino Server database mode where transaction log files are overwritten only after they have been backed up.

**ASR Set**

A collection of files stored on several diskettes, required for proper reconfiguration of the replacement disk (disk partitioning and logical volume configuration) and automatic recovery of the original system configuration and user data that was backed up during the full client backup. These files are stored as an ASR archive file on the Cell Manager in the directory *Data\_Protector\_program\_data\Config\Server\dr\asr* (Windows Server 2008), *Data\_Protector\_home\Config\Server\dr\asr* (other Windows systems), or */etc/opt/omni/server/dr/asr* (UNIX systems) as well as on the backup medium. After a disaster occurs, the ASR archive file is extracted to diskettes which you need to perform ASR.

**Audit Logs**

Data files to which auditing information is stored.

**Audit Report**

User-readable output of auditing information created from data stored in audit log files.

**Auditing Information**

Data about every backup session that was performed over an extended, user-defined period for the whole Data Protector cell.

**autochanger**

See [library](#).

**autoloader**

See [library](#).

**Automatic Storage Management**

(*Oracle specific term*) Automatic Storage Management is an Oracle 10g/11g integrated filesystem and volume manager that manages Oracle database files. It eliminates complexity

associated with managing data and disk and provides striping and mirroring capabilities to optimize performance.

- automigration** *(VLS specific term)* The functionality that allows data backups to be first made to the VLS' virtual tapes and then migrated to physical tapes (one virtual tape emulating one physical tape) without using an intermediate backup application. See also [Virtual Library System \(VLS\)](#) and [virtual tape](#).
- BACKINT** *(SAP R/3 specific term)* SAP R/3 backup programs can call the Data Protector backint interface program via an open interface, which enables them to communicate with Data Protector software. For backup and restore, SAP R/3 programs issue orders for the Data Protector backint interface.
- backup API** The Oracle interface between the Oracle backup/restore utility and the backup/restore media management layer. The interface defines a set of routines to allow the reading and writing of data to the backup media, the creation, searching and removing the backup files.
- backup chain** See [restore chain](#).
- backup device** A device configured for use with Data Protector, which can write data to and read data from storage media. This can be, for example, a standalone DDS/DAT drive or a library.
- backup generation** One backup generation includes one full backup and all incremental backups until the next full backup.
- backup ID** An identifier of an integration object that equals the session ID of the backup of this object. The backup ID is preserved when an object is copied, exported, or imported.
- backup object** A backup unit that contains all items backed up from one disk volume (logical disk or mount point). The backed up items can be any number of files, directories, or the entire disk or mount point. Additionally, a backup object can be a database/application entity or a disk image (rawdisk). A backup object is defined by:
- Client name: Hostname of the Data Protector client where the backup object resides.
  - Mount point: For filesystem objects — the access point in a directory structure on the client where the backup object is

located (drive on Windows and mount point on UNIX). For integration objects — backup stream identification, indicating the backed up database/application items.

- Description: For filesystem objects — uniquely defines objects with identical client name and mount point. For integration objects — displays the integration type (for example, SAP or Lotus).
- Type: Backup object type. For filesystem objects — filesystem type (for example, WinFS). For integration objects — “Bar”.

**backup owner** Each backup object in the IDB has an owner. The default owner of a backup is the user who starts the backup session.

**backup session** A process that creates a copy of data on storage media. The activities are specified in a backup specification or an interactive session. All clients configured in one backup specification are backed up together in one backup session using the same backup type (full or incremental). The result of a backup session is a set of media, which was written to, also called the backup or media set.  
*See also* [backup specification](#), [incremental backup](#), and [full backup](#).

**backup set** A complete set of integration objects associated with a backup.

**backup set** (*Oracle specific term*) A logical grouping of backed up files that are created using the RMAN backup command. A backup set is a complete set of files associated with a backup. The files can be multiplexed to increase performance. A backup set contains either datafiles or archived logs, but not both together.

**backup specification** A list of objects to be backed up, together with a set of devices or drives to be used, backup options for all objects in the specification, and days and time that you want backups to be performed. The objects are entire disks/volumes or parts of them such as files, directories, or even the Windows Registry for example. File selection lists such as include-lists and exclude-lists can be specified.

**backup system** (*ZDB specific term*) A system connected to target volumes of one or multiple application systems. The backup system is typically connected to a backup device to perform the backup of the data in a replica.

See also [application system](#), [target volume](#), and [replica](#).

- backup types** See [incremental backup](#), [differential backup](#), [transaction backup](#), [full backup](#), and [delta backup](#).
- backup view** Data Protector provides different views for backup specifications:  
By Type - according to the type of data available for backups/templates. Default view.  
By Group - according to the group to which backup specifications/templates belong.  
By Name - according to the name of backup specifications/templates.  
By Manager - if you are running MoM, you can also set the Backup view according to the Cell Manager to which backup specifications/templates belong.
- BC** (*EMC Symmetrix specific term*) Business Continuance are processes that allow customers to access and manage instant copies of EMC Symmetrix standard devices.  
See also [BCV](#).
- BC** (*HP StorageWorks Disk Array XP specific term*) The Business Copy XP allows to maintain internal copies of HP StorageWorks Disk Array XP LDEVs for purposes such as data backup or data duplication. The copies (secondary volumes or S-VOLs) can be separated from the primary volumes (P-VOLs) and connected to a different system for various purposes, such as backup and development. For backup purposes, P-VOLs should be connected to the application system, and one of the S-VOL mirror sets should be connected to the backup system.  
See also [HP StorageWorks Disk Array XP LDEV](#), [CA](#), [Main Control Unit](#), [application system](#), and [backup system](#).
- BC EVA** (*HP StorageWorks EVA specific term*) Business Copy EVA is a local replication software solution enabling you to create point-in-time copies (replicas) of the source volumes using the snapshot and clone capabilities of the EVA firmware.  
See also [replica](#), [source volume](#), [snapshot](#), and [CA+BC EVA](#).
- BC Process** (*EMC Symmetrix specific term*) A protected storage environment solution that has defined specially configured EMC Symmetrix devices as mirrors or Business Continuance Volumes to protect data on EMC Symmetrix standard devices.  
See also [BCV](#).

- BC VA** *(HP StorageWorks Virtual Array specific term)* Business Copy VA allows you to maintain internal copies of HP StorageWorks Virtual Array LUNs for data backup or data duplication within the same virtual array. The copies (child or Business Copy LUNs) can be used for various purposes, such as backup, data analysis or development. When used for backup purposes, the original (parent) LUNs are connected to the application system and the Business Copy (child) LUNs are connected to the backup system. See also [HP StorageWorks Virtual Array LUN](#), [application system](#), and [backup system](#).
- BCV** *(EMC Symmetrix specific term)* Business Continuance Volumes, or BCV devices, are dedicated SLDs that are pre-configured in the ICDA on which the business continuation operation runs. BCV devices are assigned separate SCSI addresses, differing from the addresses used by the SLDs they mirror. The BCV devices are used as splittable mirrors of the primary EMC Symmetrix SLDs that need to be protected. See also [BC](#) and [BC Process](#).
- Boolean operators** The Boolean operators for the full text search functionality of the online Help system are AND, OR, NOT, and NEAR. Used when searching, they enable you to define your query precisely by creating a relationship between search terms. If no operator is specified in a multi-word search, AND is used by default. For example, the query manual disaster recovery is equivalent to manual AND disaster AND recovery.
- boot volume/disk/partition** A volume/disk/partition with files required for the initial step of the boot process. Microsoft terminology defines the boot volume/disk/partition as a volume/disk/partition containing the operating system files.
- BRARCHIVE** *(SAP R/3 specific term)* An SAP R/3 backup tool that allows you to archive redo log files. BRARCHIVE also saves all the logs and profiles of the archiving process. See also [BRBACKUP](#), and [BRRESTORE](#).
- BRBACKUP** *(SAP R/3 specific term)* An SAP R/3 backup tool that allows an online or offline backup of the control file, of individual data files, or of all tablespaces and, if necessary, of the online redo log files. See also [BRARCHIVE](#), and [BRRESTORE](#).

<b>BRRESTORE</b>	<p><i>(SAP R/3 specific term)</i> An SAP R/3 tool that can be used to restore files of the following type:</p> <ul style="list-style-type: none"> <li>• Database data files, control files, and online redo log files saved with BRBACKUP</li> <li>• Redo log files archived with BRARCHIVE</li> <li>• Non-database files saved with BRBACKUP</li> </ul> <p>You can specify files, tablespaces, complete backups, log sequence numbers of redo log files, or the session ID of the backup. See also <a href="#">BRBACKUP</a>, and <a href="#">BRARCHIVE</a>.</p>
<b>BSM</b>	<p>The Data Protector Backup Session Manager controls the backup session. This process always runs on the Cell Manager system.</p>
<b>CA</b>	<p><i>(HP StorageWorks Disk Array XP specific term)</i> Continuous Access XP allows you to create and maintain remote copies of HP StorageWorks Disk Array XP LDEVs for purposes such as data duplication, backup, and disaster recovery. CA operations involve the main (primary) disk arrays and the remote (secondary) disk arrays. The main disk arrays contain the CA primary volumes (P-VOLs), which contain the original data and are connected to the application system. The remote disk arrays contain the CA secondary volumes (S-VOLs) connected to the backup system. See also <a href="#">BC</a> <i>(HP StorageWorks Disk Array XP specific term)</i>, <a href="#">Main Control Unit</a> and <a href="#">HP StorageWorks Disk Array XP LDEV</a>.</p>
<b>CA+BC EVA</b>	<p><i>(HP StorageWorks EVA specific term)</i> The combination of Continuous Access (CA) EVA and Business Copy (BC) EVA enables you to create and maintain copies (replicas) of the source volumes on a remote EVA, and then use these copies as the source for local replication on this remote array. See also <a href="#">BC EVA</a>, <a href="#">replica</a>, and <a href="#">source volume</a>.</p>
<b>CAP</b>	<p><i>(StorageTek specific term)</i> Cartridge Access Port is a port built into the door panel of a library. The purpose is to enter or eject media.</p>
<b>catalog protection</b>	<p>Defines how long information about backed up data (such as file names and file versions) is kept in the IDB. See also <a href="#">data protection</a>.</p>

<b>CDB</b>	<p>The Catalog Database is a part of the IDB that contains information about backup, restore, object copy, object consolidation, object verification, and media management sessions. Depending on the selected logging level, it also contains file names and file versions. This part of the database is always local to the cell.</p> <p>See also <a href="#">MMDB</a>.</p>
<b>CDF file</b>	<p><i>(UNIX specific term)</i> A Context Dependent File is a file consisting of several files grouped under the same pathname. The system ordinarily selects one of the files using the context of the process. This mechanism allows machine dependent executables, system data, and device files to work correctly from all hosts in a cluster while using the same pathname.</p>
<b>cell</b>	<p>A set of systems that are under the control of a Cell Manager. The cell typically represents the systems on a site or an organizational entity, which are connected to the same LAN. Central control is available to administer the backup and restore policies and tasks.</p>
<b>Cell Manager</b>	<p>The main system in the cell where the essential Data Protector software is installed and from which all backup and restore activities are managed. The GUI used for management tasks can be located on a different system. Each cell has one Cell Manager system.</p>
<b>centralized licensing</b>	<p>Data Protector allows you to configure centralized licensing for the whole enterprise environment consisting of several cells. All Data Protector licenses are installed and kept on the Enterprise Cell Manager system. You can then allocate licenses to specific cells to suit your needs.</p> <p>See also <a href="#">MoM</a>.</p>
<b>Centralized Media Management Database (CMMDB)</b>	<p>See <a href="#">CMMDB</a>.</p>
<b>Change Journal</b>	<p><i>(Windows specific term)</i> A Windows filesystem feature that logs a record of each change as it occurs to the files and directories on a local NTFS volume.</p>

<b>Change Log Provider</b>	<i>(Windows specific term)</i> A module that can be queried to determine which objects on a filesystem have been created, modified, or deleted.
<b>channel</b>	<p><i>(Oracle specific term)</i> An Oracle Recovery Manager resource allocation. Every allocated channel starts a new Oracle process, which performs backup, restore, and recovery actions. The type of channel allocated determines the type of media used:</p> <ul style="list-style-type: none"> <li>• type 'disk'</li> <li>• type 'sbt_tape'</li> </ul> <p>If the specified channel is of type 'sbt_tape' and Oracle is integrated with Data Protector, the server process will attempt to read backups from or write data files to Data Protector.</p>
<b>circular logging</b>	<i>(Microsoft Exchange Server and Lotus Domino Server specific term)</i> Circular logging is a Microsoft Exchange Server database and Lotus Domino Server database mode, in which the transaction log file contents are periodically overwritten after the corresponding data is committed to the database. Circular logging reduces disk storage space requirements.
<b>client backup</b>	<p>A backup of all volumes (filesystems) mounted on a Data Protector client.</p> <p>What is actually backed up depends on how you select objects in a backup specification:</p> <ul style="list-style-type: none"> <li>• If you select the check box next to the client system name, a single backup object of the <code>Client System</code> type is created. As a result, at the time of the backup, Data Protector first detects all volumes that are mounted on the selected client and then backs them up. On Windows clients, <code>CONFIGURATION</code> is also backed up.</li> <li>• If you individually select all volumes that are mounted on the client system, a separate backup object of the <code>Filesystem</code> type is created for each volume. As a result, at the time of the backup, only the selected volumes are backed up. Volumes that have been potentially mounted on the client after the backup specification was created are not backed up.</li> </ul>
<b>client or client system</b>	Any system configured with any Data Protector functionality and configured in a cell.

<b>cluster-aware application</b>	It is an application that supports the cluster Application Programming Interface. Each cluster-aware application declares its own critical resources (disk volumes (on Microsoft Cluster Server), volume groups (on MC/ServiceGuard), application services, IP names and addresses, and so on).
<b>cluster continuous replication</b>	<p><i>(Microsoft Exchange Server specific term)</i> Cluster continuous replication (CCR) is a high availability solution that uses cluster management and failover options to create and maintain an exact copy (CCR copy) of a storage group. A storage group is replicated to a separate server. CCR removes any single point of failure in your Exchange back-end servers. You can perform backups using VSS on your passive Exchange Server node where a CCR copy is located and thus reducing the load on the active node.</p> <p>A CCR copy is used for disaster recovery since you can switch to the CCR copy in a few seconds. A replicated storage group is represented as a new instance of Exchange writer called Exchange Replication Service and can be backed up (using VSS) like an ordinary storage group.</p> <p>See also <a href="#">Exchange Replication Service</a> and <a href="#">local continuous replication</a>.</p>
<b>CMD Script for Informix Server</b>	<i>(Informix Server specific term)</i> A Windows CMD script that is created in INFORMIXDIR when an Informix Server database is configured. The CMD script is a set of system commands that export environment variables for Informix Server.
<b>CMMDB</b>	<p>The Data Protector Centralized Media Management Database (CMMDB) is the result of merging MMDBs from several cells in the MoM environment. It allows you to share high-end devices and media across multiple cells in a MoM environment. One cell can control the robotics, serving the devices that are connected to systems in other cells. The CMMDB must reside on the Manager-of-Managers. A reliable network connection between the MoM cell and the other Data Protector cells is highly recommended</p> <p>See also <a href="#">MoM</a>.</p>
<b>COM+ Class Registration Database</b>	<i>(Windows specific term)</i> The COM+ Class Registration Database and the Windows Registry store application attributes, class attributes, and computer-level attributes. This guarantees consistency among these attributes and provides common operation on top of these attributes.

<b>command-line interface (CLI)</b>	A set of DOS and UNIX like commands that you can use in shell scripts to perform Data Protector configuration, backup, restore, and management tasks.
<b>Command View (CV) EVA</b>	<i>(HP StorageWorks EVA specific term)</i> The user interface that enables you to configure, manage, and monitor your HP StorageWorks EVA storage system. It is used to perform various storage management tasks, for example, creating virtual disk families, managing storage system hardware, and creating snapclones and snapshots of virtual disks. The Command View EVA software runs on the HP Storage Management Appliance, and is accessed by a Web browser. See also <a href="#">HP StorageWorks EVA SMI-S Agent</a> and <a href="#">HP StorageWorks SMI-S EVA provider</a> .
<b>Command View VLS</b>	<i>(VLS specific term)</i> A web browser-based GUI that is used to configure, manage, and monitor the VLS through a LAN. See also <a href="#">Virtual Library System (VLS)</a> .
<b>concurrency</b>	See <a href="#">Disk Agent concurrency</a> .
<b>control file</b>	<i>(Oracle and SAP R/3 specific term)</i> An Oracle data file that contains entries specifying the physical structure of the database. It provides database consistency information used for recovery.
<b>copy set</b>	<i>(HP StorageWorks EVA specific term)</i> A pair that consists of the source volumes on a local EVA and their replica on a remote EVA. See also <a href="#">source volume</a> , <a href="#">replica</a> , and <a href="#">CA+BC EVA</a>
<b>CRS</b>	The Cell Request Server process (service), which runs on the Data Protector Cell Manager, and starts and controls the backup and restore sessions. The service is started as soon as Data Protector is installed on the Cell Manager. On Windows systems, the CRS runs under the account of the user specified at installation time. On UNIX systems, it runs under the account <code>root</code> .
<b>CSM</b>	The Data Protector Copy and Consolidation Session Manager process controls the object copy and object consolidation sessions and runs on the Cell Manager system.

<b>data file</b>	<i>(Oracle and SAP R/3 specific term)</i> A physical file created by Oracle that contains data structures such as tables and indexes. A data file can only belong to one Oracle database.
<b>data protection</b>	Defines how long the backed up data on media remains protected, that is, Data Protector will not overwrite it. When the protection expires, Data Protector will be able to reuse the media in one of the next backup sessions. See also <a href="#">catalog protection</a> .
<b>data stream</b>	Sequence of data transferred over the communication channel.
<b>Data_Protector_home</b>	On Windows Vista and Windows Server 2008, the directory containing Data Protector program files. On other Windows operating systems, the directory containing Data Protector program files and data files. Its default path is <code>%ProgramFiles%\OmniBack</code> , but the path can be changed in the Data Protector Setup Wizard at installation time. See also <a href="#">Data_Protector_program_data</a> .
<b>Data_Protector_program_data</b>	On Windows Vista and Windows Server 2008, the directory containing Data Protector data files. Its default path is <code>%ProgramData%\OmniBack</code> , but the path can be changed in the Data Protector Setup Wizard at installation time. See also <a href="#">Data_Protector_home</a> .
<b>database library</b>	A Data Protector set of routines that enables data transfer between Data Protector and a server of an online database integration, for example, Oracle Server.
<b>database parallelism</b>	More than one database is backed up at a time if the number of available devices allows you to perform backups in parallel.
<b>Data Replication (DR) group</b>	<i>(HP StorageWorks EVA specific term)</i> A logical grouping of EVA virtual disks. It can contain up to eight copy sets provided they have common characteristics and share a common CA EVA log. See also <a href="#">copy set</a> .
<b>database server</b>	A computer with a large database stored on it, such as the SAP R/3 or Microsoft SQL database. A server has a database that can be accessed by clients.

<b>Dboject</b>	<i>(Informix Server specific term)</i> An Informix Server physical database object. It can be a blob space, db space, or logical log file.
<b>DC directory</b>	The Detail Catalog (DC) directory contains DC binary files, which store information about file versions. It represents the DCBF part of the IDB, which occupies approximately 80% of the IDB. The default DC directory is called the <code>dcbf</code> directory and is located on the Cell Manager in the directory <code>Data_Protector_program_data\db40</code> (Windows Server 2008), <code>Data_Protector_home\db40</code> (other Windows systems), or <code>/var/opt/omni/server/db40</code> (UNIX systems). You can create more DC directories and use a custom location. Up to 50 DC directories are supported per cell. The default maximum size of a DC directory is 16 GB.
<b>DCBF</b>	The Detail Catalog Binary Files (DCBF) part of the IDB stores information about file versions and attributes. It occupies approximately 80% of the IDB. One DC binary file is created for each Data Protector medium used for backup. Its maximum size is limited by the file system settings.
<b>delta backup</b>	A delta backup is a backup containing all the changes made to the database from the last backup of any type. See also <a href="#">backup types</a> .
<b>device</b>	A physical unit which contains either just a drive or a more complex unit such as a library.
<b>device chain</b>	A device chain consists of several standalone devices configured for sequential use. When a medium in one device gets full, the backup automatically continues on a medium in the next device in the device chain.
<b>device group</b>	<i>(EMC Symmetrix specific term)</i> A logical unit representing several EMC Symmetrix devices. A device cannot belong to more than a single device group. All devices in a device group must be on the same EMC Symmetrix unit. You can use a device group to identify and work with a subset of the available EMC Symmetrix devices.
<b>device streaming</b>	A device is streaming if it can feed enough data to the medium to keep it moving forward continuously. Otherwise, the tape has to be stopped, the device waits for more data, reverses the

tape a little and resumes to write to the tape, and so on. In other words, if the data rate written to the tape is less or equal the data rate which can be delivered to the device by the computer system, then the device is streaming. Streaming significantly improves the performance of the device and use of space.

- DHCP server** A system running the Dynamic Host Configuration Protocol (DHCP) providing dynamic IP address assignment and network configuration for DHCP clients.
- differential backup** An incremental backup that backs up changes made since the last full backup. To perform this type of backup, specify the Incr 1 backup type.  
See also [incremental backup](#).
- differential backup** (*Microsoft SQL Server specific term*) A database backup that records only the data changes made to the database after the last full database backup.  
See also [backup types](#).
- differential database backup** A differential database backup records only those data changes made to the database after the last full database backup.
- direct backup** A SAN-based backup solution in which data movement directly from disk to tape (or to other secondary storage) is facilitated by the SCSI Extended Copy (Xcopy) command. Direct backup lessens the backup I/O load on systems in a SAN environment. The data movement is facilitated directly from disk to tape (or to other secondary storage) by the SCSI Extended Copy (XCOPY) command. The command is provided by any element of the infrastructure including bridges, switches, tape libraries, and disk subsystems.  
See also [XCOPY engine](#).
- directory junction** (*Windows specific term*) Directory junctions use the reparse point concept of Windows. An NTFS 5 directory junction allows you to redirect a directory/file request to another location.
- disaster recovery** A process to restore a client's main system disk to a state close to the time when a (full) backup was performed.
- disaster recovery operating system** See [DR OS](#).

<b>Disk Agent</b>	A component needed on a client to back it up and restore it. The Disk Agent controls reading from and writing to a disk. During a backup session, the Disk Agent reads data from a disk and sends it to the Media Agent, which then moves it to the device. During a restore session the Disk Agent receives data from the Media Agent and writes it to the disk. During an object verification session the Disk Agent receives data from the Media Agent and performs the verification process, but no data is written to disk.
<b>Disk Agent concurrency</b>	The number of Disk Agents that are allowed to send data to one Media Agent concurrently.
<b>disk group</b>	<i>(Veritas Volume Manager specific term)</i> The basic unit of data storage in VxVM system. A disk group can consist of one or more physical volumes. There can be more than one disk group on the system.
<b>disk image (rawdisk) backup</b>	A high-speed backup where Data Protector backs up files as bitmap images. A disk image (rawdisk) backup does not track the files and directory structure stored on the disk, but stores a disk image structure on byte level. You can perform a disk image backup of either specific disk sections or a complete disk.
<b>disk quota</b>	A concept to manage disk space consumption for all or a subset of users on a computer system. This concept is used by several operating system platforms.
<b>disk staging</b>	The process of backing up data in several phases to improve the performance of backups and restores, reduce costs of storing the backed up data, and increase the data availability and accessibility for restore. The backup stages consist of backing up data to one media type first (for example disk) and later copying it to a different media type (for example tape).
<b>distributed file media format</b>	A media format, available with the file library, which supports a space efficient type of synthetic backup called virtual full backup. Using this format is a prerequisite for virtual full backup. See also <a href="#">virtual full backup</a> .
<b>Distributed File System (DFS)</b>	A service that connects file shares into a single namespace. The file shares can reside on the same or on different computers. DFS provides client access to the resources in a location-transparent manner.

<b>DMZ</b>	The Demilitarized Zone (DMZ) is a network inserted as a "neutral zone" between a company's private network (intranet) and the outside public network (Internet). It prevents outside users from getting direct access to company servers in the intranet.
<b>DNS server</b>	In the DNS client-server model, this is the server containing information about a portion of the DNS database that makes computer names available to client resolvers querying for name resolution across the Internet.
<b>domain controller</b>	A server in a network that is responsible for user security and verifying passwords within a group of other servers.
<b>DR image</b>	Data required for temporary disaster recovery operating system (DR OS) installation and configuration.
<b>DR OS</b>	An operating system environment in which disaster recovery runs. It provides Data Protector with a basic runtime environment (disk, network, tape, and filesystem access). It has to be installed on disk or loaded into memory and configured before the Data Protector disaster recovery can be performed. DR OS can be either temporary or active. A temporary DR OS is used exclusively as a host environment for some other operating system restore along with the target operating system configuration data. It is deleted after the target system is restored to the original system configuration. An active DR OS not only hosts the Data Protector disaster recovery process but can also be a part of the restored system because it replaces its own configuration data with the original configuration data.
<b>drive</b>	A physical unit that receives data from a computer system and can write it onto a magnetic medium (typically a tape drive). It can also read the data from the medium and send it to the computer system.
<b>drive-based encryption</b>	Data Protector drive-based encryption uses the encryption functionality of the drive. While performing the backup, the drive encrypts both the data and the meta-data that is written to the medium.
<b>drive index</b>	A number that identifies the mechanical position of a drive inside a library device. This number is used by the robotic control to access a drive.

<b>dynamic client</b>	See <a href="#">client backup with disk discovery</a> .
<b>EMC Symmetrix Agent (SYMA) (EMC Symmetrix specific term)</b>	See <a href="#">Symmetrix Agent (SYMA)</a> .
<b>emergency boot file</b>	<i>(Informix Server specific term)</i> The Informix Server configuration file <code>ixbar.server_id</code> that resides in the directory <code>INFORMIXDIR/etc</code> (on Windows) or <code>INFORMIXDIR\etc</code> (on UNIX). <code>INFORMIXDIR</code> is the Informix Server home directory and <code>server_id</code> is the value of the <code>SERVERNUM</code> configuration parameter. Each line of the emergency boot file corresponds to one backup object.
<b>encryption key</b>	A 256-bit randomly generated number used by the Data Protector encryption algorithm to encode information during backups for which AES 256-bit software encryption or drive-based encryption has been specified. The same key is used for subsequent decryption of the information. Encryption keys for a Data Protector cell are stored in a central keystore on the Cell Manager.
<b>encryption key KeyID-StoreID</b>	Combined identifier used by the Data Protector Key Management Server to identify and administer encryption keys used by Data Protector. <code>KeyID</code> identifies the key within the keystore. <code>StoreID</code> identifies the keystore on the Cell Manager. If Data Protector has been upgraded from an earlier version with encryption functionality, there may be several <code>StoreIDs</code> used on the same Cell Manager.
<b>enhanced incremental backup</b>	Conventional incremental backup backs up files that have changed since a previous backup, but has certain limitations in detection of changes. Unlike conventional incremental backup, enhanced incremental backup reliably detects and backs up also renamed and moved files, as well as files with changes in attributes.
<b>Enterprise Backup Environment</b>	Several cells can be grouped together and managed from a central cell. The enterprise backup environment includes all clients located in several Data Protector cells which are managed and administered from a central cell using the Manager-of-Managers concept. See also <a href="#">MoM</a> .

<b>Event Log (Data Protector Event Log)</b>	A central repository of all Data Protector related notifications. By default, all notifications are sent to the Event Log. The Event Log is accessible only to Data Protector users in the <code>Admin</code> group and to Data Protector users who are granted the <code>Reporting</code> and <code>notifications</code> user rights. You can view or delete all events in the Event Log.
<b>Event Logs</b>	<i>(Windows specific term)</i> Files in which Windows logs all events, such as the starting or stopping of services and the logging on and off of users. Data Protector can back up Windows Event Logs as part of the Windows configuration backup.
<b>Exchange Replication Service</b>	<i>(Microsoft Exchange Server specific term)</i> The Microsoft Exchange Server service that represents storage groups that were replicated using either local continuous replication (LCR) or cluster continuous replication (CCR) technology. See also <a href="#">cluster continuous replication</a> and <a href="#">local continuous replication</a> .
<b>exchanger</b>	Also referred to as SCSI Exchanger. See also <a href="#">library</a> .
<b>exporting media</b>	A process that removes all data about backup sessions, such as systems, objects, and file names, which reside on the media from the IDB. Information about the media and their relation to a pool is also removed from the IDB. The data on the media remains unchanged. See also <a href="#">importing media</a> .
<b>Extensible Storage Engine (ESE)</b>	<i>(Microsoft Exchange Server specific term)</i> A database technology used as a storage system for information exchange in Microsoft Exchange Server.
<b>failover</b>	Transferring of the most important cluster data, called group (on Windows) or package (on UNIX) from one cluster node to another. A failover can occur mostly because of software or hardware failures or maintenance on the primary node.
<b>failover</b>	<i>(HP StorageWorks EVA specific term)</i> An operation that reverses the roles of source and destination in CA+BC EVA configurations. See also <a href="#">CA+BC EVA</a> .
<b>FC bridge</b>	See <a href="#">Fibre Channel bridge</a> .

<b>Fibre Channel</b>	An ANSI standard for high-speed computer interconnection. Using either optical or copper cables, it allows the high speed bi-directional transmission of large data files and can be deployed between sites kilometers apart. Fibre Channel connects nodes using three physical topologies: point-to-point, loop, and switched.
<b>Fibre Channel bridge</b>	A Fibre Channel bridge or multiplexer provides the ability to migrate existing parallel SCSI devices, like RAID arrays, solid state disks (SSD), and tape libraries to a Fibre Channel environment. On one side of the bridge or multiplexer there is a Fibre Channel interface while on the other side there are parallel SCSI ports. The bridge or multiplexer enables SCSI packets to be moved between the Fibre Channel and parallel SCSI devices.
<b>file depot</b>	A file containing the data from a backup to a file library device.
<b>file jukebox device</b>	A device residing on disk consisting of multiple slots used to store file media.
<b>file library device</b>	A device which resides on a disk emulating a library with several media, hence containing multiple files, referred to as file depots.
<b>File Replication Service (FRS)</b>	A Windows service that replicates the domain controller store logon scripts and group policies. FRS also enables replication of Distributed File System (DFS) shares between systems and allows any server to perform replication activity.
<b>file tree walk</b>	<i>(Windows specific term)</i> The process of traversing a filesystem to determine which objects have been created, modified, or deleted.
<b>file version</b>	The same file can be backed up multiple times in case of full backups and incremental backups (if the file changed). If the log level ALL is selected for backup, Data Protector retains one entry in the IDB for the filename itself and one for each version (date/time) of the file.
<b>filesystem</b>	The organization of files on a hard disk. A filesystem is backed up so that the file attributes and the file contents are stored on the backup media.
<b>first-level mirror</b>	<i>(HP StorageWorks Disk Array XP specific term)</i> HP StorageWorks Disk Array XP allows up to three mirror copies of a primary

volume and each of these copies can have additional two copies. The three mirror copies are called first-level mirrors. See also [primary volume](#) and [MU number](#).

<b>flash recovery area</b>	<p>(Oracle specific term) Flash recovery area is an Oracle 10g/11g managed directory, filesystem, or Automatic Storage Management disk group that serves as a centralized storage area for files related to backup and recovery (recovery files). See also <a href="#">recovery files</a>.</p>
<b>fnames.dat</b>	<p>The <code>fnames.dat</code> files of the IDB contain information on the names of the backed up files. Typically, these files occupy about 20% of the IDB, if filenames are stored.</p>
<b>formatting</b>	<p>A process that erases any data contained on a medium and prepares it for use with Data Protector. Information about media (medium ID, description, and location) is saved in the IDB as well as on the respective media (media header). Data Protector media with protected data are not formatted until the protection expires or the media are unprotected/recycled.</p>
<b>free pool</b>	<p>An auxiliary source of media for use by media pools when they run out of media. The media pools must be configured to use free pools.</p>
<b>full backup</b>	<p>A backup in which all selected objects are backed up, whether or not they have been recently modified. See also <a href="#">backup types</a>.</p>
<b>full database backup</b>	<p>A backup of all data in a database, not only the data that has been changed after the last (full or incremental) backup of the database. A full database backup does not depend on any other backup.</p>
<b>full mailbox backup</b>	<p>A full mailbox backup is a backup of the entire mailbox content.</p>
<b>full ZDB</b>	<p>A ZDB to tape or ZDB to disk+tape session in which all selected objects are streamed to tape, even if there are no changes from the previous backup. See also <a href="#">incremental ZDB</a>.</p>
<b>global options file</b>	<p>A file that allows you to customize Data Protector. It explains the global options, which cover various aspects of Data</p>

Protector, typically time-outs and limits, and affect the entire Data Protector cell. The file is located on the Cell Manager in the directory

*Data\_Protector\_program\_data*\Config\Server\Options (Windows Server 2008),

*Data\_Protector\_home*\Config\Server\Options (other Windows systems), or /etc/opt/omni/server/options (HP-UX or Solaris systems).

- group** *(Microsoft Cluster Server specific term)* A collection of resources (for example disk volumes, application services, IP names, and addresses) that are needed to run a specific cluster-aware applications.
- GUI** A graphical user interface provided by Data Protector for easy access to all configuration, administration, and operation tasks. Besides the original Data Protector GUI that runs on Windows, Data Protector also provides a Java-based graphical user interface with the same look and feel, which runs on numerous platforms.
- hard recovery** *(Microsoft Exchange Server specific term)* A Microsoft Exchange Server database recovery that is performed after a restore by the database engine, using transaction log files.
- heartbeat** A cluster data set with a time stamp carrying information about the operational status of a particular cluster node. This data set or packet is distributed among all cluster nodes.
- Hierarchical Storage Management (HSM)** A method for optimizing the use of expensive hard disk storage by migrating less frequently used data to less expensive optical platters. When needed, the data is migrated back to hard disk storage. This balances the need for fast retrieval from hard disk with the lower cost of optical platters.
- Holidays file** A file that contains information about holidays. You can set different holidays by editing the Holidays file on the Cell Manager in the directory  
*Data\_Protector\_program\_data*\Config\Server\holidays (Windows Server 2008),  
*Data\_Protector\_home*\Config\Server\holidays (other Windows systems), or /etc/opt/omni/server/Holidays (UNIX systems).

<b>hosting system</b>	A working Data Protector client used for Disk Delivery Disaster Recovery with a Data Protector Disk Agent installed.
<b>HP Operations Manager</b>	HP Operations Manager provides powerful capabilities for operations management of a large number of systems and applications in a network. Data Protector provides an integration into this management product. This integration is implemented as a SMART Plug-In for HP Operations Manager management servers on Windows, HP-UX, Solaris, and Linux. Earlier versions of HP Operations Manager were called IT/Operation, Operations Center, Vantage Point Operations, and OpenView Operations.
<b>HP Operations Manager SMART Plug-In (SPI)</b>	A fully integrated, out-of-the-box solution which "plugs into" HP Operations Manager, extending the managed domain. Through the Data Protector integration, which is implemented as an HP Operations Manager SMART Plug-In, a user can have an arbitrary number of Data Protector Cell Managers monitored as an extension to HP Operations Manager.
<b>HP StorageWorks Disk Array XP LDEV</b>	A logical partition of a physical disk within an HP StorageWorks Disk Array XP. LDEVs are entities that can be replicated in the Continuous Access XP (CA) and Business Copy XP (BC) configurations, or can be used as standalone entities. See also <a href="#">BC</a> , <a href="#">CA</a> (HP StorageWorks Disk Array XP specific term), and <a href="#">replica</a> .
<b>HP StorageWorks EVA SMI-S Agent</b>	A Data Protector software module that executes all tasks required for the HP StorageWorks Enterprise Virtual Array integration. With the EVA SMI-S Agent, the control over the array is established through HP StorageWorks SMI-S EVA provider, which directs communication between incoming requests and CV EVA. See also <a href="#">Command View (CV) EVA</a> and <a href="#">HP StorageWorks SMI-S EVA provider</a> .
<b>HP StorageWorks SMI-S EVA provider</b>	An interface used for controlling HP StorageWorks Enterprise Virtual Array. SMI-S EVA provider runs as a separate service on the HP Storage Management Appliance system and acts as a gateway between incoming requests and Command View EVA. With the Data Protector HP StorageWorks EVA integration, SMI-S EVA provider accepts standardized requests from the EVA SMI-S Agent, communicates with Command View EVA for

information or method invocation, and returns standardized responses.

See also [HP StorageWorks EVA SMI-S Agent](#) and [Command View \(CV\) EVA](#).

- HP StorageWorks Virtual Array LUN** A logical partition of a physical disk within an HP StorageWorks Virtual Array. LUNs are entities that can be replicated in the HP StorageWorks Business Copy VA configuration, or can be used as standalone entities.  
See also [BC VA](#) and [replica](#).
- ICDA** *(EMC Symmetrix specific term)* EMC's Symmetrix Integrated Cached Disk Arrays (ICDA) is a disk array device that combines a set of physical disks, a number of FWD SCSI channels, an internal cache memory, and control and diagnostic software commonly referred to as the microcode.
- IDB** The Data Protector Internal Database is an embedded database located on the Cell Manager that keeps information regarding which data is backed up, on which media it is backed up, how backup and restore sessions are run, and which devices and libraries are configured.
- IDB recovery file** An IDB file (obrindex.dat) with information about IDB backups, media, and devices used for the backup. This information can significantly simplify IDB recovery. It is recommended to relocate the file, together with IDB transaction logs, to a separate physical disk from other IDB directories, and, additionally, to make an additional copy of the file.
- importing media** A process that re-reads all data about backup sessions which are on the medium back into the IDB. This then allows for fast and convenient access to the data on the media.  
See also [exporting media](#).
- incremental backup** A backup that selects only files that have changed since a previous backup. Several levels of incremental backup are available, which enables detailed control of restore chain length.  
See also [backup types](#).
- incremental backup** *(Microsoft Exchange Server specific term)* A backup of the Microsoft Exchange Server data that has changed since the last full or incremental backup. With the incremental backup, only the transaction log files are backed up.

See also [backup types](#).

- incremental mailbox backup** An incremental mailbox backup backs up all the changes made to the mailbox after the last backup of any type.
- incremental1 mailbox backup** An incremental1 mailbox backup backs up all the changes made to the mailbox after the last full backup.
- incremental (re)-establish** *(EMC Symmetrix specific term)* A BCV or SRDF control operation. In BCV control operations, an incremental establish causes the BCV device to be synchronized incrementally and to function as an EMC Symmetrix mirrored medium. The EMC Symmetrix devices must have been previously paired. In SRDF control operations, an incremental establish causes the target (R2) device to be synchronized incrementally and to function as an EMC Symmetrix mirrored medium. The EMC Symmetrix devices must have been previously paired.
- incremental restore** *(EMC Symmetrix specific term)* A BCV or SRDF control operation. In BCV control operations, an incremental restore reassigns a BCV device as the next available mirror of the standard device in the pair. However, the standard devices are updated with only the data that was written to the BCV device during the time of the original pair split, and the data that was written to the standard device during the split is overwritten with data from the BCV mirror. In SRDF control operations, an incremental restore reassigns a target (R2) device as the next available mirror of the source (R1) device in the pair. However, the source (R1) devices are updated with only the data that was written to the target (R2) device during the time of the original pair split, and the data that was written to the source (R1) device during the split is overwritten with data from the target (R2) mirror.
- incremental ZDB** A filesystem ZDB to tape or ZDB to disk+tape session in which only changes from the last protected full or incremental backup are streamed to tape.  
See also [full ZDB](#).
- Inet** A process that runs on each UNIX system or service that runs on each Windows system in the Data Protector cell. It is responsible for communication between systems in the cell and for starting other processes needed for backup and restore. The Inet service is started as soon as Data Protector is installed on a system. The Inet process is started by the inetd daemon.

<b>Information Store</b>	<i>(Microsoft Exchange Server specific term)</i> The Microsoft Exchange Server service that is responsible for storage management. Information Store in Microsoft Exchange Server manages two kinds of stores: mailbox stores and public folder stores. A mailbox store consists of mailboxes that belong to individual users. A public folder store contains public folders and messages that are shared among several users. <i>See also</i> <a href="#">Key Management Service</a> and <a href="#">Site Replication Service</a> .
<b>Informix Server</b>	<i>(Informix Server specific term)</i> Refers to Informix Dynamic Server.
<b>initializing</b>	See <a href="#">formatting</a> .
<b>Installation Server</b>	A computer system that holds a repository of the Data Protector software packages for a specific architecture. The Installation Server is used for remote installation of Data Protector clients. In mixed environments at least two Installation Servers are needed: one for UNIX systems and one for Windows systems.
<b>instant recovery</b>	<i>(ZDB specific term)</i> A process in which a replica, produced by a ZDB-to-disk or a ZDB-to-disk+tape session, is used to restore the contents of the source volumes to their states at the time at which the replica was created, avoiding the need to perform a restore from tape. Depending on the application or database concerned, this may be all that is required, or other steps, such as the application of transaction log files, may be required for full recovery. <i>See also</i> <a href="#">replica</a> , <a href="#">zero downtime backup (ZDB)</a> , <a href="#">ZDB to disk</a> , and <a href="#">ZDB to disk+tape</a> .
<b>integration object</b>	A backup object of a Data Protector integration, such as Oracle or SAP DB.
<b>Internet Information Services (IIS)</b>	<i>(Windows specific term)</i> Microsoft Internet Information Services is a network file and application server that supports multiple protocols. Primarily, IIS transmits information in Hypertext Markup Language (HTML) pages by using the Hypertext Transport Protocol (HTTP).
<b>IP address</b>	An Internet Protocol address is a numeric address of a system used to uniquely identify the system on the network. The IP address consists of four groups of numbers separated by periods (full stops).

<b>ISQL</b>	<i>(Sybase specific term)</i> A Sybase utility used to perform system administration tasks on Sybase SQL Server.
<b>Java GUI Client</b>	The Java GUI Client is a component of the Java GUI that contains only user interface related functionalities and requires connection to the Java GUI Server to function.
<b>Java GUI Server</b>	The Java GUI Server is a component of the Java GUI that is installed on the Data Protector Cell Manager system. The Java GUI Server receives requests from the Java GUI Client, processes them and then sends the responses back to the Java GUI Client. The communication is done through Hypertext Transfer Protocol (HTTP) on port 5556.
<b>jukebox</b>	See <a href="#">library</a> .
<b>jukebox device</b>	A device consisting of multiple slots used to store either optical or file media. When being used to store file media, the jukebox device is known as the “file jukebox device”.
<b>keychain</b>	A tool that eliminates the supply of a passphrase manually when decrypting the private key. It needs to be installed and configured on the Installation Server if you perform remote installation using secure shell.
<b>Key Management Service</b>	<i>(Microsoft Exchange Server specific term)</i> The Microsoft Exchange Server service that provides encryption functionality for enhanced security. See also <a href="#">Information Store</a> and <a href="#">Site Replication Service</a> .
<b>KMS</b>	Key Management Server (KMS) is a centralized service that runs on the Cell Manager and provides key management for the Data Protector encryption functionality. The service is started as soon as Data Protector is installed on the Cell Manager.
<b>keystore</b>	All encryption keys are centrally stored in the keystore on the Cell Manager and administered by the Key Management Server (KMS).
<b>LBO</b>	<i>(EMC Symmetrix specific term)</i> A Logical Backup Object (LBO) is an object of data storage/retrieval in the EMC Symmetrix environment. It is stored/retrieved by EMC Symmetrix as one entity and can only be restored as a whole.

<b>library</b>	Also called autochanger, jukebox, autoloader, or exchanger. A library contains media in repository slots. Each slot holds one medium (for example, DDS/DAT). Media are moved between slots and drives by a robotic mechanism, allowing random access to media. The library can contain multiple drives.
<b>lights-out operation or unattended operation</b>	A backup or restore operation that takes place outside of normal business hours without an operator. This implies that no operator personnel is present to work with the backup application or service mount requests, for example.
<b>LISTENER.ORA</b>	<i>(Oracle specific term)</i> An Oracle configuration file that describes one or more Transparent Network Substrate (TNS) listeners on a server.
<b>load balancing</b>	By default, Data Protector automatically balances the usage of devices selected for backup, so that they are used evenly. Load balancing optimizes the device usage by balancing the number of objects written to each device. Since load balancing is done automatically during backup time, you do not need to manage how the data is actually backed up. You just specify the devices to be used. If you do not want to use load balancing, you can select which device will be used for each object in the backup specification. Data Protector will access the devices in the specified order.
<b>local and remote recovery</b>	Remote recovery is performed if all Media Agent hosts specified in the SRD file are accessible. If any of them fails, the disaster recovery process fails over to the local mode. This means that the target system is searched for locally attached devices. If only one device is found, it is automatically used. Otherwise, Data Protector prompts you to select the device, which will be used for restore.
<b>local continuous replication</b>	<i>(Microsoft Exchange Server specific term)</i> Local continuous replication (LCR) is a single-server solution that creates and maintains an exact copy (LCR copy) of a storage group. An LCR copy is located on the same server as the original storage group. When an LCR copy is created, it is kept up to date through change propagation (log replay) technology. The replication feature in LCR guarantees that logs that have not been replicated are not deleted. The implication of this behavior is that running backups in a mode that deletes logs may not actually free space if replication is sufficiently far behind in its log copying.

An LCR copy is used for disaster recovery because you can switch to the LCR copy in a few seconds. If an LCR copy is used for backup and if it is located on a different disk than the original data, then the I/O load on a production database is minimal. A replicated storage group is represented as a new instance of Exchange writer called Exchange Replication Service and can be backed up (using VSS) as a normal storage group. See also [cluster continuous replication](#) and [Exchange Replication Service](#).

- lock name** You can configure the same physical device several times with different characteristics, by using different device names. The lock name is a user specified string that is used for locking all such device configurations to prevent collision if several such devices (device names) are used concurrently. Use an identical lock name for all device definitions which use the same physical device.
- log\_full shell script** (*Informix Server UNIX specific term*) A script provided by ON-Bar that you can use to start backing up logical log files when Informix Server issues a logfull event alarm. The Informix Server `ALARMPROGRAM` configuration parameter defaults to the `INFORMIXDIR/etc/log_full.sh`, where `INFORMIXDIR` is the Informix Server home directory. If you do not want logical logs to be backed up continuously, set the `ALARMPROGRAM` configuration parameter to `INFORMIXDIR/etc/no_log.sh`.
- logging level** The logging level determines the amount of details on files and directories written to the IDB during backup, object copying, or object consolidation. You can always restore your data, regardless of the logging level used during backup. Data Protector provides four logging levels: Log All, Log Directories, Log Files, and No Log. The different logging level settings influence the IDB growth, backup speed, and the convenience of browsing data for restore.
- logical-log files** This applies to online database backup. Logical-log files are files in which modified data is first stored before being flushed to disk. In the event of a failure, these logical-log files are used to roll forward all transactions that have been committed as well as roll back any transactions that have not been committed.

<b>login ID</b>	<i>(Microsoft SQL Server specific term)</i> The name a user uses to log on to Microsoft SQL Server. A login ID is valid if Microsoft SQL Server has an entry for that user in the system table syslogin.
<b>login information to the Oracle Target Database</b>	<p><i>(Oracle and SAP R/3 specific term)</i> The format of the login information is <i>user_name/password@service</i>, where:</p> <ul style="list-style-type: none"> <li>• <i>user_name</i> is the name by which a user is known to Oracle Server and to other users. Every user name is associated with a password and both have to be entered to connect to an Oracle Target Database. This user must have Oracle SYSDBA or SYSOPER rights.</li> <li>• <i>password</i> must be the same as the password specified in the Oracle password file (<code>orapwd</code>), which is used for authentication of users performing database administration.</li> <li>• <i>service</i> is the name used to identify an SQL*Net server process for the target database.</li> </ul>
<b>login information to the Recovery Catalog Database</b>	<p><i>(Oracle specific term)</i> The format of the login information to the Recovery (Oracle) Catalog Database is <i>user_name/password@service</i>, where the description of the user name, password, and service name is the same as in the Oracle SQL*Net V2 login information to the Oracle target database. In this case, <i>service</i> is the name of the service to the Recovery Catalog Database, not the Oracle target database. Note that the Oracle user specified here must be the owner of the Oracle Recovery Catalog.</p>
<b>Lotus C API</b>	<i>(Lotus Domino Server specific term)</i> An interface for the exchange of backup and recovery information between Lotus Domino Server and a backup solution, like Data Protector.
<b>LVM</b>	A Logical Volume Manager is a subsystem for structuring and mapping physical disk space to logical volumes on UNIX systems. An LVM system consists of several volume groups, where each volume group has several volumes.
<b>Magic Packet</b>	See <a href="#">Wake ONLAN</a> .
<b>mailbox</b>	<i>(Microsoft Exchange Server specific term)</i> The location to which e-mail is delivered, which is set up by the administrator for each user. If a set of personal folders is designated as the e-mail delivery location, e-mail is routed from the mailbox to this location.

<b>mailbox store</b>	<i>(Microsoft Exchange Server specific term)</i> A part of the Information Store that maintains information in user mailboxes. A mailbox store consists of a binary rich-text <code>.edb</code> file and a streaming native internet content <code>.stm</code> file.
<b>Main Control Unit (MCU)</b>	<i>(HP StorageWorks Disk Array XP specific term)</i> An HP StorageWorks XP disk array that contains the primary volumes for the CA and BC configurations and acts as a master device. See also <a href="#">BC</a> (HP StorageWorks Disk Array XP specific term), <a href="#">CA</a> (HP StorageWorks Disk Array XP specific term), and <a href="#">HP StorageWorks Disk Array XP LDEV</a> .
<b>Manager-of-Managers (MoM)</b>	See <a href="#">MoM</a> .
<b>make_net_recovery</b>	<code>make_net_recovery</code> is an Ignite-UX command, which allows you to create a recovery archive over the network onto the Ignite-UX server or any other specified system. The target system can be recovered across subnets after booting either from a bootable tape created by the Ignite-UX <code>make_boot_tape</code> command or the system boots directly from the Ignite-UX server. Booting directly from the Ignite-UX server can be automated with the Ignite-UX <code>bootsys</code> command or interactively specified on the boot console.
<b>make_tape_recovery</b>	<code>make_tape_recovery</code> is a command on Ignite-UX which creates a bootable recovery (installation) tape, customized for your system and enables you unattended disaster recovery by connecting the backup device directly to the target system and booting the target system from the bootable recovery tape. The backup device has to be locally connected to the client during the creation of the archive and recovery of the client.
<b>MAPI</b>	<i>(Microsoft Exchange Server specific term)</i> The MAPI (Messaging Application Programming Interface) is the programming interface that lets applications and messaging clients interact with messaging and information systems.
<b>MCU</b>	See <a href="#">Main Control Unit (MCU)</a> .
<b>Media Agent</b>	A process that controls reading from and writing to a device, which reads from or writes to a medium (typically a tape). During a backup session, a Media Agent receives data from the Disk Agent and sends it to the device for writing it to the medium.

During a restore or object verification session, a Media Agent locates data on the backup medium and sends it to the Disk Agent for processing. For a restore session, the Disk Agent then writes the data to the disk. A Media Agent also manages the robotics control of a library.

<b>media allocation policy</b>	Determines in which sequence media are used for backup. The Strict allocation policy directs Data Protector to prompt for a specific medium. The Loose policy directs Data Protector to prompt for any suitable medium. The Formatted First policy directs Data Protector to give preference to unknown media, even if unprotected media are available in the library.
<b>media condition</b>	The quality of a medium as derived from the media condition factors. Heavy usage and age result in an increased number of read and write errors with tape media. Media need to be replaced when they are marked as POOR.
<b>media condition factors</b>	The user-assigned age threshold and overwrite threshold used to determine the state of a medium.
<b>medium ID</b>	A unique identifier assigned to a medium by Data Protector.
<b>media label</b>	A user-defined identifier used to describe a medium.
<b>media location</b>	A user-defined physical location of a medium, such as "building 4" or "off-site storage".
<b>media management session</b>	A session performing some action on a medium, such as initializing, scanning the content, verifying data on a medium, or copying a medium.
<b>media pool</b>	A set of media of the same type (such as DDS) used and tracked as a group. Media are formatted and assigned to a media pool.
<b>media set</b>	The result of a backup session is data backed up on a group of media called media set. Depending on the media usage policy, several sessions can share the same media.
<b>media type</b>	The physical type of media, such as DDS or DLT.
<b>media usage policy</b>	The media usage policy controls how new backups are added to the already used media. It can be <code>Appendable</code> , <code>Non-Appendable</code> , or <code>Appendable for incrementals only</code> .

<b>merging</b>	This defines one mode to resolve file conflicts during restore. If the file to be restored already exists at the destination, the one with the more recent modification date is kept. Files not present on the disk are always restored. See also <a href="#">overwrite</a> .
<b>Microsoft Exchange Server</b>	A "client-server" messaging and a workgroup system that offers a transparent connection to many different communication systems. It provides users with an electronic mail system, individual and group scheduling, online forms, and workflow automation tools. It provides a developer with a platform on which to build custom information-sharing and messaging-service applications.
<b>Microsoft Management Console (MMC)</b>	<i>(Windows specific term)</i> An administration model for Windows-based environments. It provides a simple, consistent, and integrated administration user interface allowing management of many applications through the same GUI, provided that the applications adhere to the MMC model.
<b>Microsoft SQL Server</b>	A database management system designed to meet the requirements of distributed "client-server" computing.
<b>Microsoft Volume Shadow Copy Service (VSS)</b>	A software service that provides a unified communication interface to coordinate backup and restore of a VSS-aware application regardless of its specific features. This service collaborates with the backup application, writers, shadow copy providers, and the operating system kernel to implement the management of volume shadow copies and shadow copy sets. See also <a href="#">shadow copy</a> , <a href="#">shadow copy provider</a> , <a href="#">replica</a> , and <a href="#">writer</a> .
<b>mirror (EMC Symmetrix and HP StorageWorks Disk Array XP specific term)</b>	See <a href="#">target volume</a> .
<b>mirror rotation (HP StorageWorks Disk Array XP specific term)</b>	See <a href="#">replica set rotation</a> .

<b>MMD</b>	The Media Management Daemon process (service) runs on the Data Protector Cell Manager and controls media management and device operations. The process is started when Data Protector is installed on the Cell Manager.
<b>MMDB</b>	The Media Management Database (MMDB) is a part of the IDB that contains information about media, media pools, devices, libraries, library drives, and slots configured in the cell, as well as the Data Protector media used for backup. In an enterprise backup environment, this part of the database can be common to all cells. See also <a href="#">CMMDB</a> , <a href="#">CDB</a> .
<b>MoM</b>	Several cells can be grouped together and managed from a central cell. The management system of the central cell is the Manager-of-Managers (MoM). The cells are called MoM clients. The MoM enables you to configure and manage multiple cells from a central point.
<b>mount request</b>	A screen prompt that tells you to insert a specific medium into a device. Once you respond to the mount request by providing the required medium and confirm the mount request, the session continues.
<b>mount point</b>	The access point in a directory structure for a disk or logical volume, for example <code>/opt</code> or <code>d:.</code> On UNIX, the mount points are displayed using the <code>bd</code> or <code>df</code> command.
<b>MSM</b>	The Data Protector Media Session Manager, which runs on the Cell Manager and controls media sessions, such as copying media.
<b>MU number</b>	<i>(HP StorageWorks Disk Array XP specific term)</i> Mirror Unit number. An integer number (0, 1 or 2), used to indicate a first-level mirror. See also <a href="#">first-level mirror</a> .
<b>multi-drive server</b>	A license that allows you to run an unlimited number of Media Agents on a single system. This license, which is bound to the IP address of the Cell Manager, is no longer available.
<b>obdrindex.dat</b>	See <a href="#">IDB recovery file</a> .

<b>OBDR capable device</b>	A device that can emulate a CD-ROM drive loaded with a bootable disk and can thus be used as a backup or boot device for disaster recovery purposes.
<b>object</b>	See <a href="#">backup object</a> .
<b>object consolidation</b>	The process of merging a restore chain of a backup object, consisting of a full backup and at least one incremental backup, into a new, consolidated version of this object. The process is a part of the synthetic backup procedure. The result is a synthetic full backup of the specified backup object.
<b>object consolidation session</b>	A process that merges a restore chain of a backup object, consisting of a full backup and at least one incremental backup, into a new, consolidated version of this object.
<b>object copy</b>	A copy of a specific object version that is created during an object copy session or a backup session with object mirroring.
<b>object copy session</b>	A process that creates an additional copy of the backed up data on a different media set. During an object copy session, the selected backed up objects are copied from the source to the target media.
<b>object copying</b>	The process of copying selected object versions to a specific media set. You can select object versions from one or several backup sessions to be copied.
<b>object ID</b>	<i>(Windows specific term)</i> The object IDs (OIDs) enable access to NTFS 5 files no matter where in the system the files reside. Data Protector treats the OIDs as alternate streams of the files.
<b>object mirror</b>	A copy of a backup object created using object mirroring. Object mirrors are often referred to as object copies.
<b>object mirroring</b>	The process of writing the same data to several media sets during a backup session. Data Protector enables you to mirror all or some backup objects to one or more media sets.
<b>object verification</b>	The process of verifying the data integrity of backup objects, from the Data Protector point of view, and the ability of Data Protector to deliver them to the required destination. The process can be used to provide a level of confidence in the ability to restore object versions created by backup, object copy, or object consolidation sessions.

<b>object verification session</b>	A process that verifies the data integrity of specified backup objects or object versions and the ability of selected Data Protector network components to deliver them to a specified host. Object verification sessions can be run interactively, or as specified in automated post-backup, or scheduled specifications.
<b>offline backup</b>	<p>A backup during which an application database cannot be used by the application.</p> <ul style="list-style-type: none"> <li>• For simple backup methods (non ZDB), the database is generally put into a quiescent state that allows use by the backup system, but not the application, for the whole backup period (several minutes or hours). For instance, for backup to tape, until streaming of data to the tape is finished.</li> <li>• For ZDB methods, the database is also put into the quiescent state, but for the period of the data replication process only (several seconds). Normal database operation can then be resumed for the rest of the backup process.</li> </ul> <p>See also <a href="#">zero downtime backup (ZDB)</a> and <a href="#">online backup</a>.</p>
<b>offline recovery</b>	Offline recovery is performed if the Cell Manager is not accessible, for example, due to network problems. Only standalone and SCSI library devices can be used for offline recovery. Recovery of the Cell Manager is always offline.
<b>offline redo log</b>	See <a href="#">archived redo log</a> .
<b>ON-Bar</b>	<p><i>(Informix Server specific term)</i> A backup and restore system for Informix Server. ON-Bar enables you to create a copy of your Informix Server data and later restore the data. The ON-Bar backup and restore system involves the following components:</p> <ul style="list-style-type: none"> <li>• the <code>onbar</code> command</li> <li>• Data Protector as the backup solution</li> <li>• the XBSA interface</li> <li>• ON-Bar catalog tables, which are used to back up dobjects and track instances of dobjects through multiple backups.</li> </ul>
<b>ONCONFIG</b>	<p><i>(Informix Server specific term)</i> An environment variable that specifies the name of the active ONCONFIG configuration file. If the ONCONFIG environment variable is not present, Informix Server uses the configuration values from the <code>onconfig</code> file in the directory <code>INFORMIXDIR\etc</code> (on Windows) or <code>INFORMIXDIR/etc/</code> (on UNIX).</p>

- online backup** A backup performed while a database application remains available for use. The database is placed into a special backup mode of operation for the time period that the backup application requires access to the original data objects. During this period, the database is fully operational, but there may be a small performance impact and log files may grow very quickly.
- For simple backup methods (non ZDB), backup mode is required for the whole backup period (several minutes or hours). For instance, for backup to tape, until streaming of data to tape is finished.
  - For ZDB methods, backup mode is required for the short period of the data replication process only (several seconds). Normal database operation can then be resumed for the rest of the backup process.
- In some cases, transaction logs may also have to be backed up to allow a consistent database to be restored.  
See also [zero downtime backup \(ZDB\)](#), and [offline backup](#).
- online redo log** (*Oracle specific term*) Redo logs that have not been archived, but are either available to the instance for recording database activity or are filled and waiting to be archived or reused.  
See also [archived redo log](#).
- OpenSSH** A set of network connectivity tools used to access remote machines securely, by using a variety of authentication and encryption methods. It needs to be installed and configured on the Installation Server and the client if you perform remote installation using secure shell.
- Oracle Data Guard** (*Oracle specific term*) Oracle Data Guard is Oracle's primary disaster recovery solution. Oracle Data Guard is able to maintain up to nine standby databases, each of which is a real-time copy of the production (primary) database, to protect against corruptions, data failures, human errors, and disasters. If a failure occurs on the production (primary) database, then a failover to one of the standby databases which becomes the new primary database is possible. In addition, planned downtime for maintenance can be reduced because the production processing can be moved from the current primary database to a standby database and back quickly.

<b>Oracle instance</b>	<i>(Oracle specific term)</i> Each installation of an Oracle database on one or more systems. One computer system can have several instances of a database running.
<b>ORACLE_SID</b>	<i>(Oracle specific term)</i> A unique name for an Oracle Server instance. To switch among Oracle Servers, specify the desired <i>ORACLE_SID</i> . The <i>ORACLE_SID</i> is included in the <b>CONNECT DATA</b> parts of the connect descriptor in a <b>TNSNAMES.ORA</b> file and in the definition of the TNS listener in the <b>LISTENER.ORA</b> file.
<b>original system</b>	The system configuration backed up by Data Protector before a computer disaster hits the system.
<b>overwrite</b>	An option that defines one mode to resolve file conflicts during restore. All files are restored from a backup even if they are older than existing files. See also <a href="#">merging</a> .
<b>ownership</b>	<p>Backup ownership affects the ability of users to see and restore data. Each backup session and all the data backed up within it is assigned an owner. The owner can be the user that starts an interactive backup, the account under which the CRS process is running, or the user specified as the owner in the backup specification options.</p> <p>If a user starts an existing backup specification without modifying it, the backup session is not considered as interactive.</p> <p>If a modified backup specification is started by a user, the user is the owner unless the following is true:</p> <ul style="list-style-type: none"> <li>• The user has the Switch Session Ownership user right.</li> <li>• The backup session owner is explicitly defined in the backup specification, where the username, group or domain name, and the system name are specified.</li> </ul> <p>If a backup is scheduled on a UNIX Cell Manager, the session owner is root:sys unless the above conditions are true.</p> <p>If a backup is scheduled on a Windows Cell Manager, the session owner is the user specified during the installation, unless the above conditions are true.</p>
<b>P1S file</b>	P1S file contains information on how to format and partition all disks installed in the system during Enhanced Automated Disaster Recovery (EADR). It is created during full backup and is saved on backup medium and on Cell Manager into the directory

*Data\_Protector\_program\_data\Config\Server\dr\pls* (Windows Server 2008),  
*Data\_Protector\_home\Config\Server\dr\pls* (other Windows systems), or */etc/opt/omni/server/dr/pls* (UNIX systems) with the filename *recovery.pls*.

- package** *(MC/ServiceGuard and Veritas Cluster specific term)* A collection of resources (for example volume groups, application services, IP names and addresses) that are needed to run a specific cluster-aware application.
- pair status** *(HP StorageWorks Disk Array XP specific term)* A mirrored pair of disks can have various status values depending on the action performed on it. The three most important status values are:
- **COPY** - The mirrored pair is currently re-synchronizing. Data is transferred from one disk to the other. The disks do not contain the same data.
  - **PAIR** - The mirrored pair is completely synchronized and both disks (the primary volume and the mirrored volume) contain identical data.
  - **SUSPENDED** - The link between the mirrored disks is suspended. That means that both disks are accessed and updated independently. However, the mirror relationship is still maintained and the pair can be re-synchronized without transferring the complete disk.
- parallel restore** Restoring backed up data to multiple disks at the same time (that is, in parallel) by running multiple Disk Agents, that receive data from one Media Agent. For the parallel restore to work, select data that is located on different disks or logical volumes and during backup, the data from the different objects must have been sent to the same device using a concurrency of 2 or more. During a parallel restore, the data for multiple objects selected for restore is read from media at the same time, thereby improving performance.
- parallelism** The concept of reading multiple data streams from an online database.
- phase 0 of disaster recovery** Preparation for disaster recovery - the prerequisite condition for a successful disaster recovery.

<b>phase 1 of disaster recovery</b>	Installation and configuration of DR OS, establishing previous storage structure.
<b>phase 2 of disaster recovery</b>	Restoration of operating system (with all the configuration information that defines the environment) and Data Protector.
<b>phase 3 of disaster recovery</b>	Restoration of user and application data.
<b>physical device</b>	A physical unit that contains either a drive or a more complex unit such as a library.
<b>post-exec</b>	A backup option that executes a command or script after the backup of an object or after the entire session completes. Post-exec commands are not supplied by Data Protector. You need to create your own. They can be written as executables or batch files on Windows and as shell scripts on UNIX. See also <a href="#">pre-exec</a> .
<b>pre- and post-exec commands</b>	Pre- and post-exec commands are used to perform additional action before and after a backup or restore session. They are not supplied by Data Protector. You need to create your own commands. They can be written as executables or batch files on Windows and as shell scripts on UNIX.
<b>prealloc list</b>	A subset of media in a media pool that specifies the order in which media are used for backup.
<b>pre-exec</b>	A backup option that executes a command or script before the backup of an object or before the entire session is started. Pre-exec commands are not supplied by Data Protector. You need to create your own. They can be written as executables or batch files on Windows and as shell scripts on UNIX. See also <a href="#">post-exec</a> .
<b>primary volume (P-VOL)</b>	<i>(HP StorageWorks Disk Array XP specific term)</i> Standard HP StorageWorks Disk Array XP LDEVs that act as a primary volume for the CA and BC configurations. The P-VOL is located in the MCU. See also <a href="#">secondary volume (S-VOL)</a> and <a href="#">Main Control Unit (MCU)</a> .
<b>protection</b>	See <a href="#">data protection</a> and also <a href="#">catalog protection</a> .

<b>public folder store</b>	<i>(Microsoft Exchange Server specific term)</i> The part of the Information Store that maintains information in public folders. A public folder store consists of a binary rich-text <code>.edb</code> file and a streaming native internet content <code>.stm</code> file.
<b>public/private backed up data</b>	When configuring a backup, you can select whether the backed up data will be: <ul style="list-style-type: none"> <li>• public, that is visible (and accessible for restore) to all Data Protector users</li> <li>• private, that is, visible (and accessible for restore) only to the owner of the backup and administrators</li> </ul>
<b>RAID</b>	Redundant Array of Inexpensive Disks.
<b>RAID Manager Library</b>	<i>(HP StorageWorks Disk Array XP specific term)</i> The RAID Manager Library is used internally by Data Protector on Solaris systems to allow access to HP StorageWorks Disk Array XP configuration, status, and performance data and to key HP StorageWorks Disk Array XP features through the use of function calls translated into a sequence of low level SCSI commands.
<b>RAID Manager XP</b>	<i>(HP StorageWorks Disk Array XP specific term)</i> The RAID Manager XP application provides an extensive list of commands to report and control the status of the CA and BC applications. The commands communicate through a RAID Manager instance with the HP StorageWorks Disk Array XP Disk Control Unit. This instance translates the commands into a sequence of low level SCSI commands.
<b>rawdisk backup</b>	See <a href="#">disk image backup</a> .
<b>RCU</b>	See <a href="#">Remote Control Unit (RCU)</a> .
<b>RDBMS</b>	Relational Database Management System.
<b>RDF1/RDF2</b>	<i>(EMC Symmetrix specific term)</i> A type of SRDF device group. Only RDF devices can be assigned to an RDF group. An RDF1 group type contains source (R1) devices and an RDF2 group type contains target (R2) devices.
<b>RDS</b>	The Raima Database Server process (service) runs on the Data Protector Cell Manager and manages the IDB. The process is started when Data Protector is installed on the Cell Manager.

<b>Recovery Catalog</b>	<p><i>(Oracle specific term)</i> A set of Oracle tables and views that are used by Recovery Manager to store information about Oracle databases. This information is used by Recovery Manager to manage the backup, restore, and recovery of Oracle databases. The recovery catalog contains information about:</p> <ul style="list-style-type: none"> <li>• The physical schema of the Oracle target database</li> <li>• Data file and archived log backup sets</li> <li>• Data file copies</li> <li>• Archived Redo Logs</li> <li>• Stored scripts</li> </ul>
<b>Recovery Catalog Database</b>	<p><i>(Oracle specific term)</i> An Oracle database that contains a recovery catalog schema. You should not store the recovery catalog in your target database.</p>
<b>recovery files</b>	<p><i>(Oracle specific term)</i> Recovery files are Oracle 10g/11g specific files that reside in the flash recovery area: the current control file, online redo logs, archived redo logs, flashback logs, control file autobackups, datafile copies, and backup pieces. See also <a href="#">flash recovery area</a>.</p>
<b>RecoveryInfo</b>	<p>When backing up Windows configuration files, Data Protector collects the information about the current system configuration (information on disk layout, volume, and network configuration). This information is needed for disaster recovery.</p>
<b>Recovery Manager (RMAN)</b>	<p><i>(Oracle specific term)</i> An Oracle command-line interface that directs an Oracle Server process to back up, restore, or recover the database it is connected to. RMAN uses either the recovery catalog or the control file to store information about backups. This information can be used later in restore sessions.</p>
<b>recycle</b>	<p>A process that removes the data protection from all backed up data on a medium, allowing Data Protector to overwrite it during one of the next backups. Data that belongs to the same session(s) but resides on other media is also unprotected. Recycling does not actually alter the data on the medium.</p>
<b>redo log</b>	<p><i>(Oracle specific term)</i> Every Oracle database has a set of two or more redo log files. The set of redo log files for the database is known as the database's redo log. Oracle uses the redo log to record all changes made to data.</p>

<b>Remote Control Unit (RCU)</b>	<i>(HP StorageWorks Disk Array XP specific term)</i> The Remote Control Unit (RCU) acts as a slave of an MCU in a CA configuration. In bidirectional configurations, the RCU can act as an MCU.
<b>Removable Storage Management Database</b>	<i>(Windows specific term)</i> A Windows service used for managing removable media (such as tapes and disks) and storage devices (libraries). Removable Storage allows applications to access and share the same media resources.
<b>reparse point</b>	<i>(Windows specific term)</i> A system-controlled attribute that can be associated with any directory or file. The value of a reparse attribute can have user-controlled data. The format of the data is understood by the application that stored the data and a filesystem filter that was installed to interpret the data and process such files. Whenever the filesystem encounters a file with a reparse point, it attempts to find the filesystem filter associated with the data format.
<b>replica</b>	<i>(ZDB specific term)</i> An image, at a particular point in time, of the data in source volumes that contain user-specified backup objects. Depending on the hardware or software with which it is created, the image may be an independent exact duplicate (clone) of the storage blocks at the physical disk level (for example, a split mirror or snapclone), or a virtual copy (for example, a snapshot). From perspective of a basic operating system, the complete physical disk containing backup objects is replicated. However, if a volume manager is used on UNIX, the whole volume or disk group containing a backup object (logical volume) is replicated. If partitions are used on Windows, the whole physical volume containing the selected partition is replicated. See also <a href="#">snapshot</a> , <a href="#">snapshot creation</a> , <a href="#">split mirror</a> , and <a href="#">split mirror creation</a> .
<b>replica set</b>	<i>(ZDB specific term)</i> A group of replicas, all created using the same backup specification. See also <a href="#">replica</a> and <a href="#">replica set rotation</a> .
<b>replica set rotation</b>	<i>(ZDB specific term)</i> The use of a replica set for regular backup production: Each time the same backup specification requiring the use of a replica set is run, a new replica is created and added to the set, until the maximum number for the set is

reached. After that, the oldest replica in the set is replaced, maintaining the maximum number of replicas in the set.  
See also [replica](#) and [replica set](#).

<b>restore chain</b>	All backups that are necessary for a restore of a backup object to a certain point in time. A restore chain consists of a full backup of the object and any number of related incremental backups.
<b>restore session</b>	A process that copies data from backup media to a client.
<b>resync mode</b>	<i>(HP StorageWorks Disk Array XP VSS provider specific term)</i> One of two XP VSS hardware provider operation modes. When the XP provider is in the resync mode, the source volume (P-VOL) and its replica (S-VOL) are in the suspended mirror relationship after a backup. The maximum number of replicas (S-VOLs per a P-VOL) rotated is three provided that MU range is 0-2 or 0, 1, 2. Restore from a backup in such a configuration is possible only by re-synchronization of an S-VOL with its P-VOL. See also <a href="#">VSS compliant mode</a> , <a href="#">source volume</a> , <a href="#">primary volume (P-VOL)</a> , <a href="#">replica</a> , <a href="#">secondary volume (S-VOL)</a> , <a href="#">MU number</a> , and <a href="#">replica set rotation</a> .
<b>RMAN (Oracle specific term)</b>	See <a href="#">Recovery Manager</a> .
<b>RSM</b>	The Data Protector Restore Session Manager controls restore and object verification sessions. This process always runs on the Cell Manager system.
<b>RSM</b>	<i>(Windows specific term)</i> Removable Storage Manager (RSM) includes a media management service that facilitates communication among applications, robotic changers, and media libraries. It enables multiple applications to share local robotic media libraries and tape or disk drives and to manage removable media.
<b>scan</b>	A function that identifies the media in a device. This synchronizes the MMDB with the media that are actually present at the selected locations (for example, slots in a library).
<b>scanning</b>	A function which identifies the media in a device. This synchronizes the MMDB with the media that are actually present at the selected locations (for example, slots in a library). It is

useful to perform a scan and check the actual media in the device if someone has manually manipulated media without using Data Protector to eject or enter, for example.

<b>Scheduler</b>	A function that controls when and how often automatic backups occur. By setting up a schedule, you automate the start of backups.
<b>secondary volume (S-VOL)</b>	<i>(HP StorageWorks Disk Array XP specific term)</i> secondary volumes, or S-VOLs, are XP LDEVs that act as a secondary CA or BC mirror of another LDEV (a P-VOL). In the case of CA, S-VOLs can be used as failover devices in a MetroCluster configuration. The S-VOLs are assigned separate SCSI addresses, different from the addresses used by the P-VOLs. See also <a href="#">primary volume (P-VOL)</a> and <a href="#">Main Control Unit (MCU)</a>
<b>session</b>	See <a href="#">backup session</a> , <a href="#">media management session</a> , and <a href="#">restore session</a> .
<b>session ID</b>	An identifier of a backup, restore, object copy, object consolidation, object verification, or media management session, consisting of the date when the session ran and a unique number.
<b>session key</b>	This environment variable for the pre-exec and post-exec script is a Data Protector unique identification of any session, including preview sessions. The session key is not recorded in the database, and it is used for specifying options for the <code>omnimnt</code> , <code>omnistat</code> , and <code>omniabort</code> commands.
<b>shadow copy</b>	<i>(Microsoft VSS specific term)</i> A volume that represents a duplicate of the original volume at a certain point in time. The data is then backed up from the shadow copy and not from the original volume. The original volume continues to change as the backup process continues, but the shadow copy of the volume remains constant. See also <a href="#">Microsoft Volume Shadow Copy Service</a> and <a href="#">replica</a> .
<b>shadow copy provider</b>	<i>(Microsoft VSS specific term)</i> An entity that performs the work on creating and representing the volume shadow copies. Providers own the shadow copy data and expose the shadow copies. Providers can be software (for example, system providers) or hardware (local disks, disk arrays). See also <a href="#">shadow copy</a> .

<b>shadow copy set</b>	<i>(Microsoft VSS specific term)</i> A collection of shadow copies created at the same point in time. See also <a href="#">shadow copy</a> and <a href="#">replica set</a> .
<b>shared disks</b>	A Windows disk on another system that has been made available to other users on the network. Systems with shared disks can be backed up without a Data Protector Disk Agent installed.
<b>SIBF</b>	The Serverless Integrations Binary Files (SIBF) is a part of the IDB that stores raw NDMP meta data. This data is necessary to perform restore of NDMP objects.
<b>Site Replication Service</b>	<i>(Microsoft Exchange Server specific term)</i> The Microsoft Exchange Server 2000/2003 service that permits compatibility with Microsoft Exchange Server 5.5 by emulating the Exchange Server 5.5 directory service. See also <a href="#">Information Store</a> and <a href="#">Key Management Service</a> .
<b>slot</b>	A mechanical position in a library. Each slot can hold a medium, such as a DLT tape. Data Protector references each slot with a number. To read a medium, a robotic mechanism moves the medium from a slot into the drive.
<b>SMB</b>	See <a href="#">split mirror backup</a> .
<b>smart copy</b>	<i>(VLS specific term)</i> A copy of the backed up data created from the virtual tape to the physical tape library. The smart copy process allows Data Protector to distinguish between the source and the target medium thus enabling media management. See also <a href="#">Virtual Library System (VLS)</a> .
<b>smart copy pool</b>	<i>(VLS specific term)</i> A pool that defines which destination library slots are available as smart copy targets for a specified source virtual library. See also <a href="#">Virtual Library System (VLS)</a> and <a href="#">smart copy</a> .
<b>SMBF</b>	The Session Messages Binary Files (SMBF) part of the IDB stores session messages generated during backup, restore, object copy, object consolidation, object verification, and media management sessions. One binary file is created per session. The files are grouped by year and month.
<b>snapshot</b>	<i>(HP StorageWorks VA and HP StorageWorks EVA specific term)</i> A form of replica produced using snapshot creation techniques.

A range of snapshot types is available, with different characteristics, depending on the arrays/techniques used. Such replicas are dynamic and may be either virtual copies, still reliant upon the contents of the source volumes, or independent exact duplicates (clones), depending on the snapshot type and the time since creation.

See also [replica](#) and [snapshot creation](#).

**snapshot backup**  
*(HP StorageWorks VA and HP StorageWorks EVA specific term)*

See [ZDB to tape](#), [ZDB to disk](#), and [ZDB to disk+tape](#).

**snapshot creation**

*(HP StorageWorks VA and HP StorageWorks EVA specific term)*

A replica creation technique, in which copies of source volumes are created using storage virtualization techniques. The replicas are considered to be created at one particular point in time, without pre-configuration, and are immediately available for use. However background copying processes normally continue after creation.

See also [snapshot](#).

**source (R1) device**

*(EMC Symmetrix specific term)* An EMC Symmetrix device that participates in SRDF operations with a target (R2) device. All writes to this device are mirrored to a target (R2) device in a remote EMC Symmetrix unit. An R1 device must be assigned to an RDF1 group type.

See also [target \(R2\) device](#).

**source volume**

*(ZDB specific term)* A storage volume containing data to be replicated.

**sparse file**

A file that contains data with portions of empty blocks. Examples are: a matrix in which some or much of the data contains zeros, files from image applications, and high-speed databases. If sparse file processing is not enabled during restore, it might be impossible to restore this file.

**split mirror**

*(EMC Symmetrix and HP StorageWorks Disk Array XP specific term)* A replica created using split mirror techniques. Such a replica provides an independent, exact duplicate, or clone of the contents of the source volumes.

See also [replica](#) and [split mirror creation](#).

<b>split mirror backup</b> <i>(EMC Symmetrix specific term)</i>	See <a href="#">ZDB to tape</a> .
<b>split mirror backup</b> <i>(HP StorageWorks Disk Array XP specific term)</i>	See <a href="#">ZDB to tape</a> , <a href="#">ZDB to disk</a> , and <a href="#">ZDB to disk+tape</a> .
<b>split mirror creation</b>	<i>(EMC Symmetrix and HP StorageWorks Disk Array XP specific term)</i> A replica creation technique, in which a pre-configured set of target volumes (a mirror) is kept synchronized with a set of source volumes until the time at which a replica of the contents of the source volumes is required. Then, the synchronization is stopped (the mirror is split) and a split mirror replica of the source volumes at the time of the split remains in the target volumes. See also <a href="#">split mirror</a> .
<b>split mirror restore</b>	<i>(EMC Symmetrix and HP StorageWorks Disk Array XP specific term)</i> A process in which data backed up in a ZDB-to-tape or a ZDB-to-disk+tape session is restored from tape media to a split mirror replica, which is then synchronized to the source volumes. Individual backup objects or complete sessions can be restored using this method. See also <a href="#">ZDB to tape</a> , <a href="#">ZDB to disk+tape</a> , and <a href="#">replica</a> .
<b>sqlhosts file</b>	<i>(Informix Server specific term)</i> An Informix Server connectivity information file (on UNIX) or registry (on Windows) that contains the names of each of the database servers and any aliases to which the clients on a host computer can connect.
<b>SRD file</b>	<i>(disaster recovery specific term)</i> A text file in the Unicode (UTF-16) format, generated during CONFIGURATION backup of a Windows system and stored on the Cell Manager. It contains system information required for installing and configuring the operating system on the target system in the case of a disaster. See also <a href="#">target system</a> .
<b>SRDF</b>	<i>(EMC Symmetrix specific term)</i> The EMC Symmetrix Remote Data Facility is a business continuation process that enables effective, real-time data replication of SLDs between dislocated processing environments. These environments could be situated

within the same root computer environment or separated by long distances.

<b>SSE Agent</b>	<i>(HP StorageWorks Disk Array XP specific term)</i> A Data Protector software module that executes all tasks required for a split mirror backup integration. It communicates with the HP StorageWorks Disk Array XP storing system using the RAID Manager XP utility (HP-UX and Windows systems) or RAID Manager Library (Solaris systems).
<b>sst.conf file</b>	The file <code>/usr/kernel/drv/sst.conf</code> is required on each Data Protector Sun Solaris client to which a multi-drive library device is connected. It must contain an entry for the SCSI address of the robotic mechanism of each library device connected to the client.
<b>st.conf file</b>	The file <code>/kernel/drv/st.conf</code> is required on each Data Protector Solaris client with a backup device connected. It must contain device information and a SCSI address for each backup drive connected to that client. A single SCSI entry is required for a single-drive device and multiple SCSI entries are required for a multi-drive library device.
<b>stackers</b>	Devices with multiple slots for media storage usually with only one drive. A stacker selects media from the stack sequentially. In contrast, a library can randomly select media from its repository.
<b>standalone file device</b>	A file device is a file in a specified directory to which you back up data.
<b>Storage Group</b>	<i>(Microsoft Exchange Server specific term)</i> A collection of mailbox stores and public folder stores that share a set of transaction log files. Exchange Server manages each storage group with a separate server process.
<b>StorageTek ACS library</b>	<i>(StorageTek specific term)</i> Automated Cartridge System is a library system (also known as Silo) consisting of one Library Management Unit (LMU) and one to 24 Library Storage Modules (LSM) connected to the unit.
<b>storage volume</b>	<i>(ZDB specific term)</i> A storage volume represents an object that may be presented to an operating system or some other entity (for example, a virtualization mechanism) upon which volume

management systems, file systems, or other objects may exist. The volume management systems, file systems are built on this storage. Typically, these can be created or exist within a storage system such as a disk array.

<b>switchover</b>	See <a href="#">failover</a> .
<b>Sybase Backup Server API</b>	<i>(Sybase specific term)</i> An industry-standard interface developed for the exchange of backup and recovery information between a Sybase SQL Server and a backup solution like Data Protector.
<b>Sybase SQL Server</b>	<i>(Sybase specific term)</i> The server in the Sybase “client-server” architecture. Sybase SQL Server manages multiple databases and multiple users, keeps track of the actual location of data on disks, maintains mapping of logical data description to physical data storage, and maintains data and procedure caches in memory.
<b>Symmetrix Agent (SYMA)</b>	<i>(EMC Symmetrix specific term)</i> The Data Protector software module that prepares the EMC Symmetrix environment for backup and restore operations.
<b>synthetic backup</b>	A backup solution that produces a synthetic full backup, an equivalent to a conventional full backup in terms of data, without putting stress on the production servers or the network. A synthetic full backup is created from a previous full backup and any number of incremental backups.
<b>synthetic full backup</b>	The result of an object consolidation operation, where a restore chain of a backup objects is merged into a new, synthetic full version of this object. A synthetic full backup is equivalent to a conventional full backup in terms of restore speed.
<b>System Backup to Tape</b>	<i>(Oracle specific term)</i> An Oracle interface that handles the actions required to load, label, and unload correct backup devices when Oracle issues a backup or restore request.
<b>system databases</b>	<i>(Sybase specific term)</i> The four system databases on a newly installed Sybase SQL Server are the: <ul style="list-style-type: none"><li>• master database (master)</li><li>• temporary database (tempdb)</li><li>• system procedure database (sybssystemprocs)</li><li>• model database (model).</li></ul>

<b>System Recovery Data file</b>	See <a href="#">SRD file</a> .
<b>System State</b>	<i>(Windows specific term)</i> The System State data comprises the Registry, COM+ Class Registration database, system startup files, and the Certificate Services database (if the server is a certificate server). If the server is a domain controller, Active Directory services and the SYSVOL directory are also contained in the System State data. If the server is running the Cluster service, the System State data also includes resource registry checkpoints and the quorum resource recovery log, which contains the most recent cluster database information.
<b>system volume/disk/partition</b>	A volume/disk/partition containing operating system files. Microsoft terminology defines the system volume/disk/partition as the volume/disk/partition containing files required for the initial step of the boot process.
<b>SysVol</b>	<i>(Windows specific term)</i> A shared directory that stores the server copy of the domain's public files, which are replicated among all domain controllers in the domain.
<b>tablespace</b>	A part of a database structure. Each database is logically divided into one or more tablespaces. Each tablespace has data files or raw volumes exclusively associated with it.
<b>tapeless backup (ZDB specific term)</b>	See <a href="#">ZDB to disk</a> .
<b>target database</b>	<i>(Oracle specific term)</i> In RMAN, the target database is the database that you are backing up or restoring.
<b>target (R2) device</b>	<i>(EMC Symmetrix specific term)</i> An EMC Symmetrix device that participates in SRDF operations with a source (R1) device. It resides in the remote EMC Symmetrix unit. It is paired with a source (R1) device in the local EMC Symmetrix unit and receives all write data from its mirrored pair. This device is not accessed by user applications during normal I/O operations. An R2 device must be assigned to an RDF2 group type. See also <a href="#">source (R1) device</a> .
<b>target system</b>	<i>(disaster recovery specific term)</i> A system after a computer disaster has occurred. The target system is typically in a non-bootable state and the goal of disaster recovery is to restore

this system to the original system configuration. The difference between a faulty system and a target system is that a target system has all faulty hardware replaced.

<b>target volume</b>	<i>(ZDB specific term)</i> A storage volume to which data is replicated.
<b>Terminal Services</b>	<i>(Windows specific term)</i> Windows Terminal Services provide a multi-session environment that allows clients to access a virtual Windows desktop session and Windows-based programs running on the server.
<b>thread</b>	<i>(Microsoft SQL Server specific term)</i> An executable entity that belongs to only one process. It comprises a program counter, a user-mode stack, a kernel-mode stack, and a set of register values. Several threads can run at a time within one process.
<b>TimeFinder</b>	<i>(EMC Symmetrix specific term)</i> A business continuation process that creates an instant copy of single or multiple Symmetrix Logical Devices (SLDs). The instant copy is created on specially preconfigured SLDs called BCVs and is accessible via a separate device address to the system(s).
<b>TLU</b>	Tape Library Unit.
<b>TNSNAMES.ORA</b>	<i>(Oracle and SAP R/3 specific term)</i> A network configuration file that contains connect descriptors mapped to service names. The file may be maintained centrally or locally, for use by all or individual clients.
<b>transaction</b>	A mechanism for ensuring that a set of actions is treated as a single unit of work. Databases use transactions to keep track of database changes.
<b>transaction backup</b>	Transaction backups generally use fewer resources than database backups, so they can be created more frequently than database backups. By applying transaction backups, you can recover the database to a specific point in time prior to when a problem occurred.
<b>transaction backup</b>	<i>(Sybase and SQL specific term)</i> A backup of the transaction log providing a record of changes made since the last full or transaction backup.
<b>transaction log backup</b>	Transaction log backups generally use fewer resources than database backups so they can be created more frequently than

database backups. By applying transaction log backups, you can recover the database to a specific point in time.

<b>transaction log files</b>	Files that record transactions of the database modifications, and provide fault tolerance in case of a database disaster.
<b>transaction logs</b>	<i>(Data Protector specific term)</i> Keep track of IDB changes. The archiving of transaction logs should be enabled to prevent you from losing the transaction log files that are created after the last IDB backup and are necessary for IDB recovery.
<b>transaction log table</b>	<i>(Sybase specific term)</i> A system table in which all changes to the database are automatically recorded.
<b>transportable snapshot</b>	<i>(Microsoft VSS specific term)</i> A shadow copy that is created on the application system and can be presented to the backup system where a backup can be performed. See also <a href="#">Microsoft Volume Shadow Copy Service (VSS)</a> .
<b>TSANDS.CFG file</b>	<i>(Novell NetWare specific term)</i> A file that allows you to specify the names of containers where you want backups to begin. It is a text file located in the <code>SYS:SYSTEM\TSA</code> directory on the server where <code>TSANDS.NLM</code> is loaded.
<b>UIProxy</b>	The Java GUI Server ( <code>UIProxy</code> service) runs on the Data Protector Cell Manager. It is responsible for communication between the Java GUI Client and the Cell Manager, moreover, it performs business logic operations and sends only important information to the client. The service is started as soon as Data Protector is installed on the Cell Manager.
<b>unattended operation</b>	See <a href="#">lights-out operation</a> .
<b>user account (Data Protector user account)</b>	You can use Data Protector only if you have a Data Protector user account, which restricts unauthorized access to Data Protector and to backed up data. Data Protector administrators create this account specifying a user logon name, the systems from which the user can log on, and a Data Protector user group membership. This is checked whenever the user starts the Data Protector user interface or performs specific tasks.
<b>User Account Control (UAC)</b>	A security component in Windows Vista and Windows Server 2008 that limits application software to standard user

privileges until an administrator authorizes an increase in privilege level.

<b>user disk quotas</b>	NTFS quota-management support enables an enhanced tracking mechanism and control over disk space usage on shared storage volumes. Data Protector backs up user disk quotas on the whole system and for all configured users at a time.
<b>user group</b>	Each Data Protector user is member of a User Group. Each User Group has a set of user rights that are given to every user in that User Group. The number of User Groups with their associated user rights can be defined as desired. Data Protector provides three default user groups: admin, operator, and user.
<b>user profile</b>	<i>(Windows specific term)</i> Configuration information retained on a user basis. This information includes desktop settings, screen colors, network connections, and so on. When the user logs on, the user profile is loaded and the Windows environment is set accordingly.
<b>user rights</b>	User rights or access rights are the permissions needed to perform specific Data Protector tasks. Configuring a backup, starting a backup session, or starting a restore session are typical user rights. Users have the access rights of the user group to which they belong.
<b>vaulting media</b>	The process of storing media to a safe and remote place. The media are brought back to the data center when they are needed for restore or are ready for reuse in subsequent backups. The vaulting procedure depends on your company's backup strategy and policies for data protection/reliability.
<b>verify</b>	A function that lets you check whether the Data Protector data on a specified medium is readable. Additionally, consistency within each block can be checked if the backup was performed with the cyclic redundancy check (CRC) option ON.
<b>Virtual Controller Software (VCS)</b>	<i>(HP StorageWorks EVA specific term)</i> The firmware that manages all aspects of storage system operation, including communication with Command View EVA through the HSV controllers. See also <a href="#">Command View (CV) EVA</a> .

<b>Virtual Device Interface</b>	<i>(Microsoft SQL Server specific term)</i> This is a SQL Server programming interface that allows fast backup and restore of large databases.
<b>virtual disk</b>	<i>(HP StorageWorks EVA specific term)</i> A unit of storage allocated from an HP StorageWorks Enterprise Virtual Array storage pool. Virtual disks are the entities that are replicated using the HP StorageWorks Enterprise Virtual Array snapshot functionality. See also <a href="#">source volume</a> and <a href="#">target volume</a> .
<b>virtual full backup</b>	An efficient type of synthetic backup where data is consolidated using pointers instead of being copied. It is performed if all the backups (the full backup, incremental backups, and the resulting virtual full backup) are written to a single file library that uses distributed file medium format.
<b>Virtual Library System (VLS)</b>	A disk-based data storage device hosting one or more virtual tape libraries (VTLs).
<b>virtual server</b>	A virtual machine in a cluster environment defined in a domain by a network IP name and address. Its address is cached by the cluster software and mapped to the cluster node that is currently running the virtual server resources. This way all requests for a particular virtual server are cached by a specific cluster node.
<b>virtual tape</b>	<i>(VLS specific term)</i> An archival storage technology that backs up data to disk drives in the same way as if it were being stored on tape. Benefits of virtual tape systems include improved backup and recovery speed and lower operating costs. See also <a href="#">Virtual Library System (VLS)</a> and <a href="#">Virtual Tape Library</a> .
<b>Virtual Tape Library (VTL)</b>	<i>(VLS specific term)</i> An emulated tape library that provides the functionality of traditional tape-based storage. See also <a href="#">Virtual Library System (VLS)</a> .
<b>VMware management client</b>	<i>(VMware integration specific term)</i> The client that Data Protector uses to communicate with VMware Virtual Infrastructure. This can be a VirtualCenter Server system (VirtualCenter environment) or an ESX Server system (standalone ESX Server environment).
<b>volser</b>	<i>(ADIC and STK specific term)</i> A VOLume SERial number is a label on the medium to identify the physical tape used in very

large libraries. A volser is a naming convention specific to ADIC/GRAU and StorageTek devices.

<b>volume group</b>	A unit of data storage in an LVM system. A volume group can consist of one or more physical volumes. There can be more than one volume group on the system.
<b>volume mount point</b>	<i>(Windows specific term)</i> An empty directory on a volume that can be used to mount another volume. The volume mount point acts as a gateway to the target volume. Provided that the volume is mounted, users and applications can refer to the data on the mounted volume by the full (merged) filesystem path as if both volumes are one integral part.
<b>Volume Shadow Copy Service</b>	See <a href="#">Microsoft Volume Shadow Copy Service</a> .
<b>VSS</b>	See <a href="#">Microsoft Volume Shadow Copy Service</a> .
<b>VSS compliant mode</b>	<i>(HP StorageWorks Disk Array XP VSS provider specific term)</i> One of two XP VSS hardware provider operation modes. When the XP provider is in the VSS compliant mode, the source volume (P-VOL) and its replica (S-VOL) are in simplex, unpaired state after a backup. Therefore the number of replicas (S-VOLs per a P-VOL) rotated is not limited. Restore from a backup in such a configuration is possible only by switching of the disks. See also <a href="#">resync mode</a> , <a href="#">source volume</a> , <a href="#">primary volume (P-VOL)</a> , <a href="#">replica</a> , <a href="#">secondary volume (S-VOL)</a> , and <a href="#">replica set rotation</a> .
<b>VxFS</b>	Veritas Journal Filesystem.
<b>VxVM (Veritas Volume Manager)</b>	A Veritas Volume Manager is a system for managing disk space on Solaris platforms. A VxVM system consists of an arbitrary group of one or more physical volumes organized into logical disk groups.
<b>Wake ONLAN</b>	Remote power-up support for systems running in power-save mode from some other system on the same LAN.
<b>Web reporting</b>	The Data Protector functionality that allows you to view reports on backup, object copy, and object consolidation status and Data Protector configuration using the Web interface.
<b>wildcard character</b>	A keyboard character that can be used to represent one or many characters. The asterisk (*), for example, typically represents

one or more characters, and the question mark (?) typically represents a single character. Wildcard characters are often used in operating systems as a means of specifying more than one file by name.

<b>Windows CONFIGURATION backup</b>	Data Protector allows you to back up Windows CONFIGURATION, including Windows Registry, user profiles, Event Logs, and WINS and DHCP server data (if configured on a system) in one step.
<b>Windows Registry</b>	A centralized database used by Windows to store configuration information for the operating system and the installed applications.
<b>WINS server</b>	A system running Windows Internet Name Service software that resolves Windows networking computer names to IP addresses. Data Protector can back up WINS server data as part of the Windows configuration.
<b>writer</b>	<i>(Microsoft VSS specific term)</i> A process that initiates change of data on the original volume. Writers are typically applications or system services that write persistent information on a volume. Writers also participate in the shadow copy synchronization process by assuring data consistency.
<b>XBSA interface</b>	<i>(Informix Server specific term)</i> ON-Bar and Data Protector communicate with each other through the X/Open Backup Services Application Programmer's Interface (XBSA).
<b>XCopy engine</b>	<i>(direct backup specific term)</i> A SCSI-3 copy command that allows you to copy data from a storage device having a SCSI source address to a backup device having a SCSI destination address, thus enabling direct backup. The data flows from a source device (either block or streaming, that is, disk or tape) to the destination device (either block or streaming) through XCopy. This releases the controlling server of reading the data from the storage device into memory and then writing the information to the destination device. See also <a href="#">direct backup</a> .
<b>ZDB</b>	See <a href="#">zero downtime backup (ZDB)</a> .
<b>ZDB database</b>	<i>(ZDB specific term)</i> A part of the IDB, storing ZDB related information such as source volumes, replicas and security

information. The ZDB database is used for ZDB, instant recovery, and split mirror restore.

See also [zero downtime backup \(ZDB\)](#).

**ZDB to disk**

*(ZDB specific term)* A form of zero downtime backup where the replica produced is kept on the disk array as a backup of the source volumes at a specific point in time. Multiple replicas, produced using the same backup specification at different times, can be kept in a replica set. A replica from ZDB to disk can be restored using the instant recovery process.

See also [zero downtime backup \(ZDB\)](#), [ZDB to tape](#), [ZDB to disk+tape](#), [instant recovery](#), and [replica set rotation](#).

**ZDB to disk+tape**

*(ZDB specific term)* A form of zero downtime backup where the replica produced is kept on the disk array as a backup of the source volumes at a specific point in time, in the same way as with ZDB to disk. However, data in the replica is also streamed to a backup medium, as with ZDB to tape. If this backup method is used, data backed up in the same session can be restored using the instant recovery process, the standard Data Protector restore from tape, or on split mirror arrays, split mirror restore.

See also [zero downtime backup \(ZDB\)](#), [ZDB to disk](#), [ZDB to tape](#), [instant recovery](#), [replica](#), and [replica set rotation](#).

**ZDB to tape**

*(ZDB specific term)* A form of zero downtime backup where data in the replica produced is streamed to a backup medium, typically tape. Instant recovery is not possible from such a backup, so the replica need not be retained on the disk array after backup completion. The backed-up data can be restored using standard Data Protector restore from tape. On split mirror arrays, split mirror restore can also be used.

See also [zero downtime backup \(ZDB\)](#), [ZDB to disk](#), [instant recovery](#), [ZDB to disk+tape](#), and [replica](#).

**zero downtime backup (ZDB)**

A backup approach in which data replication techniques, provided by a disk array, are used to minimize the impact of backup operations on an application system. A replica of the data to be backed up is created first. All subsequent backup operations are performed on the replicated data rather than the original data, while the application system can be returned to normal operation.

See also [ZDB to disk](#), [ZDB to tape](#), [ZDB to disk+tape](#), and [instant recovery](#).



---

# Index

## A

- architecture
  - NDMP integration, 164
  - Sybase integration, 114
  - VMware integration, 31
- audience, 17

## B

- backing up NDMP
  - backup types, 163
  - starting backups, 185
- backing up NNM
  - backup types, 149, 151
- backing up Sybase
  - backup types, 113
  - previewing backups, 128
- backing up VMware
  - previewing backups, 73
  - starting backups, 74
- backing up NDMP, 179 - 185
  - backup specification, creating, 180
  - backup specification, modifying, 185
- backing up NNM, 151 - 155
  - backup modes, 151
  - backup specifications, creating, 152
  - backup specifications, modifying, 153
  - backup templates, 152
  - full backups, 151
  - incremental backups, 151
  - scheduling backups, 153
  - starting backups, 154
- backing up Sybase, 122 - 131
  - backup options, 127
  - backup specifications, creating, 122
  - backup specifications, modifying, 127
  - database objects backup, 122
  - full backups, 113, 122
  - scheduling backups, 127
  - scheduling backups, example, 127
  - starting backups, 130
  - transaction logs backups, 113, 122
- backing up VMware, 48 - 77
  - backup methods, 49
  - backup options, 72
  - backup specifications, creating, 68
  - backup types, 66
  - backup specification, modifying, 72
  - differential backups, 66
  - full backups, 66
  - incremental backups, 66
  - scheduling backups, 72
  - scheduling backups, example, 72
- backup
  - XenServer integration, 204
- backup options
  - VMware integration, 72
- backup specifications, scheduling
  - VMware integration, 72
- backup methods
  - VMware integration, 49
- backup modes
  - NNM integration, 151
- backup options
  - Sybase integration, 127

- backup specification
  - XenServer integration, 207
- backup specifications, creating
  - NNM integration, 152
- backup specifications, modifying
  - NNM integration, 153
- backup specifications, creating
  - NDMP integration, 180
  - Sybase integration, 122
  - VMware integration, 68
- backup specifications, modifying
  - NDMP integration, 185
  - Sybase integration, 127
  - VMware integration, 72
- backup specifications, scheduling
  - NNM integration, 153
  - Sybase integration, 127
- backup templates
  - NNM integration, 152
- backup types
  - NDMP integration, 163
  - NNM integration, 149, 151
  - Sybase integration, 113
  - VMware integration, 66
- block size
  - NDMP integration, 178

## C

- Celerra NAS devices
  - NDMP integration, 165, 177
  - NDMP integration, 178, 188
- checking configuration
  - Sybase integration, 121
  - VMware integration, 47
- concepts
  - NDMP integration, 163
  - NNM integration, 150
  - Sybase integration, 113
  - VMware integration, 30
  - XenServer integration, 195
- configuring Sybase, 115

- configuring NDMP, 166 - 179
  - configuring NDMP devices, 169
  - creating media pools, 168
  - importing NDMP Servers, 166
- configuring NNM, 150 - 151
- configuring Sybase
  - checking configuration, 121
- configuring VMware, 37 - 48
  - checking configuration, 47
- conventions
  - document, 25
- creating backup specifications
  - NDMP integration, 180
  - NNM integration, 152
  - Sybase integration, 122
  - VMware integration, 68

## D

- differential backups
  - VMware integration, 66
- document
  - conventions, 25
  - related documentation, 17
- documentation
  - HP website, 17
  - providing feedback, 28

## E

- environment variables
  - NDMP integration, 189
- examples, Sybase integration
  - restore, 142
  - scheduling backups, 127
- examples, VMware integration
  - scheduling backups, 72
  - starting interactive backups, 75

## F

- file history swap files
  - NDMP integration, 165

- full backups
  - NNM integration, 151
  - Sybase integration, 113, 122
  - VMware integration, 66

## H

- help
  - obtaining, 27
- HP
  - technical support, 27

## I

- incremental backups
  - NNM integration, 151
  - VMware integration, 66
- installing XenServer integration, 201
- interactive backups
  - NDMP integration, 185
  - NNM integration, 154
  - Sybase integration, 130
  - VMware integration, 74
- introduction
  - NDMP integration, 163
  - NNM integration, 149
  - Sybase integration, 113
  - VMware integration, 29

## M

- main integration components
  - XenServer integration, 200
- media management
  - NDMP integration, 192
- modifying backup specifications
  - NDMP integration, 185
  - NNM integration, 153
  - Sybase integration, 127
  - VMware integration, 72

- monitoring sessions
  - NNM integration, 155
  - Sybase integration, 145
  - VMware integration, 109

## N

- NDMP configuration
  - configuring NDMP devices, 169
  - creating media pools, 168
  - importing NDMP Servers, 166
- NDMP integration
  - concepts, 163
  - introduction, 163
  - media management, 192
- NDMP backup, 179 - 185
  - backup specification, creating, 180
  - backup specification, modifying, 185
  - backup types, 163
  - starting backups, 185
- NDMP configuration, 166 - 179
- NDMP integration
  - architecture, 164
  - backup, 179 - 185
  - configuration, 166 - 179
  - environment variables, 189
  - file history swap files, 165
  - omnirc file variables, 190
  - restore, 185 - 189
  - troubleshooting, 193 - 194
- NDMP restore, 185 - 189
  - direct access restore, 187
  - using another device, 189
  - using GUI, 186
- NDMP troubleshooting, 193 - 194
- NetApp NAS devices
  - NDMP integration, 165, 176, 188
  - NDMP integration, 178
- NNM backup
  - backup modes, 151

- NNM integration
  - concepts, 150
  - introduction, 149
  - monitoring sessions, 155
- NNM backup, 151 - 155
  - backup specifications, creating, 152
  - backup specifications, modifying, 153
  - backup templates, 152
  - backup types, 149, 151
  - full backups, 151
  - incremental backups, 151
  - scheduling backups, 153
  - starting backups, 154
- NNM configuration, 150 - 151
- NNM integration
  - backup, 151 - 155
  - configuration, 150 - 151
  - restore, 155
  - troubleshooting, 156 - 161
- NNM restore, 155
- NNM troubleshooting, 156 - 161

## O

- offline backup
  - XenServer integration, 196
- omnirc file variables
  - NDMP integration, 190
- online backup
  - XenServer integration, 195
- online backups
  - NNM integration, 152
  - VMware integration, 29

## P

- previewing backups
  - Sybase integration, 128
  - VMware integration, 73

## R

- related documentation, 17

- restore
  - XenServer integration, 209
- restore options
  - VMware integration, 89
- restore from offline backup
  - XenServer integration, 197
- restore from online backup
  - XenServer integration, 197
- restore processes
  - XenServer integration, 198
- restoring NDMP
  - direct access restore, 187
  - using another device, 189
  - using GUI, 186
- restoring Sybase
  - using another device, 145
- restoring VMware
  - using another device, 108
- restoring NDMP, 185 - 189
- restoring NNM, 155
- restoring Sybase, 131 - 145
  - examples, 142
  - finding information for restore, 132
  - using the Sybase isql command, 139
- restoring VMware, 77 - 109
  - finding information, 79
  - restore options, 89
  - using CLI, 89
  - using GUI, 81
- running backups
  - See starting backups
- running backups
  - See starting backups
- running backups
  - See starting backups

## S

- scheduling backups
  - NNM integration, 153
  - Sybase integration, 127
  - VMware integration, 72

- starting backups
  - NDMP integration, 185
  - VMware integration, 74
- starting backups
  - NNM integration, 154
  - Sybase integration, 130
- Subscriber's Choice, HP, 28
- Sybase backup
  - database objects backup, 122
- Sybase integration
  - concepts, 113
  - introduction, 113
  - monitoring sessions, 145
- Sybase backup, 122 - 131
  - backup specifications, modifying, 127
  - backup options, 127
  - backup specifications, creating, 122
  - backup types, 113
  - full backups, 113, 122
  - previewing backups, 128
  - scheduling backups, 127
  - scheduling backups, example, 127
  - starting backups, 130
  - transaction logs backups, 113, 122
- Sybase configuration, 115
  - checking configuration, 121
- Sybase integration
  - architecture, 114
  - backup, 122 - 131
  - configuration, 115
  - restore, 131 - 145
  - troubleshooting, 145 - 147
- Sybase restore, 131 - 145
  - examples, 142
  - finding information for restore, 132
  - using another device, 145
  - using the Sybase isql command, 139
- Sybase troubleshooting, 145 - 147

## T

- technical support
  - HP, 27

- technical support
  - service locator website, 28
- transaction logs backups
  - Sybase integration, 113, 122
- troubleshooting NDMP, 193 - 194
- troubleshooting NNM, 156
- troubleshooting Sybase, 145 - 147
- troubleshooting VMware, 109 - 112

## V

- VMware backup
  - backup methods, 49
  - backup types, 66
  - differential backups, 66
  - scheduling backups, 72
- VMware configuration, 37 - 48
- VMware integration
  - concepts, 30
  - introduction, 29
  - monitoring sessions, 109
- VMware management client
  - VMware integration, 39
- VMware restore
  - finding information, 79
  - using CLI, 89
  - using GUI, 81
- VMware troubleshooting, 109 - 112
- VMware backup, 48 - 77
  - backup specification, modifying, 72
  - backup options, 72
  - backup specifications, creating, 68
  - full backups, 66
  - incremental backups, 66
  - previewing backups, 73
  - scheduling backups, example, 72
  - starting backups, 74
- VMware configuration
  - checking configuration, 47

- VMware integration
  - architecture, [31](#)
  - backup, [48 - 77](#)
  - configuration, [37 - 48](#)
  - restore, [77 - 109](#)
  - troubleshooting, [109 - 112](#)
- VMware restore, [77 - 109](#)
  - restore options, [89](#)
  - using another device, [108](#)

## W

- websites
  - HP Subscriber's Choice for Business, [28](#)
  - HP , [28](#)
  - product manuals, [17](#)

## X

- XenServer integration
  - concepts, [195](#)
  - offline backup, [196](#)
  - online backup, [195](#)
  - restore processes, [198](#)
- XenServer integration
  - backup, [204](#)
  - backup specification, [207](#)
  - installation, [201](#)
  - integration scripts, [204](#)
  - main integration components, [200](#)
  - restore, [209](#)
  - restore from offline backup, [197](#)
  - restore from online backup, [197](#)
  - specifying restore, [212](#)
  - updating DPxen\_config.py for backup, [205](#)
  - updating DPxen\_config.py for restore, [209](#)