

HP OpenView Select Identity

Connector for Windows NT Local Systems

Installation and Configuration Guide

Connector Version: 3.4
Select Identity Version: 3.3.1



August 2005

© 2005 Hewlett-Packard Development Company, L.P.

Legal Notices

Warranty

Hewlett-Packard makes no warranty of any kind with regard to this document, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Hewlett-Packard shall not be held liable for errors contained herein or direct, indirect, special, incidental or consequential damages in connection with the furnishing, performance, or use of this material.

A copy of the specific warranty terms applicable to your Hewlett-Packard product can be obtained from your local Sales and Service Office.

Restricted Rights Legend

Use, duplication, or disclosure by the U.S. Government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause in DFARS 252.227-7013.

Hewlett-Packard Company
United States of America

Rights for non-DOD U.S. Government Departments and Agencies are as set forth in FAR 52.227-19(c)(1,2).

Copyright Notices

© 2005 Hewlett-Packard Development Company, L.P.

No part of this document may be copied, reproduced, or translated into another language without the prior written consent of Hewlett-Packard Company. The information contained in this material is subject to change without notice.

This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>). Portions Copyright (c) 1999-2003 The Apache Software Foundation. All rights reserved.

Select Identity uses software from the Apache Jakarta Project including:

- Commons-beanutils.
- Commons-collections.
- Commons-logging.
- Commons-digester.
- Commons-httpclient.

- Element Construction Set (ecs).
- Jakarta-poi.
- Jakarta-regexp.
- Logging Services (log4j).

Additional third party software used by Select Identity includes:

- JasperReports developed by SourceForge.
- iText (for JasperReports) developed by SourceForge.
- BeanShell.
- Xalan from the Apache XML Project.
- Xerces from the Apache XML Project.
- Java API for XML Processing from the Apache XML Project.
- SOAP developed by the Apache Software Foundation.
- JavaMail from SUN Reference Implementation.
- Java Secure Socket Extension (JSSE) from SUN Reference Implementation.
- Java Cryptography Extension (JCE) from SUN Reference Implementation.
- JavaBeans Activation Framework (JAF) from SUN Reference Implementation.
- OpenSPML Toolkit from OpenSPML.org.
- JGraph developed by JGraph.
- Hibernate from Hibernate.org.
- BouncyCastle engine for keystore management, bouncycastle.org.

This product includes software developed by Teodor Danciu <http://jasperreports.sourceforge.net>). Portions Copyright (C) 2001-2004 Teodor Danciu (teodord@users.sourceforge.net). All rights reserved.

Portions Copyright 1994-2004 Sun Microsystems, Inc. All Rights Reserved.

This product includes software developed by the Waveset Technologies, Inc. (www.waveset.com). Portions Copyright © 2003 Waveset Technologies, Inc. 6034 West Courtyard Drive, Suite 210, Austin, Texas 78730. All rights reserved.

Portions Copyright (c) 2001-2004, Gaudenz Alder. All rights reserved.

Trademark Notices

HP OpenView Select Identity is a trademark of Hewlett-Packard Development Company, L.P. Microsoft, Windows, the Windows logo, and SQL Server are trademarks or registered trademarks of Microsoft Corporation.

Sun™ workstation, Solaris Operating Environment™ software, SPARCstation™ 20 system, Java technology, and Sun RPC are registered trademarks or trademarks of Sun Microsystems, Inc. JavaScript is a trademark of Sun Microsystems, Inc., used under license for technology invented and implemented by Netscape.

This product includes the Sun Java Runtime. This product includes code licensed from RSA Security, Inc. Some portions licensed from IBM are available at <http://oss.software.ibm.com/icu4j/>.

IBM, DB2 Universal Database, DB2, WebSphere, and the IBM logo are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group.

This product includes software provided by the World Wide Web Consortium. This software includes xml-apis. Copyright © 1994-2000 World Wide Web Consortium, (Massachusetts Institute of Technology, Institute National de Recherche en Informatique et en Automatique, Keio University). All Rights Reserved. <http://www.w3.org/Consortium/Legal/>

Intel and Pentium are trademarks or registered trademarks of Intel Corporation in the United States, other countries, or both.

AMD and the AMD logo are trademarks of Advanced Micro Devices, Inc.

BEA and WebLogic are registered trademarks of BEA Systems, Inc.

VeriSign is a registered trademark of VeriSign, Inc. Copyright © 2001 VeriSign, Inc. All rights reserved.

All other product names are the property of their respective trademark or service mark holders and are hereby acknowledged.

Support

Please visit the HP OpenView web site at:

<http://www.managementsoftware.hp.com/>

This web site provides contact information and details about the products, services, and support that HP OpenView offers.

You can also go directly to the support web site at:

<http://support.openview.hp.com/>

HP OpenView online software support provides customer self-solve capabilities. It provides a fast and efficient way to access interactive technical support tools needed to manage your business. As a valuable support customer, you can benefit by using the support site to:

- Search for knowledge documents of interest
- Submit and track progress on support cases
- Manage a support contract
- Look up HP support contacts
- Review information about available services
- Enter discussions with other software customers
- Research and register for software training

Most of the support areas require that you register as an HP Passport user and log in. Many also require a support contract.

To find more information about access levels, go to:

http://support.openview.hp.com/access_level.jsp

To register for an HP Passport ID, go to:

<https://passport2.hp.com/hpp/newuser.do>

contents

Chapter 1	Installing the Connector	7
	Operations Supported by the Connector	8
	System Requirements.	9
	Deploying on the Web Application Server.	10
	Installing the Agent on the Windows Server	13
Chapter 2	Understanding the Mapping Files	17
	User Attributes.	18
	Group Attributes.	20
	Reverse Synchronization	20
Chapter 3	Configuring the Connector	23
Chapter 4	Uninstalling the Connector	27
	Uninstalling the Connector from WebLogic	27
	Uninstalling the Connector from WebSphere.	28
	Uninstalling the Agent.	28

Installing the Connector

The Windows NT Local connector enables HP OpenView Select Identity to provision in the local domain on Windows NT, XP, and 2000 systems. This connector is a two-way connector and can send data back to Select Identity based on changes made in the local domain.

The Windows NT Local connector is packaged in the following files in the `NTLocal` directory on the Select Identity Connector CD:

- `NTLConnector.rar` — Contains the binaries.
- `NTLschema.jar` — Contains the following attribute mapping files, which control how Select Identity fields are mapped to Windows NT Local fields:
 - `NTLUser.properties` — Maps user attributes from the Select Identity User Model to Windows user attributes.
 - `NTLGroup.properties` — Maps group attributes from the Select Identity Group Model to Windows group attributes.
 - `ntlocal.xsl` — Maps attributes on the Windows server to attributes on the Select Identity server. This file is used by the agent during reverse synchronization.
- `NTLSetup.zip` — Contains the installation executable for the NT Local agent.

Operations Supported by the Connector

The Windows NT Local connector enables Select Identity to perform the following provisioning tasks on Windows NT, XP, and 2000 systems:

- Add, update, and remove users
- Retrieve user attributes
- Enable and disable users
- Verify a user's existence
- Change user passwords
- Reset user passwords
- Expire user passwords
- Retrieve all entitlements
- Retrieve a list of supported user attributes
- Assign and unassign entitlements to and from users

The Select Identity agent can also send changes made on the Windows system to Select Identity. This is called **reverse synchronization**. The updates made to Select Identity data depend on whether the Windows system is an authoritative or non-authoritative resource:

Operation	If the Resource is Authoritative	If the Resource is Non-authoritative
User is added on the resource.	The user is added to the respective Service.	User is not added. However, if the user exists, the entitlements are modified (not the user attributes).
User attributes are modified on the resource.	Attributes are updated in Select Identity.	Attributes are not updated in Select Identity.
User entitlements are modified on the resource.	Entitlements are modified in Select Identity.	Entitlements are modified in Select Identity.

Operation	If the Resource is Authoritative	If the Resource is Non-authoritative
User is deleted on the resource.	The user's Service membership is deleted in Select Identity.	The user is not deleted. in Select Identity, though the entitlements for the resource are deleted.
Password is changed on the resource.	The user's password is reset in all Services for which the user is registered.	The user's password is reset in all Services for which the user is registered.

Additional configuration steps are required to enable reverse synchronization.

System Requirements

The Windows NT Local connector is supported in the following environment:

Select Identity Version	Application Server	Database
3.0.2	WebLogic 8.1.2 on Windows 2003	SQL Server 2000
	WebLogic 8.1.2 on Solaris 9	Oracle 9i
	WebLogic 8.1.2 on HP-UX 11i	Oracle 9i
	WebSphere 5.1.1 on Solaris 9	DB2 8.2 (or DB2 8.1 Service Pack 7)
3.3	WebLogic 8.1.4 on Windows 2003	SQL Server 2000
	WebLogic 8.1.4 on Solaris 9	Oracle 9i
	WebLogic 8.1.4 on Red Hat Enterprise Linux 3.0	SQL Server 2000
3.3.1	WebLogic 8.1.4 on Windows 2003	SQL Server 2000
	WebSphere 5.1.1 on HP-UX 11i	Oracle 9i

This connector is supported with Windows NT 4.0, Windows 2000, Windows 2003, and Windows XP.

The agent is supported in the following environment:

Operating system	<ul style="list-style-type: none"> • Microsoft Windows NT Server/Workstation, Service Pack 6 or later • Windows XP Professional, Service Pack 1 • Windows 2000 Professional, Service Pack 4 • Windows 2000 Server
Browser	Internet Explorer 5.5 or later (supporting MSXML 2.0 or later)
Winsock	Version 2.0 or later

You will also need the administrative user name and password for the machine during the installation.

Deploying on the Web Application Server

To install the Windows NT Local connector on the Select Identity server, complete these steps:

- 1 Create a subdirectory in the Select Identity home directory where the connector's RAR file will reside. For example, you could create the `C:\Select_Identity\connectors` folder on Windows. (A connector subdirectory may already exist.)
- 2 Copy the `NtlConnector.rar` file from the Select Identity Connector CD to the connector subdirectory.
- 3 If deploying the connector on WebLogic, complete the following steps. If deploying on WebSphere, skip to [Step 4 on page 11](#).
 - a Create a schema subdirectory in the Select Identity home directory where the connector's mapping file(s) will reside. For example, you could create the `C:\Select_Identity\schema` folder. (This subdirectory may already exist.)

- b** Extract the contents of the `NTLschema.jar` file (on the Select Identity Connector CD) to the `schema` subdirectory.
 - c** Ensure that the `CLASSPATH` environment variable in the WebLogic server startup script references the `schema` subdirectory.
 - d** Start the application server if it is not currently running.
 - e** Log on to the WebLogic Server Console.
 - f** Navigate to ***My_domain*** → **Deployments** → **Connector Modules**.
 - g** Click **Deploy a New Connector Module**.
 - h** Locate and select the `NTLConnector.rar` file from the list. It is stored in the `connector` subdirectory.
 - i** Click **Target Module**.
 - j** Select the **My Server** (your server instance) check box.
 - k** Click **Continue**. Review your settings.
 - l** Keep all default settings and click **Deploy**. The Status of Last Action column should display **Success**.
- 4** If deploying the connector on WebSphere, complete the following steps:
- a** Stop the application server.
 - b** Extract the contents of the `NTLschema.jar` file (on the Select Identity Connector CD) to the `WebSphere\AppServer\lib\ext` directory.
 - c** Start the application server.
 - d** Log on to the WebSphere Application Server Console.
 - e** Navigate to **Resources** → **Resource Adapters**.
 - f** Click **Install RAR**.
 - g** In the **Server path** field, enter the path to the `NTLConnector.rar` file. It is stored in the subdirectory created in [Step 1](#).
 - h** Click **Next**.
 - i** In the **Name** field, enter a name for the connector.
 - j** Click **OK**.
 - k** Click the **Save** link (at the top of the page).

- l** On the Save to Master Configuraton dialog, click the **Save** button.
 - m** Click **Resources** → **Resource Adapters**.
 - n** Click the new connector.
 - o** Click **J2C Connection Factories** in the Additional Properties table.
 - p** Click **New**.
 - q** In the Name field, enter the name of the factory for the connector. For the SQL connector, enter `eis/NTL`.
 - r** Click **OK**.
 - s** Click the **Save** link.
 - t** On the Save to Master Configuraton dialog, click the **Save** button.
 - u** Restart WebSphere.
- 5** Modify the mapping files, if necessary. See [Understanding the Mapping Files on page 17](#) for details.
- 6** To configure reverse synchronization on the server, extract the `ntlocal.xml` file from the `NTLschema.jar` to the Select Identity home directory. This file maps user attributes on the Windows server to attributes in Select Identity.
- Because the attributes in the `ntlocal.xml` file are based on those in the `NTLUser.properties` and `NTLGroup.properties` files, you must modify the `ntlocal.xml` file to reflect changes made to these files (Step 5).

After installing the connector, see [Configuring the Connector on page 23](#) for information about registering and configuring the connector in Select Identity.

Installing the Agent on the Windows Server


After you install the Windows NT Local connector on the Select Identity server, you can install the agent on the Windows server. The agent is a suite of Services and support DLLs deployed on the resource. Perform the following to install the agent:

- 1 Copy the `NTLSetup.zip` file from the Select Identity Connector CD to a directory on the NT Local server.
- 2 Extract the ZIP file.
- 3 Double-click **SETUP.exe** to start the installation program.
- 4 Click **Next** to proceed through the installation.
- 5 If needed, provide administrative logon information when prompted.

Configuration is defined on the NTL Connector page.

- 6 Configure the Enable NTL Connector Agent options, as follows:
 - a Select the **Enable NTL Connector Agent** check box. This enables the agent to receive and send data to the connector.
 - b Select the **Enable Log Options** check box, which enables the agent to log events.

encrypt and will generate the encrypted password. Be sure to copy the entire encrypted password in the field, as shown here:



```

C:\WINDOWS\system32\cmd.exe
Microsoft Windows [Version 5.2.3790]
(C) Copyright 1985-2003 Microsoft Corp.

C:\Documents and Settings\gadiap>cd C:\si3.3.1\weblogic\keystore

C:\si3.3.1\weblogic\keystore>encode.bat
Please enter the string to encode :abc123
Please enter the string to encode again :abc123
<ENC:1:cfrM1Gvylj+a8XEWiWo5cx9A+PC0WeS2Z0LieW0dUbeK/jGrgha54K0k060hlmrvND2tkUzjo
GuVeEEDBpUmWo2dIN11ywhxwEDnsZLFxT4r349W/0/6sgoPbuJt3C4vYs8rQk0KpeUng2IG9bftJbuU0
Bjyk6vU5qCTS?Rr1Ds=>

C:\si3.3.1\weblogic\keystore>

```

- j Keep the **TimeOut** and **Retries** settings.
- k In the **UserName** field (in the **Operational Attribute** section), enter the administrator account name in **Select Identity**. The default is `sis`.
- l Enter the password of the administrative account in **Select Identity** in the **Password** field.
- m Add the following operational attributes. This builds the operational attributes that are sent in SPML requests back to **Select Identity** for synchronization. Click the **>>** button after each addition.
 - Attribute Name: `urn:trulogica:concero:2.0#resourceId`
Attribute Value: `resource_name`

This is the name of the resource that you add in **Select Identity** for this NT server. For example, if you specify `NT_LocalMachine` here, then specify `NT_LocalMachine` as the resource name in **Select Identity**.
 - Attribute Name: `urn:trulogica:concero:2.0#reverseSync`
Attribute Value: `true`
 - Attribute Name: `urn:trulogica:concero:2.0#resourceType`
Attribute Value: `ntlocal`

This is the name of the XSL file (without the `.xsl` extension), which provides reverse mappings for the agent to send data to **Select Identity**.

- 8 After defining all of your settings, click **OK**.
- 9 After the installation is complete, click **Finish**.
- 10 Restart the server.

The install process performed the following:

- Creates the target directory with the binaries and support files in the appropriate folders. Places `TLPassfilt.dll` and `TLUtils.dll` in the Windows System directory, `$WinSysPath$`. (`c:\winnt\system32`). The following is the folder structure created:
 - `<TARGETDIR>`
The parent folder
 - `<TARGETDIR>\Bin`
Program binaries
 - `<TARGETDIR>\Lib`
Connector library folder
 - `<TARGETDIR>\Logs`
Connector log folder
 - `<TARGETDIR>\Map`
Mapping of operational attributes
 - `<TARGETDIR>\Servers`
Server binaries
- Creates and configures corresponding services.
- Creates a Program group and shortcuts for the connector configuration console and the uninstall script.
- Sets up the registry for program parameters.

Understanding the Mapping Files

The NT Local connector is deployed with the following mapping files:

- `NTLUser.properties`
- `NTLGroup.properties`

These files reside in the `NTLSchema.jar` file and map user account additions and modifications from Select Identity to the system resource. When you deploy a resource using the Resources page of the Select Identity client, you can review these files.

In addition, the NT Local connector provides the `ntlocal.xml` file, which maps attributes in Windows to those in Select Identity (reverse mapping). Configure this file if you wish to support reserve synchronization.

You can create attributes that are specific to Select Identity using the Attributes page in the Select Identity client. These attributes can be used to associate Select Identity user accounts with system resources by editing the connector mapping file described in this chapter. This process becomes necessary because, for example, a single attribute “username” can have a different name on different resources, such as “user” for UNIX, “UID” for a database, and “UserID” on a Windows server.

The mapping files do not need to be edited unless you want to map additional attributes to your resource. If attributes and values are not defined in the mapping files, they cannot be saved to the resource through Select Identity.

User Attributes

The `NTLUser.properties` file is a text file that maps each Select Identity attribute to an attribute on the resource; the attributes are delimited by `|`. Consider this excerpt:

```
User Name|UserId
```

The Select Identity user attribute is named `User Name` and it is mapped to the `UserId` attribute on the NT Local resource.

Attributes can be concatenated. The attribute names and the separators must not contain the `|` delimiter. For concatenation, the format is as follows:

```
[<SI Attribute>]<separator>[<SI Attribute>]|<Resource Attribute>
```

as in this example:

```
[First Name], [Middle Name] [Last Name]| FullName
```

where `First Name` and `Last Name` are attributes in Select Identity. They are concatenated to form the value of the `FullName` attribute in NT. A space is used as a separator between the two Select Identity attributes.

It is necessary to use the NT User Attribute Name column for mapping in the user properties file.

The following table provides a list of all NT attributes that you can map if you wish to provision users with this information. Here is a description of the columns provided in the table:

- **Select Identity Resource Attribute**— The attribute used by the NT Local connector, as defined in the mapping file.
- **NT Attribute** — The name of the attribute on the Windows server.
- **Label on NT UI** — The name of the property on the Windows UI that corresponds to the attribute on the Windows server.
- **Description** — A description of the attribute and any noteworthy information needed when assigning values to the attribute.

The primary key for Windows NT Local is `UserId`. This attribute must be mapped to an attribute in Select Identity in order for user information to be stored on the Windows server. It should be the first entry in `NTLUser.properties` and `Password` needs to be the second entry.

Select Identity Attribute	NT Attribute	Label on NT UI	Description
User Name	UserId	User Logon Name	Primary Key for NT Domain and NT Local User; <i>this attribute is mandatory and must be mapped.</i>
Password	Password	Password	User's password; <i>this attribute is mandatory and must be mapped.</i>
First Name + Last Name	FullName	Full Name	Full name; <i>this attribute is mandatory and must be mapped.</i>
Description	Comment	Description	Description.
UserComment	User Comment	User Comment	A user comment.
ProfilePath	Profile Path (not available for NT Workstation)	User Profile Path	A path to the user's profile. This value can be a null string, a local absolute path, or a UNC path.
ScriptPath	ScriptPath	Logon Script Name	The path for the user's logon script file. The script file can be a .CMD file, an .EXE file, or a .BAT file.
HomeDirectory Drive	Home Directory Drive	Home Directory: Connect	The local directory path. Not available for NT Workstation.

Group Attributes

The `NTLGroup.properties` file is a text file that maps each Select Identity group attribute to an attribute on the resource; the attributes are delimited by `|`. Consider this excerpt:

```
GroupId|GroupId
```

The Select Identity user attribute is named `GroupId` and it is mapped to the `GroupId` attribute on the NT Local resource. The attributes are named the same in this example but need not be.

Attributes can be concatenated. The attribute names and the separators must not contain the `|` delimiter. For concatenation, the format is as follows:

```
[<SI Attribute>]<separator>[<SI Attribute>]|<Resource Attribute>
```

Use the NT Group Attribute column for mapping in the group properties file.

The primary key for Windows NT Group is `GroupId` and needs to be mapped to an attribute of in the Select Identity Group Model. This attribute must be the first entry in `NTLGroup.properties` file.

Select Identity Attribute	NT Attribute Name	Label on NT UI	Description
GroupId	GroupId	Group Name	Primary Key for the NT Local Group
Description	Comment	Description	Description

Reverse Synchronization

The agent can send changes made to user attributes on the Windows server to the Select Identity server. The agent sends an SPML request to the Select Identity server that contains the attribute changes. The names of the attributes in the SPML request are defined by Windows. To transform the attribute names to Select Identity attribute names, the request is parsed by Select Identity using the `ntlocal.xsl` file.

The `NTLUser.properties` file contains generic Windows attributes that are typically used when a user is created. As described above, you can configure this file to include or exclude attributes. Any addition or deletion of attributes in `NTLUser.properties` must also be made in `ntlocal.xsl`. Each block in `ntlocal.xsl` corresponds with each attribute entry in `NTLUser.properties`.

If the following mapping is added to `NTLUser.properties`:

```
SI_RESOURCE_ATTRIBUTE|NT_ATTRIBUTE
```

You must add the following block to `ntlocal.xsl`:

```
<xsl:when test="$ATTRNAME = ' NT_ATTRIBUTE' ">
  <xsl:call-template name="AttributeBuilder">
    <xsl:with-param name="DSMLELEMENT" select="$DSMLELEMENT"/>
    <xsl:with-param name="ATTRNAME" select="'
      SI_RESOURCE_ATTRIBUTE' "/>
    <xsl:with-param name="ATTRVALUE" select="$ATTRVALUE"/>
    <xsl:with-param name="MODIFYFLAG" select="$MODIFYFLAG"/>
  </xsl:call-template>
</xsl:when>
```

where `NT_ATTRIBUTE` represents the attribute passed from the Windows server and `SI_RESOURCE_ATTRIBUTE` represents the attribute defined by Select Identity and displayed in the resource attributes list.



Note that the XSL file is case sensitive; attributes must be specified exactly as they exist in Select Identity and on the resource. For example, if the mail attribute is defined in Windows, you must specify `mail`, not `Mail` or `MAIL`, and so on.

The following is an example. The mail attribute is added to `NTLUser.properties`, as follows:

```
Email|mail
```

Then, the following block is added to `ntlocal.xsl`:

```
<xsl:when test="$ATTRNAME = 'mail'">
  <xsl:call-template name="AttributeBuilder">
    <xsl:with-param name="DSMLELEMENT" select="$DSMLELEMENT"/>
    <xsl:with-param name="ATTRNAME" select="'Email'"/>
    <xsl:with-param name="ATTRVALUE" select="$ATTRVALUE"/>
    <xsl:with-param name="MODIFYFLAG" select="$MODIFYFLAG"/>
  </xsl:call-template>
</xsl:when>
```

where `mail` represents the attribute passed from the Windows server and `Email` represents the attribute in Select Identity.

For composite attributes defined in the `NTLUser.properties` file, such as `[First Name]` `[Last Name]`, you must provide two attribute name-value pairs in the `ntlocal.xsl` file. For example, for the following entry in `NTLUser.properties`:

```
[First Name] [Last Name]|displayname
```

The `ntlocal.xsl` file must contain the following:

```
<xsl:when test="$ATTRNAME = 'displayname'">
  <xsl:choose>
    <xsl:when test="contains($ATTRVALUE, ' ')">
      <!-- First Name is before space char -->
      <xsl:call-template name="AttributeBuilder">
        <xsl:with-param name="DSMLELEMENT" select="$DSMLELEMENT"/>
        <xsl:with-param name="ATTRNAME" select="'First Name'"/>
        <xsl:with-param name="ATTRVALUE"
          select="substring-before($ATTRVALUE, ' ')/>
        <xsl:with-param name="MODIFYFLAG" select="$MODIFYFLAG"/>
      </xsl:call-template>
      <!-- Last Name is after space char -->
      <xsl:call-template name="AttributeBuilder">
        <xsl:with-param name="DSMLELEMENT" select="$DSMLELEMENT"/>
        <xsl:with-param name="ATTRNAME" select="'Last Name'"/>
        <xsl:with-param name="ATTRVALUE"
          select="substring-after($ATTRVALUE, ' ')/>
        <xsl:with-param name="MODIFYFLAG" select="$MODIFYFLAG"/>
      </xsl:call-template>
    </xsl:when>
    <xsl:otherwise>
      <!-- If no space, take the whole string as First Name -->
      <xsl:call-template name="AttributeBuilder">
        <xsl:with-param name="DSMLELEMENT" select="$DSMLELEMENT"/>
        <xsl:with-param name="ATTRNAME" select="'First Name'"/>
        <xsl:with-param name="ATTRVALUE" select="$ATTRVALUE"/>
        <xsl:with-param name="MODIFYFLAG" select="$MODIFYFLAG"/>
      </xsl:call-template>
    </xsl:otherwise>
  </xsl:choose>
</xsl:when>
```

Configuring the Connector

After you deploy the connector on the application server, you must configure Select Identity to use the connector by deploying it in the Select Identity client. The following provides an overview of the procedures you must complete in order to deploy your connector. It also provides connector-specific information you must provide when configuring Select Identity to use the connector.

- 1 Register the connector with Select Identity by clicking the **Deploy New Connector** button on the Connectors home page. Complete this procedure as described in the “Connectors” chapter of the *HP OpenView Select Identity Administrator Guide*.

After you deploy the connector, the connector properties will look similar to this:

[Home](#) > [Connectors](#) > **View Connector : NTLConnector**

Connector Information	
*Connector Name:	NTLConnector
*Pool Name:	eis/NTL

- 2 Deploy a resource that uses the newly created connector. On the Resources home page, click the **Deploy New Resource** button. When

configuring the resource, refer to the following for parameters specific to this connector:

Field Name	Sample Values	Description
Resource Name	local_server	Name given to the resource. If you enabled reverse synchronization, this must be the same as the value provided for the urn:trulogica:concerno:2.0#resourceId attribute on the agent console.
Resource Type	NT	The connector that was deployed in Step 1 on page 23 .
Authoritative Source*	No	Whether this resource is a system that is considered to be the authoritative source for user data in your environment. Specify No if the connector is not enabled for reverse synchronization. Specify Yes if you want to add users through reverse synchronization. If the resource is not authoritative, the resource can only modify user entitlements during reverse synchronization.
Associate to Group	Selected	Whether the system uses the concept of groups. For this connector, select this option.
UserName	Administrator	Administrative account on the target resource.
Password	Password123	Password corresponding to the administrative account.
Server	server.company.com	Target resource NETBIOS name or IP address.
ServerPort	5001	Forward connector server port, as configured on the resource agent.

* Instead of creating an authoritative resource, you can create authoritative attributes (in the next step) for the attributes that will be synchronized.

Entitlements are authoritative by default in a non-authoritative resource but other attributes are not.

Complete the steps in this procedure as described in the “Resources” chapter of the *HP OpenView Select Identity Administrator Guide*. After you deploy the resource for the connector, the Basic Info page of the resource properties will look similar to this:

Resource Information	
* Resource Name:	NTL
Resource Description:	<input type="text"/>
* Resource Type:	NTLConnector
* Authoritative Source:	Yes
* Delete User:	Yes
Reconciliation Workflow:	ReconciliationDefaultProcess
Resource Owner:	sis
* Resource Id:	1620

The Additional Info page will look similar to this:

Resource Information	
Resource Name:	NTL
<input checked="" type="checkbox"/> Manage User	
Associate to Group:	<input checked="" type="checkbox"/>

The Access Info page will look similar to this:

Resource Access Information	
* Resource Name:	NTL
* Username:	administrator
* Password:	*****
* Server Name:	sint6
* AgentPort:	5000

- 3 Create attributes that link Select Identity to the connector. For each mapping in the connector’s mapping file, create an attribute using the Attributes capability on the Select Identity client.

Refer to the “Attributes” chapter in the *HP OpenView Select Identity Administrator Guide* for more information. After you create the attributes

for the connector, the View Attributes page for the resource will look similar to this:

(Resource Name=NTL)				
<< < Page 1 of 1 > >>				Total Records:10
Name	Min Length	Max Length	Attribute Mapped To	Authoritative
CountryId	0	255	Country	N
Description	0	255	Description	N
First Name	0	255	FirstName	N
HomeDirectory	0	255	HomeDirectory	N
Last Name	0	255	LastName	N
NTL_ENTITLEMENTS	1	255	NTL_ENTITLEMENTS	Y
NTL_KEY	1	255	NTL_KEY	Y
Password	0	255	Password	N
ScriptPath	0	255	ScriptPath	N
User Name	0	255	UserName	N

- 4 Create a Service that will use the newly created resource. To do so, click the **Deploy New Service** button on the Services home page. Complete this procedure as described in “Services” of the *HP OpenView Select Identity Administrator Guide*. You will reference your new resource created in [Step 2](#) while creating this service.

If you are enabling reverse synchronization, configure the Service as follows:

- When selecting the Business Relationship, choose the **ReconciliationDefaultProcess** workflow for the **RECONCILIATION:Add Service** and **RECONCILIATION:Delete Service Membership** request events. For **RECONCILIATION:Add Service**, use the user addition view.
- In the user addition view, specify mandatory attributes that are guaranteed to be passed by the reverse synchronization request when adding a user. If you specify a mandatory attribute that is not passed by the resource, the user will be created in Select Identity but reverse synchronization will not succeed.
- When specifying the context, obtain the value from the add request issued by the resource. For example, if the context is Country and the value is US, the `<addRequest>` element in the reverse synchronization request should have an attribute called `country` and a value of US. If the context attribute is not present in the add user request, the user will be created in Select Identity but will not be assigned to a Service.

Uninstalling the Connector

If you need to uninstall a connector from Select Identity, make sure that the following are performed:

- All resource dependencies are removed.
- The connector is deleted using the Select Identity client Connectors pages.

Uninstalling the Connector from WebLogic

Perform the following to delete a connector:

- 1 Log on to the WebLogic Server Console.
- 2 Navigate to *My_Domain* → **Deployments** → **Connector Modules**.
- 3 Click the delete icon next to the connector that you want to uninstall.
- 4 Click **Yes** to confirm the deletion.
- 5 Click **Continue**.

Uninstalling the Connector from WebSphere

Complete the following steps to uninstall the connector on WebSphere:

- 1 Log on to the WebSphere Application Server Console.
- 2 Navigate to **Resources** → **Resource Adapters**.
- 3 Select the connector to uninstall.
- 4 Click **Delete**.
- 5 Click the **Save** link (at the top of the page).
- 6 On the Save to Master Configuraton dialog, click the **Save** button.

Uninstalling the Agent

Perform the following steps to delete the agent on the Windows server:

- 1 From the Start menu, select **Programs** → **HP OpenView NTLocalConnector** → **Uninstall Agent**.
- 2 Complete the installation as prompted by the wizard.