

# HP Operations Manager

For the for the UNIX and Linux operating systems

Software Version: 9.20

## Web Services Integration Guide

Document Release Date: May 2014

Software Release Date: May 2014



## Legal Notices

### Warranty

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

The information contained herein is subject to change without notice.

### Restricted Rights Legend

Confidential computer software. Valid license from HP required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

### Copyright Notice

© Copyright 2008-2014 Hewlett-Packard Development Company, L.P.

### Trademark Notices

Adobe® and Acrobat® are trademarks of Adobe Systems Incorporated.

HP-UX Release 10.20 and later and HP-UX Release 11.00 and later (in both 32 and 64-bit configurations) on all HP 9000 computers are Open Group UNIX 95 branded products.

Intel®, Itanium®, and Pentium® are trademarks of Intel Corporation in the U.S. and other countries.

Java is a registered trademark of Oracle and/or its affiliates.

Microsoft® and Windows® are U.S. registered trademarks of Microsoft Corporation.

Oracle is a registered trademark of Oracle and/or its affiliates.

UNIX® is a registered trademark of The Open Group.

## Documentation Updates

The title page of this document contains the following identifying information:

- Software Version number, which indicates the software version.
- Document Release Date, which changes each time the document is updated.
- Software Release Date, which indicates the release date of this version of the software.

To check for recent updates or to verify that you are using the most recent edition of a document, go to: <http://h20230.www2.hp.com/selfsolve/manuals>

This site requires that you register for an HP Passport and sign in. To register for an HP Passport ID, go to: <http://h20229.www2.hp.com/passport-registration.html>

Or click the **New users - please register** link on the HP Passport login page.

You will also receive updated or new editions if you subscribe to the appropriate product support service. Contact your HP sales representative for details.

## Support

Visit the HP Software Support Online web site at: <http://www.hp.com/go/hpsoftwaresupport>

This web site provides contact information and details about the products, services, and support that HP Software offers.

HP Software online support provides customer self-solve capabilities. It provides a fast and efficient way to access interactive technical support tools needed to manage your business. As a valued support customer, you can benefit by using the support web site to:

- Search for knowledge documents of interest
- Submit and track support cases and enhancement requests
- Download software patches
- Manage support contracts
- Look up HP support contacts
- Review information about available services
- Enter into discussions with other software customers
- Research and register for software training

Most of the support areas require that you register as an HP Passport user and sign in. Many also require a support contract. To register for an HP Passport ID, go to:

<http://h20229.www2.hp.com/passport-registration.html>

To find more information about access levels, go to:

[http://h20230.www2.hp.com/new\\_access\\_levels.jsp](http://h20230.www2.hp.com/new_access_levels.jsp)

**HP Software Solutions Now** accesses the HPSW Solution and Integration Portal Web site. This site enables you to explore HP Product Solutions to meet your business needs, includes a full list of Integrations between HP Products, as well as a listing of ITIL Processes. The URL for this Web site is

<http://h20230.www2.hp.com/sc/solutions/index.jsp>

# Contents

Contents .....	3
Chapter 1: Introduction to the HPOM Web Services .....	6
HPOM Incident Web Service .....	6
HPOM Tool Web Service .....	6
Features and Benefits .....	7
Prerequisite Knowledge .....	7
Sample and Demo Clients .....	8
Incident to Message Mappings .....	9
XML Namespaces .....	15
Endpoint References .....	16
Chapter 2: Configuring the HPOM Web Services .....	19
Service Configuration .....	20
Port Configuration .....	23
Web Server Configuration .....	23
Chapter 3: Incident Operations Reference .....	24
Get .....	25
Put .....	27
Create .....	29
Close .....	31
Reopen .....	33
EnumerateOp .....	35
PullOp .....	38
ReleaseOp .....	40
SubscribeOp .....	42
UnsubscribeOp .....	46
RenewOp .....	48
OwnMany .....	49
DisownMany .....	51
GetAnnotations .....	53

AddAnnotation .....	55
UpdateAnnotation .....	57
DeleteAnnotation .....	59
SetCustomAttribute .....	61
DeleteCustomAttribute .....	63
CloseMany .....	65
ReopenMany .....	66
StartAction .....	67
StopAction .....	69
GetInstructionText .....	71
<b>Chapter 4: Tool Operations Reference .....</b>	<b>73</b>
Create .....	74
Delete .....	77
EnumerateOp .....	79
Get .....	81
SubscribeOp .....	82
RenewOp .....	85
UnsubscribeOp .....	87
PullOp .....	89
ReleaseOp .....	91
<b>Chapter 5: Security for Web Service Clients .....</b>	<b>93</b>
User Authentication .....	93
Secure HTTP Connections .....	94
<b>Chapter 6: Basic Troubleshooting .....</b>	<b>95</b>
Troubleshoot Connectivity .....	95
Troubleshoot the Incident Web Service .....	95
Troubleshoot on HPOM on UNIX or HPOM on Linux .....	98
<b>Appendix 7: SOAP Envelope Examples .....</b>	<b>99</b>
Create Request SOAP Envelope Example .....	99
Create Response SOAP Envelope Example .....	101
Close Request SOAP Envelope Example .....	102

Close Response SOAP Envelope Example .....	103
Enumerate Request SOAP Envelope Example .....	104
Enumerate Response SOAP Envelope Example .....	107
Pull Request SOAP Envelope Example .....	108
Pull Response SOAP Envelope Example .....	109
Subscribe Request SOAP Envelope Example .....	112

# Chapter 1: Introduction to the HPOM Web Services

HP Operations Manager (HPOM) Web Services enable you to develop remote clients that access HPOM management servers using industry-standard terminology and technical standards, instead of product-specific interfaces.

HPOM provides the following web services:

- Incident Web Service

Enables clients to access HPOM messages.

- Tool Web Service

Enables clients to execute tools from an HPOM management server.

## HPOM Incident Web Service

In HPOM, a message is a structured, readable notification that HPOM generates after detecting, filtering, and correlating one or more events. These events relate to changes in application, system, network, or service status. HPOM messages are conceptually similar to incidents, as defined by the IT Infrastructure Library (ITIL) version 3 framework for service management. An ITIL-compliant incident is an event that could interrupt a service or degrade the quality of a service.

The HPOM Incident Web Service exposes HPOM messages as ITIL-compliant incidents. The service enables remote clients that you develop to get incidents from HPOM, and update and create incidents in HPOM. Clients can also trigger incident state changes in HPOM, for example, to close an incident.

## HPOM Tool Web Service

HPOM provides an action system that enables users to start applications, scripts, and commands on managed nodes. The HPOM Tool Web Service enables remote clients that you develop to launch tools on managed nodes using the HPOM action system. To launch a tool, the client creates a new tool execution using the service. After a tool is executed on a managed node, the agent sends back a result code and any output. Clients can subscribe to receive details of updated tool executions.

## Features and Benefits

The web services provide the following features and benefits:

- Consistent interfaces on HP Operations Manager for UNIX, HP Operations Manager for Windows, and HP Operations Manager on Linux management servers. Clients can integrate seamlessly with HPOM management servers on all platforms.
- Compliance with the Distributed Management Task Force (DMTF) Web Services for Management (WS-Management) standard. This compliance enables you to develop clients for the web service using tools that support WS-Management, for example Wiseman.
- Support for client development using other web service development tools (for example Apache Axis and Windows Communication Framework (WCF)).
- Standard operations that WS-Management specifies (for example Get, Create), and in addition custom operations for incidents (for example Close, Reopen).

## Prerequisite Knowledge

Developing a client to access the HPOM Web Services requires knowledge of the standards and tools that you will use. Discussion of these standards and tools is outside the scope of this document.

You may want to consult the following external resources:

- Web services definition language: [www.w3.org](http://www.w3.org)
- ITIL: [www.itil-officialsite.com](http://www.itil-officialsite.com)
- WS-Management: [www.dmtf.org](http://www.dmtf.org) (document number DSP0226)
- Wiseman: [wiseman.dev.java.net](http://wiseman.dev.java.net)
- Apache Axis: [ws.apache.org](http://ws.apache.org)
- WCF: [msdn.microsoft.com](http://msdn.microsoft.com)

## Sample and Demo Clients

HPOM provides sample and demo clients to help you get started with developing your own clients.

**Note:** The sample and demo clients are provided for your convenience. HP does not provide support for them. When you use the sample and demo clients you do so at your own risk. HP is not liable for problems that are caused by these clients.

The sample clients directories on the management server contain the source code of sample clients for every supported web service framework.

- Incident Web Service sample clients

```
/opt/OV/contrib/OprWsInc/client
```

- Tool Web Service sample clients

```
/opt/OV/contrib/OprWsTool/client
```

The demo clients are fully operational command line clients that enable you to test the HPOM Web Services.

To start a demo client, run the following commands on the management server:

- Incident Web Service demo client

```
/opt/OV/support/OprWsInc/client/java/runclient.sh
```

- Tool Web Service demo client

```
/opt/OV/support/OprWsInc/client/java/runtoolclient.sh
```

For example, to create a new message, type:

```
/opt/OV/support/OprWsInc/client/java/runclient.sh \  
-host omservers.example.com -port 8444 -ssl \  
-user Administrator -password password \  
-action create -title TestMessage \  
-emittingnode omagent.example.com
```

## Incident to Message Mappings

The HPOM Incident Web Service exposes HPOM messages as ITIL-compliant incidents. HPOM messages are conceptually similar to incidents, but do not have identical attributes. To enable operations on incidents for HPOM, the service maps HPOM message attributes into incident subelements, and incident subelements into HPOM message attributes.

For some standard incident subelements, there are conceptually equivalent HPOM message attributes, and so the service maps them directly. The service also includes an extension to the standard incident definition, which makes it possible to map additional HPOM message attributes to incidents elements. Although an incident can contain other extensions, the service ignores them.

For other incident subelements, there are no conceptually equivalent HPOM message attributes. In some cases, the service maps these incident attributes to a custom message attribute (CMA). Each custom message attribute is a name-value pair. In HPOM, each message can have any number of custom message attributes attached to it.

["Mapping of Incident Subelements to HPOM Message Attributes"](#) below shows the mapping of Incident subelements to HPOM message attributes.

### Mapping of Incident Subelements to HPOM Message Attributes

Incident Subelement	HPOM Message Attribute	Description
IncidentID	Message No.	Unique identifier for this incident. HPOM generates this ID.
Description	CMA with the name "Description"	Detailed description of the incident.
Title	Message Text	Brief description of the event that this incident relates to.
LifeCycleState		Not mapped to an HPOM message attribute. The service uses the following rules to set the LifeCycleState in incidents that the service returns: <ul style="list-style-type: none"><li>• If the message is acknowledged, LifeCycleState contains "closed".</li><li>• If the message is owned, LifeCycleState contains "work in progress".</li><li>• If the message is not acknowledged or owned, LifeCycleState contains "open".</li></ul>
Severity	Severity	Severity of the event that the incident relates to.
Solution	CMA with the name "Solution"	Description of steps taken in response to the incident.

**Mapping of Incident Subelements to HPOM Message Attributes, continued**

<b>Incident Subelement</b>	<b>HPOM Message Attribute</b>	<b>Description</b>
Category	Message Group	String used for organizing incidents. Incidents that have some logical connection have the same category.
SubCategory	CMA with the name "Subcategory"	String used for more detailed organization of incidents that have the same category.
ProductType	CMA with the name "Product Type"	String that may be used for integration with a service management product. The service management product defines the string's value and purpose.
ProblemType	CMA with the name "Problem Type"	String that may be used for integration with a service management product. The service management product defines the string's value and purpose.
CollaborationMode	CMA with the name "Collaboration Mode"	String that may be used for integration with a service management product. The service management product defines the string's value and purpose.
EmittingCI.ID	Service Name	ID of the service that the incident relates to. The severity of an incident can affect the status of a service that it relates to.
EmittingNode.DnsName	Node	Name of the node generating the incident.
AssignedOperator.Name	Owner	Name of the HPOM user that is currently responsible for the incident. If the incident has an owner, HPOM prevents other users from starting some tasks on that incident.
AffectedCI	<i>Not mapped to HPOM messages</i>	
RequesterReference	<i>Not mapped to HPOM messages</i>	
Type	Message Type	String used for organizing incidents, for example, to group different types of incident within a category.

"[Mapping of OperationsExtension Subelements to HPOM Message Attributes](#)" below shows the mapping of OperationsExtension subelements.

**Mapping of OperationsExtension Subelements to HPOM Message Attributes**

OperationsExtension Subelements	HPOM Message Attribute	Description
Application	Application	Name of the application to which the incident relates.
Object	Object	Name of the object to which the incident relates.
StateChangeTime	Time Owned or Time Acknowledged	The time at which the incident was owned or acknowledged. The service maps whichever time is later (the time owned or the time acknowledged) to the StateChangeTime subelement.
CreationTime	Time Created	Time at which the agent created the incident.
ReceivedTime	Time Received	Time at which the management server received the incident.
NumberOfDuplicates	Number of Duplicates	Number of duplicates that the management server has detected for the incident. If duplicate detection is disabled, the value of this is 0.
CorrelationKey	Message Key	String that enables other processes to identify incidents that relate to each other. Related incidents have similar message keys. Message keys are not unique.
AcknowledgeCorrelationKey (added in version 8.30)	Acknowledge Messages Matching this Message Key Pattern	String that instructs the management server to close other incidents when the management server receives this incident. The management server closes any existing incidents with a CorrelationKey that matches this string.
ConditionMatched	Unmatched	Indicates whether the incident was sent to the server because of a matched condition in a policy or template.
AutomaticAction.ActionStatus (added in version 8.30)	Automatic Action Status	Status of the automatic action, if one is associated with the incident.

**Mapping of OperationsExtension Subelements to HPOM Message Attributes, continued**

<b>OperationsExtension Subelements</b>	<b>HPOM Message Attribute</b>	<b>Description</b>
AutomaticAction.ActionCommand (added in version 8.30)	Action Command	Command and parameters that run when the action starts.
AutomaticAction.DnsName (added in version 8.30)	Action Node	Name of the node on which the action runs.
AutomaticAction.ActionType (added in version 8.30)	Action Type	Indicates that the action is automatic.
OperatorAction.ActionStatus (added in version 8.30)	Operator Action Status	Status of the operator-initiated action, if one is associated with the incident.
OperatorAction.ActionCommand (added in version 8.30)	Action Command	Command and parameters that run when the action starts.
OperatorAction.DnsName (added in version 8.30)	Action Node	Name of the node on which the action runs.
OperatorAction.ActionType (added in version 8.30)	Action Type	Indicates that the action is operator-initiated.
EscalationStatus	Escalation (flag in the message browser)	Defines the escalation status of the incident, if the incident was escalated by this management server, or to a different management server.
OriginalEvent	Original Message	Details of the event that is the cause of this incident.

**Mapping of OperationsExtension Subelements to HPOM Message Attributes, continued**

OperationsExtension Subelements	HPOM Message Attribute	Description
CustomAttributes	Custom Attributes	<p>Each incident can have any number of custom message attributes. Each custom message attribute is a name-value pair.</p> <p>The service excludes the following custom message attributes from the CustomAttributes subelement:</p> <ul style="list-style-type: none"> <li>• Description</li> <li>• Solution</li> <li>• Subcategory</li> <li>• Product Type</li> <li>• Problem Type</li> <li>• Collaboration Mode</li> </ul> <p>The service maps these custom message attributes to Incident subelements instead (see "<a href="#">Mapping of Incident Subelements to HPOM Message Attributes</a>" on page 9).</p>
NumberOfAnnotations	Number of annotations	<p>Number of annotations that have been added to the incident. An annotation is a short note about the incident. For example, a user can add an annotation to summarize actions taken in response to the message.</p>
Source	Source	<p>Contains the name and version of the policy that created the message.</p>
AutomaticActionStatus (deprecated in version 8.30)	Automatic Action Status	<p>Status of the automatic action, if one is associated with the incident.</p> <p>(This subelement is deprecated and available only for backwards compatibility. HP intends to remove this subelement in a future version of this web service.)</p>

**Mapping of OperationsExtension Subelements to HPOM Message Attributes, continued**

<b>OperationsExtension Subelements</b>	<b>HPOM Message Attribute</b>	<b>Description</b>
OperatorActionStatus (deprecated in version 8.30)	Operator Action Status	Status of the operator-initiated action, if one is associated with the incident.  (This subelement is deprecated and available only for backwards compatibility. HP intends to remove this subelement in a future version of this web service.)

For an example incident in XML, see ["Pull Response SOAP Envelope Example"](#) on page 109.

## XML Namespaces

"[Prefixes and XML Namespaces Used in this Document](#)" below lists the prefixes used in this document to show the namespaces of element types.

### Prefixes and XML Namespaces Used in this Document

Prefix	XML Namespace
inc	http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
incExt	http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/Incident
incFil	http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/Incident Filter
ismCi	http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem
ismNode	http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node
ismWorkItem	http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem
s	http://www.w3.org/2003/05/soap-envelope
tool	http://schemas.hp.com/opr/ws/ServiceOperation/ToolManagement/1/ToolExecution
toolFil	http://schemas.hp.com/opr/ws/ServiceOperation/ToolManagement/1/ToolExecutionFilter
wsa	http://schemas.xmlsoap.org/ws/2004/08/addressing
wse	http://schemas.xmlsoap.org/ws/2004/08/eventing
wsen	http://schemas.xmlsoap.org/ws/2004/09/enumeration
wsman	http://schemas.dmtf.org/wbem/wsman/1/wsman.xsd
xs	http://www.w3.org/2001/XMLSchema

## Endpoint References

The WS-Management specification uses WS-Addressing endpoint references (EPRs) as the addressing model for individual resource instances. ["XML Namespaces" on the previous page](#) lists the prefixes used in this section to show the namespace of each element type.

An EPR is an XML element of the type *wsa:EndpointReferenceType*. An EPR element contains subelements that, in combination, provide the full reference to a resource instance. In terms of the HPOM Incident Web Service, this means that an EPR provides the full reference to an individual incident on a particular management server. In terms of the HPOM Tool Web Service, an EPR provides the full reference one execution of a tool.

The following XML element shows an example of an EPR for the HPOM Incident Web Service:

```
<wsa:EndpointReference>
  <wsa:Address>
    https://manager1.example.com:8444/opr-webservice/Incident.svc/
  </wsa:Address>
  <wsa:ReferenceParameters>
    <wsman:ResourceURI>
      http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
    </wsman:ResourceURI>
    <wsman:SelectorSet>
      <wsman:Selector Name="IncidentID">
        2b9cdf48-d6ca-71db-0d4b-1039228b0000
      </wsman:Selector>
    </wsman:SelectorSet>
  </wsa:ReferenceParameters>
</wsa:EndpointReference>
```

The above EPR contains the following conceptual elements:

- Address at which the service is available on a management server. This is in the format:  
**https://<server\_name>:<port>/opr-webservice/Incident.svc/**
- Unique identifier for the type of resource. This is the following URI:  
http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
- Selector set that identifies an incident. This contains one selector, which contains an incident ID.

When you create a new incident using the service, the service returns an EPR for the new incident. You can store this EPR, and use it to uniquely identify the incident if you need to update it later. (See ["Create" on page 29.](#))

WS-Addressing specifies that, to use an EPR in a request to a service, clients should add the contents of the EPR's *wsa:Address* subelement as the contents of the *wsa:To* subelement in the SOAP header. Where possible, clients should not rely on the *wsa:ReferenceParameters* subelement containing any particular subelements. Clients should instead treat the *wsa:ReferenceParameters* subelement as opaque, by unwrapping its contents and adding them all to the SOAP header of the request.

The following XML fragment shows an example of a SOAP header that contains the EPR of an incident:

```
<s:Header>
...
  <wsa:To>
    https://manager1.example.com:8444/opr-webservice/Incident.svc/
  </wsa:To>
  <wsman:ResourceURI>
    http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
  </wsman:ResourceURI>
  <wsman:SelectorSet>
    <wsman:Selector Name="IncidentID">
      2b9cdf48-d6ca-71db-0d4b-1039228b0000
    </wsman:Selector>
  </wsman:SelectorSet>
...
</s:Header>
```

# Chapter 2: Configuring the HPOM Web Services

The service provides several configuration parameters that enable you to configure how the service responds to client requests. You can also configure the port that the service uses to listen for connections.

The following topics provide more details:

- ["Service Configuration" on the next page](#)
- ["Port Configuration" on page 23](#)
- ["Web Server Configuration" on page 23](#)

**Tip:** To check which version of the HPOM Web Services is available on your management server, open a web browser and navigate to the following location:

```
https://<server_name>:<port>/opr-webservice/Incident.svc?wsdl
```

The service listens for HTTPS connections on port 8444 by default. You may need to accept a certificate and provide credentials for the HPOM management server.

## Service Configuration

The HPOM Web Services provide several configuration parameters that enable you to configure how each service responds to client requests. You can change the values of these parameters to suit your environment.

You can configure the parameters using `ovconfchg`. The parameters for the Incident Web Service are in the `opc.WebService` namespace. The parameters for the Tool Web Service are in the `opc.ToolWebService` namespace.

"[General Service Configuration Parameters](#)" below lists the parameters that are common to both web services.

### General Service Configuration Parameters

Name	Default Value	Description
EnumerationExpiration	10 (minutes)	Default duration that enumeration contexts are valid for.
EnumerationExpirationMaximum	60 (minutes)	Maximum duration that enumeration contexts are valid for. If a client specifies a longer duration, the service overrides the client and uses the value of this parameter instead.
SubscriptionExpiration	60 (minutes)	Default duration that subscriptions are valid for.
SubscriptionExpirationMaximum	1440 (minutes)	Maximum duration that subscriptions are valid for. If a client specifies a longer duration, the service overrides the client and uses the value of this parameter instead.
MaxItems	100	Maximum number of items that the service returns for a PullOp operation if the client does not specify a value.
MaxItemsMaximum	500	Maximum number of items that service returns for a PullOp operation. If a client specifies a larger number, the service uses this value instead. Set this parameter to a value below 5000. A value of 5000 or higher may cause heap space exceptions.
EventQueueSize	1000	Maximum number of events that an event queue can store. If the event queue contains the maximum number of events, and a new event occurs, the service discards the oldest event from the queue before it adds the new event to the end of the queue.

[Incident Web Service Configuration Parameters](#) lists the additional parameters for the HPOM Incident Web Service.

**Incident Web Service Configuration Parameters**

Name	Default value	Description
DefaultSource	IncidentWS	<p>Default value of <i>inc:Extensions/incExt:OperationsExtension/incExt:Source</i> in incidents that the service creates.</p> <p>DefaultSource must be 12 characters or less in length.            DefaultSource must contain only alphabetic characters.</p> <p>Added in version 9.10.</p>
FilterCmaList	empty	<p>Configures a list of custom message attributes that incidents must match to be returned by the Incident Web Service, for example by the PullOp operation. Only custom message attributes that match the filter list are returned with the incident. Custom message attributes that do not match the filter list are dropped.</p> <p>The list can contain custom message attribute keys, keys and values, or a combination of both, for example:</p> <ul style="list-style-type: none"> <li>• List of keys, separated by semi-colons (;):           <pre>&lt;key1&gt;;&lt;key2&gt;;...;&lt;keyn&gt;</pre> </li> <li>• List of key-value pairs (use colons (:)) to separate keys and values, use semi-colons (;) to separate key-value pairs):           <pre>&lt;key1&gt;:&lt;value1&gt;;&lt;key2&gt;:&lt;value2&gt;;...;&lt;keyn&gt;:&lt;valuen&gt;</pre> </li> <li>• Combination of keys and key-value pairs:           <pre>&lt;key1&gt;;&lt;key2&gt;:&lt;value2&gt;;&lt;key3&gt;;...;&lt;keyn&gt;:&lt;valuen&gt;</pre> </li> <li>• Same key with different values:           <pre>&lt;key1&gt;:&lt;value1&gt;;&lt;key1&gt;:&lt;value2&gt;;...;&lt;key1&gt;:&lt;valuen&gt;</pre> </li> </ul> <p>If you change this value, you must restart the ovtomcatB component for your changes to take effect:</p> <pre>/opt/OV/bin/ovc -restart ovtomcatB</pre> <p>Added in Server Accessories 09.10.220 patches PHSS_42845, ITOSOL_00775, and OML_00053 (and higher).</p>

[Tool Service Configuration Parameters](#) lists the additional parameters for the HPOM Tool Web Service.

#### Tool Service Configuration Parameters

Name	Default value	Description
FinishedInstanceExpiration	300 (seconds)	Duration that the Tool Web Service stores details of finished tool executions. Clients must read the result of a tool execution within the defined number of seconds after the tool execution finishes.
RunningInstanceExpiration	43200 (seconds)	Duration that the Tool Web Service stores details of running tool executions. If an agent does not send a tool execution result within the defined number of seconds after the tool execution starts, the service deletes the tool execution.

## Port Configuration

The port that the HPOM Incident Web Service is available on depends on the configuration of the Tomcat (B) servlet container on HPOM on UNIX or HPOM on Linux management servers.

The service listens for HTTPS connections on port 8444 by default.

On HPOM on UNIX or HPOM on Linux management servers, the service also listens for insecure HTTP connections on port 8081. This can be useful for testing your client.

To configure the service to listen for HTTPS connections on a different port, open a shell prompt on the management server, and then type the following command:

```
ovtomcatbctl -sethttpsport <port number>
```

## Web Server Configuration

The HPOM Web Services binary files are signed for security. Every time the web server on the HPOM management server starts an HPOM Web Service, it attempts to verify the signatures. The web server needs Internet access to verify the signatures. If the web server has no Internet access, the web service may not start for several minutes. This delay can degrade performance if, for example, the web server regularly unloads idle web services and restarts them when necessary.

If the management server only has access to the Internet through a proxy, you can configure the web server to use this proxy.

You can set the system web proxy using the following command:

```
export http_proxy="http://<proxy>:<port>"
```

For example:

```
export http_proxy="http://web-proxy.example.com:8080 "
```

## Chapter 3: Incident Operations Reference

The HPOM Incident Web Service provides a Web Services Definition Language (WSDL) document, which describes the service. After you install the service, the WSDL is available from the following location on the HPOM management server:

**`https://<server_name>:<port>/opr-webservice/Incident.svc?wsdl`**

This WSDL document refers to the other WSDL documents and associated XML Schema Documents (XSDs), and gives their location on the management server. These documents provide complete information about the operations that the service supports. The details of how your client uses these operations depends on the web service client development toolkit that you choose.

HP provides unsupported examples for several client development toolkits. The examples are also available on the HPOM management server after you install the service.

The following read-me files provide more information on how to develop clients with each toolkit:

- Apache Axis2

`/opt/OV/contrib/OprWsInc/clients/axis/readme.txt`

- Windows Communication Foundation

`/opt/OV/contrib/OprWsInc/clients/wcf/readme.txt`

- Wiseman

`/opt/OV/contrib/OprWsInc/clients/wiseman/readme.txt`

Alternatively, you can develop a client using any other suitable toolkit or programming language.

This chapter provides a generic reference to the operations that the service provides. For specific examples of SOAP envelopes that the service receives and sends, see "[SOAP Envelope Examples](#)" on page 99

"[XML Namespaces](#)" on page 15 lists the prefixes used in this section to show the namespace of each element type.

**Note:** The WSDL document contains the following operations that the service does not actually support:

- Delete
- SubscriptionEndOp

If your client attempts to use these operations, the service returns an ActionNotSupported fault.

## Get

This operation returns one incident, which is identified by the incident ID.

## Input

### SOAP Body

Empty.

### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.xmlsoap.org/ws/2004/09/transfer/Get
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndPointReferenceType*. (See ["Endpoint References" on page 16.](#))

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value IncidentID.
- *wsman:Selector* must contain the ID of the incident instance to get.

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## Output

The SOAP body contains an element *inc:Incident* of type *inc:Incident*.

## Fault

If it cannot return the incident, the service returns a fault according to the WS-Management standard.

## Put

This operation updates an existing incident, which is identified by the incident ID.

## Input

### SOAP Body

Element *inc:Incident* of type *inc:Incident*. *inc:Incident* can contain any of the following the subelements to update on the server:

- Element *inc:Title* of type *xs:string*.
- Element *inc:Severity* of type *xs:string*. This can be one of the following strings:
  - Normal
  - Warning
  - Minor
  - Major
  - Critical

*inc:Incident* can also contain other valid subelements, although this operation ignores them and returns an incident with the contents of those subelements unchanged. In other words, if Incident contains immutable subelements, the operation does not return a fault.

### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.xmlsoap.org/ws/2004/09/transfer/Put
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndpointReferenceType*. (See "[Endpoint References](#)" on page 16.)

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value IncidentID.
  - *wsman:Selector* must contain the ID of the incident instance to get.
- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## Output

The SOAP body contains an element *inc:Incident* of type *inc:Incident*, which contains the updated incident.

## Fault

If it cannot update the incident, the service returns a fault according to the WS-Management standard.

## Create

This operation stores a new incident on the management server.

## Input

### SOAP Body

Element *inc:Incident* of type *inc:Incident*. *inc:Incident* must contain the following subelements:

- *inc>Title*
- *inc:EmittingNode/ismNode:DnsName*
- *Incident* can contain any of the following subelements:
  - *inc:Description*
  - *inc:Severity* (default: "Unknown")
  - *inc:Solution*
  - *inc:Category*
  - *inc:SubCategory*
  - *inc:ProductType*
  - *inc:ProblemType*
  - *inc:CollaborationMode* (default: "FYI")
  - *inc:EmittingCI/ismCi:ID*
  - *inc>Type*
  - *inc:Extensions/incExt:OperationsExtension/incExt:Application*
  - *inc:Extensions/incExt:OperationsExtension/incExt:Object*
  - *inc:Extensions/incExt:OperationsExtension/incExt:CreationTime* (default: the current time)
  - *inc:Extensions/incExt:OperationsExtension/incExt:CorrelationKey* (default: null)
  - *inc:Extensions/incExt:OperationsExtension/incExt:CustomAttributes* (default: an empty list)

*inc:Incident* can also contain other valid subelements, although this operation ignores them.

The service uses the value of the `DefaultSource` parameter on the management server to set the value of the `inc:Extensions/incExt:OperationsExtension/incExt:Source` subelement. (See "[Service Configuration](#)" on page 20.)

## SOAP Header

- Element `wsa:Action` of type `wsa:ActionType` that contains the following string:

```
http://schemas.xmlsoap.org/ws/2004/09/transfer/Create
```

- Element `wsman:ResourceURI` of type `wsman:AttributableURI`

Contains a string that identifies the resource type. You can use the element `wsa:ReferenceParameters/wsman:ResourceURI` from an element of type `wsa:EndPointReferenceType`.

Alternatively, create a `wsman:ResourceURI` element that contains the following string:

```
http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element `wsman:OperationTimeout` of type `wsman:AttributableDuration`

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a `TimedOut` fault if it cannot respond in time.

For an example, see "[Create Request SOAP Envelope Example](#)" on page 99.

## Output

The SOAP body contains an element `wsa:EndpointReference` of type `wsa:EndpointReferenceType`. This element contains the subelements `wsman:ResourceURI` and `wsman:SelectorSet`, which you can use to uniquely identify the incident in subsequent operations.

For an example, see "[Create Response SOAP Envelope Example](#)" on page 101.

## Fault

If the service cannot store the incident, it returns a fault according to the WS-Management standard.

## Close

This operation sets the lifecycle state of an existing incident to closed. The incident is identified by the incident ID. Alternatively, you can use the CloseMany operation to close multiple incidents in one operation. (See "[CloseMany](#)" on page 65.)

## Input

### SOAP Body

Empty.

### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/ism/ServiceOperation/Common/1/Close
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndPointReferenceType*. (See "[Endpoint References](#)" on page 16.)

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value IncidentID.
- *wsman:Selector* must contain the ID of the incident instance to close.

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

For an example, see ["Close Request SOAP Envelope Example"](#) on page 102.

## Output

The SOAP body is empty. For an example, see ["Close Response SOAP Envelope Example"](#) on page 103.

## Fault

If it cannot close the incident, the service returns a fault according to the WS-Management standard.

## Reopen

This operation sets the lifecycle state of a closed incident to open. The incident is identified by the incident ID.

Alternatively, you can use the ReopenMany operation to open multiple incidents in one operation. (See ["ReopenMany" on page 66.](#))

## Input

### SOAP Body

Empty.

### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/ism/ServiceOperation/Common/1/Reopen
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndpointReferenceType*. (See ["Endpoint References" on page 16.](#))

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value IncidentID.
- *wsman:Selector* must contain the ID of the incident instance to reopen.
- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## **Output**

The SOAP body is empty.

## **Fault**

If it cannot reopen the incident, the service returns a fault according to the WS-Management standard. The service returns a fault if the incident is already open.

## EnumerateOp

This operation returns an enumeration context, which you can then use with the PullOp operation to get batches of incidents from the service. You can specify a filter, so that the enumeration context contains only specific incidents.

### Input

#### SOAP Body

Element *Enumerate* of type *wsen:Enumerate*. This element can contain the following subelements:

- Optional element *wsen:Expires* of type *wsen:ExpirationType*.

Contains a duration, for which the client requires the enumeration context. If you omit this subelement, the service uses the value of the EnumerationExpiration parameter on the management server. If you specify a duration that exceeds the value of the EnumerationExpirationMaximum parameter, the service uses the value of EnumerationExpirationMaximum instead. (See "[Service Configuration](#)" on page 20.)

- Optional element *wsen:Filter* of type *wsen:FilterType* or *wsman:Filter* of type *wsman:dialectableMixedDataType*. For compatibility with different toolkits, the service supports a filter of either type, but you must specify only one of them.

*Filter* attribute Dialect must have the following value:

```
http://schemas.hp.com/  
opr/ws/ServiceOperation/IncidentManagement/1/IncidentFilter
```

*Filter* must contain the subelement *incFil:IncidentEnumerationFilter* of type *incFil:IncidentEnumerationFilter*. *IncidentEnumerationFilter* can contain any of the following subelements:

- Optional element *incFil:Severity* of type *inc:Severity\_OpenType*
- Optional element *incFil:EmittingNode* of type *incFil:EmittingNode*
- Optional element *incFil:Category* of type *xs:string*
- Optional element *incFil:Application* of type *xs:string*
- Optional element *incFil:Object* of type *xs:string*
- Optional element *incFil:EmittingCI* of type *incFil:EmittingCI*
- Optional element *incFil:CorrelationKey* of type *xs:string*
- Optional element *incFil:EscalationStatus* of type *xs:string*

- Optional element *incFil:ConditionMatched* of type *xs:boolean*
- Optional element *incFil:ReceivedTime* of type *incFil:TimeFilter*
- Optional element *incFil:Title* of type *incFil:KeywordFilter*
- Optional element *incFil:CustomAttributes* of type *incFil:CustomAttributes*

The service enumerates incidents that match the contents of the *incFil:IncidentEnumerationFilter* subelements that you specify. For more details on incident attributes, see ["Incident to Message Mappings" on page 9](#).

If you omit *Filter*, the service enumerates all incidents that have the status open or work in progress.

## SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.xmlsoap.org/ws/2004/09/enumeration/Enumerate
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
```

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a *TimedOut* fault if it cannot respond in time.

For an example, see ["Enumerate Request SOAP Envelope Example" on page 104](#).

## Output

The SOAP body contains an element *wsen:EnumerateResponse* (of anonymous type), which contains the following subelements:

- Element *wsen:Expires* of type *wsen:ExpirationType*.

Contains a duration, for which the enumeration context is valid. You can use the *ReleaseOp* operation to cancel the enumeration context early. (See ["ReleaseOp" on page 40.](#))

- Element *wsen:EnumerationContext* of type *wsen:EnumerationContextType*.

Contains a string that identifies the enumeration context. Use *wsen:EnumerationContext* with the *PullOp* operation to get batches of incidents from the service. (See ["PullOp" on the next page.](#))

For an example, see ["Enumerate Response SOAP Envelope Example" on page 107.](#)

## Fault

If it cannot return the enumeration context, the service returns a fault according to the WS-Management standard.

## PullOp

This operation returns a batch of incidents from an enumeration context.

### Input

#### SOAP Body

Element *wsen:Pull* (of anonymous type), which contains the following subelements:

- Element *wsen:EnumerationContext* of type *wsen:EnumerationContextType*.

Contains a string that identifies the enumeration context. Use a *wsen:EnumerationContext* that one of the following operations returns:

- EnumerateOp (see "[EnumerateOp](#)" on page 35)
- SubscribeOp (see "[SubscribeOp](#)" on page 42)
- PullOp (see below)

- Optional element *wsen:MaxElements* of type *xs:positiveInteger*.

Contains an integer that indicates the maximum number of incidents to return in this batch. If you omit this subelement, the service uses the value of the *MaxItems* parameter on the management server. (See "[Service Configuration](#)" on page 20.)

The HPOM Incident Web Service does not support the subelements *wsen:MaxTime* or *wsen:MaxCharacters*. You should omit these subelements.

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.xmlsoap.org/ws/2004/09/enumeration/Pull
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
```

- Optional element *wsm:OperationTimeout* of type *wsm:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a *TimedOut* fault if it cannot respond in time.

For enumeration contexts from the *SubscribeOp* operation, if the event queue remains empty for the specified *OperationTimeout*, *PullOp* returns a *TimedOut* fault.

For an example, see ["Pull Request SOAP Envelope Example" on page 108](#).

## Output

The SOAP body contains an element *wsen:PullResponse* (of anonymous type), which contains the following subelements:

- Element *wsen:EnumerationContext* of type *wsen:EnumerationContextType*.

Contains a string that identifies the enumeration context. This is the same as the input *wsen:EnumerationContext*.

- Element *wsen:Items* of the type *wsen:ItemListType*.

Contains multiple *inc:Incident* elements of type *inc:Incident*.

- Optional element *wsen:EndOfSequence* of type *wsen:attributableEmpty*.

This element is empty. If *wsen:EndOfSequence* is present, there are no remaining items to pull for this enumeration context and the enumeration context is no longer valid.

For an example, see ["Pull Response SOAP Envelope Example" on page 109](#).

## Fault

If it cannot return the batch of incidents, the service returns a fault according to the WS-Management standard.

## ReleaseOp

This operation cancels an existing enumeration context early (that is, before the client has pulled all the incidents, and before the enumeration context has expired).

You can use this operation to cancel an enumeration context from an enumerate operation. To cancel an enumeration context from a subscription operation, unsubscribe instead. (See ["UnsubscribeOp" on page 46.](#))

## Input

### SOAP Body

Element *wsen:Release* (of anonymous type), which contains the subelement *wsen:EnumerationContext* of type *wsen:EnumerationContextType*.

*wsen:EnumerationContext* contains a string that identifies the enumeration context. Use a *wsen:EnumerationContext* that one of the following operations returns:

- EnumerateOp (see ["EnumerateOp" on page 35](#))
- PullOp (see ["PullOp" on page 38](#))

### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

`http://schemas.xmlsoap.org/ws/2004/09/enumeration/Release`

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

`http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident`

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## **Output**

The SOAP body is empty.

## **Fault**

If it cannot release the enumeration context, the service returns a fault according to the WS-Management standard.

## SubscribeOp

This operation returns an enumeration context, which you can then use with the PullOp operation to get batches of new or updated incidents from the service. The service maintains an event queue of new or updated incidents. If an existing incident changes several times, the service adds the incident to the event queue several times (the service does not consolidate the events).

The value of the EventQueueSize parameter on the management server constrains the size of the event queue. (See "[Service Configuration](#)" on page 20.) To prevent the service from deleting events from the queue, you must pull batches of updated incidents at appropriate intervals. Consider using the following procedure to manage a subscription:

1. Use the SubscribeOp operation to get an enumeration context.
2. Immediately after SubscribeOp returns the enumeration context, start a PullOp operation. As soon as the event queue contains events, PullOp returns a batch of incidents.

If the event queue remains empty for the specified OperationTimeout, PullOp returns a TimedOut fault.

3. Immediately after the PullOp returns incidents or a fault, start another PullOp operation.

This step ensures that you always have a PullOp running, which should prevent the event queue from becoming too large.

The HPOM Incident Web Service records each subscription in the log file  
`/var/opt/OV/log/om/incident_ws.*`.

**Caution:** If you restart the HPOM Incident Web Service, the service releases any enumeration contexts. The service does not maintain an event queue of new or updated incidents until the client subscribes again. This situation can also arise if the management server is part of a cluster and a failover occurs.

## Input

### SOAP Body

Element *wse:Subscribe* of type *wse:SubscribeType*, which contains the following subelements:

- Element *wse:Delivery* of type *wse:DeliveryType*. *wse:Delivery* attribute Mode must have the following value:

```
http://schemas.dmtf.org/wbem/wsman/1/wsman/Pull
```

- Optional element *wse:Expires* of type *wse:ExpirationType*.

Contains either a duration that specifies how long the client requires the subscription, or a date and time at which the subscription should expire. If you omit this subelement, the service uses the value of the `SubscriptionExpiration` parameter on the management server. If you specify a duration that exceeds the value of the `SubscriptionExpirationMaximum` parameter, the service uses the value of `SubscriptionExpirationMaximum` instead. (See "[Service Configuration](#)" on [page 20](#).)

- Optional element *wse:Filter* of type *wse:FilterType* or *wsman:Filter* of type *wsman:dialectableMixedDataType*. For compatibility with different toolkits, the service supports a filter of either type, but you must specify only one of them.

*Filter* attribute `Dialect` must have the following value:

```
http://schemas.hp.com/  
opr/ws/ServiceOperation/IncidentManagement/1/IncidentFilter
```

*Filter* must contain the subelement *incFil:IncidentEventingFilter* of type *incFil:IncidentEventingFilter*. *IncidentEventingFilter* can contain any of the following subelements:

- Optional element *incFil:Severity* of type *inc:Severity\_OpenType*
- Optional element *incFil:EmittingNode* of type *incFil:EmittingNode*
- Optional element *incFil:Category* of type *xs:string*

*incFil:Category* enables you to filter incidents depending on a category (message group).

For example, if you are interested in incidents with the category `msggrp1` only, you specify a filter with a *incFil:Category* subelement that contains `msggrp1`. To subscribe to a combination of categories, specify several *incFil:ChangeCategory* subelements.

- Optional element *incFil:Application* of type *xs:string*
- Optional element *incFil:Object* of type *xs:string*
- Optional element *incFil:EmittingCI* of type *incFil:EmittingCI*
- Optional element *incFil:CorrelationKey* of type *xs:string*
- Optional element *incFil:Type* of type *xs:string*
- Optional element *incFil:EscalationStatus* of type *xs:string*
- Optional element *incFil:ConditionMatched* of type *xs:boolean*
- Optional element *incFil:ForwardToTroubleTicket* of type *xs:boolean*

*incFil:ForwardToTroubleTicket* enables you to filter incidents, depending on whether the corresponding HPOM message is flagged for forwarding to an external trouble ticket system.

- Optional element *incFil:ForwardToNotification* of type *xs:boolean*

*incFil:ForwardToNotification* enables you to filter incidents depending on whether the corresponding HPOM message is flagged for forwarding to an external notification system.

- Optional element *incFil:Title* of type *incFil:KeywordFilter*

- Optional elements *incFil:ChangeType* of type *xs:string*

*incFil:ChangeType* enables you to filter incidents depending on how they have changed (whether they are new, updated, closed, or reopened). *incFil:ChangeType* must contain one of the following strings:

- new
- modified
- closed
- reopened

For example, if you are interested in new incidents only, you specify a filter with a *incFil:ChangeType* subelement that contains *new*. To subscribe to a combination of change types, specify several *incFil:ChangeType* subelements.

To subscribe to all change types, you can omit the *incFil:ChangeType* subelements.

- Optional element *incFil:CustomAttributes* of type *incFil:CustomAttributes*

The service enumerates all incidents that match the contents of the *incFil:IncidentEventingFilter* subelements that you specify. For more details on incident attributes, see ["Incident to Message Mappings" on page 9](#).

If you omit *Filter*, the service enumerates all incidents that have the status open or work in progress.

## SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

`http://schemas.xmlsoap.org/ws/2004/08/eventing/Subscribe`

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a *TimedOut* fault if it cannot respond in time.

For an example, see ["SOAP Envelope Examples" on page 99](#).

## Output

The SOAP body contains an element *wse:SubscribeResponse* (of anonymous type), which contains the following subelements:

- Element *wse:SubscriptionManager* of type *wsa:EndpointReferenceType*.

Contains the subelement *wsa:ReferenceParameters/wse:Identifier* of type *wse:Identifier*, which you use to identify the subscription if you unsubscribe or renew it. (See ["UnsubscribeOp" on the next page](#) and ["RenewOp" on page 48](#).)

- Element *wse:Expires* of type *wse:ExpirationType*.

Contains a duration, for which the service maintains the subscription. You can use the *RenewOp* operation to renew the subscription before it expires. (See ["RenewOp" on page 48](#).)

- Element *wsen:EnumerationContext* of type *wsen:EnumerationContextType*.

Contains a string that identifies the enumeration context. Use *EnumerationContext* with the *PullOp* operation to get batches of updated incidents from the service. (See ["PullOp" on page 38](#).)

## Fault

If it cannot return the enumeration context, the service returns a fault according to the WS-Management standard.

## UnsubscribeOp

This operation cancels a subscription before the subscription expires.

The HPOM Incident Web Service records each unsubscription in the log file `/var/opt/OV/log/om/incident_ws.*`.

### Input

#### SOAP Body

Element *wse:Unsubscribe* of type *wse:UnsubscribeType*. This element is required, but should be empty.

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.xmlsoap.org/ws/2004/08/eventing/Unsubscribe
```

- Element *wse:Identifier* of type *xs:anyURI*.

Contains the identifier of an active subscription. You can use the element *wse:SubscriptionManager/wsa:ReferenceParameters/wse:Identifier* from the output of a *SubscribeOp* operation. (See "[SubscribeOp](#)" on page 42.)

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
```

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a *TimedOut* fault if it cannot respond in time.

### Output

The SOAP body is empty.

## **Fault**

If it cannot cancel the subscription, the service returns a fault according to the WS-Management standard.

## RenewOp

This operation renews a subscription before it expires.

### Input

#### SOAP Body

Element *wse:Renew* (of anonymous type), which contains the optional subelement *wse:Expires* of type *wse:ExpirationType*.

Contains either a duration that specifies how long the client requires the subscription, or a date and time at which the subscription should expire. If you omit this subelement, the service uses the value of the *SubscriptionExpiration* parameter on the management server. If you specify a duration that exceeds the value of the *SubscriptionExpirationMaximum* parameter, the service uses the value of *SubscriptionExpirationMaximum* instead. (See ["Service Configuration" on page 20.](#))

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.xmlsoap.org/ws/2004/08/eventing/Renew
```

- Element *wse:Identifier* of type *xs:anyURI*.

Contains the identifier of an active subscription. You can use the element *wse:SubscriptionManager/wsa:ReferenceParameters/wse:Identifier* from the output of a *SubscribeOp* operation. (See ["SubscribeOp" on page 42.](#))

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a *TimedOut* fault if it cannot respond in time.

## Output

The SOAP body contains an element *wse:RenewResponse* (of anonymous type), which contains the subelement *wse:Expires* of type *wse:ExpirationType*.

*wse:Expires* contains the new date and time at which the subscription expires.

## Fault

If it cannot renew the subscription, the service returns a fault according to the WS-Management standard.

## OwnMany

This operation sets the value of the *ismWorkItem:AssignedOperator/ismWorkItem:PersonAttributes/Name* element for one or more incidents. The incidents are identified by incident IDs. The operation sets value of the *Name* element to the user name of the currently authenticated HPOM user. ("[User Authentication](#)" on [page 93](#).)

## Input

### SOAP Body

Element *incExt:IncidentIDs* of type *incExt:IncidentIDs*, which contains any number of *incExt:id* elements of type *xs:string*.

Each *incExt:id* contains the ID of an incident to own.

### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/  
opr/ws/ServiceOperation/IncidentManagement/1/Incident/OwnMany
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## Output

The SOAP body is empty.

## Fault

If it cannot own the incidents, the service returns a fault according to the WS-Management standard.

## DisownMany

This operation clears the value of the *ismWorkItem:AssignedOperator/ismWorkItem:PersonAttributes/Name* element for one or more incidents. The incidents are identified by incident IDs.

### Input

#### SOAP Body

Element *incExt:IncidentIDs* of type *incExt:IncidentIDs*, which contains any number of *incExt:id* elements of type *xs:string*.

Each *incExt:id* contains the ID of an incident to disown.

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/  
opr/ws/ServiceOperation/IncidentManagement/1/Incident/DisownMany
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Optional element *OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a *TimedOut* fault if it cannot respond in time.

### Output

The SOAP body is empty.

## **Fault**

If it cannot disown the incidents, the service returns a fault according to the WS-Management standard.

## GetAnnotations

This operation returns the annotations for one incident, which is identified by the incident ID.

### Input

#### SOAP Body

Empty.

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/  
opr/ws/ServiceOperation/IncidentManagement/1/Incident/GetAnnotations
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndPointReferenceType*. (See ["Endpoint References" on page 16.](#))

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value IncidentID.
- *wsman:Selector* must contain the ID of the incident instance to get annotations for.

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## Output

The SOAP body contains an element *incExt:Annotations* of type *incExt:Annotations*, which contains any number of *incExt:Annotation* elements of type *incExt:Annotation*.

Each *incExt:Annotation* contains the following subelements:

- Optional element *incExt:Author* of type *xs:string*.
- Element *incExt:Text* of type *xs:string*.
- Optional element *incExt:Date* of type *xs:dateTime*.
- Optional element *incExt:ID* of type *xs:string*.

## Fault

If it cannot return the annotations, the service returns a fault according to the WS-Management standard.

## AddAnnotation

This operation stores a new annotation to an existing **message** incident. The incident is identified by incident ID.

### Input

#### SOAP Body

Element *incExt:AnnotationText* of type *xs:string*, which contains<sup>1</sup> the text of the annotation to add. (HPOM sets the annotation's *incExt:ID*, *incExt:Date*, and *incExt:Author* automatically.)

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/  
opr/ws/ServiceOperation/IncidentManagement/1/Incident/AddAnnotation
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndPointReferenceType*. (See ["Endpoint References" on page 16.](#))

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value IncidentID.
  - *wsman:Selector* must contain the ID of the incident instance to add the annotation to.
- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

<sup>1</sup>this is a test

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## Output

The SOAP body contains element *incExt:AnnotationId* of type *xs:string*. This is the ID that HPOM generates for the annotation.

## Fault

If it cannot add the annotation, the service returns a fault according to the WS-Management standard.

## UpdateAnnotation

This operation updates an annotation to an existing incident. The annotation to update is identified by annotation ID. The existing incident is identified by incident ID.

### Input

#### SOAP Body

Element *incExt:UpdateAnnotation* of type *incExt:UpdateAnnotation*, which contains the following subelements:

- Element *incExt:AnnotationId* of type *xs:string*.  
Contains the ID of the annotation to update.
- Element *incExt:AnnotationText* of type *xs:string*.  
Contains the updated text for the annotation.

(HPOM updates the annotation's *incExt:Date* and *incExt:Author* automatically.)

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/opr/ws/ServiceOperation/  
IncidentManagement/1/Incident/UpdateAnnotation
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndPointReferenceType*. (See ["Endpoint References" on page 16.](#))

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value IncidentID.
- *wsman:Selector* must contain the ID of the incident instance that contains the annotation.
- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## Output

The SOAP body is empty.

## Fault

If it cannot update the annotation, the service returns a fault according to the WS-Management standard.

## DeleteAnnotation

This operation deletes an annotation from an existing incident. The annotation to delete is identified by annotation ID. The existing incident is identified by incident ID.

### Input

#### SOAP Body

Element *incExt:AnnotationId* of type *xs:string*, which contains the ID of the annotation to delete.

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/opr/ws/ServiceOperation/  
IncidentManagement/1/Incident/DeleteAnnotation
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*  
Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndPointReferenceType*. (See ["Endpoint References" on page 16.](#))

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value IncidentID.
- *wsman:Selector* must contain the ID of the incident instance that contains the annotation to delete.
- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## **Output**

The SOAP body is empty.

## **Fault**

If it cannot delete the annotation, the service returns a fault according to the WS-Management standard.

## SetCustomAttribute

This operation creates or updates a custom attribute for an existing incident. The existing incident is identified by incident ID.

### Input

#### SOAP Body

Element *incExt:CustomAttribute* of type *incExt:CustomAttribute*, which contains the following subelements:

- Element *incExt:Key* of type *xs:string*.

Contains the key for the custom attribute. If a custom attribute with this key exists, the operation updates the existing a custom attribute. If a custom attribute with the specified key does not exist, the operation stores an new custom attribute.

- Element *incExt:Text* of type *xs:string*.

Contains the value of the custom attribute.

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/opr/ws/ServiceOperation/  
IncidentManagement/1/Incident/SetCustomAttribute
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndpointReferenceType*. (See ["Endpoint References" on page 16.](#))

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value IncidentID.
- *wsman:Selector* must contain the ID of the incident instance that contains the custom attribute.
- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## Output

The SOAP body is empty.

## Fault

If it cannot create or update the custom attribute, the service returns a fault according to the WS-Management standard.

## DeleteCustomAttribute

This operation deletes a custom attribute from an existing incident. The existing incident is identified by incident ID.

### Input

#### SOAP Body

Element *incExt:CustomAttributeKey* of type *xs:string*, which contains the key of the custom attribute to delete.

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/opr/ws/ServiceOperation/  
IncidentManagement/1/Incident/DeleteCustomAttribute
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndPointReferenceType*. (See ["Endpoint References" on page 16.](#))

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value IncidentID.
  - *wsman:Selector* must contain the ID of the incident instance that contains the custom attribute to delete.
- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## **Output**

The SOAP body is empty.

## **Fault**

If it cannot delete the custom attribute, the service returns a fault according to the WS-Management standard.

## CloseMany

This operation sets the lifecycle state of multiple existing incidents to closed. The incidents are identified by incident IDs.

### Input

#### SOAP Body

Element *incExt:IncidentIDs* of type *incExt:IncidentIDs*, which contains any number of *incExt:id* elements of type *xs:string*.

Each *incExt:id* contains the ID of an incident to close.

#### SOAP Header

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a *TimedOut* fault if it cannot respond in time.

### Output

The SOAP body is empty.

### Fault

If it cannot close the incidents, the service returns a fault according to the WS-Management standard.

## ReopenMany

This operation sets the lifecycle state of multiple closed incidents to open. The incidents are identified by incident IDs.

### Input

#### SOAP Body

Element *incExt:IncidentIDs* of type *incExt:IncidentIDs*, which contains any number of *incExt:id* elements of type *xs:string*.

Each *incExt:id* contains the ID of an incident to close.

#### SOAP Header

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a *TimedOut* fault if it cannot respond in time.

### Output

The SOAP body is empty.

### Fault

If it cannot reopen the incidents, the service returns a fault according to the WS-Management standard. If any incident is already open, the service returns a fault and stops processing the list of incidents. The service does not roll back changes to incidents that it completed successfully before the fault occurred.

## StartAction

This operation starts the automatic or operator-initiated action of an existing incident. The incident is identified by the incident ID.

### Input

#### SOAP Body

Element *incExt:ActionType* of type *xs:string*. This can be one of the following strings:

- AutomaticAction
- OperatorAction

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/opr/ws/ServiceOperation/  
IncidentManagement/1/Incident/StartAction
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndPointReferenceType*. (See ["Endpoint References" on page 16.](#))

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

*wsman:Selector* attribute Name must have the value IncidentID.

*wsman:Selector* must contain the ID of the incident instance to get.

- Optional element *wsmam:OperationTimeout* of type *wsmam:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## Output

The SOAP body is empty.

## Fault

If it cannot start the action, the service returns a fault according to the WS-Management standard.

## StopAction

This operation stops the automatic or operator-initiated action of an existing incident. The incident is identified by the incident ID.

### Input

#### SOAP Body

Element *incExt:ActionType* of type *xs:string*. This can be one of the following strings:

- AutomaticAction
- OperatorAction

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/  
opr/ws/ServiceOperation/IncidentManagement/1/Incident/StopAction
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndPointReferenceType*. (See "[Endpoint References](#)" on page 16.)

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

*wsman:Selector* attribute Name must have the value IncidentID.

*wsman:Selector* must contain the ID of the incident instance to get.

- Optional element *wsmam:OperationTimeout* of type *wsmam:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## Output

The SOAP body is empty.

## Fault

If it cannot stop the action, the service returns a fault according to the WS-Management standard.

## GetInstructionText

This operation returns the instruction text for one incident, which is identified by the incident ID.  
(Added in version 9.10)

### Input

#### SOAP Body

Empty.

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.hp.com/opr/ws/ServiceOperation/  
IncidentManagement/1/Incident/GetInstructionText
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
ism/ServiceOperation/IncidentManagement/1/Incident
```

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the incident instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndPointReferenceType*. (See ["Endpoint References" on page 16.](#))

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value IncidentID.
  - *wsman:Selector* must contain the ID of the incident instance to get annotations for.
- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## Output

The SOAP body contains an element *incExt:InstructionText* of type *xs:string*, which contains the instruction text.

## Fault

If it cannot return the instruction text, the service returns a fault according to the WS-Management standard.

## Chapter 4: Tool Operations Reference

The HPOM Tool Web Service provides a Web Services Definition Language (WSDL) document, which describes the service. After you install the service, the WSDL is available from the following location on the HPOM management server:

**`https://<server_name>:<port>/opr-toolwebservice/ToolWebService.svc?wsdl`**

This WSDL document refers to the other WSDL documents and associated XML Schema Documents (XSDs), and gives their location on the management server. These documents provide complete information about the operations that the service supports. The details of how your client uses these operations depend on the web service client development toolkit that you choose.

You can develop a client using any suitable toolkit or programming language. For example, you can develop your client with one of the following web service client development toolkits:

- Apache Axis2
- Windows Communication Foundation
- Wiseman

This chapter provides a generic reference to the operations that the service provides. ["Prefixes and XML Namespaces Used in this Document" on page 15](#) lists the prefixes used in this section to show the namespace of each element type.

## Create

This operation requests the management server to execute a specified command on a specified node. Consider using the following procedure to manage tool executions:

1. Use the `SubscribeOp` operation to get an enumeration context.
2. Create a tool execution.
3. Start a `PullOp` operation. As soon as the event queue contains events, `PullOp` returns a batch of updated tool executions. The updated tool executions contain the current `tool:LifecycleState`. When `tool:LifecycleState` is finished, the service inserts the results into `tool:Output`, `tool:ResultCode`, and `tool:FinishTime`.

If the event queue remains empty for the specified `OperationTimeout`, `PullOp` returns a `TimedOut` fault.

4. Immediately after the `PullOp` returns updated tool executions or a fault, start another `PullOp` operation.

## Input

### SOAP Body

Element `tool:ToolExecution` of type `tool:ToolExecution`. `tool:ToolExecution` must contain the following subelements:

- `tool:Command` of type `xs:string`.  
Contains a string that specifies the tool to execute. The command can be either of the following:
  - the unique ID of an existing tool on the management server
  - an executable with all parameters
  - a script

The command must be in the format that the agent expects. The service does no parameter replacement or other modification on this string.

- `tool:CommandType` of type `tool:CommandType_OpenType`  
Contains a string that specifies the type of command. This string can be any value, including the following strings:
  - `server-defined`  
To use this command type, `tool:Command` must contain the unique ID of a tool.
  - `executable`

- vbscript
- jscript
- perl
- wshost
- *tool:Node/ismNode:DnsName*  
Contains a string that specifies the fully qualified domain name of the node on which to execute the command. The node must exist on the HPOM management server.

*tool:ToolExecution* can contain any of the following subelements:

- *tool:AdditionalParameters*  
  
Contains a string that specifies parameters for an existing tool on the management server. The *tool:CommandType* must be *server-defined*, and the existing tool must allow operators to change parameters.
- *tool:ReplacementVariables* of type *tool:ReplacementVariables*  
  
Contains any number of subelements of type *tool:ReplacementVariable*. Each *tool:ReplacementVariable* contains a name-value pair, which the service uses to replace an environment variable in the command of an existing tool on the management server. The *tool:CommandType* must be *server-defined*. When you launch a tool from the HPOM user interface, the management server automatically replaces the environment variables with values. When you execute a tool using the tool with the tool web service, you have to specify the values.
- *tool:User* of type *xs:string*  
  
Contains a string that specifies the name of the user to execute the command on the node. *tool:User* can contain the name of a real user or the string *\$AGENT\_USER*. The behavior is the same as when you execute a tool from within the HPOM user interface.
- *tool:Password* of type *xs:string*  
  
Contains the password of the specified *tool:User*. If you specify *tool:User* without *tool:Password*, the agent attempts to switch to the specified user without the password. After the service starts the tool execution, the service replaces the password with asterisks (\*).
- *tool:Context* of type *xs:string*  
  
Contains any string that you want to store with the tool execution. The tool web service does not use this string.
- *tool:SessionId* of type *xs:string*

Contains any string that you want to store with the tool execution. The tool web service does not use this string.

- *tool:Display* of type *xs:string*

Contains a display environment variable, which the agent sets before it starts the tool. You can use this to redirect the display for X programs on nodes with a UNIX or Linux operating system.

*tool:ToolExecution* can also contain other valid subelements, although this operation ignores them.

## SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

`http://schemas.xmlsoap.org/ws/2004/09/transfer/Create`

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

`http://schemas.hp.com/  
opr/ws/ServiceOperation/ToolManagement/1/ToolExecution`

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a `TimedOut` fault if it cannot respond in time.

## Output

The SOAP body contains an element *wsa:EndpointReference* of type *wsa:EndpointReferenceType*. This element contains the subelements *wsman:ResourceURI* and *wsman:SelectorSet*, which you can use to uniquely identify the tool execution in subsequent operations.

## Fault

If the service cannot execute the tool, it returns a fault according to the WS-Management standard.

## Delete

This operation deletes an existing tool execution, which is identified by the tool execution ID. The management server sends a request to the agent to stop the tool.

## Input

### SOAP Body

Empty.

### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

`http://schemas.xmlsoap.org/ws/2004/09/transfer/Delete`

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

`http://schemas.hp.com/  
opr/ws/ServiceOperation/ToolManagement/1/ToolExecution`

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the tool execution instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndPointReferenceType*. (See "[Endpoint References](#)" on page 16.)

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute Name must have the value ID .
- *wsman:Selector* must contain the ID of the tool execution to delete.

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## **Output**

The SOAP body is empty.

## **Fault**

If the service cannot stop the tool execution, it returns a fault according to the WS-Management standard.

## EnumerateOp

This operation returns an enumeration context, which you can then use with the PullOp operation to get batches of tool executions from the service. You can specify a filter, so that the enumeration context contains only specific tool executions.

### Input

#### SOAP Body

Element *Enumerate* of type *wsen:Enumerate*. This element can contain the following subelements:

- Optional element *wsen:Expires* of type *wsen:ExpirationType*.

Contains a duration, for which the client requires the enumeration context. If you omit this subelement, the service uses the value of the EnumerationExpiration parameter on the management server. If you specify a duration that exceeds the value of the EnumerationExpirationMaximum parameter, the service uses the value of EnumerationExpirationMaximum instead. (See "[Service Configuration](#)" on page 20.)

- Optional element *wsen:Filter* of type *wsen:FilterType* or *wsman:Filter* of type *wsman:dialectableMixedDataType*. For compatibility with different toolkits, the service supports a filter of either type, but you must specify only one of them.

*Filter* attribute *Dialect* must have the following value:

```
http://schemas.hp.com/  
opr/ws/ServiceOperation/ToolManagement/1/ToolExecutionFilter
```

*Filter* must contain the subelement *toolFil:ToolExecutionEnumerationFilter* of type *toolFil:ToolExecutionEnumerationFilter*. *ToolExecutionEnumerationFilter* can contain any of the following subelements:

- Optional element *tool:ID* of type *xs:string*
- Optional element *tool:SessionId* of type *xs:string*

The service enumerates tool executions that match the contents of the *toolFil:ToolExecutionEnumerationFilter* subelements that you specify.

If you omit *Filter*, the service enumerates all tool executions.

## SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

`http://schemas.xmlsoap.org/ws/2004/09/enumeration/Enumerate`

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

`http://schemas.hp.com/  
opr/ws/ServiceOperation/ToolManagement/1/ToolExecution`

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a `TimedOut` fault if it cannot respond in time.

## Output

The SOAP body contains an element *wsen:EnumerateResponse* (of anonymous type), which contains the following subelements:

- Element *wsen:Expires* of type *wsen:ExpirationType*.

Contains a duration, for which the enumeration context is valid. You can use the `ReleaseOp` operation to cancel the enumeration context early. (See "[ReleaseOp](#)" on page 91.)

- Element *wsen:EnumerationContext* of type *wsen:EnumerationContextType*.

Contains a string that identifies the enumeration context. Use *wsen:EnumerationContext* with the `PullOp` operation to get batches of tool executions from the service. (See "[PullOp](#)" on page 89.)

## Fault

If it cannot return the enumeration context, the service returns a fault according to the WS-Management standard.

## Get

This operation returns one tool execution, which is identified by the tool execution ID.

## Input

### SOAP Body

Empty.

### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

`http://schemas.xmlsoap.org/ws/2004/09/transfer/Get`

- Element *wsman:SelectorSet* of type *wsman:SelectorSetType*

Contains one element of type *wsman:SelectorType*, which identifies the tool execution instance. You can use the element *wsa:ReferenceParameters/wsman:SelectorSet* from an element of type *wsa:EndpointReferenceType*. (See ["Endpoint References" on page 16.](#))

Alternatively, create a *wsman:SelectorSet* that contains one *wsman:Selector* element of type *wsman:SelectorType*:

- *wsman:Selector* attribute *Name* must have the value `ID` .
- *wsman:Selector* must contain the ID of the tool execution to get.
- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a `TimedOut` fault if it cannot respond in time.

## Output

The SOAP body contains an element *tool:ToolExecution* of type *tool:ToolExecution*.

## Fault

If it cannot return the tool execution, the service returns a fault according to the WS-Management standard.

## SubscribeOp

This operation returns an enumeration context, which you can then use with the PullOp operation to get batches of updated tool executions from the service.

### Input

#### SOAP Body

Element *wse:Subscribe* of type *wse:SubscribeType*, which contains the following subelements:

- Element *wse:Delivery* of type *wse:DeliveryType*. *wse:Delivery* attribute *Mode* must have the following value:

`http://schemas.dmtf.org/wbem/wsman/1/wsman/Pull`

- Optional element *wse:Expires* of type *wse:ExpirationType*. Contains either a duration that specifies how long the client requires the subscription, or a date and time at which the subscription should expire. If you omit this subelement, the service uses the value of the *SubscriptionExpiration* parameter on the management server. If you specify a duration that exceeds the value of the *SubscriptionExpirationMaximum* parameter, the service uses the value of *SubscriptionExpirationMaximum* instead. (See "[Service Configuration](#)" on [page 20](#).)
- Optional element *wsen:Filter* of type *wsen:FilterType* or *wsman:Filter* of type *wsman:dialectableMixedDataType*. For compatibility with different toolkits, the service supports a filter of either type, but you must specify only one of them.

*Filter* attribute *Dialect* must have the following value:

`http://schemas.hp.com/opr/ws/ServiceOperation/ToolManagement/1/ToolExecutionFilter`

*Filter* must contain the subelement *toolFil:ToolExecutionEventingFilter* of type *toolFil:ToolExecutionEventingFilter*. *ToolExecutionEventingFilter* can contain any of the following subelements:

- Optional element *tool:ID* of type *xs:string*
- Optional element *tool:SessionId* of type *xs:string*

The service enumerates tool executions that match the contents of the *toolFil:ToolExecutionEventingFilter* subelements that you specify.

If you omit *Filter*, the service enumerates all tool executions.

## SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

`http://schemas.xmlsoap.org/ws/2004/08/eventing/Subscribe`

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

`http://schemas.hp.com/  
opr/ws/ServiceOperation/ToolManagement/1/ToolExecution`

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a `TimedOut` fault if it cannot respond in time.

## Output

The SOAP body contains an element *wse:SubscribeResponse* (of anonymous type), which contains the following subelements:

- Element *wse:SubscriptionManager* of type *wsa:EndpointReferenceType*.

Contains the subelement *wsa:ReferenceParameters/wse:Identifier* of type *wse:Identifier*, which you use to identify the subscription if you unsubscribe or renew it. (See "[UnsubscribeOp](#)" on page 87 and "[RenewOp](#)" on page 85.)

- Element *wse:Expires* of type *wse:ExpirationType*.

Contains a duration, for which the service maintains the subscription. You can use the `RenewOp` operation to renew the subscription before it expires. (See "[RenewOp](#)" on page 85.)

- Element *wsen:EnumerationContext* of type *wsen:EnumerationContextType*.

Contains a string that identifies the enumeration context. Use *EnumerationContext* with the `PullOp` operation to get batches of updated tool executions from the service. (See "[PullOp](#)" on page 89.)

## Fault

If it cannot return the enumeration context, the service returns a fault according to the WS-Management standard.

## RenewOp

This operation renews a subscription before it expires.

### Input

#### SOAP Body

Element *wse:Renew* (of anonymous type), which contains the optional subelement *wse:Expires* of type *wse:ExpirationType*.

Contains either a duration that specifies how long the client requires the subscription, or a date and time at which the subscription should expire. If you omit this subelement, the service uses the value of the *SubscriptionExpiration* parameter on the management server. If you specify a duration that exceeds the value of the *SubscriptionExpirationMaximum* parameter, the service uses the value of *SubscriptionExpirationMaximum* instead. (See "[Service Configuration](#)" on page 20.)

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.xmlsoap.org/ws/2004/08/eventing/Renew
```

- Element *wse:Identifier* of type *xs:anyURI*.

Contains the identifier of an active subscription. You can use the element *wse:SubscriptionManager/wsa:ReferenceParameters/wse:Identifier* from the output of a *SubscribeOp* operation. (See "[SubscribeOp](#)" on page 82.)

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
opr/ws/ServiceOperation/ToolManagement/1/ToolExecution
```

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a *TimedOut* fault if it cannot respond in time.

## Output

The SOAP body contains an element *wse:RenewResponse* (of anonymous type), which contains the subelement *wse:Expires* of type *wse:ExpirationType*.

*wse:Expires* contains the new date and time at which the subscription expires.

## Fault

If the service cannot renew the subscription, the service returns a fault according to the WS-Management standard.

## UnsubscribeOp

This operation cancels a subscription before the subscription expires.

### Input

#### SOAP Body

Element *wse:Unsubscribe* of type *wse:UnsubscribeType*. This element is required, but should be empty.

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

`http://schemas.xmlsoap.org/ws/2004/08/eventing/Unsubscribe`

- Element *wse:Identifier* of type *xs:anyURI*.

Contains the identifier of an active subscription. You can use the element *wse:SubscriptionManager/wsa:ReferenceParameters/wse:Identifier* from the output of a *SubscribeOp* operation. (See "[SubscribeOp](#)" on page 82.)

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

`http://schemas.hp.com/  
opr/ws/ServiceOperation/ToolManagement/1/ToolExecution`

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a *TimedOut* fault if it cannot respond in time.

### Output

The SOAP body is empty.

## **Fault**

If it cannot cancel the subscription, the service returns a fault according to the WS-Management standard.

## PullOp

This operation returns a batch of tool executions from an enumeration context.

### Input

#### SOAP Body

Element *wsen:Pull* (of anonymous type), which contains the following subelements:

- Element *wsen:EnumerationContext* of type *wsen:EnumerationContextType*.  
Contains a string that identifies the enumeration context. Use a *wsen:EnumerationContext* that one of the following operations returns:
  - EnumerateOp (see "[EnumerateOp](#)" on page 79)
  - SubscribeOp (see "[SubscribeOp](#)" on page 82)
  - PullOp (see below)
- Optional element *wsen:MaxElements* of type *xs:positiveInteger*.

Contains an integer that indicates the maximum number of tool executions to return in this batch. If you omit this subelement, the service uses the value of the *MaxItems* parameter on the management server. (See "[Service Configuration](#)" on page 20.)

The HPOM Tool Web Service does not support the subelements *wsen:MaxTime* or *wsen:MaxCharacters*. You should omit these subelements.

#### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.xmlsoap.org/ws/2004/09/enumeration/Pull
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
opr/ws/ServiceOperation/ToolManagement/1/ToolExecution
```

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a `TimedOut` fault if it cannot respond in time.

For enumeration contexts from the `SubscribeOp` operation, if the event queue remains empty for the specified `OperationTimeout`, `PullOp` returns a `TimedOut` fault.

## Output

The SOAP body contains an element `wsen:PullResponse` (of anonymous type), which contains the following subelements:

- Element `wsen:EnumerationContext` of type `wsen:EnumerationContextType`.  
Contains a string that identifies the enumeration context. This is the same as the input `wsen:EnumerationContext`.
- Element `wsen:Items` of the type `wsen:ItemListType`.  
Contains one or more `tool:ToolExecution` elements of type `tool:ToolExecution`.
- Optional element `wsen:EndOfSequence` of type `wsen:attributableEmpty`.  
This element is empty. If `wsen:EndOfSequence` is present, there are no remaining items to pull for this enumeration context and the enumeration context is no longer valid.

## Fault

If the service cannot return the batch of tool executions, the service returns a fault according to the WS-Management standard.

## ReleaseOp

This operation cancels an existing enumeration context early (that is, before the client has pulled all the tool executions, and before the enumeration context has expired).

You can use this operation to cancel an enumeration context from an enumerate operation. To cancel an enumeration context from a subscription operation, unsubscribe instead. (See ["UnsubscribeOp" on page 87.](#))

## Input

### SOAP Body

Element *wsen:Release* (of anonymous type), which contains the subelement *wsen:EnumerationContext* of type *wsen:EnumerationContextType*.

*wsen:EnumerationContext* contains a string that identifies the enumeration context. Use a *wsen:EnumerationContext* that one of the following operations returns:

- EnumerateOp (see ["EnumerateOp" on page 79](#))
- PullOp (see ["PullOp" on page 89](#))

### SOAP Header

- Element *wsa:Action* of type *wsa:ActionType* that contains the following string:

```
http://schemas.xmlsoap.org/ws/2004/09/enumeration/Release
```

- Element *wsman:ResourceURI* of type *wsman:AttributableURI*

Contains a string that identifies the resource type. You can use the element *wsa:ReferenceParameters/wsman:ResourceURI* from an element of type *wsa:EndPointReferenceType*.

Alternatively, create a *wsman:ResourceURI* element that contains the following string:

```
http://schemas.hp.com/  
opr/ws/ServiceOperation/ToolManagement/1/ToolExecution
```

- Optional element *wsman:OperationTimeout* of type *wsman:AttributableDuration*

Contains a maximum duration within which you expect the service to respond. On an HPOM on UNIX or HPOM on Linux management server, the service returns a TimedOut fault if it cannot respond in time.

## **Output**

The SOAP body is empty.

## **Fault**

If it cannot release the enumeration context, the service returns a fault according to the WS-Management standard.

## Chapter 5: Security for Web Service Clients

When the client that you develop connects to an HPOM Web Service, it must use HTTP basic authentication to specify the username and password of a valid HPOM user. To ensure that malicious users cannot intercept these credentials and other communications, HP recommends that you use HTTPS connections.

The following topics provide more details:

- ["User Authentication" below](#)
- ["Secure HTTP Connections" on the next page](#)

### User Authentication

A client must connect to an HPOM Web Service using HTTP basic authentication. Use your normal client development toolkit to specify a username and password in the client's HTTP requests.

The username and password that you specify must be those of a valid HPOM user. The user must have appropriate rights to perform the operations that the client attempts.

On HPOM for UNIX and HPOM on Linux, if the user that you specify is an operator, the client has the same permissions as the operator would have in the HPOM console. For example, the Incident Web Service EnumerateOp returns only incidents that the operator would see as messages in the console.

In contrast, on HPOM for Windows, the client may have more permissions than the operator would have in the HPOM console. In particular, any restrictions from user roles do not apply. For example, the Incident Web Service can enumerate all messages, and change messages that are not already owned by another user.

## Secure HTTP Connections

HP recommends that you connect to the HPOM Web Services using HTTPS connections, which require a suitable certificate on the server. The management server installation creates a self-signed certificate for HTTPS communication, but you can replace this with a different certificate if necessary. The port that the service uses for HTTPS communication depends on the configuration of the HPOM management server.

The default HTTPS port number on HPOM on UNIX or HPOM on Linux is 8444 .

For further security, HP recommends that you verify the hostname and certificate for each HTTPS connection. To verify the certificate for an HTTPS connection, the client system must trust the server's certificate. You may need to export the server's certificate and import it to the client system.

You can export the server's certificate from your management server as follows:

1. Open a shell and navigate to the directory that contains the keystore file:

```
cd /var/opt/OV/certificates/tomcat/b
```

2. Export the certificate using the following command:

```
/opt/OV/nonOV/jre/b/bin/keytool -keystore tomcat.keystore \  
-export -alias ovtomcatb -file /tmp/server.cer
```

After you export the server's certificate from the management server, you must import it using the appropriate tools for your client environment. You can then program your client to verify HTTPS connections using the methods that your client development toolkit provides.

# Chapter 6: Basic Troubleshooting

If you experience problems with the HPOM Web Services, check that your client can connect to the service over the network, and that the service is available.

The following topics provide more details:

- ["Troubleshoot Connectivity" below](#)
- ["Troubleshoot the Incident Web Service" below](#)
- ["Troubleshoot on HPOM on UNIX or HPOM on Linux " on page 98](#)

## Troubleshoot Connectivity

- Check the network connectivity from your client system to the HPOM management server. For example:
  - Use nslookup to check that the client system can resolve the management server's hostname.
  - Use ping to check that the client system can reach the management server.
- Check the connectivity from your client system to the HPOM Web Service.

Open a web browser and navigate to the following locations on the HPOM management server:

- `https://<server_name>:<port>/opr-webservice/Incident.svc?wsdl`
- `https://<server_name>:<port>/opr-toolwebservice/ToolWebService.svc?wsdl`

The port that the service is available on depends on the configuration of the HPOM management server. The service listens for HTTPS connections on port 8444 by default. On HPOM for UNIX or Linux management servers, the service also listens for insecure HTTP connections on port 8081.

You may need to accept a certificate and provide credentials for the HPOM management server. If your browser cannot open the WSDL document, check that the service is installed and running. (See ["Troubleshoot on HPOM on UNIX or HPOM on Linux " on page 98.](#))

## Troubleshoot the Incident Web Service

You can use the `runclient` demo client to test and troubleshoot the Incident Web Service.

The following example demonstrates how to generate incidents with a message key. You then create an enumeration context with a filter on the message key. The context enables you to get all incidents with that context from the Incident Web Service.

For more information about runclient, see ["Sample and Demo Clients" on page 8](#).

1. Create a script that generates sample incidents with a message key.

In a text editor, create the script `incident_create.inc` and add the following lines:

```
/opt/OV/support/OprWsInc/client/java/runclient.sh \  
-host $(hostname) -port $(ovconfget NONOV.TomcatB HTTPSPort) \  
-user opc_adm -password opc_adm -ssl -action create \  
-title "test_message" -emittingnode $(hostname) -severity Minor \  
-category "HP_RST" -customattribute "HP_Incident_Key_text \  
INCIDENT.KEY" -correlationkey "MESSAGEKEY"
```

Run the script three times to generate three incidents. The script returns three incident IDs, for example:

```
<ID>303cc68e-63e8-71e1-0e1c-1019f89b0000</ID>  
<ID>33cfa758-63e8-71e1-0e1c-1019f89b0000</ID>  
<ID>3621b1e0-63e8-71e1-0e1c-1019f89b0000</ID>
```

2. Run the runclient tool with the `enumerate` parameter to create an enumeration context with a filter on MESSAGEKEY:

```
/opt/OV/support/OprWsInc/client/java/runclient.sh \  
-host host.example.com -port 8444 -user opc_adm \  
-password opc_adm -ssl -action enumerate -filter \  
-correlationkey MESSAGEKEY
```

The tool returns the context ID, for example:

```
<Context>977fdab6-458c-412e-8fb6-e1145270f29d</Context>
```

3. You can now use the context ID to pull the incidents from the Incident Web Service:

```
/opt/OV/support/OprWsInc/client/java/runclient.sh \  
-host host.example.com -port 8444 \  
-user opc_adm -password opc_adm -ssl -action pull \  
-context 977fdab6-458c-412e-8fb6-e1145270f29d
```

The tool returns three incidents. The following example output shows only one of these incidents:

```
<Incident>  
  <IncidentID>303cc68e-63e8-71e1-0e1c-1019f89b0000</IncidentID>  
  <Description>>null</Description>  
  <Title>test_message</Title>  
  <LifecycleState>open</LifecycleState>  
  <Severity>Minor</Severity>  
  <Solution>>null</Solution>  
  <Category>HP_RST</Category>  
  <SubCategory>>null</SubCategory>  
  <ProductType>>null</ProductType>  
  <ProblemType>>null</ProblemType>
```

```
<CollaborationMode>fyi</CollaborationMode>
<EmittingCI></EmittingCI>
<EmittingNode>host.example.com</EmittingNode>
<AssignedOperator></AssignedOperator>
<Type></Type>
<OperationsExtension>
  <Application></Application>
  <Object></Object>
  <StateChangeTime>1970-01-01T01:00:00.000+01:00</StateChangeTime>
  <CreationTime>2012-03-01T22:47:49.000+01:00</CreationTime>
  <ReceivedTime>2012-03-01T22:47:49.000+01:00</ReceivedTime>
  <NumberOfDuplicates>0</NumberOfDuplicates>
  <NumberOfAnnotations>0</NumberOfAnnotations>
  <CorrelationKey>MESSAGEKEY</CorrelationKey>
  <AcknowledgeCorrelationKey></AcknowledgeCorrelationKey>
  <ConditionMatched>false</ConditionMatched>
  <AutomaticActionStatus>NOT_AVAILABLE</AutomaticActionStatus>
  <OperatorActionStatus>NOT_AVAILABLE</OperatorActionStatus>
  <EscalationStatus>NOT_ESCALATED</EscalationStatus>
  <Source>IncidentWS</Source>
  <OriginalEvent></OriginalEvent>
  <CustomAttributes>
    <CustomAttribute>
      <Key>HP_Incident_Key_text</Key>
      <Text>INCIDENT.KEY</Text>
    </CustomAttribute>
  </CustomAttributes>
</OperationsExtension>
</Incident>
```

## Troubleshoot on HPOM on UNIX or HPOM on Linux

- The service runs within the Tomcat (B) servlet container. Check the status of the ovtomcatB component by typing the following command:

```
/opt/OV/bin/ovc -status ovtomcatB
```

If ovtomcatB is not running, type the following command to start it:

```
/opt/OV/bin/ovc -start ovtomcatB
```

You may also check the Tomcat (B) log file for errors and warnings:

```
/var/opt/OV/log/tomcat/ovtomcatb.out
```

- Check the installation of the HPOM Incident Web Service.

Open a shell prompt or file browser, and then navigate to the following directory:

```
/opt/OV/nonOV/tomcat/b/www/webapps
```

The directory should contain the files opr-webservice.war file and the subdirectory opr-webservice directory,

If any of the files or directories are missing, type the following command:

```
/opt/OV/bin/ovc -restart ovtomcatB
```

If the files or folders are still missing, reinstall the service.

- The HPOM Incident Web Service logs the following information in a log file:
  - Errors and warnings
  - Subscriptions and unsubscriptions (including the context ID and number of active subscriptions)

Check the following log file:

```
/var/opt/OV/log/om/incident_ws.*
```

## Appendix 7: SOAP Envelope Examples

The following examples show SOAP envelopes that the HPOM Incident Web Service receives and sends for various operations.

### Create Request SOAP Envelope Example

```
<env:Envelope xmlns:env="http://www.w3.org/2003/05/soap-envelope"
  xmlns:mdo="http://schemas.wiseman.dev.java.net/metadata/messagetypes"
  xmlns:mex="http://schemas.xmlsoap.org/ws/2004/09/mex"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:wse="http://schemas.xmlsoap.org/ws/2004/08/eventing"
  xmlns:wsen="http://schemas.xmlsoap.org/ws/2004/09/enumeration"
  xmlns:wsman="http://schemas.dmtf.org/wbem/wsman/1/wsman.xsd"
  xmlns:wsmeta="http://schemas.dmtf.org/wbem/wsman/1/wsman/version1.0.0.a/default-addressing-model.xsd"
  xmlns:wxf="http://schemas.xmlsoap.org/ws/2004/09/transfer" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <env:Header>
    <wsa:Action env:mustUnderstand="true">http://schemas.xmlsoap.org/ws/2004/09/transfer/Create</wsa:Action>
    <wsa:ReplyTo>
      <wsa:Address env:mustUnderstand="true">http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:
Address>
    </wsa:ReplyTo>
    <wsa:MessageID env:mustUnderstand="true">uuid:b2930379-bcef-4536-9f13-193f6f775da0</wsa:MessageID>
    <wsa:To env:mustUnderstand="true">http://manager1.example.com:8765/opr-webservice/Incident.svc</wsa:To>
```

```
<wsman:ResourceURI>http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident</wsman:ResourceURI>
<wsman:OperationTimeout>P0Y0M0DT0H10M0.000S</wsman:OperationTimeout>
</env:Header>
<env:Body>
  <ns10:Incident xmlns="http://www.w3.org/2003/05/soap-envelope"
    xmlns:ns10="http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident"
    xmlns:ns11="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem"
    xmlns:ns12="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node"
    xmlns:ns13="http://schemas.hp.com/ism/Common/1/Common"
    xmlns:ns14="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/Incident"
    xmlns:ns2="http://schemas.xmlsoap.org/ws/2004/08/addressing"
    xmlns:ns3="http://schemas.xmlsoap.org/ws/2004/08/eventing"
    xmlns:ns4="http://schemas.xmlsoap.org/ws/2004/09/enumeration"
    xmlns:ns5="http://schemas.xmlsoap.org/ws/2004/09/transfer"
    xmlns:ns6="http://schemas.dmtf.org/wbem/wsman/1/wsman.xsd"
    xmlns:ns7="http://schemas.xmlsoap.org/ws/2004/09/mex"
    xmlns:ns8="http://schemas.wiseman.dev.java.net/metadata/messagetypes"
    xmlns:ns9="http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem">
    <ns10:Title>test_incident</ns10:Title>
    <ns10:EmittingNode>
      <ns12:NodeProperties>
        <ns12:DnsName>node1.example.com</ns12:DnsName>
      </ns12:NodeProperties>
    </ns10:EmittingNode>
  </ns10:Incident>
</env:Body>
</env:Envelope>
```

```
</ns10:EmittingNode>
<ns10:Extensions>
  <ns14:OperationsExtension>
    <ns14:CustomAttributes></ns14:CustomAttributes>
  </ns14:OperationsExtension>
</ns10:Extensions>
</ns10:Incident>
</env:Body>
</env:Envelope>
```

## Create Response SOAP Envelope Example

```
<s:Envelope xmlns:a="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:s="http://www.w3.org/2003/05/soap-envelope">
  <s:Header>
    <a:Action s:mustUnderstand="1">http://schemas.xmlsoap.org/ws/2004/09/transfer/CreateResponse</a:Action>
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <ResourceCreated xmlns="http://schemas.xmlsoap.org/ws/2004/09/transfer">
      <a:Address>http://manager1.example.com:8765/opr-webservice/Incident.svc</a:Address>
      <a:ReferenceParameters>
        <SelectorSet xmlns="http://schemas.dmtf.org/wbem/wsman/1/wsman.xsd">
          <Selector Name="IncidentID">8f51350e-a81b-4488-a542-50b73f9703d6</Selector>
        </SelectorSet>
      </a:ReferenceParameters>
    </ResourceCreated>
  </s:Body>
</s:Envelope>
```

```
</SelectorSet>
  <ResourceURI xmlns="http://schemas.dmtf.org/wbem/wsman/1/wsman.xsd">
    http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
  </ResourceURI>
</a:ReferenceParameters>
</ResourceCreated>
</s:Body>
</s:Envelope>
```

## Close Request SOAP Envelope Example

```
<env:Envelope xmlns:env="http://www.w3.org/2003/05/soap-envelope"
  xmlns:mdo="http://schemas.wiseman.dev.java.net/metadata/messagetypes"
  xmlns:mex="http://schemas.xmlsoap.org/ws/2004/09/mex"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:wse="http://schemas.xmlsoap.org/ws/2004/08/eventing"
  xmlns:wsen="http://schemas.xmlsoap.org/ws/2004/09/enumeration"
  xmlns:wsman="http://schemas.dmtf.org/wbem/wsman/1/wsman.xsd"
  xmlns:wsmeta="http://schemas.dmtf.org/wbem/wsman/1/wsman/version1.0.0.a/default-addressing-model.xsd"
  xmlns:wxf="http://schemas.xmlsoap.org/ws/2004/09/transfer" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <env:Header>
    <wsa:Action env:mustUnderstand="true">http://schemas.hp.com/ism/ServiceOperation/Common/1/Close</wsa:Action>
    <wsa:ReplyTo>
```

```
<wsa:Address env:mustUnderstand="true">http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:
Address>
</wsa:ReplyTo>
<wsa:MessageID env:mustUnderstand="true">uuid:35016ff8-cb3a-488c-9fdb-fa0a48050a71</wsa:MessageID>
<wsa:To env:mustUnderstand="true">http://manager1.example.com:8765/opr-webservice/Incident.svc</wsa:To>
<wsman:ResourceURI>http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident</wsman:ResourceURI>
<wsman:OperationTimeout>P0Y0M0DT0H10M0.000S</wsman:OperationTimeout>
<wsman:SelectorSet>
  <wsman:Selector Name="IncidentID">8f51350e-a81b-4488-a542-50b73f9703d6</wsman:Selector>
</wsman:SelectorSet>
</env:Header>
<env:Body></env:Body>
</env:Envelope>
```

## Close Response SOAP Envelope Example

```
<s:Envelope xmlns:a="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:s="http://www.w3.org/2003/05/soap-envelope">
  <s:Header>
    <a:Action s:mustUnderstand="1">http://schemas.hp.com/ism/ServiceOperation/Common/1/CloseResponse</a:Action>
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema"></s:B
ody>
</s:Envelope>
```

## Enumerate Request SOAP Envelope Example

```
<env:Envelope xmlns:env="http://www.w3.org/2003/05/soap-envelope"
  xmlns:mdo="http://schemas.wiseman.dev.java.net/metadata/messagetypes"
  xmlns:mex="http://schemas.xmlsoap.org/ws/2004/09/mex"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:wse="http://schemas.xmlsoap.org/ws/2004/08/eventing"
  xmlns:wsen="http://schemas.xmlsoap.org/ws/2004/09/enumeration"
  xmlns:wsman="http://schemas.dmtf.org/wbem/wsman/1/wsman.xsd"
  xmlns:wsmeta="http://schemas.dmtf.org/wbem/wsman/1/wsman/version1.0.0.a/default-addressing-model.xsd"
  xmlns:wxf="http://schemas.xmlsoap.org/ws/2004/09/transfer" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <env:Header>
    <wsa:Action xmlns:ns11="http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem"
      xmlns:ns12="http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident"
      xmlns:ns13="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem"
      xmlns:ns14="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node"
      xmlns:ns15="http://schemas.hp.com/ism/Common/1/Common"
      xmlns:ns16="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/IncidentFilter"
      env:mustUnderstand="true">
      http://schemas.xmlsoap.org/ws/2004/09/enumeration/Enumerate
    </wsa:Action>
    <wsa:ReplyTo xmlns:ns11="http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem"
      xmlns:ns12="http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident"
```

```
xmlns:ns13="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem"
xmlns:ns14="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node"
xmlns:ns15="http://schemas.hp.com/ism/Common/1/Common"
xmlns:ns16="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/IncidentFilter">
  <wsa:Address env:mustUnderstand="true">http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:Address>
</wsa:ReplyTo>
<wsa:MessageID xmlns:ns11="http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem"
  xmlns:ns12="http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident"
  xmlns:ns13="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem"
  xmlns:ns14="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node"
  xmlns:ns15="http://schemas.hp.com/ism/Common/1/Common"
  xmlns:ns16="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/IncidentFilter"
  env:mustUnderstand="true">
  uuid:494cb0d6-1e14-48f0-b011-232ff1659526
</wsa:MessageID>
<wsa:To xmlns:ns11="http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem"
  xmlns:ns12="http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident"
  xmlns:ns13="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem"
  xmlns:ns14="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node"
  xmlns:ns15="http://schemas.hp.com/ism/Common/1/Common"
  xmlns:ns16="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/IncidentFilter"
  env:mustUnderstand="true">
  http://manager1.example.com:8765/opr-webservice/Incident.svc
```

```
</wsa:To>
<wsman:ResourceURI xmlns:ns11="http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem"
  xmlns:ns12="http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident"
  xmlns:ns13="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem"
  xmlns:ns14="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node"
  xmlns:ns15="http://schemas.hp.com/ism/Common/1/Common"
  xmlns:ns16="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/IncidentFilter">
  http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident
</wsman:ResourceURI>
<wsman:SelectorSet xmlns:ns11="http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem"
  xmlns:ns12="http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident"
  xmlns:ns13="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem"
  xmlns:ns14="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node"
  xmlns:ns15="http://schemas.hp.com/ism/Common/1/Common"
  xmlns:ns16="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/IncidentFilter">
</wsman:SelectorSet>
<wsman:RequestTotalItemsCountEstimate xmlns:ns11="http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem"
  xmlns:ns12="http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident"
  xmlns:ns13="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem"
  xmlns:ns14="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node"
  xmlns:ns15="http://schemas.hp.com/ism/Common/1/Common"
  xmlns:ns16="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/IncidentFilter">
</wsman:RequestTotalItemsCountEstimate>
```

```
</env:Header>
<env:Body>
  <wsen:Enumerate xmlns:ns11="http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem"
    xmlns:ns12="http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident"
    xmlns:ns13="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem"
    xmlns:ns14="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node"
    xmlns:ns15="http://schemas.hp.com/ism/Common/1/Common"
    xmlns:ns16="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/IncidentFilter">
  </wsen:Enumerate>
</env:Body>
</env:Envelope>
```

## Enumerate Response SOAP Envelope Example

```
<s:Envelope xmlns:a="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:s="http://www.w3.org/2003/05/soap-envelope">
  <s:Header>
    <a:Action s:mustUnderstand="1">http://schemas.xmlsoap.org/ws/2004/09/enumeration/EnumerateResponse</a:Action>
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <EnumerateResponse xmlns="http://schemas.xmlsoap.org/ws/2004/09/enumeration">
      <Expires>2010-02-18T16:13:00.090+01:00</Expires>
      <EnumerationContext>cd0d1bc5-9481-4c2e-9b3f-f9a1b9a4133c</EnumerationContext>
    </EnumerateResponse>
```

```
</s:Body>  
</s:Envelope>
```

## Pull Request SOAP Envelope Example

```
<env:Envelope xmlns:env="http://www.w3.org/2003/05/soap-envelope"  
  xmlns:mdo="http://schemas.wiseman.dev.java.net/metadata/messagetypes"  
  xmlns:mex="http://schemas.xmlsoap.org/ws/2004/09/mex"  
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"  
  xmlns:wse="http://schemas.xmlsoap.org/ws/2004/08/eventing"  
  xmlns:wsen="http://schemas.xmlsoap.org/ws/2004/09/enumeration"  
  xmlns:wsman="http://schemas.dmtf.org/wbem/wsman/1/wsman.xsd"  
  xmlns:wsmeta="http://schemas.dmtf.org/wbem/wsman/1/wsman/version1.0.0.a/default-addressing-model.xsd"  
  xmlns:wxf="http://schemas.xmlsoap.org/ws/2004/09/transfer" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <env:Header>  
    <wsa:Action env:mustUnderstand="true">http://schemas.xmlsoap.org/ws/2004/09/enumeration/Pull</wsa:Action>  
    <wsa:ReplyTo>  
      <wsa:Address env:mustUnderstand="true">http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:  
Address>  
    </wsa:ReplyTo>  
    <wsa:MessageID env:mustUnderstand="true">uuid:69cab899-ad6a-41e2-b70d-980a434850da</wsa:MessageID>  
    <wsa:To env:mustUnderstand="true">http://manager1.example.com:8765/opr-webservice/Incident.svc</wsa:To>  
    <wsman:ResourceURI>http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident</wsman:ResourceURI>  
    <wsman:OperationTimeout>P0Y0M0DT0H1M0.000S</wsman:OperationTimeout>
```

```
</env:Header>
<env:Body>
  <wsen:Pull>
    <wsen:EnumerationContext>cd0d1bc5-9481-4c2e-9b3f-f9a1b9a4133c</wsen:EnumerationContext>
    <wsen:MaxTime>PT30.000S</wsen:MaxTime>
    <wsen:MaxElements>2</wsen:MaxElements>
  </wsen:Pull>
</env:Body>
</env:Envelope>
```

## Pull Response SOAP Envelope Example

```
<s:Envelope xmlns:a="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:s="http://www.w3.org/2003/05/soap-envelope">
  <s:Header>
    <a:Action s:mustUnderstand="1">http://schemas.xmlsoap.org/ws/2004/09/enumeration/PullResponse</a:Action>
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <PullResponse xmlns="http://schemas.xmlsoap.org/ws/2004/09/enumeration">
      <EnumerationContext>cd0d1bc5-9481-4c2e-9b3f-f9a1b9a4133c</EnumerationContext>
      <Items>
        <Incident xmlns="http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident">
          <AssignedOperator xmlns="http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem">
            <PersonAttributes>
```

```
        <Name xmlns=""></Name>
    </PersonAttributes>
</AssignedOperator>
<IncidentID>ae71d370-1c9e-71df-0f09-103922a40000</IncidentID>
<Title>t1</Title>
<LifecycleState>open</LifecycleState>
<Severity>Normal</Severity>
<Category></Category>
<CollaborationMode>fyi</CollaborationMode>
<EmittingCI>
    <ConfigurationItemProperties
        xmlns="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem">
        <ID></ID>
    </ConfigurationItemProperties>
</EmittingCI>
<EmittingNode>
    <NodeProperties xmlns="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node">
        <DnsName>vmis03.ovowtest.dom</DnsName>
    </NodeProperties>
</EmittingNode>
<Type></Type>
<Extensions>
```

```
t">
    <OperationsExtension xmlns="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/IncidentManagement">
        <Application>a</Application>
        <Object>o</Object>
        <StateChangeTime>2010-02-18T16:02:50</StateChangeTime>
        <CreationTime>2010-02-18T16:02:50</CreationTime>
        <ReceivedTime>2010-02-18T16:02:50</ReceivedTime>
        <NumberOfDuplicates>0</NumberOfDuplicates>
        <CorrelationKey></CorrelationKey>
        <AcknowledgeCorrelationKey></AcknowledgeCorrelationKey>
        <ConditionMatched>>false</ConditionMatched>
        <Source>opcmsg(11.0)</Source>
        <NumberOfAnnotations>0</NumberOfAnnotations>
        <OriginalEvent>Node:          node1
Message group:
Application:  a
Object:      o
Text:        t1
    </OriginalEvent>
    <AutomaticActionStatus>notAvailable</AutomaticActionStatus>
    <OperatorActionStatus>notAvailable</OperatorActionStatus>
    </OperationsExtension>
    <ChangeType xmlns="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/Incident/Change">
        Undefined
    </ChangeType>
    </OperationsExtension>
    </Incident>
</IncidentManagement>
</soap:Body>
</soap:Envelope>

```

```
        </ChangeType>
      </Extensions>
    </Incident>
  </Items>
</EndOfSequence></EndOfSequence>
</PullResponse>
</s:Body>
</s:Envelope>
```

## Subscribe Request SOAP Envelope Example

```
<env:Envelope xmlns:env="http://www.w3.org/2003/05/soap-envelope"
  xmlns:mdo="http://schemas.wiseman.dev.java.net/metadata/messagetypes"
  xmlns:mex="http://schemas.xmlsoap.org/ws/2004/09/mex"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:wse="http://schemas.xmlsoap.org/ws/2004/08/eventing"
  xmlns:wsen="http://schemas.xmlsoap.org/ws/2004/09/enumeration"
  xmlns:wsman="http://schemas.dmtf.org/wbem/wsman/1/wsman.xsd"
  xmlns:wsmeta="http://schemas.dmtf.org/wbem/wsman/1/wsman/version1.0.0.a/default-addressing-model.xsd"
  xmlns:wxf="http://schemas.xmlsoap.org/ws/2004/09/transfer" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <env:Header>
    <wsa:Action env:mustUnderstand="true">http://schemas.xmlsoap.org/ws/2004/08/eventing/Subscribe</wsa:Action>
    <wsa:ReplyTo>
```

```
<wsa:Address env:mustUnderstand="true">http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:
Address>
</wsa:ReplyTo>
<wsa:MessageID env:mustUnderstand="true">uuid:d69e3354-2517-45bd-9700-68d15c4ddde2</wsa:MessageID>
<wsa:To env:mustUnderstand="true">http://manager1.example.com:8765/opr-webservice/Incident.svc</wsa:To>
<wsman:ResourceURI>http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident</wsman:ResourceURI>
<wsman:OperationTimeout>P0Y0M0DT0H10M0.000S</wsman:OperationTimeout>
</env:Header>
<env:Body>
<wse:Subscribe xmlns:ns11="http://schemas.hp.com/ism/ServiceOperation/Common/1/WorkItem"
xmlns:ns12="http://schemas.hp.com/ism/ServiceOperation/IncidentManagement/1/Incident"
xmlns:ns13="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/ConfigurationItem"
xmlns:ns14="http://schemas.hp.com/ism/ServiceTransition/ConfigurationManagement/1/Node"
xmlns:ns15="http://schemas.hp.com/ism/Common/1/Common"
xmlns:ns16="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/Incident"
xmlns:ns17="http://schemas.hp.com/opr/ws/ServiceOperation/IncidentManagement/1/IncidentFilter">
<wse:Delivery Mode="http://schemas.dmtf.org/wbem/wsman/1/wsman/Pull">
<wse:NotifyTo>
<wsa:Address env:mustUnderstand="true"></wsa:Address>
</wse:NotifyTo>
</wse:Delivery>
</wse:Subscribe>
</env:Body>
</env:Envelope>
```

