

Configuring HP CSA to Work with Oracle RAC

CSA 4.10

Table of contents

Scope and Purpose of this Document	2
Oracle RAC.....	2
HP CSA Database Configuration for Non-RAC.....	2
HP CSA Database Configuration for Oracle RAC.....	3
For More Information	6



Scope and Purpose of this Document

Enterprise applications such as HP CSA are usually deployed in high-availability database environments. This document describes Oracle RAC-specific configuration for HP CSA. This document does not cover how to install HP CSA, or how to install and configure Oracle RAC.

Oracle RAC

Oracle RAC provides clustering and high availability for Oracle database environments. In an Oracle RAC environment, two or more database instances concurrently access a single database. A typical RAC environment includes the instances running on different physical machines with a Single Client Access Name (SCAN) that allows clients to access the database using a single hostname/ip address, instead of specifying the hostnames/ip addresses for each of the instances in the connection URL.

HP CSA Database Configuration for Non-RAC

The HP CSA installer prompts users to enter database information (server hostname/ip, username, password etc.). This information is stored in configuration files and used by the Cloud Service Management Console to connect to the database.

In a **standalone environment**, the configuration file is located at:

```
%CSA_HOME%\jboss-as-7.1.1.Final\standalone\configuration\standalone.xml (Windows)  
$CSA_HOME\ jboss-as-7.1.1.Final\standalone\configuration\standalone.xml (Linux)
```

All the database configuration information is specified in the <datasource> element. An example is shown below:

```
<datasource jndi-name="java:jboss/datasources/csaDS" pool-name="OracleDS">  
    <connection-url>jdbc:oracle:thin:@127.0.0.1:1521:XE</connection-url>  
    <driver>oracleDriver</driver>  
    <pool>  
        <min-pool-size>10</min-pool-size>  
        <max-pool-size>200</max-pool-size>  
        <prefill>true</prefill>  
        <use-strict-min>false</use-strict-min>  
        <flush-strategy>FailingConnectionOnly</flush-strategy>  
    </pool>  
    <security>  
        <security-domain>csa-encryption-sec</security-domain>  
    </security>  
</datasource>
```

NOTE: This configuration in standalone.xml is for non-RAC environments.

In a **clustered environment**, the configuration file is located at:

```
%CSA_HOME%\jboss-as-7.1.1.Final\domain\configuration\domain.xml (Windows)  
$CSA_HOME\jboss-as-7.1.1.Final\domain\configuration\domain.xml (Linux)
```

All the database configuration information is specified in the <datasource> element. An example is shown below:

```
<datasource jta="true" jndi-name="java:jboss/datasources/csaDS" pool-name="OracleDS" enabled="true" use-java-context="true" use-ccm="true">  
    <connection-url>jdbc:oracle:thin:@ 127.0.0.1:1521:XE</connection-url>  
    <driver>oracleDriver</driver>    <driver>oracleDriver</driver>  
    <pool>  
        <min-pool-size>10</min-pool-size>  
        <max-pool-size>200</max-pool-size>  
        <prefill>true</prefill>  
        <use-strict-min>false</use-strict-min>  
        <flush-strategy>FailingConnectionOnly</flush-strategy>  
    </pool>  
    <security>  
        <security-domain>csa-encryption-sec</security-domain>  
    </security>  
</datasource>
```

NOTE: This configuration in domain.xml is for non-RAC environments.

HP CSA Database Configuration for Oracle RAC

Getting HP CSA to work with Oracle RAC is straightforward with minimal configuration changes to the standalone.xml file, described in the previous section.

Steps to Configure HP CSA for Oracle RAC

1. Install HP CSA. In the screen that asks for database information, enter the SCAN for the RAC and the service name or the hostname/ip address of one of the instances and its System Identifier (SID). If this information is not correct, the installer is not able to connect to the database and installation does not proceed until this issue is resolved.
2. After installing HP CSA, navigate to the configuration file. As specified in the previous section, this file is located at:

Standalone Environment

```
%CSA_HOME%\jboss-as-7.1.1.Final\standalone\configuration\standalone.xml (Windows)  
$CSA_HOME\jboss-as-7.1.1.Final\standalone\configuration\standalone.xml (Linux)
```

Clustered Environment

```
%CSA_HOME%\jboss-as-7.1.1.Final\domain\configuration\domain.xml (Windows)  
$CSA_HOME\jboss-as-7.1.1.Final\domain\configuration\domain.xml (Linux)
```

3. Before modifying the standalone.xml or domain.xml file, back up the file by making a copy of it.
4. Find the section that configures the HP CSA datasource. An example is shown below:

Standalone Environment

```
<datasource jndi-name="java:jboss/datasources/csaDS" pool-name="OracleDS">  
    <connection-url>jdbc:oracle:thin:@127.0.0.1:1521:XE</connection-url>
```

Clustered Environment

```
<datasource jta="true" jndi-name="java:jboss/datasources/csaDS" pool-name="OracleDS" enabled="true" use-java-context="true" use-ccm="true">
    <connection-url>jdbc:oracle:thin:@127.0.0.1:1521:XE</connection-url>
```

5. Replace the `<connection-url>` element with the following:

```
<connection-url>
    jdbc:oracle:thin:@(description=(address_list=(address=(protocol=tcp)
        (host=<host1>)(port=<port1>))(address=(protocol=tcp)(host=<host2>)
        (port=<port2>))(failover=yes)(load_balance=yes))(connect_data=
        (service_name=<racdb>)(failover_mode=(type=select)(method=basic)(retries=10)
        (delay=5)))
</connection-url>
```

NOTE: The bold text must be replaced with appropriate values.

6. Add the following to the `<datasource>` element:

```
<validation>
    <check-valid-connection-sql>select 1 from dual</check-valid-connection-sql>
    <validate-on-match>false</validate-on-match>
    <background-validation>true</background-validation>
    <use-fast-fail>false</use-fast-fail>
    <exception-sorter class-
name="org.jboss.jca.adapters.jdbc.extensions.oracle.OracleExceptionSorter" />
</validation>
```

When you are done with these changes, the datasource configuration looks like the following:

NOTE: Elements highlighted below are the elements that you have changed and the bold text was replaced with appropriate values.

Standalone Environment

```
<datasource jndi-name="java:jboss/datasources/csaDS" pool-name="OracleDS">
    <connection-url>
        jdbc:oracle:thin:@(description=(address_list=(address=(protocol=tcp)(host=<host1>)
            (port=<port1>))(address=(protocol=tcp)(host=<host2>)(port=<port2>))(failover=yes)
            (load_balance=yes))(connect_data=(service_name=<racdb>)(failover_mode=
            (type=select)(method=basic)(retries=10)(delay=5)))
    </connection-url>
    <driver>oracleDriver</driver>
    <pool>
        <min-pool-size>10</min-pool-size>
        <max-pool-size>200</max-pool-size>
        <prefill>true</prefill>
        <use-strict-min>false</use-strict-min>
        <flush-strategy>FailingConnectionOnly</flush-strategy>
    </pool>
    <security>
        <security-domain>csa-encryption-sec</security-domain>
    </security>
    <validation>
        <check-valid-connection-sql>select 1 from dual</check-valid-connection-sql>
        <validate-on-match>false</validate-on-match>
        <background-validation>true</background-validation>
        <use-fast-fail>false</use-fast-fail>
        <exception-sorter class-
name="org.jboss.jca.adapters.jdbc.extensions.oracle.OracleExceptionSorter" />
    </validation>
```

```
</datasource>
```

Clustered Environment

```
<datasource jndi-name="java:jboss/datasources/csADS" pool-name="OracleDS"
enabled="true" jta="true" use-java-context="true" use-ccm="true">
    <connection-url>
        jdbc:oracle:thin:@(description=(address_list=(address=(protocol=tcp)(host=<host1>)
        (port=<port1>))(address=(protocol=tcp)(host=<host2>)(port=<port2>))(failover=yes)
        (load_balance=yes))(connect_data=(service_name=<racdb>)(failover_mode=
        (type=select)(method=basic)(retries=10)(delay=5))))
    </connection-url>
    <driver>oracleDriver</driver>
    <pool>
        <min-pool-size>10</min-pool-size>
        <max-pool-size>200</max-pool-size>
        <prefill>true</prefill>
        <use-strict-min>false</use-strict-min>
        <flush-strategy>FailingConnectionOnly</flush-strategy>
    </pool>
    <security>
        <security-domain>csa-encryption-sec</security-domain>
    </security>
    <validation>
        <check-valid-connection-sql>select 1 from dual</check-valid-connection-sql>
        <validate-on-match>false</validate-on-match>
        <background-validation>true</background-validation>
        <use-fast-fail>false</use-fast-fail>
        <exception-sorter class-
            name="org.jboss.jca.adapters.jdbc.extensions.oracle.OracleExceptionSorter"/>
    </validation>
</datasource>
```

7. Restart HP CSA.

HP CSA is now connected to the Oracle RAC instance and supports failover. If one of the database instances goes down, HP CSA continues to function normally by connecting to another database instance that is up and running.

For More Information

To access other toolkits to design and extend cloud services running on HP CloudSystem, go to <http://www.hp.com/go/csdevelopers>.

For more information on HP CloudSystem, visit <http://www.hp.com/go/cloudsystem>.

HP software product manuals and documentation for the following products can be found at <http://h20230.www2.hp.com/selfsolve/manuals>. You will need an HP Passport to sign in and gain access.

- HP Cloud Service Automation
- HP Server Automation
- HP Operations Orchestration

VMware vCenter and vSphere documentation can be found at <http://www.vmware.com/support/pubs/>.

To help us improve our documents, please send feedback to CSAdocs@hp.com.



© Copyright 2012 - 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft® and Windows® are U.S. registered trademarks of Microsoft Corporation. Oracle and Java are registered trademarks of Oracle and/or its affiliates. RED HAT READY™ Logo and RED HAT CERTIFIED PARTNER™ Logo are trademarks of Red Hat, Inc. The OpenStack word mark and the Square O Design, together or apart, are trademarks or registered trademarks of OpenStack Foundation in the United States and other countries, and are used with the OpenStack Foundation's permission.

Last updated July 2014.

