

HP Service Activator

Migration Guide

Version 6.2 to 7.0

Edition: V70-1A

**for Microsoft Windows® Server 2012 R2, HP-UX 11i v3,
and Red Hat Enterprise Linux 6.6 operating systems**



Manufacturing Part Number: None

January 18, 2015

© Copyright 2001-2015 Hewlett-Packard Development Company, L.P.

Legal Notices

Warranty.

Hewlett-Packard makes no warranty of any kind with regard to this manual, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Hewlett-Packard shall not be held liable for errors contained herein or direct, indirect, special, incidental or consequential damages in connection with the furnishing, performance, or use of this material.

A copy of the specific warranty terms applicable to your Hewlett-Packard product can be obtained from your local Sales and Service Office.

Restricted Rights Legend.

Use, duplication or disclosure by the U.S. Government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause in DFARS 252.227-7013.

Hewlett-Packard Company
United States of America

Rights for non-DOD U.S. Government Departments and Agencies are as set forth in FAR 52.227-19(c)(1,2).

Copyright Notices.

© Copyright 2001-2015 Hewlett-Packard Development Company, L.P .

Confidential computer software. Valid license from HP required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Trademark Notices.

Java™ is a registered trademark of Oracle and/or its affiliates.

Linux is a U.S. registered trademark of Linus Torvalds

Microsoft® is a U.S. registered trademark of Microsoft Corporation.

Red Hat® Enterprise Linux® is a registered trademark of Red Hat, Inc.

JBoss® is a registered trademark of Red Hat, Inc. in the United States and other countries

EnterpriseDB® is a registered trademark of EnterpriseDB.

Postgres Plus® Advanced Server is a registered trademark of EnterpriseDB.

Oracle® is a registered trademark of Oracle and/or its affiliates.

UNIX® is a registered trademark of the Open Group.

Windows® and MS Windows® are U.S. registered trademarks of Microsoft Corporation. Document id: HPSA p158-pd002108

Contents

1 Migration Overview	8
2 Migration Tasks by Component	9
Database	9
Workflows and the Workflow Manager	9
Inventory	9
Inventory Trees.....	9
Plug-ins.....	10
Compound Tasks	10
Custom JSPs	10
Web UI	10
Data Sources	10
Deployment Manager and Solutions	10
Localization (I10N)	10
Common Network Resource Model	10
Integrations with NA and NNMi	11
3 Migration Tasks	12
1. Install the New Version of Service Activator	12
2. Copy the Solution Files	13
3. Update the Solution Files on the New Server.....	13
Service Activator RMI Interface.....	13
Custom Workflow Nodes and Handlers	13
Custom Workflow Module	13
Workflows	13
Inventory.....	13
Inventory Trees.....	13
Plug-ins.....	14
Compound Tasks	14
Custom JSPs	14
Customized AskFor Node JSPs	14
Solution.....	14
4. Migrate the System and Inventory Databases.....	14
5. Configure the New Version of Service Activator.....	15
6. Deploy Your Solution.....	15
7. Shut Down the Old Version of Service Activator	16
8. Install a New License File	16
9. Start the New Version of Service Activator	16

Install Location Descriptors

The following names are used to define install locations throughout this guide.

Descriptor	What the Descriptor Represents
<code>\$ACTIVATOR_OPT</code>	The base install location of Service Activator. The UNIX® location is <code>/opt/OV/ServiceActivator</code> The Windows® location is <code><install drive>:\HP\OpenView\ServiceActivator</code>
<code>\$ACTIVATOR_ETC</code>	The install location of specific Service Activator files. The UNIX location is <code>/etc/opt/OV/ServiceActivator</code> The Windows location is <code><install drive>:\HP\OpenView\ServiceActivator\etc</code>
<code>\$ACTIVATOR_VAR</code>	The install location of specific Service Activator files. The UNIX location is <code>/var/opt/OV/ServiceActivator</code> The Windows location is <code><install drive>:\HP\OpenView\ServiceActivator\var</code>
<code>\$ACTIVATOR_BIN</code>	The install location of specific Service Activator files. The UNIX location is <code>/opt/OV/ServiceActivator/bin</code> The Windows location is <code><install drive>:\HP\OpenView\ServiceActivator\bin</code>
<code>\$ACTIVATOR_THIRD_PARTY</code>	In HP Service Activator 5.1 and earlier, this was the location for Java components such as workflow nodes and modules. In Service Activator 7.0 this location is no longer used; the new location is <code>\$JBOSS_EAR_LIB</code> . The UNIX location was <code>/opt/OV/ServiceActivator/3rd-party</code> The Windows location was <code><install drive>:\HP\OpenView\Service Activator\3rd-party</code> Customized inventory files used to be stored in the following locations: UNIX: <code>\$ACTIVATOR_THIRD_PARTY/inventory</code> Windows: <code>\$ACTIVATOR_THIRD_PARTY\inventory</code>
<code>\$JBOSS_EAR_LIB</code>	The new location of libraries (Java *.jar file, including 3 rd -party libraries and inventory class files) to be executed by the HP Service Activator engine (Workflow Manager and Resource Manager). Location: <code>\$JBOSS_DEPLOY/hpsa.ear/lib</code>
<code>\$JBOSS_HOME</code>	The install location for JBoss. The UNIX location is <code>/opt/HP/jboss</code> The Windows location is <code><install drive>:\HP\jboss</code>

<code>\$JBOSS_DEPLOY</code>	The new install location of the Service Activator JEE components. The UNIX location is <code>/opt/HP/jboss/standalone/deployments</code> The Windows location is <code><install drive>:\HP\jboss\standalone\deployments</code>
<code>\$SOLUTION_HOME</code>	The directory in which your solution resides: <code>\$ACTIVATOR_OPT/SolutionName</code>

In This Guide

This guide gives instructions on migrating your HP Service Activator solution from version 6.2 to version 7.0. The guide lists the changes that have been made in version 7.0 and explains how those changes affect the migration process.

First of all, read the Migration Overview sections in this guide to acquaint yourself with the migration issues. Then, when reading the Migration Tasks section, notice how those issues influence your migration tasks.

Before starting the migration process, read the *Release Notes* for HP Service Activator 7.0. Also read the *Installation Guide* to become familiar with the installing and configuring Service Activator 7.0 as well as the document *Solution Separation and the Deployment Manager* to get a full overview of Service Activator solutions. The documents are available either in the `Documentation/` directory on your Service Activator DVD or in the `$ACTIVATOR_OPT/docs/` directory of the installed product.

If you wish to migrate your solution from Service Activator 6.1, you should also read the *HP Service Activator 6.1 to 6.2 Migration Guide*. This document is available in the `Documentation/` directory on your Service Activator DVD. The migration database scripts for this migration are included in the HP Service Activator 7.0 and can be found in the directory specified in the migration guide.

Please note that the operating system Red Hat Enterprise Linux 6.4 is no longer supported. Instead Service Activator 7.0 has added support for Red Hat Enterprise Linux 6.6. The supported databases are Oracle 12g, Oracle 12g RAC, and Postgres Plus Advanced Server 9.2.

A number of file/directory locations are specified in this guide as environment variables, e.g. `$ACTIVATOR_OPT`, `$SOLUTION_HOME`, etc. You can find the definition for these install locations in the “Install Location Descriptors” section.

NOTE	This guide does <i>not</i> describe how to migrate an existing Oracle database to Postgres Plus Advanced Server. For information about how to migrate an Oracle database to Postgres Plus Advanced Server, you should study the document <i>Postgres Plus Advanced Server Migration Guide</i> which is available on EnterpriseDB's homepage (http://www.enterprisedb.com).
IMPORTANT	HP cannot be held responsible for the methodologies and processes described in the document <i>Postgres Plus Advanced Server Migration Guide</i> .

Audience

The audience for this guide is the Solutions Integrator who has developed the Service Activator 6.2 solution and wishes to migrate it to Service Activator 7.0.

1 Migration Overview

Migration is a multi-staged manual process that requires careful planning. There are several steps to follow to ensure the successful migration of a HP Service Activator solution. These steps will be covered in more detail later in this document:

- Develop an understanding of whether the components of an earlier version of Service Activator must be modified in order to work correctly in a new version.
- Record and understand the customizations and configurations that have been made in an earlier version in order to properly migrate these customizations to a new installation.
- Install the new version of Service Activator on new hardware using an evaluation license.
- Migrate all components of the customer specific solution that have been applied to the earlier installation Service Activator.
- Export the content of the old Oracle DB and import it into the new Oracle DB and run the database migration scripts in order to make the DB schema compatible with HP Service Activator 7.0. You can skip this step, if you don't wish to reuse the content of the old database or if you have your own procedure to migrate the solution data.
- Carefully test your deployment in a production environment.
- Shut down the earlier version of Service Activator.
- Move the license file used by the earlier version of Service Activator to the new installation.
- Start the new version of Service Activator.

NOTE 1 This guide assumes that the solution has been deployed using the Deployment Manager; i.e. all solution components are located in the `$SOLUTION_HOME` directory.

NOTE 2 Migration to a newer version of Oracle or to Postgres Plus Advanced Server is outside the scope of this document.

2 Migration Tasks by Component

The following sections break down the migration tasks by Service Activator component. These sections will point out the information you will need to record and carefully consider before migrating your solution.

Database

In Service Activator 7.0 the system database plays a major role. The schema and the contents of the system database have changed slightly since Service Activator 6.2; hence, your old database needs to be modified if you wish to reuse it in your new installation. The majority of the changes in the system database are a result of the added support for XMaps, conflict module, and the queuing sub-system.

HP Service Activator 7.0 comes with three SQL scripts that can be used to migrate a Service Activator 6.2 system database to version 7.0.

IMPORTANT

There are no scripts to roll back a Service Activator 7.0 system database to version 6.2. Hence, you should make sure to make a backup of the system database before attempting to migrate it to version 7.0.

It is recommended that you create a new database instance and/or a new database user to be used by Service Activator 7.0 and then decommission your old database after you have completed all migration tasks.

Migrating service data from the old resource tables to the new database is not a major migration project, however it must be planned.

Workflows and the Workflow Manager

Workflow Manager modules and nodes that have been developed for HP Service Activator 6.2 can be reused with Service Activator 7.0. They just need to be recompiled with java 7.

Workflows developed for HP Service Activator 6.2 can be used “as-is” with Service Activator 7.0.

Inventory

The layout of the database schema generated by the Inventory Builder has not changed between Service Activator 6.2 and 7.0.

Inventory Trees

Inventory trees developed for Service Activator 6.2 can be used directly in Service Activator 7.0.

Plug-ins

If you have developed your own plug-ins for Service Activator 6.2, you can use them directly after recompiling with java 7 in Service Activator 7.0.

Compound Tasks

Compound tasks can be reused without changes.

Custom JSPs

If your solution contains custom JSPs, you can use them without modification in Service Activator 7.0.

Web UI

The file `$JBOSS_DEPLOY/hpsa.ear/activator.war/WEB-INF/web.xml` has been changed slightly since HP Service Activator 6.2. So if you have manually changed the `web.xml` file you need to manually merge the changes into the new `web.xml` file.

Data Sources

As in Service Activator 7.0, data-sources are configured in one common file named `$JBOSS_HOME/standalone/configuration/standalone.xml`.

Deployment Manager and Solutions

Solutions built to be deployed with Service Activator 6.2's Deployment Manager should be deployable in Service Activator 7.0, except for one thing. The version file must be updated to now also contain a solution-name tag. Please see the `version.dtd` file for the syntax.

Localization (I10N)

As in HP Service Activator 6.2, all resource bundle files are grouped in a single JAR file called `$JBOSS_EAR_LIB/nls.jar`. Hence, if you need to follow this procedure in order to localize the resource bundle files that are located in the `$ACTIVATOR_ETC/nls` directory:

- Create copies of the resource bundle files and prefix them appropriately (i.e. using the country code).
- Edit the messages in the copied resource bundle files.
- Create a new JAR file named `nls.jar` (it must contain *all* resource bundle files) and copy it to the `$JBOSS_EAR_LIB` directory.

Common Network Resource Model

If your solution makes use of the Common Network Resource Model (CRModel) and you want to preserve the database tables then use `deploy_oracle.xml` or `deploy_ppas.xml`. However if you want to migrate from HP Service Activator 6.1 then use the `deploy_update_oracle6.1.xml` or `deploy_update_ppas6.1.xml` file when deploying the solution on the new installation. When doing this then the create inventory tables should not be checked.

Integrations with NA and NNMi

HP Service Activator 6.2 integrates with the same versions of NA and NNMi as Service Activator 6.2. This means that integration with NA version 9.2 and NNMi version 9.10 are supported. Older versions of NA and NNMi are not supported.

3 Migration Tasks

This chapter is grouped into nine major steps:

1. Install the new version of Service Activator on new hardware using an evaluation license.
2. Copy the solution files, i.e. all files from the \$SOLUTION_HOME directory, from the old server to the \$SOLUTION_HOME directory of the new server.
3. Update the solution files on the new server so that they are compatible with Service Activator 7.0.
4. Migrate your old system database as well as the old inventory database so that they work with Service Activator 7.0. (Optional)
5. Configure the new version of Service Activator.
6. Deploy your solution on the new version of Service Activator.
7. Shut down the old Service Activator version.
8. Get a new license for HP Service Activator 7.0 (or move your current Service Activator 6.2 license) and install it in the new installation.
9. Start the new version of Service Activator and test your solution.

NOTE 1 Step 4 can be skipped if you do not want to migrate your old data or if you have defined other processes for migrating your data.

NOTE 2 If you are running your solution in a cluster environment, you need to deploy the modified solution on all your cluster nodes. However, you must only migrate the system and inventory databases once.

1. Install the New Version of Service Activator

Install Service Activator 7.0 on new hardware following the instructions in the *Installation Guide*. This includes installing Java Development Kit 7.0.

Install an evaluation license during the install phase. The evaluation license is valid for 180 days.

When installing the new version of Service Activator, you will need to supply the username, password, and database hostname, and database instance name values to ActivatorConfig. Make sure that you use the new database instance and make sure that the “Create database tables” checkbox is selected since ActivatorConfig will not accept the database schema from an earlier version of Service Activator.

NOTE If you want to migrate the system database from Service Activator 6.2, you must *not* run ActivatorConfig as part of the installation process. Just close the window when it is displayed.

2. Copy the Solution Files

Copy all solution files from the old server to the new server using the following steps:

- Create a `$(SOLUTION_HOME)` directory on the new server. The name of the directory must match that of the solution and its length must not exceed 8 characters.
- Copy all files from `$(SOLUTION_HOME)` directory on the old server to the `$(SOLUTION_HOME)` directory on the new server

3. Update the Solution Files on the New Server

This section describes at a high-level the steps that you need to follow in order to migrate your solution from Service Activator 6.2 to version 7.0. The solution components that do *not* need any modifications will not be mentioned.

Service Activator RMI Interface

The Java RMI interface in Service Activator 7.0 is backward compatible with Service Activator 6.2. If your solution makes use of the RMI interface, you should not need to make any modifications.

Custom Workflow Nodes and Handlers

You can reuse your own custom workflow nodes and handlers with Service Activator 7.0. They will be deployed to the runtime system as part of the Deployment Manager's solution deployment process. The only thing you need to do is to recompile the java classes with Jave 7.

Custom Workflow Module

You can reuse your own custom workflow modules with Service Activator 6.2. The only thing you need to do is to recompile the java classes with Jave 7.

Workflows

Your workflows from Service Activator 6.1 can be reused directly in Service Activator 6.2. If you migrate the system database using the procedure described later in this chapter, your workflows will be migrated automatically. Otherwise, your workflows will be deployed in the new system database as part of the Deployment Manager's solution deployment process.

Inventory

You can reuse your resource definition files from Service Activator 6.2. The only thing you need to do is to recompile the java classes with Jave 7 if you have any customized bean which are not compiled as part of the standard procedure.

Inventory Trees

If you migrate the system database from Service Activator 6.2 to version 7.0, the inventory trees will be migrated automatically. Otherwise, you will need to use the Deployment Manager to deploy your inventory trees to HP Service Activator 7.0.

NOTE

If you undeploy your old inventory trees, you will need to recreate all role mappings to tree, operation types, and branch types.

Plug-ins

Plug-ins can be reused without changes with Service Activator 6.2. If you migrate the system database from Service Activator 6.2 to version 7.0, the plug-ins should be deployed again after recompiled to java 7..

Alternatively, your plug-ins can be deployed using the Deployment Manager as part of the solution deployment process.

If your solution uses any of the plug-ins delivered with Service Activator (GenericCLI, GenericHTTP, or GenericLDAP), you should deploy the new plug-ins.

Compound Tasks

Compound tasks can be reused without changes. If you migrate the system database from Service Activator 6.2 to version 7.0, the compound tasks will be migrated automatically. Alternatively, your compound tasks can be deployed using the Deployment Manager as part of the solution deployment process.

Custom JSPs

Your custom JSPs should work with Service Activator 7.0 without any modifications.

Customized AskFor Node JSPs

No changes are required for the customized AskFor node JSPs. Your customized AskFor node JSPs will be copied to the proper location as part of the Deployment Manager's solution deploy process.

If you are using customized AskFor JSPs you need to edit the configuration file `$(JBASS_DEPLOY)/hpsa.ear/activator.war/WEB-INF/web.xml` and set the value of the `customizeAskForNodeJSP` to `true`.

Solution

Since the files in the `$(SOLUTION_HOME)` directory on your new server are a copies of the old solution (including the old DTD files), you need to do the following before deploying your solution on HP Service Activator 7.0:

- Copy `$(ACTIVATOR_ETC)/config/deploy.dtd` and `$(ACTIVATOR_ETC)/config/version.dtd` to `$(SOLUTION_HOME)`.
- Copy `$(ACTIVATOR_ETC)/workflows/workflow.dtd` to `$(SOLUTION_HOME)/etc/workflows`.
- Copy `$(ACTIVATOR_ETC)/config/inventoryTree/inventoryTree.dtd` to `$(SOLUTION_HOME)/etc/config/inventoryTree`.
- Copy `$(ACTIVATOR_ETC)/config/bean.dtd` to `$(SOLUTION_HOME)/inventory`.

NOTE

Not all DTDs are strictly necessary for the solution to be deployable. However, for your own convenience you should ensure that all Service Activator 6.1 DTDs are replaced with their Service Activator 6.2 counterparts.

4. Migrate the System and Inventory Databases

NOTE

This step is optional. If you do not wish to reuse your old data or if you have defined your own procedure for migrating data, you can skip this step.

The Service Activator system database schema has changed slightly from version 6.2 to 7.0. In order to migrate your system database, you need to perform the following steps:

- Log into the old system database server and export the database to a file using standard Oracle/PPAS utilities. You need to do this when no jobs are running and no scheduled jobs will be scheduled during the migration period.
- Log into the new system database server and import the file that you just exported.
- The migration SQL scripts will create temporary copies of some of the database tables. Therefore, you should that you have approximately 50% free space on the new database server to secure a successful database migration.
- On the new database server, run the following migration SQL script:

```
For Oracle
$ACTIVATOR_OPT/migration/migrate_6.2_to_7.0_Oracle.sql
For PPAS
$ACTIVATOR_OPT/migration/migrate_6.2_to_7.0_PPAS.sql
```

Now, your Service Activator system database will be ready for use with Service Activator 7.0.

In order to migrate your inventory database, you need to perform the following steps:

- Nothing to be done

Now, your Service Activator inventory database will be ready for Service Activator 6.2.

NOTE

If your system and inventory data are stored in the same database (which is frequently the case) you only need to run the export/import steps once.

5. Configure the New Version of Service Activator

If you have completed step 4 and migrated your databases from Service Activator 6.2 to 7.0 you will now need to run `ActivatorConfig` in order to generate new configuration files. You must remember to uncheck the “Create database tables” checkbox.

If, on the other hand, you have skipped step 4, you must now run `ActivatorConfig` and remember to *check* the “Create database tables” checkbox.

After having run `ActivatorConfig` you may want to make manual changes to Service Activator’s configuration files. This migration guide will not walk you through all Service Activator configuration files. However, the following configuration files are commonly modified in Service Activator solutions:

- `$ACTIVATOR_ETC/config/mwfm.xml`
- `$ACTIVATOR_ETC/config/resmgr.xml`
- `$ACTIVATOR_ETC/role_mappings.xml` (optional)
- `$JBOSS_DEPLOY/hpsa.ear/activator.war/WEB-INF/web.xml`

Go through all these files (as well as the other configuration files that you need to modify) and carefully migrate your configuration changes from the corresponding configuration files on the old Service Activator server.

6. Deploy Your Solution

After having modified your solution so that it is compatible with Service Activator 7.0, you can deploy it using the Deployment Manager’s `deploy solution` operation. If you are running Service

Activator in a cluster environment, you need to deploy your solution on all cluster nodes. In this case you need to make sure that you only perform database operations (such as deployment of workflows, inventory tree, etc.) once.

7. Shut Down the Old Version of Service Activator

The recommended way to shut down Service Activator is as follows:

- Stop feeding new workflows into the Workflow Manager.
- Allow all running workflows to complete.

Now, you can stop the old version of Service Activator as follows:

- **HP-UX:** `/sbin/init.d/activator stop`
- **Linux:** `service activator stop`
- **Windows:** Stop the service called “HP Service Activator”

8. Install a New License File

Once you have obtained a new license file for HP Service Activator 7.0 you need to install it. This is done by running the following utility and following the on-screen instructions:

- **UNIX:** `$ACTIVATOR_OPT/bin/updateLicense`
- **Windows:** `$ACTIVATOR_OPT/bin/updateLicense.bat`

9. Start the New Version of Service Activator

Start the new version of Service Activator as follows:

- **HP-UX:** `/sbin/init.d/activator start`
- **Linux:** `service activator start`
- **Windows:** Start the service called “HP Service Activator”

Finally, you should test the correct operation of your solution according to your test specification.