



HP Universal CMDB & Configuration Manager

Software Version: 10.11 CUP4

Release Notes

Document Release Date: April 2015 (Second Edition)
Software Release Date: March 2015

Legal Notices

Warranty

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

The information contained herein is subject to change without notice.

Restricted Rights Legend

Confidential computer software. Valid license from HP required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

Copyright Notice

© 2002 - 2015 Hewlett-Packard Development Company, L.P.

Trademark Notices

Adobe™ is a trademark of Adobe Systems Incorporated.

Microsoft® and Windows® are U.S. registered trademarks of Microsoft Corporation.

UNIX® is a registered trademark of The Open Group.

Documentation Updates

The title page of this document contains the following identifying information:

- Software Version number, which indicates the software version.
- Document Release Date, which changes each time the document is updated.
- Software Release Date, which indicates the release date of this version of the software.

To check for recent updates or to verify that you are using the most recent edition of a document, go to: <https://softwaresupport.hp.com/>.

This site requires that you register for an HP Passport and to sign in. To register for an HP Passport ID, click **Register** on the HP Support site or click **Create an Account** on the HP Passport login page.

You will also receive updated or new editions if you subscribe to the appropriate product support service. Contact your HP sales representative for details.

Document Changes

Publication Date	Summary of Changes
April 2015 (10.11 CUP4, Second Edition)	<ul style="list-style-type: none"> • Added a note regarding the potential performance degradation after deploying 10.11 CUP4, suggested actions are also available. • Added the SQL script that users must run for the fix implemented for QCCR1H95638 to work.

Support

Visit the HP Software Support site at: <https://softwaresupport.hp.com>.

This website provides contact information and details about the products, services, and support that HP Software offers.

HP Software online support provides customer self-solve capabilities. It provides a fast and efficient way to access interactive technical support tools needed to manage your business. As a valued support customer, you can benefit by using the support website to:

- Search for knowledge documents of interest
- Submit and track support cases and enhancement requests
- Download software patches
- Manage support contracts
- Look up HP support contacts
- Review information about available services
- Enter into discussions with other software customers
- Research and register for software training

Most of the support areas require that you register as an HP Passport user and to sign in. Many also require a support contract. To register for an HP Passport ID, click **Register** on the HP Support site or click **Create an Account** on the HP Passport login page.

To find more information about access levels, go to: <https://softwaresupport.hp.com/web/softwaresupport/access-levels>.

HP Software Solutions Now accesses the HPSW Solution and Integration Portal website. This site enables you to explore HP Product Solutions to meet your business needs, includes a full list of Integrations between HP Products, as well as a listing of ITIL Processes. The URL for this website is <http://h20230.www2.hp.com/sc/solutions/index.jsp>.

Contents

HP Universal CMDB & Configuration Manager Release Notes	4
What's New in UCMDB 10.11 CUP4	4
HP Universal CMDB and Configuration Manager 10.11 CUP4 Files/Components	6
System Requirements	6
Install 10.11 CUP4 on the HP Universal CMDB and Configuration Manager Servers	7
HP Universal CMDB 10.11 CUP4 Manual Data Flow Probe Installation	9
HP Universal CMDB and CM 10.11 CUP4 Uninstall Procedure	9
Notes	11
Enhancements Requests	22
Fixed Defects for UCMDB 10.11 CUP4	23
Fixed Defects for UCMDB 10.11 CUP3	26
Fixed Defects for UCMDB 10.11 CUP2	32
Fixed Defects for UCMDB 10.11 CUP1	34
Documentation Errata	35
Enable Secure Login for the JMX Console	36
Appendixes	37
1_script_delete_index.sql	37
2_script_delete_constraint.sql	38
Send Documentation Feedback	40

HP Universal CMDB & Configuration Manager Release Notes

Keep your system up to date with the most recent cumulative update package (CUP) for UCMDB 10.11. This package contains all of the UCMDB 10.11 hotfixes that have been released since the initial release of UCMDB 10.11.

What's New in UCMDB 10.11 CUP4

UCMDB 10.11 CUP4 contains the following new features and changes:

- **A lockout mechanism is now available**

The lockout mechanism allows UCMDB administrators to:

- enable or disable the lockout mechanism
- specify how many failed login attempts are allowed before a user is locked out
- specify the period of time after which the locked accounts will be automatically released
- retrieve a list of locked out users and unlock certain users

In addition, all failed login attempts will be logged, and consecutive attempts are reported to the proper security administration personnel in your organization.

The table below describes the new infrastructure settings available with the lockout mechanism (**Administration > Infrastructure Settings Manager > Security Settings**):

Name	Description	Default Value
User lockout mechanism enabled	Enable the user lockout mechanism after a number of failed login attempts.	True
User lockout timeout value (minutes)	The time value in minutes until the next login attempt can be successfully permitted in case the current user is locked out.	10

Name	Description	Default Value
The maximum number of failed login attempts prior to a user lockout	The maximum number of failed login attempts before a user enters the timed lock out state.	3

Also in JMX, under **Security Services**, two new methods are added for unlocking users:

- **retrieveCurrentlyLockedOutUsers.** Retrieves a list of the currently locked out users and allows individual unlocking.
- **unlockUser.** Allows unlocking a certain user that is currently locked out by the login mechanism.
- Added a new API method **void setDiscoveryConfigurationXML(String xmlString, boolean includeGroup)**

Compared to the existing API method **void setDiscoveryConfigurationXML(String xmlString)**, this new method contains the **includeGroup** parameter. The **includeGroup** parameter allows you to set whether you want to update the entire device group.

For example, if you want to update IP ranges and credentials only and leave the statuses of all jobs as is, you can invoke this new method by setting the **includeGroup** parameter to **false**.

- Added multi-tenant status information into the system information to show whether the UCMDDB Server is set up as a single-tenant or multi-tenant environment

The multi-tenant status information can be seen in two places:

a. **Mbean: UCMDDB:service=Server Services. Method: viewSystemInformation**

When executing the JMX method **viewSystemInformation**, the result now displays an additional line:

MT: [enabled | disabled]

b. **Mbean: UCMDDB:service=Supportability Services. Method: runSupportHandlersForAllCategories**

When exporting the UCMDDB System Info information by executing the JMX supportability tool (JMX method **runSupportHandlersForAllCategories**), in one of the archive files created (**systemInfo.properties**), a new line is added to display the status of the multi-tenancy:

MT: [enabled | disabled]

HP Universal CMDB and Configuration Manager 10.11 CUP4 Files/Components

HP UCMDDB 10.11 CUP4 is packaged in one .zip file.

The **UCMDDB_00156.zip** (for Windows) includes the following files/components:

- **HPUCMDDB_Server_10.11.CUP4.exe.** The installation of the version 10.11 CUP4 HP UCMDDB Server and Data Flow Probe for Windows.
- **HPCM_10.11.CUP4.exe.** The installation of version 10.11 CUP4 HP UCMDDB Configuration Manager for Windows.
- **ReleaseNotes.pdf** (this file)

The **UCMDDB_00157.zip** (for Linux) includes the following files/components:

- **HPUCMDDB_Server_10.11.CUP4.bin.** The installation of the version 10.11 CUP4 HP UCMDDB Server and Data Flow Probe for the Linux platform.
- **HPCM_10.11.CUP4.bin.** The installation of version 10.11 CUP4 HP UCMDDB Configuration Manager for the Linux platform.
- **ReleaseNotes.pdf** (this file)

System Requirements

For a list of system requirements, see the **HP UCMDDB Support Matrix** PDF file. Check the most previous Release Notes for any additions or changes to the matrix.

Note: If you are using an Oracle version that is prior to 10.2.0.5, you must apply the Oracle patch that fixes Oracle defect # 5866410. For details, go to the Oracle website and find the information regarding this defect number.

Install 10.11 CUP4 on the HP Universal CMDB and Configuration Manager Servers

CUP Installation for both HP Universal CMDB and Configuration Manager is performed through an automated procedure using the installation wizard.

You can still install the Data Flow Probes separately by upgrading the Data Flow Probes using the UCMDB user interface. For details, see "[HP Universal CMDB 10.11 CUP4 Manual Data Flow Probe Installation](#)" on [page 9](#).

Note:

- HP UCMDB 10.11 CUP4 can be installed only on top of an HP Universal CMDB version 10.11.
- HP UCMDB CM 10.11 CUP4 can be installed only on top of HP UCMDB CM 10.11.
- The UCMDB CUP version and the CM CUP version must be the same.

Pre-requisites - UCMDB Server and Data Flow Probes

1. Extract **UCMDB_00156.zip** (for Windows) or **UCMDB_00157.zip** (for Linux) to a temporary directory.
2. Stop the HP Universal CMDB 10.11 server and the HP Universal CMDB Integration Service (if running) before starting the 10.11 CUP4 installation.

Note: If you have a High Availability configuration, the CUP must be installed on all the servers in the cluster, and prior to installation, you must stop all the servers in the cluster.

3. If you have received private patches for the Data Flow Probe, you must delete them before performing the upgrade. These steps for deleting a private patch must be followed whether you are upgrading the probes during the installation wizard, or if you upgrading the probes using the UCMDB user interface after installation is complete.
 - a. Stop the Data Flow Probe.
 - b. Delete all private patches that were installed on the system prior to this CUP by deleting the following directory:

\\hp\UCMDB\DataFlowProbe\classes directory

- c. Start up the version 10.11 Data Flow Probe.

CUP Installation

You must first install the UCMDB CUP, start up the server, and then perform the Configuration Manager (CM) CUP installation.

1. For UCMDB: Double-click the file **HPUCMDB_Server_10.11.CUP4.exe** (for Windows) or **HPUCMDB_Server_10.11.CUP4.bin** (for Linux) to open the HP Universal CMDB Server CUP Installation Wizard.

For Configuration Manager: Double click the file **HPCM_10.11.CUP4.exe** (for Windows) or **HPCM_10.11.CUP4.bin** (for Linux) to open the HP Universal CMDB Configuration Manager CUP Installation Wizard.

2. While running the wizard:
 - In the Choose Install Folder screen, select the installation directory in which UCMDB/CM is already installed.
 - For UCMDB, in the Install Data Flow Probe CUP screen, select the following option:
 - **Automatically update Data Flow Probe with the new CUP version** to automatically update during this installation all the Data Flow Probes reporting to this UCMDB.
 - **Update the Data Flow Probe manually** to update the Data Flow Probes reporting to this UCMDB using the UCMDB user interface after completing the installation of this CUP on the UCMDB server. For details, see "[HP Universal CMDB 10.11 CUP4 Manual Data Flow Probe Installation](#)" on the next page.
 - In the Required Actions screen, follow the instruction to ensure that the server is down.
3. Once the installation wizard for UCMDB is completed, start up the version 10.11 server per the instructions in the Deployment Guide for version 10.11. Go back to step 1 to install the CM CUP.

Once the CM CUP installation is completed, start up Configuration Manager version 10.11 per the instructions in the Deployment Guide for version 10.11.

HP Universal CMDB 10.11 CUP4 Manual Data Flow Probe Installation

(Applicable only when **Update the Data Flow Probes manually** is selected in the CUP installation wizard.)

To install the Data Flow Probe CUP upgrade using the UCMDB user interface, follow these steps.

Note: All Data Flow Probes that are associated with the UCMDB are upgraded.

1. If you have received private patches for the Data Flow Probe, perform the steps in the section ["Pre-requisites - UCMDB Server and Data Flow Probes"](#) on page 7.
2. In UCMDB, go to **Data Flow Management > Data Flow Probe Setup**, and click **Deploy Probe Upgrade**.
3. In the Deploy Probe Upgrade dialog box, navigate to the **<SERVER_HOME>\content\probe_patch\probe-patch-10.11.CUP4-windows/linux.zip** and click **OK**.

HP Universal CMDB and CM 10.11 CUP4 Uninstall Procedure

When performing the uninstall procedure, this procedure must be performed for both the UCMDB Server and the Data Flow probes, as well as Configuration Manager.

1. Stop the HP Universal CMDB and Configuration Manager servers, and all running Data Flow Probes before uninstalling the version CUP.
2. For UCMDB:
 - Windows: Go to **<CMDB installation folder>\UninstallerCup** and double-click **Uninstall HP Universal CMDB Server CUP**. After the CUP is successfully uninstalled, go to **<CMDB installation folder>\runtime** and delete the **jsp** and **jetty-cache** folders.
 - Linux: Go to **<CMDB installation folder>/UninstallerCup** and run **Uninstall HP Universal CMDB Server CUP**. After the CUP is successfully uninstalled, go to **<CMDB installation folder>/runtime** and delete the **jsp** and **jetty-cache** folders.

3. For Configuration Manager:
 - Windows: Go to **Start** menu > **Programs** > **HP Universal CMDB Configuration Manager 10.11** and double click **Uninstall HP Universal CMDB Configuration Manager 10.11 CUP4**.
 - Linux: Go to **<CM installation folder>/_sp_installation/** and run **HPCM_10.11_CUP4-Uninstall**.
4. Uninstall all existing Probes as follows:
 - a. **Start > All Programs > HP UCMDB > Uninstall Data Flow Probe.**
 - b. Start the server.
 - c. Undeploy the **probeUpdate** package.
5. Reinstall the Probes with the same configuration, that is, use the same Probe IDs, domain names, and server names as for the previous Probe installations. Remember that the Probe ID is case sensitive.

Note: After performing an upgrade and installing the new Data Flow Probe, all the Discovery jobs that were active before the upgrade are automatically run.

Notes

- 10.11 CUP3 supports CP15. CP15 can be downloaded at <https://hpln.hp.com/node/11274/contentfiles/?dir=22815>.

However, the following adapters in CP15 cannot work with 10.11 CUP3 (they can only work properly with 10.20):

- ASM adapters
- Top-Down Discovery adapters
- AM Generic Adapter
- Service Manager Enhanced Adapter

10.11 CUP3 can work with UDC 0.91. UDC 0.91 can be downloaded at <https://hpln.hp.com/node/11/otherfiles/?dir=15055>.

- HP provides the following recommendations for increasing the security of your overall infrastructure for informational purposes only. These are only recommendations and are not intended to be a guarantee of protection against all potential vulnerabilities and attacks. Please note that some security measures may impact the features and functionality of your overall system; so, it is recommended that every customer become aware of those impacts when implementing any changes to your environment.

Use of this HP Software Product [UCMDB CUP] may require the pre-installation of certain third-party components that are not provided by HP ("Third Party Components"). HP recommends that its customers check frequently for the most current updates to the Third Party Components, which may include fixes or patches for security vulnerabilities.

- UCMDB server experiences performance degradation after deploying 10.11 CUP3, because all discovery jobs send a full result set to the UCMDB server. (QCCR1H99640)

The UCMDB Probe normally caches data. Some CUPs require a database schema change and the cache needs to be cleaned to ensure there are no unexpected issues. The probe will re-build the cache during the next discovery cycle. However since the probe no longer has the prior history, all newly discovered results are sent to the UCMDB Server for reconciliation. This causes the additional load on the server.

Workaround: If you are concerned about the impact of extra load on the server, you can take one or more of the following actions:

- Inform users to expect a system slowdown
 - Schedule the CUP installation on weekend
 - Schedule the discovery jobs to run on weekend after the CUP installation
 - Spread out the normal discovery over a longer period of time by adjusting the discovery job schedule
- 10.11 CUP4 does not contain the latest MindTerm jar file (**mindterm-4.1.5.jar**). If you want to upgrade your MindTerm from version 4.0beta6 to 4.1.5, go to the following location and download the hotfix: <https://patch-hub.corp.hp.com/crypt-web/protected/viewContent.do?patchId=QCCR1H90627>.
 - JMX remote access on Configuration Manager is not secure enough. (QCCR1H98135)

Workaround: To secure the JMX remote access on Configuration Manager, do the following on the Configuration Manager machine:

- a. Stop the Windows CM service.
- b. Open a command prompt console as an Administrator.
- c. Navigate to the **<CM_Install_Home>\tomcat\bin** folder.
- d. Run the following command:

```
tomcat7w.exe //ES//HPUCMDBCM1010server0
```
- e. In the window that pops up, go to the **Java** tab and locate the **Java Options** textbox.
- f. In this textbox, remove the following three entries that refer to `jmxremote`:

```
-Dcom.sun.management.jmxremote.authenticate=false  
-Dcom.sun.management.jmxremote.ssl=false  
-Dcom.sun.management.jmxremote.port=39600
```
- g. Click **OK**.
- h. Start the Windows Configuration Manager service.

- InfrastructureService models are working with the following types of custom key attributes used for identification (without the **Name** attribute): boolean, date number, double number, float number, integer, list of integers, list of strings, long number, string.

However, the following types of attributes are not supported: bytes, xml, some custom lists (such as lists of dates).

- The priority for TQL queries under the pattern-based model are changed from medium on UCMDB 9.05 to inactive on UCMDB 10.xx. The performance may be affected if the TQL queries under the pattern-based model are set to low or medium priority on UCMDB 10.xx. In this case, you can see that the locked gates and calculation for scheduled pattern-based model can take a couple of hours. (QCCR1H95041)
- If you want to change the default credentials for basic authentication, do the following:
 - a. Open the JMX Console of the UCMDB Server side, enter **changeBasicAuthenticationCredential** in the quick search field and click the link that appears.
 - b. Specify the **userName** and **password** that you want. For example:

changeBasicAuthenticationCredential

Change basic authentication credential.

Name	Type	Value	Description
customerid	int	<input type="text" value="1"/>	Customer Id
userName	java.lang.String	<input type="text" value="test"/>	new user name for basic authentication.
password	java.lang.String	<input type="text" value="123456"/>	new password for basic authentication.

Invoke

Note: Password must contain at least six characters.

- c. Click **Invoke**.
- d. Encrypt the password by using the JMX Console of the probe side as follows:
 - i. Open the JMX Console of the probe side, enter **getEncryptedKeyPassword** in the quick search field and click the link that appears.

- ii. Enter the password that you specified.

getEncryptedKeyPassword

Encrypt a password for use with Keystore/Truststore properties file

Name	Type	Value	Description
Key Password	java.lang.String	<input type="text" value="123456"/>	
Invoke			

- iii. Click **Invoke** and then the encrypted password is generated.
- e. Copy the encrypted password.
- f. Edit the **DataFlowProbe.properties** file as follows:

```
appilog.agent.Probe.BasicAuth.User = <the user name that you specified>  
appilog.agent.Probe.BasicAuth.Pwd = <the encrypted password that you just  
copied>
```

- g. Save the change and then restart the probe.
- When the **appilog.collectors.storeDomainScopeDocument** property in the **DataFlowProbe.properties** file is set to **false**, some jobs which run in the remote process mode may fail, because the remote process cannot read the probe memory, thus having no access to the **domainScopeDocument** file stored in the memory. When the setting is false, the file is only stored in the probe memory.
Workaround: If some jobs run in the remote process mode, make sure that you set the value of the **appilog.collectors.storeDomainScopeDocument** property in the **DataFlowProbe.properties** file to **true**. (QCCR1H96126)
- When using PostgreSQL as your database on the Windows platform, the UCMDB_Probe_DB service is not starting as a non-system user. This is a third-party product limitation, because PostgreSQL is able to "irrevocably give up administrative rights at startup". For details, see [this PostgreSQL wiki page](#). (QCCR1H96208)

Workaround: In order for the UCMDB_Probe_DB service to start properly, you may configure the **Log On** options for the UCMDB_Probe_DB service as follows:

- a. Locate the UCMDB_Probe_DB service in the Services window.
- b. Right-click **UCMDB_Probe_DB** and select **Properties**.
- c. In the UCMDB_Probe_DB Properties window, go to the **Log On** tab, and do either of the following:
 - Select the **Local System account** option.

Note: This is the recommended option, because the SYSTEM account can access all necessary folders according to the default settings on Windows.

- Select **This account**, and specify the account name and password.

Note: This option is NOT recommended. Even if you specify an administrator account, it will be treated as a common user account by PostgreSQL, because PostgreSQL is able to "irrevocably give up administrative rights at startup".

If you really need to specify a different account, make sure that the USERS group on your Windows platform has:

- **Read** and **Write** access to the **C:/hp/UCMDB/DataFlowProbe/pgsql** folder.
- **Read** access to the files in system library (for example, the **C:/Windows/System32** folder) that PostgreSQL needs to access.

For the list of files that PostgreSQL needs to access, see PostgreSQL documentation.

- d. Click **OK**.
- After deleting some customized protocols, adding or editing credentials or ranges may fail with the "Can not find class protocol" error. (QCCR1H96595)

Workaround: Before you add or edit credentials or ranges, do the following:

- a. Re-add the deleted protocol.

- b. Go to **Data Flow Management > Data Flow Probe Setup > Domains and Probes** pane > **Domains and Probes** root node > a domain > **Credentials**, locate the protocol that you just re-added.
 - c. Delete all credentials under this protocol, and click **OK** to save the change.
 - d. Delete the customized protocol again.
- After installing the CUP, manually redeploy the UCMDDB 9.x integration adapter package located in the **C:\hp\UCMDDB\UCMDBServer\content\adapters** directory. (QCCR1H96944)

If the package is not redeployed, the integration adapter still works, but the reconciliation issue fixed in QCCR1H92320 will re-occur.

- A new attribute **isTopologyRequired** is added in the **<connected-ci-condition>** XML tag of the reconciliation rule of a CI type. Setting the **isTopologyRequired** attribute value to **true** overrides the UNKNOWN result with FALSE for a validation criterion when there are no connected CIs. (QCCR1H96982)

The following example shows the usage of the attribute, which is taken from the identification rule for the **sap_system** CI type:

```
<validation-criterion priority="2">
  <connected-ci-condition ciType="sap_app_server" linkType="membership"
  isTopologyRequired="true"conditionType="approveAndContradict">
    <overlap-fixed-operator number-of-matches="1"/>
  </connected-ci-condition>
</validation-criterion>
```

- **LIMITATION:** You cannot create one integration point for both data push and population. (QCCR1H97157)

Workaround: To create an integration point for both data push and population, do the following:

- a. Update the value for **Object Root** from **managed_object** to **root**.
 - i. Log in to UCMDDB with an administrator account and go to **Administration > Infrastructure Settings Manager**.
 - ii. From the **Filter by column** drop-down list, click **Name**, type **Object Root** in the text box and double-click the **Object Root** entry that is displayed.

- iii. In the Properties dialog, go to the **Current Value** field, change **managed_object** to **root**, and then click **Save**.
 - iv. Log out of UCMDB and log in to UCMDB again for the change to take effect.
- b. Add the **discoverypattern_mdr_type** attribute to **Auto Discovery Pattern definition**.
- i. Go to **Modeling > CI Type Manager > CI Types** pane > **Root** tree > **Data > Object > Configuration**, and click **Auto Discovery Pattern definition**.
 - ii. In the right pane, click the **Attributes** tab and click the **Add**  button.
 - iii. In the Add Attribute dialog, type **discoverypattern_mdr_type** in the **Attribute Name** and **Display Name** fields, and click **OK**.
- c. If you already create an integration point, delete it and create it again.
- d. Open Adapter Source Editor and save.
- i. Go to **Data Flow Management > Adapter Management > Resources** pane, select the adapter that is related to your integration point.
 - ii. Right-click the adapter, select **Edit adapter source**.
 - iii. In the Adapter Source Editor dialog, click **Save**.
- The **WebSphere to Web Server Dependency** job is causing **OutOfMemoryError** on the probe side. (QCCR1H97711)
Workaround: The probe requires at least 4G memory to run the **WebSphere to Web Server Dependency** job. Therefore, allocate at least 4G memory for the probe.
 - If the Enrichment rule is active, the calculation is triggered by attribute changes. Then the Enrichment rule will take into consideration only the changed values and constants when concatenating multiple attributes and constants. (QCCR1H97897)
Workaround: To calculate all attributes, make sure that the Enrichment rule is NOT active and use the scheduler to calculate at certain intervals.
 - (High Availability environment only) In order for all changes in Global Settings that require the server's restart to take effect, you must restart all nodes from the cluster (one by one or with the **restartCluster** JMX method). (QCCR1H98141)

- When you create an NNMi integration point in the CP13 environment, and then upgrade CP13 to CP15, an error is returned while running the integration job. (QCCR1H98191)

Workaround: To fix this issue, you must recreate the NNMi integration point in the CP15 environment.

- When upgrading the Data Flow Probe:
 - In a multi-customer environment, if the Data Flow Probe is not automatically upgraded to the latest CUP version, use the manual upgrade procedure to upgrade the Probe manually. For details on the manual upgrade procedure, see "How to Deploy a Data Flow Probe CUP Manually" in the *HP Universal CMDB Data Flow Management Guide*.
 - The automatic upgrade is not available for Data Flow Probes running on Linux. Use the manual upgrade procedure to upgrade the Probe manually. When the automatic upgrade runs on other Probes, it may begin to run for Probes running on Linux. In such a case, stop the upgrade and run the manual upgrade procedure.
 - The Data Flow Probe upgrade is only available for upgrades between CUP versions. When performing an upgrade to a major or minor release, you must reinstall the Probe.
 - When operating the Data Flow Probe Manager and the Data Flow Probe Gateway on separate machines (that is, separate mode), use the manual upgrade procedure to upgrade the Probe manually. For details on the manual upgrade procedure, see "How to Deploy a Data Flow Probe CUP Manually" in the *HP Universal CMDB Data Flow Management Guide*.
- If you encounter an error when installing the CUP under Linux on the **/tmp** directory because the **/tmp** directory is configured not to run executables, set the IATEMPDIR environment variable to a location with sufficient permissions and disk space. The IATEMPDIR variable is recognized by InstallAnywhere.
- Fixed a documentation error that occurred in the following location of the Content Guide: Supported Content > Supported Protocols > SSH Protocol. In the Command List column, the description is missing a period. Specifically, the following sentence "For example, entering *uname would select all of the following expressions:" should be changed to "For example, entering .*uname would select all of the following expressions:" (QCCR1H92999)
- No password is required when running clearprobedata.bat to clear the data on the Data Flow Probe. (QCCR1H93320)

- When the parameter `appilog.collectors.storeDomainScopeDocument` in the **<UCMDB_HOME>\DataFlowProbe\conf\DataFlowProbe.properties** file is set to false, some jobs which run in the remote process mode fail because the process cannot get domainScopeDocument from the file system. As a workaround, set the parameter `appilog.collectors.storeDomainScopeDocument` to true. (QCCR1H93459)
- Basic authentication does not support probes that are installed in separate mode.
- Before the installation of 10.11 CUP2 (fixed QCCR1H92519), a CIT may have gotten corrupted and no instances of it could be created. This issue is caused by newly-created classes that contain attribute qualifiers on **root_iconproperties**. The following error message is displayed in the log:

"[ErrorCode [404] Attribute [[0]] contains calculated attribute qualifier without items in it.{root_ iconproperties}]. Attribute [root_ iconproperties] contains calculated attribute qualifier without items in it."

Workaround: After installing this CUP, this issue no longer happens but if a CIT is corrupted, it must be manually edited in the XML. Do the following:

- a. Export all class models using `jmx exportClassModelToXml` from Class Model Services.
 - b. Locate the **<Attribute-Qualifier name="CALCULATED_ATTRIBUTE" is-factory="false" />** line in the **root_ iconproperties Attribute-Override** section as follows.

```
<Attribute-Override is-partially-override="true" name="root_ iconproperties" is-factory="true">
  <Attribute-Qualifiers>
    <Attribute-Qualifier name="APPLICATIVE_ATTRIBUTE" is-factory="true" origin="basic-deployment" version="10" />
    <Attribute-Qualifier name="CALCULATED_ATTRIBUTE" is-factory="false" />
```
 - c. Note down the CITs whose definitions contain the above problematic line.
 - d. Log in to the UCMDDB UI and go to **Modeling > CI Type Manager**.
 - e. Locate the CITs that you noted down and export them to XML.
 - f. Open the XML file and delete the **<Attribute-Qualifier name="CALCULATED_ATTRIBUTE" is-factory="false"/>** line.
 - g. Save the resource and restart the server.
- Fixed an issue that occurred when properties of any CI under the CIT **running_software** could not be

viewed (QCCR1H95512). This issue is caused by the fact that a certain custom attribute with the default constraint or index cannot be deleted. The issue is reproduced only on MSSQL when a new attribute is deleted.

To delete the problematic attribute from the database, perform the following steps:

- a. Stop the UCMDB server.
- b. Back up the UCMDB database. Make sure that the database is backed up appropriately and UCMDB starts with the database backup.
- c. Run the following scripts to delete the attribute from all tables: **1_script_delete_index.sql** and **2_script_delete_constraint.sql** (See "[Appendixes](#)" on page 37). The scripts must be run by Database Administrator in CMDB Database. Set the column name or attribute name to be deleted in the scripts (SET @column_name = 'Column Name').
 - If the attribute has an index property, first run **1_script_delete_index.sql** and then run **2_script_delete_constraint.sql**.
 - If the attribute does not have an index property, simply run **2_script_delete_constraint.sql**.

Note: These scripts will be useless if the same attribute is defined for more classes (more CI Types). For one CI Type, the attribute can be deleted from all related types (from all the children). If you are not clear which CI Types include the attribute, run the SQL statement that is described in the following step e to verify.

- d. Save the output generated on MSSQL in the text file.
- e. Run the following SQL statement to check whether any columns are left. Replace the **Column Name** value with your column name or attribute name that you want to delete.

```
use 'CMDB DB NAME'
```

```
SELECT
    df.name constraint_name ,
    t.name table_name
FROM sys.default_constraints df
INNER JOIN sys.tables t ON df.parent_object_id = t.object_id
INNER JOIN sys.columns c ON df.parent_object_id = c.object_id AND df.parent_
column_id = c.column_id
WHERE c.name = 'Column Name'
```

- f. Start UCMDB.
- g. Run **rebuildModelDBSchemaAndViews** and **rebuildModelViews** from UCMDB JMX Console under UCMDB:service=DAL services for the CI Type whose attribute is deleted. Check for any errors in dal logs.
- h. Check the CI properties from IT Universe Manager.

Note: This issue also occurs when certain custom attributes are deleted. A permanent fix will be available in the next UCMDB version (QCCR1H91560).

- Fixed an issue that occurred when Pattern-based models were inconsistent with the TQL if the view was changed (QCCR1H95551). This issue is caused by the fact that Package Manager Resource Selector cannot be accessed while creating a new package or opening an existent package. The following error message is displayed in the logs:

"Caused by: java.lang.IllegalStateException: EnrichmentBusinessViewDefinition *ModelName* is not synchronized with its pattern. Element number 12 does not exist in pattern graph."

ModelName and 12 in the error message could be different values.

To fix this issue, use one of the following two ways:

- Delete the model and then recreate it
 - i. Log in to UCMDB JMX Console and URM Services.
 - ii. Run method **listResources** for Resources of type: **Topology_ENRICHMENT_BUSINESS_VIEW**.
 - iii. Locate the EnrichmentBusinessView that is mentioned in the error message and delete it. Then the model is deleted.
 - iv. Recreate the model from Modeling Studio using the same TQL.
- Edit the unsynchronized resources of the problematic model
 - i. Log in to UCMDB JMX Console and URM Services.
 - ii. Run method **listResources** for Resources of type: **Topology_ENRICHMENT_BUSINESS_VIEW** and **Topology_TQL**.

- iii. Retrieve the xml definition of the **Topology_ENRICHMENT_BUSINESS_VIEW** and **Topology_TQL** of the problematic model.
- iv. Open the **EnrichmentBusinessView** and locate the ID that is mentioned in the error message.

```
<CmdbProperty>
    <Key>nodeNumberEnd2</Key>
    <Type>integer</Type>
    <Value>12</Value>
</CmdbProperty>
```

- v. Do one of the following:
 - Change the missing ID in the **EnrichmentBusinessView** with an existing one from the **Topology_TQL** definition and save the resource.
 - Add the missing ID in the **Topology_TQL** definition by replacing an existing one and then save the resource.

Here is an example:

```
<tql:node class="node" name="Node" id="19">
    <tql:where>
        <tql:data-stores>
            <tql:data-store>UCMDB</tql:data-store>
        </tql:data-stores>
    </tql:where>
</tql:node>
```

If you do not have id 12 in the tql, you can change it in the following way:

```
<tql:node class="node" name="Node" id="12">
```

Note: Pattern-based models must be created or edited only from the model instead of from the TQL. The same TQL cannot be used both by the model and by the view.

Enhancements Requests

Here is a list of the enhancement requests that were implemented in the CUP4 release.

Global ID	Problem	Solution
QCCR1H98666	Pattern Based Models (PBMs) created based on existing Instance Base Models (IBMs) in an environment (for example, development) are not available in the Package Manager for exporting to other environments.	Enhanced the Package Manager to provide the capability of exporting all the resources of a Pattern Based Model that is created based on an Instance Base Model, including the business enrichment, TQL, and model CI. Now Pattern Based Models that were created based on existing Instance Based Models are available in the Package Manager for selection when exporting a package.

Fixed Defects for UCMDB 10.11 CUP4

Here is a list of the defects fixed in the CUP4 release.

Global ID	Problem	Solution
QCCR1H95235	After changing the SAP Server icons in CI Type Manager, the changes do not appear in the CI Type tree or anywhere else.	Now SAP Server icons in CI Type Manager can be changed and the changes appear as expected.
QCCR1H95558	After upgrading from 10.01 CUP4 to 10.01 CUP10, discovery probes in non-union mode cannot run discovery jobs.	Now discovery probes in non-union mode can run discovery jobs.
QCCR1H97566	Many triggers for several discovery jobs fail randomly with the "Java.lang.NullPointerException" error.	Fixed the issue by a code change so that discovery jobs can successfully run.
QCCR1H97715	The Server database returns the time-out error when processing the result.	Fixed the issue by modifying the batch chunk from 10000 to 200 so that the chunk can be processed in a short time.
QCCR1H97925	The tenantOwner attribute is wrong for some CIs.	Call Home can return the correct tenant owner ID for CIs.
QCCR1H97950	When using Java API setDiscoveryConfigurationXML to update Probe IP address ranges, all	Fixed the issue by adding a new method void setDiscoveryConfigurationXML (String xmlString, boolean includeGroup) . If you want to update IP address ranges

Global ID	Problem	Solution
	<p>jobs are restarted because setDiscoveryConfigurationXML contains the following parameter that enables or disables all jobs in the group:</p> <pre data-bbox="428 520 857 672" style="background-color: #f0f0f0; padding: 5px;"> <DiscoveryGroup name="Network"> <IsEnabled>True </IsEnabled> </pre>	<p>and credentials only, you can use this new method by setting the includeGroup parameter to false. For more details, see the What's New section.</p>
QCCR1H98037	<p>The values of normalized fields are not in a user-friendly format.</p>	<p>Fixed the issue by unifying the result content when Data Flow Probe sends the result to UCMDB.</p>
QCCR1H98051	<p>When multiples roles are assigned to a user, the user's permission level is set to the role with the minimum permissions. This is the desired behavior, but it is not explained in full details, thus causing confusion.</p>	<p>The HP Universal CMDB Administration Guide is updated as follows:</p> <p>For CIT Menu Items, you select a CIT from the tree and then select specific actions from the Available Actions pane and move them to the Selected Actions pane. You can also right-click a CIT and select the actions from the pop-up dialog box. If no permissions are assigned for any CIT, all the menu items are permitted by default (in accordance with the permissions granted in the General Actions tab).</p> <p>The following important note is added to clarify the desired behavior:</p> <div data-bbox="894 1486 1369 1869" style="background-color: #f0f0f0; padding: 10px;"> <p>Note: The above principle remains valid when there are multiple roles with menu items permissions/general actions. Both the menu items permissions and the general actions are accumulated. If there are NO menu items permissions accumulated from all the user's roles, all the menu</p> </div>

Global ID	Problem	Solution
		<p>items are permitted by default (in accordance with the permissions granted by accumulating all the General Actions from all the user's roles). In the opposite way, if there are menu items permissions accumulated from all the user's roles, they will be taken into account and the UI will enforce them, even in the case when a role with no CIT Menu Items is aggregated with a role with CIT Menu Items.</p>
QCCR1H98095	Browser search stops working because of changes in the snapshot CI type instances.	Browser search works as expected.
QCCR1H98116	The following error message is returned in the management zone: "Failed to initialize CM client (sleep interrupted)".	Now credentials can be fetched from the Confidential Manager Client.
QCCR1H98117	Many unsent results exist on probes.	Fixed the issue by reducing the unsent results on probes.
QCCR1H98290	Custom jobs are stuck with zero working threads, for example, no triggers on one probe are running.	Custom jobs now can run as expected.
QCCR1H98458	The "NullPointerException" error is thrown in processing discovery results.	Fixed the issue to avoid processing null objects.
QCCR1H98485	Identification by key attributes is not working for certain types of attributes (for example, long) when you create an InfrastructureService model.	<p>Now InfrastructureService models are working with the following types of custom key attributes used for identification (without the Name attribute):</p> <p>boolean, date number, double number, float number, integer, list of integers, list of strings, long number, string.</p>

Global ID	Problem	Solution
		However, the following types of attributes are not supported: bytes, xml, some custom lists (such as lists of dates).
QCCR1H98737	When a Full Synchronization is completed, running a differential synchronization with NNMi pull integration sends Layer 2 Connection CIs without the required reconciliation information.	After a Full Synchronization, a differential synchronization can be run as expected.
QCCR1H99001	After you upgrade to 10.11 CUP3, the Normalization rule does not work.	The Normalization rule works as expected.

Fixed Defects for UCMDB 10.11 CUP3

Here is a list of the defects fixed in the CUP3 release.

Global ID	Summary
QCCR1H88798	Fixed an issue that occurred when global_id was not updated if UCMDB was not configured as a global_id generator.
QCCR1H90278	Added the functionality to re-run a job with commlog enabled.
QCCR1H91007	Fixed an issue that occurred when trying to populate some links from Service Manager to UCMDB and errors were returned.
QCCR1H91923	Fixed an issue that occurred when resources were not updated in UCMDB during the content pack deployment because of double file extensions.
QCCR1H92224	Fixed an issue that occurred when the input parameters for the content validator of a job was not available.
QCCR1H92742	Fixed an issue that occurred when the AM integration failed with an error.
QCCR1H92925	Fixed an issue that occurred when the change report did not work correctly if selecting the LastMonth option as the parameter.
QCCR1H93378	Fixed an issue that occurred when all triggers were added to the job with Probe Limit

Global ID	Summary
	disabled.
QCCR1H94507	Fixed an issue that occurred when the <code>getProbeFromHost()</code> method did not check whether an IP address was configured in the management zone range before using this IP address's probe name.
QCCR1H94686	Fixed an issue that occurred when editing a service tree failed with the following error: "Pattern existing ci tql has identical names for its (Node or Link) Elements".
QCCR1H94855	Fixed an issue that occurred when the ORA-01400 and ORA-30926 errors were returned on probe logs.
QCCR1H94956	Fixed an issue that occurred when the probe did not properly run from a restart.
QCCR1H95112	Fixed an issue that occurred when errors were returned by the Viewer on the Windows 2012 probe.
QCCR1H95195	Fixed an issue that occurred when the scheduler in the Integration Studio could not support a long repetition period.
QCCR1H95277	Fixed an issue that occurred when the discovery task took several hours to be dispatched to the probe.
QCCR1H95322	Fixed an issue that occurred when the data was not displayed in the CI Type Manager if a particular CI type had two attributes with the same name.
QCCR1H95544	Fixed an issue that occurred when software that was registered by Package Rules could not be identified in UCMDB.
QCCR1H95599	Fixed an issue that occurred when the external policies results were invisible in Configuration Manager.
QCCR1H95638 QCCR1H99900	<p>Fixed an issue that occurred when UCMDB incorrectly assigned Universal Discovery full licenses to incomplete Node CIs with no operating system that were not in the probe scope.</p> <p>Note: In order for this fix to work, make sure you clean up the UCMDB database by running the following SQL script:</p> <pre>update CDM_NODE_1 set A_LIC_TYPE_UDF = 0, A_LIC_ TYPE_UDI = 0 where A_HOST_KEY is not null;</pre>
QCCR1H95665	Fixed an issue that occurred when many "java.lang.NullPointerException" errors

Global ID	Summary
	occurred in the probe-error.log.
QCCR1H95698	Fixed an issue that occurred when the "java.sql.BatchUpdateException" errors constantly occurred in the probe-error.log.
QCCR1H95813	Fixed an issue that occurred when a relationship could not be individually deleted from the IT Universe Manager.
QCCR1H95852	Fixed an issue that occurred when the "Cannot invoke trigger" error was returned.
QCCR1H95915	Fixed an issue that occurred when UNIX nodes were incorrectly merged.
QCCR1H96037	Fixed an issue that occurred when user.zsai was incorrectly imported into the UCMDB Software Library using Import SAI file .
QCCR1H96176	Fixed an issue that occurred when the scheduler in the Integration Studio could not support Week for the Interval repetition.
QCCR1H96216	Fixed an issue that occurred when UCMDB Server encountered the OutOfMemoryError in Java heap in processing the discovery results of the Host Resources by Shell and Host Applications by Shell jobs.
QCCR1H96241	Fixed an issue that occurred when an error was returned while running loggrabber.bat .
QCCR1H96242	Fixed an issue that occurred when the "java.lang.RuntimeException: Could not find domain" error was returned.
QCCR1H96251	Fixed an issue that occurred when the authorization failed with errors.
QCCR1H96267	Fixed an issue that occurred when the Host Applications by Shell job failed on the UCMDB Server caused by the "java.lang.NullPointerException" error.
QCCR1H96324	Fixed an issue that occurred when the discovery status in the management zone did not update.
QCCR1H96336	<p>Added the capability to control, when LDAP authentication is enabled, whether non-interactive flows are verified against the LDAP Server or not. By default, when LDAP authentication is enabled, all the authentication flows, whether interactive (manual user login) or non-interactive (authentication of integrations, Web Services, API's) are checked in the LDAP repository.</p> <p>A new setting enable.ldap.authentication.in.non.interactive.flow is added to control whether the non-interactive flows should be verified against the LDAP Server</p>

Global ID	Summary
	or not. By default, it is set on true . When setting to false , the-non interactive flows will be verified only against the local UCMDB user repository.
QCCR1H96349	Fixed an issue that occurred when not all Trigger CIs were dispatched to the probes correctly.
QCCR1H96397	<p>Added the Enable the use of the pfiles command check box to allow you to enable or disable the use of pfiles command in TCP/IP connectivity detection in scanner on the Solaris and HP-UX platforms.</p> <p>To enable the use of pfiles command in TCP/IP connectivity detection on the Solaris or HP-UX platform when you generate scanners,</p> <ol style="list-style-type: none"> 1. Go to Data Flow Management > Adapter Management > Resources > InventoryDiscovery > Scanner Configuration Files > <Select a configuration file (.cxz) file>. 2. In the right pane, click . 3. In the Scanner Generate (Manual Deployment Mode) dialog box that opens, provide necessary information and go to the Scanner Options page. 4. Go to the Miscellaneous tab, and select the Enable the use of the pfiles command check box for the TCP/IP connectivity options section. By default this setting is not selected.
QCCR1H96504	Fixed an issue that occurred when generating a CI Change report took too much time.
QCCR1H96577	Improved the UCMDB Browser search performance. Folding rules are configurable through a new setting cmdb.search.enriching.use.folding.rules for search enriching.
QCCR1H96626	Improved the UCMDB Browser search performance. Enriching no longer runs for a large amount of CIs.
QCCR1H96659	Improved the return messages for an integration point job that operates on a busy Data Flow Probe.
QCCR1H96660	<p>Fixed an issue that occurred when the push adapter did not check credentials.</p> <p>Note: You must manually redeploy the push adapter.</p>

Global ID	Summary
QCCR1H96685	Fixed an issue that occurred when discovery jobs could not be saved under existing discovery modules after upgrading to 10.11 CUP2.
QCCR1H96688	Fixed an issue that occurred when the Enable aging attribute of CIs that were created by the Import from Excel adapter was true though this attribute was set to false.
QCCR1H96783	Fixed an issue that occurred when the push to DB integration was triggered at each server restart.
QCCR1H96842	Fixed an issue that occurred when the UCMDB to UCMDB push adapter returned an error message.
QCCR1H96845	Fixed an issue that occurred when ExternalImpl threw "NullPointerException" errors for attributes of type DATE and BYTES.
QCCR1H96907	Fixed an issue that occurred when the Generic Database Adapter did not automatically delete CIs or links.
QCCR1H96982	<p>Fixed an issue that caused an incorrect merging of the sap_system CIs in rare cases when the associated node could not be identified and inserted into UCMDB.</p> <p>As a result, a new attribute isTopologyRequired is added in the <connected-ci-condition> XML tag of the reconciliation rule of a CI type. For details, see the Notes section.</p>
QCCR1H97031	Fixed the null pointer exception issue that occurred when processing the NNMI integration data.
QCCR1H97099	Fixed an issue that occurred when the Number of Changes report failed on database selection with the following error: "Failed to load report".
QCCR1H97103	Fixed an issue that occurred when about 1000 CIs that were in the results of the trigger query disappeared in the triggered CIs list.
QCCR1H97157	<p>Fixed an issue that occurred when the Management Data Repositories (MDR) licenses were counted by integration points. A new mechanism is provided to allow users to create one integration point for both data push and population.</p> <p>For instructions about creating one integration for both data push and population, see the Notes section.</p> <p>Note: Deployment of the Universal Discovery Content Pack 15.00 is required for</p>

Global ID	Summary
	<p style="background-color: #f0f0f0; padding: 5px;">this defect fix to work.</p>
QCCR1H97168	Fixed an issue that occurred when the following error was returned: "Can't add to DataContainer because its size larger than the fuse 200000 which defined by reconciliation.internal.data.container.size.fuse".
QCCR1H97197	Fixed an issue that occurred when the "collection error -1(-1)" error occurred in the Analysis Workbench after performing a software teaching and using the "Unload Scan File" function.
QCCR1H97273	Fixed an issue that occurred when new errors were returned after applying the ORA30926_classes.zip hotfix.
QCCR1H97374	Added procedure on how to disable the HTTP TRACE or TRACK methods on the probe.
QCCR1H97512	Fixed an issue that occurred when the UCMDB-NNMi integration failed with reconciliation errors on Non-SNMP nodes.
QCCR1H97779	<p>Fixed an inconsistency issue that occurred at minor upgrade from UCMDB 10.01 to UCMDB 10.1x. The links were not migrated correctly from the ROOT table to the ROOT_LINK table during the minor upgrade procedure.</p> <p>If you plan to upgrade from UCMDB 10.01 to UCMDB 10.1x, it is recommended that you proceed with upgrading directly to UCMDB 10.11 CUP3. That is to say, after UCMDB 10.11 is installed, do NOT start the UCMDB server yet. Only after UCMDB 10.11 CUP3 is applied, start the UCMDB Server, which will then trigger the minor upgrade.</p>
QCCR1H97790	Fixed an issue that occurred when the recognition engine incorrectly reported applications after importing a new user SAI file in the Software Library in UCMDB.
QCCR1H97871	Fixed an issue that occurred when the last use date for the discovered software was incorrect.
QCCR1H97888	Fixed an issue that occurred when the NNMi sync took a long time to insert data into UCMDB.
QCCR1H97904	<p>Fixed an issue that occurred when false restarts of UCMDB writer server happened occasionally.</p> <p>Important: Before starting the UCMDB server, open the \\UCMDBServer\bin\wrapper.conf file, locate the following settings and modify their values as indicated below:</p> <div style="background-color: #f0f0f0; height: 80px; margin-top: 10px;"></div>

Global ID	Summary
	<pre> wrapper.cpu.timeout=60 wrapper.ping.timeout=320 wrapper.ping.interval=30 wrapper.stop.timeout=320 wrapper.shutdown.timeout=320 wrapper.jvm_exit.timeout=320 </pre>
QCCR1H97941	Fixed an issue that occurred when Infrastructure Service instances could not be created without a name value.

Fixed Defects for UCMDB 10.11 CUP2

Here is a list of the defects fixed in the CUP2 release.

Global ID	Summary
QCCR1C20050	Added support for reporting multiple installations of the same software version.
QCCR1H92474	Fixed an issue that occurred when the MSSQL Server Connection by SQL job failed to discover while using the NTLM authentication.
QCCR1H94134	Fixed an issue that occurred when trigger CIs for jobs under the management zone were in the status of Progress . The UI status of the trigger CI did not update and even continued for several days.
QCCR1H94525	Fixed an issue that occurred when a misleading message indicating that all the CIs were touched was returned when using the touch window.
QCCR1H94615	Fixed an issue that occurred when the Host Applications by shell job reported a node CI without any properties except one IP address.
QCCR1H94693	Fixed an issue that occurred when the upgrade from 9.05 to 10.10 failed because of the missing of the server_side attribute for the adapter_config class.
QCCR1H94792	Added the time value for the date cells in exported Microsoft Excel reports.
QCCR1H94815	Fixed an issue that occurred when the XML Enrichment service could not start on any probes with the timezone of GMT +9:30 because of the incorrect WrapperEnricherLicense.conf.
QCCR1H94832	Fixed an issue that occurred when discovery jobs stopped triggering all available CIs after the upgrade from 10.10 to 10.11.

Global ID	Summary
QCCR1H94901	Fixed an issue that occurred when the Merge Clustered Software job did not properly merge the duplicated database instances that fit the trigger TQL.
QCCR1H95016	Fixed an issue that occurred when the Inventory Discovery by Scanner job did not display the correct trigger count.
QCCR1H95063	Fixed an issue that occurred when the Layer2 Topology Import job from NNMi failed with the following error "ORA-12899: value too large for column "UCMDB10"."DDM_TEMP_MAPPINGS"."TEMPID" (actual: 53, maximum: 43)".
QCCR1H95112	Fixed an issue that occurred when Viewer did not work and errors were returned on Windows 2012 probe.
QCCR1H95146	Fixed an issue that occurred when UCMDB on postgresql could not modify the CIT attribute size.
QCCR1H95157	Fixed an issue that occurred when the disconnected 9.05 probes from UCMDB could not be removed.
QCCR1H95182	Fixed an issue that occurred when the Package Manager resource selection took a long time to populate on UI.
QCCR1H95201	Fixed an issue that occurred when the custom adapter and script were deleted from Adapter Management > Resources > Packages > <<No Package>> .
QCCR1H95216	Fixed an issue that occurred when a newly-installed probe or LWP could not connect the UCMDB server with basic authentication enabled.
QCCR1H95223	Fixed an issue that occurred when the topology reporting by SiteScope integrated with BSM failed without any alerts.
QCCR1H95264	Added Application-Name to Manifest of GUI jars.
QCCR1H95284	Fixed an issue that occurred when the following warning message in the WrapperProbeGw.log file was returned while running the Inventory Discovery by Scanner job: "Can not execute the script. The reason is forceDontExecute=false or the script file contains mainfunction=false".
QCCR1H95347	Fixed an issue that occurred when searching in UCMDB Browser froze the server.
QCCR1H95470	Fixed an issue that occurred when the Push IDs into NNMi adapter produced the following errors in RemoteProcesses.log: "The ucmdb_wrapper.jar module, which is not valid, caused null"and "java.lang.ExceptionInInitializerError".

Global ID	Summary
QCCR1H95472	Fixed an issue that occurred when manually deployed scanners could not be created.
QCCR1H95545	Fixed an issue that occurred when a Data Flow Probe randomly-stopped discovering and sending results to the server.
Configuration Manager Fixed Defects	
QCCR1H95306	Fixed an issue that occurred when the current version of the view did not match the last authorized version.
QCCR1H95599	Fixed an issue that occurred when the external policies results were invisible in Configuration Manager.

Fixed Defects for UCMDB 10.11 CUP1

Here is a list of the defects fixed in the CUP1 release.

Global ID	Summary
QCCR1H84172	Windows Server 2012 is supported for Data Flow Probe and Universal Discovery.
QCCR1H89618	Fixed an issue that occurred when UCMDB Configuration Manager login is case sensitive.
QCCR1H91624	Fixed an issue that occurred when a trigger was dispatched to the wrong Data Flow Probe.
QCCR1H93238	Fixed an issue that IP addresses CIs discovered by member probes of clusters cannot be dispatched on host connection jobs.
QCCR1H93287	Fixed an issue that occurred when Universal Discovery Agent application is not populated to UCMDB.
QCCR1H93297	Fixed an issue that occurred when the SCCM adapter was configured to use the temp table.
QCCR1H93418	Fixed an issue that occurred when modifying the output node for a pattern-based model and an error was returned.
QCCR1H93480	Fixed an issue that occurred when executing UCMDB API Web Service "updateProbeScope".
QCCR1H93712	Fixed an issue that occurred when some scan files are moved to scans\Failed\error

Global ID	Summary
	folder with error : String index out of range: -1.
QCCR1H93725	Added support for Oracle12c.
QCCR1H93798	Fixed an issue that occurred when new packages were not created.
QCCR1H93805	Fixed an issue that occurred when a user with no permissions attempts to login to UCMDB.
QCCR1H93836	Fixed an issue that occurred when WebSEAL passed the PD session cookie to the backend during a WebSEAL integration. A new setting is added which caused the browser cookies to be read at applet start time. The setting name is mam.web.should.read.web.browser.cookies.
QCCR1H93940	Fixed an issue that occurred when the UcmdbService calculateImpact() method is not able to cope with global Ids.
QCCR1H93980	Fixed an issue that occurred when a processing error was returned because of a List System Type definition.
QCCR1H93982	Fixed an issue that occurred when an "Access Denied" error was returned while logging in to Configuration Manager after an upgrade.
QCCR1H94051	Fixed an issue that occurred when Pattern-Based models with ENUM Attributes revert values back to default values.
QCCR1H94162	Fixed an issue that occurred when the Rerun discovery button did not rerun discovery and the following error message was returned: "maximum number of expressions in a list is 1000".
QCCR1H94313	Fixed an issue that occurred when SQL error messages were returned in the Data Flow Probe: "ddm_gw_task_results_pkey index violation".
QCCR1H94350	Fixed an issue that occurred when Class B/C IPs by ICMP jobs failed with error "java.lang.NumberFormatException: For input string..".

Documentation Errata

The following items are listed incorrectly in the documentation.

HP Universal CMDB Administration Guide

Important note about a user's CIT Menu Items permissions when both custom and Out Of Box roles are assigned to the user

Location: *HP Universal CMDB Administration Guide*, version 10.10, page 188

Error: When multiples roles are assigned to a user, the user's permission level is set to the role with the minimum permissions. This is the desired behavior, but it is not explained in full details, thus causing confusion. (QCCR1H98051)

Correction: Under the current bullet as follows,

- For **CIT Menu Items**, you select a CIT from the tree and then select specific actions from the Available Actions pane and move them to the Selected Actions pane. You can also right-click a CIT and select the actions from the pop-up dialog box. If no permissions are assigned for any CIT, all the menu items are permitted by default (in accordance with the permissions granted in the General Actions tab).

The following important note shall be added to clarify the desired behavior:

Note: The above principle remains valid when there are multiple roles with menu items permissions/general actions. Both the menu items permissions and the general actions are accumulated. If there are NO menu items permissions accumulated from all the user's roles, all the menu items are permitted by default (in accordance with the permissions granted by accumulating all the General Actions from all the user's roles). In the opposite way, if there are menu items permissions accumulated from all the user's roles, they will be taken into account and the UI will enforce them, even in the case when a role with no CIT Menu Items is aggregated with a role with CIT Menu Items.

Enable Secure Login for the JMX Console

To enable secure login for the JMX console,

1. Access the UCMDDB JMX console: Launch a Web browser and enter the following address:
http://<UCMDDB machine name or IP address>:8080/jmx-console. You may have to log in with a user name and password (default is sysadmin/sysadmin).

2. Locate **UCMDB:service=Ports Management Services** and click the link to open the Operations page.
3. Locate the **mapComponentToConnectors** operation.
4. To enable secure login for the JMX console, invoke the **mapComponentToConnectors** method with the following parameters:
 - o **componentName**: jmx-console
 - o **isHTTPS**: true
 - o All other flags: false
5. Restart the server.
6. Log in to the JMX console using **https://** and port **8443** (default) or the one for https if it was changed.

For example, **https://mymachine:8443**.

Note: HP also recommends you setting a strong password for the **sysadmin** user and any other user that can access the JMX console.

Appendixes

This appendix includes:

1_script_delete_index.sql	37
2_script_delete_constraint.sql	38

1_script_delete_index.sql

The **1_script_delete_index.sql** script is as follows:

```
use 'CMDB Database'  
  
declare  
  @column_name nvarchar(255),  
  @index_name nvarchar(255),
```

```
@table_name nvarchar(255),
@sql_str nvarchar(4000) = ''

SET @column_name = 'COLUMN_NAME'

DECLARE ColumnCursor CURSOR FOR
SELECT
    ind.name as index_name,
    t.name as table_name
FROM sys.indexes ind
INNER JOIN sys.index_columns ic
    ON ind.object_id = ic.object_id
    AND ind.index_id = ic.index_id
INNER JOIN sys.columns col
    ON ic.object_id = col.object_id
    AND ic.column_id = col.column_id
INNER JOIN sys.tables t
    ON ind.object_id = t.object_id
WHERE col.name = @column_name

OPEN ColumnCursor

FETCH NEXT FROM ColumnCursor INTO @index_name, @table_name
WHILE @@FETCH_STATUS = 0
BEGIN
    -- drop index
    set @sql_str = 'DROP INDEX ' + @index_name + ' ON ' + @table_name

    print @sql_str
    exec sp_executesql @sql_str

FETCH NEXT FROM ColumnCursor INTO @index_name, @table_name
END
CLOSE ColumnCursor
DEALLOCATE ColumnCursor
```

2_script_delete_constraint.sql

The **2_script_delete_constraint.sql** script is as follows:

```
use 'CMDB Database'

declare
    @column_name nvarchar(255),
    @constraint_name nvarchar(255),
    @table_name nvarchar(255),
    @sql_str nvarchar(4000) = ''
```

```
SET @column_name = 'COLUMN_NAME'

DECLARE ColumnCursor CURSOR FOR
SELECT
    df.name constraint_name ,
    t.name table_name
FROM sys.default_constraints df
INNER JOIN sys.tables t ON df.parent_object_id = t.object_id
INNER JOIN sys.columns c ON df.parent_object_id = c.object_id AND df.parent_column_
id = c.column_id
WHERE c.name = @column_name

OPEN ColumnCursor

FETCH NEXT FROM ColumnCursor INTO @constraint_name, @table_name
WHILE @@FETCH_STATUS = 0
BEGIN
    -- drop constraint
    set @sql_str = 'ALTER TABLE ' + @table_name + ' DROP CONSTRAINT ' + @constraint_
name
    print @sql_str
    exec sp_executesql @sql_str
    --drop column
    set @sql_str = 'ALTER TABLE ' + @table_name + ' DROP COLUMN ' + @column_name
    print @sql_str
    exec sp_executesql @sql_str

FETCH NEXT FROM ColumnCursor INTO @constraint_name, @table_name
END
CLOSE ColumnCursor
DEALLOCATE ColumnCursor
```

Send Documentation Feedback

If you have comments about this document, you can [contact the documentation team](#) by email. If an email client is configured on this system, click the link above and an email window opens with the following information in the subject line:

Feedback on Release Notes (Universal CMDB & Configuration Manager 10.11 CUP4)

Just add your feedback to the email and click send.

If no email client is available, copy the information above to a new message in a web mail client, and send your feedback to cms-doc@hp.com.

We appreciate your feedback!