

Peregrine

Connect-It



Remedy Service Management - AssetCenter

©2006 Copyright Peregrine Systems, Inc.
All Rights Reserved.

Information contained in this document is proprietary to Peregrine Systems, Incorporated, and may be used or disclosed only with written permission from Peregrine Systems, Inc. This manual, or any part thereof, may not be reproduced without the prior written permission of Peregrine Systems, Inc. This document refers to numerous products by their trade names. In most, if not all, cases these designations are claimed as Trademarks or Registered Trademarks by their respective companies.

Peregrine Systems and Connect-It are trademarks or registered trademarks of Peregrine Systems, Inc. or one of its affiliates.

This product includes software developed by the Apache Software Foundation (<http://www.apache.org>).

This document and the related software described in this manual are supplied under license or nondisclosure agreement and may be used or copied only in accordance with the terms of the agreement. The information in this document is subject to change without notice and does not represent a commitment on the part of Peregrine Systems, Inc. Contact Peregrine Systems, Inc., Customer Support to verify the date of the latest version of this document.

The names of companies and individuals used in the sample database and in examples in the manuals are fictitious and are intended to illustrate the use of the software. Any resemblance to actual companies or individuals, whether past or present, is purely coincidental.

If you need technical support for this product, or would like to request documentation for a product for which you are licensed, contact Peregrine Systems, Inc. Customer Support by email at support@peregrine.com.

If you have comments or suggestions about this documentation, contact Peregrine Systems, Inc. Technical Publications by email at doc_comments@peregrine.com.

This edition applies to version 3.6.0 of the licensed program

Connect-It

Peregrine Systems, Inc.
3611 Valley Centre Drive San Diego, CA 92130
858.481.5000
Fax 858.481.1751
www.peregrine.com



Table of Contents

Business process integration	7
Document Introduction	7
Assumptions	7
Technical reference	8
About data integration	8
Preintegration Set Up - AssetCenter	9
Preintegration Set Up - Remedy Service Management	10
Chapter 1. Initial Propagation of data to AssetCenter	15
Classification Information	15
Location Information	18
Department Information	19
People Information	20
Asset Information	21



List of Tables

1.1. Asset Natures	16
1.2. Contract Natures	16
1.3. Models	17
1.4. Contract Models	17
1.5. Location - Region and Site	18
1.6. Location -Address	18
1.7. Location -Office	19
1.8. Departments	20
1.9. People	20
1.10. Main Asset Information	22
1.11. Component Asset Information	23
1.12. Workstation/Computer Asset Information	24



Business process integration

Document Introduction

This document focuses on specific points of integration between RSM Helpdesk and AssetCenter.

There are two primary aspects to this integration.

- 1 The data replication between the two systems, people, assets, cost centers, request templates, etc.
- 2 The ability to bring the processes of Problem/Helpdesk management together with the processes of Asset Management.

Assumptions

This proposal is designed with the understanding that the prospective clients of this product will have Remedy HD 4.x or 5.x and have not purchased Remedy Asset Management as an add-on products.



Note:

Field support will be using AssetCenter for work orders. Helpdesk support engineers will be using RSM Helpdesk.

Technical reference

- Remedy Service Management Help Desk records are referenced as "RSM HD Ticket"
- Remedy Service Management Change Management records are referenced as "RSM Change Request"
- AssetCenter Requests are referenced as "AC Request"
- AssetCenter Integrated Tickets are referenced as "AC Ticket"
- AssetCenter Expenses Lines are referenced as "AC Expenses"

About data integration

This integration assumes an existing Remedy Help Desk implementation to which Peregrine AssetCenter is being added. Some existing data in Remedy Help Desk must be replicated in the AssetCenter database to assure synchronization and interoperability. Connect-It scenarios have been created to perform the initial propagation of data. After they have been configured to suit your environment, scheduling should be enabled to maintain replication.

Requirements

Software	Version
Action Request System	4.x or 5
Remedy Helpdesk	4.x or 5
AssetCenter	4.1

Software	Version
Connect-It	3.x

Supported Development Server Operating Systems

The following is a list of all server operating systems supported by the implementation process:

- Windows NT 4
- Windows 2000 Server Addition

Supported Client Operating Systems

The following is a list of all client operating systems supported by the implementation process

- Windows 95/98
- Windows NT 4
- Windows 2000

Supported DBMS

For a list of all DBMSs supported by the implementation process, refer to the compatibility matrix on the following web site: <http://support.peregrine.com>.

Preintegration Set Up - AssetCenter

To enable the integration of AssetCenter with the RSM products, a few steps must be taken in AssetCenter prior to running the Connect-It scenarios. It is important to the success of the integration that you follow these steps precisely.

- 1 To aid reconciliation, a Feature must be added to amPortfolio, amAsset and amComputer. - Import the feature fv_RemedyAssetID from the file **features.zip**.

Preintegration Set Up - Remedy Service Management

A few steps must be taken in on the Action Request Server prior to running the Connect-It scenarios. It is important to the success of the integration that you follow these steps precisely.

- 1 Run the Remedy install program, **NAME GOES HERE**, if you would like changes to your existing Remedy server to occur automatically. We have outlined the steps here, if you would like to do them manually or are tracking changes made to your server.
- 2 The data for hard disk size and memory size are stored in character fields in the form **AST:Workstation**. The data needs to be stored as an integer with units associated. To correct existing data, Peregrine has provided an escalation and filters to attempt to copy over to new fields, your existing data in the proper format. This is only intended as an aid. It will not change existing data, only attempt to populate new fields.

The following fields are imported to **AST:Workstation**.

Field Type	Data or Display-Only	Database Name	Field Number	Enumerated Value	Default Value
Integer	Data	IntHardDiskSize	200000052	n/a	n/a
Integer	Data	IntMemorySize	200000053	n/a	n/a
Selection	Data	Hard Disk Size Units	200000054	(0)MB,(1)GB	MB
Selection	Data	Memory Size Units	200000055	(0)MB,(1)K	MB
Integer	hidden/ Display-Only	zTmpUnit	230000014	n/a	n/a
Character - length 30	hidden/Display-Only	zTmpUnitPos	230000015	n/a	n/a

- 3 To facilitate the linking of AssetCenter records with Remedy records, we've implemented the scenarios to pass ID numbers and state values. To use these scenarios these fields need to add to **CHG:Change**, **CHG:Task** and **HPD:Helpdesk**.

Field Type	Data or Display-Only	Database Name	Field Number	Enumerated Value	Default Value
------------	----------------------	---------------	--------------	------------------	---------------

Selection	Data - Read-only	AC Status	260800900	(0)Ready to Send, (1)In preparation, (2) Standard request, (3) Quoted, (4)Awaiting approval, (5) Validated, (6)Refused, (7)Reserverd, (8) Satisfied, (9)Closed, (10) Error	none
Character - length 15	Data - Read-only	AC Request ID	260100900	n/a	n/a

- 4 To facilitate the linking of related tickets, the scenarios use a field that must be added to **SHR:DefineAssociation**. The following field will be added to **SHR:DefineAssociation**

Field Type	Data or Display-Only	Database Name	Field Number	Enumerated Value	Default Value
Character - length 15	Data - Read-only	zTmpACRequest-ID	250000900	n/a	n/a

- 5 The following filters are including in the installation.

Filter Name	Related Form	Purpose
???	HPD:HelpDesk	Creates TCO:Lineltem entry
???	TCO:Lineltem	Gets rate from SHR:Person for TCO:Lineltem, then calculates cost.
???	TCO:Lineltem	Gets related asset information for TCO:Lineltem
???	HPD:HelpDesk, CHG:Change, CHG:Task	If the AC Status is set to 'Error', sends a notification to the Remedy Administrator.

- 6 The following active links are including in the installation. The notation of (UPDATE) means a previous version existed and has been replaced.

Active Link Name	Related Forms	Purpose
SHRDA:INTG-PushACReqID_Adv	SHR:DefineAssociation	???
SHRDA:INTG-PushACReqID_Pre	SHR:DefineAssociation	???
SHRH:HPD-CreateRelatedHPD (UPDATE)	HPD:HelpDesk	Tied to the Create->Case menu. If the user has selected to create a related case, it runs a macro that opens the HPD:HelpDesk form in Submit mode with information from the current case passed to the submit window.
SHRH:HPD-CreateRelatedH- PD_new	HPD:HelpDesk	???
SHRH:SHR-SearchViaCP1 (UP- DATE)	HPD:HelpDesk	???
SHRH:SHR-SearchViaCP2 (UP- DATE)	HPD:HelpDesk	???

7 The following escalations are including in the installation.

Escalation Name	Related Forms	Purpose
AST:Workstation RUN ONCE TO CLEAN UP DISK AND MEM SIZE	AST:Workstation	See step below.

- 8 Set the escalation **AST:Workstation RUN ONCE TO CLEAN UP DISK AND MEM SIZE** to run at a time when the production data can be updated in bulk. This escalation should be run once, then disabled. After the escalation has run, check the data to see that data from the old Hard Disk and Memory fields has successful updated to the new fields. Once this has been done, we recommend you hide the old fields and utilize the 4 new fields. The filters that are included in this definition file will continue to set the new data fields if you have any pushfield or import operations that might be referencing the old fields.
- 9 Verify that data stored in the 'Phone' field on the form **SHR:People** does not exceed 20 characters. Using the Remedy Administrator tool, shorten the database length of the field to 20 characters. This is necessary because the 'Phone' field in AssetCenter is 20 characters long and phone numbers will be truncated on import if they exceed this length.
- 10 On the form **AST:Workstation**, the information about CPU Type needs to be standardized. In Remedy Service Management, this field is a free-format field, whereas in AssetCenter the CPU Type and CPU Speed information are stored in two different fields. If you only store the CPU Type in the

corresponding Remedy Service Management field, there is no further operation that needs to be performed. If, on the contrary, you store both the CPU Type and the CPU Speed in this field, you will have to create an additional field, following the example developed in item 2 above.

- 11 Errors occurring during the execution of scenarios are stored in XML files located in the **scenario\error** folder of the Connect-It installation folder (typically **C:\Program Files\Peregrine\ConnectIt**).
You may, for example, encounter problems while propagating the department names from Remedy Service Management to AssetCenter. This particular field is limited to 50 characters in AssetCenter and names cannot be truncated to this limit to avoid reconciliation problems. Such records will not be processed and an error will be logged in the aforementioned XML file. Please, check this file after any propagation attempt to make sure that all your data has safely been transferred.
- 12 Errors occurring during the execution of the Helpdesk and Change scenarios additionally send a notification of the error occurrence. By default this notification will go to the user "Demo", using the default notification method set in the AR System form, User. To modify the notification, use the AR Administrator tool and change the escalation **NAME GOES HERE**.



1 Initial Propagation of data to AssetCenter

CHAPTER

- 1 Launch Connect-It.
 - Open each of the following scenarios and configure them to run with your installation.
 - Right click the Action Request System connector and configure it to your server.
 - Right click the Asset Management connector and configure it to your server.
- 2 Run the scenarios in the following order

Classification Information

amNature

Nature data must be entered first. The Nature of an Asset is the generic classification of an item, such as Monitor, Server, Laptop, Printer, etc. Assuming the Remedy installation followed the sample data provided in SHR: Categorization the information would be found as follows. If this mapping is incorrect, the implementor will need to adjust it.

Table 1.1. Asset Natures

Scenario Name	SHRCategorization
Mapping Name	SHR:CategorizationSrc-amNatureDst
Source Document Type	SHR:CategorizationSrc
Destination Document Type	amNatureDst
Mapping constraint	if [Type] = "---" then pifignoreDocumentMapping end if



Rec. Key	Element	Mapping
	Code	[Category]
	Name	[Category]
	seBasis	if [ApplicationSchemaKeyword] = "ALL" then RetVal = 99 else RetVal = 1 end if
	seMgtConstraint	if [ApplicationSchemaKeyword] = "ASSETIN-STOCK" then RetVal = 0 else RetVal = 2 end if

Table 1.2. Contract Natures

Scenario Name	SHRCategorization
Mapping Name	SHR:CategorizationSrc-amNatureDst (Contracts)
Source Document Type	SHR:CategorizationSrc
Destination Document Type	amNatureDstContracts
Mapping constraint	if [Type] <> "---" then pifignoreDocumentMapping end if

Rec. Key	Element	Mapping
	Code	RetVal= "Contract"
	Name	RetVal= "Contract"
	seBasis	4

 **Note:**

After the scenario has been run to propagate Nature information, you must open the Natures table and set the information on the general tab. This step must be done to assure assets are created properly. Additionally, you may choose to update the Code field to a prefix type code, an example would be Standard Asset has a code of STD_ASSET.

amModel

Model data must be entered after Nature because a model is a specific type of a nature. An example of model data would be "Satellite Pro 490CDT" for a Brand of "Toshiba" under the Nature of "Laptop". Assuming the Remedy installation followed the sample data provided in SHR: Categorization the information would be found as follows. If this is incorrect, the mapping will need to be adjusted.

Table 1.3. Models

Scenario Name	SHRCategorization
Mapping Name	SHR:CategorizationSrc-amModelDst
Source Document Type	SHR:CategorizationSrc
Destination Document Type	amModelDst
Mapping constraint	if [Type] = "---" then piflgnoreDocumentMapping end if









Rec. Key	Element	Mapping
	Name	[Item]
	Nature.Name	[Category]
	Parent.Name	[Type]
	Parent.Nature.Name	[Category]

Table 1.4. Contract Models

Scenario Name	SHRCategorization
Mapping Name	SHR:CategorizationSrc-amModelDst (Contracts)
Source Document Type	SHR:CategorizationSrc
Destination Document Type	amModelDstContracts
Mapping constraint	if [Type] <> "---" then piflgnoreDocumentMapping end if

Rec. Key	Element	Mapping
	Name	[Category]
	Nature.Name	RetVal = "Contract"

Rec. Key	Element	Mapping
	Parent.Name	f [ApplicationSchemaKeyword] = "ASSETSOFTWARE" then RetVal = "Software License" elseif [ApplicationSchemaKeyword] = "ASSETLEASE" then RetVal = "Lease" elseif [ApplicationSchemaKeyword] = "ASSETSUPPORT" then RetVal = "Support" elseif [ApplicationSchemaKeyword] = "ASSETWARRANTY" then RetVal = "Warranty" elseif [ApplicationSchemaKeyword] = "ASSETMAINTENANCE" then RetVal = "Maintenance" end if
	Parent.Nature.Name	RetVal = "Contract"

Location Information

Location information for AssetCenter is stored in amLocation. Location information in Remedy Service Management is stored in multiple locations. To reconcile this difference in the two products, three scenarios must be run.

Table 1.5. Location - Region and Site

Scenario Name	SHRLocation
Mapping Name	SHR:LocationSrc-amLocationDst (Region, Site)
Source Document Type	SHR:LocationSrc
Destination Document Type	amLocationDst
Mapping constraint	if [Region] = "" Or [Site] = "" then pifignoreDocumentMapping end if



Rec. Key	Element	Mapping
	Name	[Site]
	Parent.Name	[Region]

Table 1.6. Location -Address

Scenario Name	SHRPeople_Location
Mapping Name	SHR:PeopleSrc-amLocationDst (Address)
Source Document Type	SHR:PeopleSrc

Destination Document Type	amLocationDst
Mapping constraint	if [Region] = "" Or [Site] = "" Or [AddrLine] = "" then piIgnore-DocumentMapping end if






Rec. Key	Element	Mapping
	Address1	[AddrLine]
	BarCode	[Site]+[AddrLine]
	City	[City Name+]
	Name	[AddrLine]
	State	[State/Prov+]
	ZIP	[Postal Code+]
	Parent.Name	[Site]
	Parent.Parent.Name	[Region]

Table 1.7. Location -Office

Scenario Name	SHRPeople_Location
Mapping Name	SHR:PeopleSrc-amLocationDst (Office)
Source Document	SHR:PeopleSrc
Type	
Destination Document	amLocationDst1
Type	
Mapping constraint	if [Office] = "" Or [Site] = "" Or [AddrLine] = "" Or [Region] = "" then piIgnoreDocumentMapping end if





Rec. Key	Element	Mapping
	BarCode	[AddrLine]+ [Office]
	Name	[Office]
	Parent.Name	[AddrLine]
	Parent.Parent.Name	[Site]
	Parent.Parent.Parent.Name	[Region]

Department Information

Department information for AssetCenter is stored in amEmpIDept. The source of the information in Remedy Helpdesk and Asset Management is SHR:Location.

Table 1.8. Departments

Scenario Name	SHRLocation
Mapping Name	SHR:LocationSrc-amEmplDeptDst (Dept)
Source Document	SHR:LocationSrc
Type	
Destination Document	amEmplDeptDst
Type	
Mapping constraint	if [Region] = "" Or [Site] = "" Or [Department] = "" then piflgnoreDocu- mentMapping end if

Rec. Key	Element	Mapping
	bDepartment	1
	Name	[Site] + "(" + [Department] + ")"
	Location.Name	[Site]
	Location.Parent.Name	[Region]
	Parent.bDepartment	1
	Parent.Name	[Department]

People Information

The source of information is SHR:People. The target is amEmpDept and associated links.





 Note:

The difference in field length of Phone in amEmpDept and SHR:People must be reconciled before running this scenario. See the preintegration sets for details.

Table 1.9. People

Scenario Name	SHRPeople
Mapping Name	SHR:PeopleSrc-amEmplDeptDst
Source Document	SHR:PeopleSrc
Type	
Destination Document	amEmplDeptDst
Type	

Mapping constraint if (([Region] = "") OR ([Site] = "") OR ([Department] = "")) then piflgnore-DocumentMapping end if

Rec. Key	Element	Mapping
	BarCode	[Login Name]
	bDepartment	0
	Email	[Email]
	FirstName	[First Name]
	Name	[Last Name]
	Phone	[Phone]
	Location.FullName	if [Region] <> "" And [Site] <> "" And [AddrLine] <> "" And [Office] <> "" thenRetVal = "/" + [Region] + "/" + [Site] + "/" + [AddrLine] + "/" + [Office] + "/" elseif [Region] <> "" And [Site] <> "" And [AddrLine] <> "" thenRetVal = "/" + [Region] + "/" + [Site] + "/" + [AddrLine] + "/" elseif [Region] <> "" And [Site] <> "" thenRetVal = "/" + [Region] + "/" + [Site] + "/" elseif [Region] <> "" thenRetVal = "/" + [Region] + "/" elseRetVal = "" end if
	Parent.bDepartment	1
	Parent.Name	[Site] + "(" + [Department] + ")"
	Parent.Parent.bDepartment	1
	Parent.Parent.Name	[Department]
	Title	[Training Received]



Asset Information

The final area of the initial replication of data is to populate the asset tables in AssetCenter with known asset information from asset forms in RSM. This will include data from AST:Asset, AST:Component, and AST:Workstation. These scenarios must be run in the order listed.

The first scenario imports the data from AST:Asset.

Table 1.10. Main Asset Information














Scenario Name	ASTAsset2Portfolio
Mapping Name	AST:AssetSrc1-amPortfolioDst
Source Document Type	AST:AssetSrc1
Destination Document Type	amPortfolioDst
Mapping constraint	

Rec. Key	Element	Mapping
	Asset Tag	[Asset ID+]
	Code	[Asset ID+]
	fv_RemediesAssetID	[Entry-Id]
	seAssignment	if [Status] = 0 thenRetVal = 3 elseif [Status] = 1 thenRetVal = 1 elseif [Status] = 2 thenRetVal = 1 elseif [Status] = 3 thenRetVal = 0 elseif [Status] = 4 thenRetVal = 4 elseif [Status] = 5 thenRetVal = 4 elseif [Status] = 6 thenRetVal = 2 elseif [Status] = 7 thenRetVal = 1 elseif [Status] = 8 thenRetVal = 2 end if
	Asset.AssetTag	[Asset ID+]
	Asset.BarCode	[Asset ID+]
	Asset.dAcquisition	[Installation Date]
	Asset.SerialNo	[Serial Number]
	Asset.SharingName	[Name]
	Asset.Model.Name	[Item]
	Asset.Model.Nature.Name	[Category]
	Asset.Model.Parent.Name	[Type]
	Asset.Model.Parent.Nature.Name	[Category]
	Location.Name	[Site]
	Location.Parent.Name	[Region]
	Model.Name	[Item]
	Model.Nature.Name	[Category]
	Model.Parent.Name	[Type]
	Model.Parent.Nature.Name	[Category]

The second scenario imports the data from AST:Component. Components in a Remedy implementation are assumed to be children of a specific asset. The parent would have been imported by running the previous scenario. This scenario will find that parent asset and link the components.

Table 1.11. Component Asset Information

Scenario Name	ASTComponent2Portfolio
Mapping Name	AST:ComponentSrc-amPortfolioDst
Source Document Type	AST:ComponentSrc
Destination Document Type	amPortfolioDst
Mapping constraint	

Rec. Key	Element	Mapping
	Asset Tag	[Component ID+]+[Main Asset ID]
	fv_RemedAssetID	[Entry-Id]
	seAssignment	if [Status] = 0 then RetVal = 0 elseif [Status] = 1 then RetVal = 4 elseif [Status] = 2 then RetVal = 1 elseif [Status] = 3 then RetVal = 3 elseif [Status] = 4 then RetVal = 1 end if
	Asset.AssetTag	[Component ID+]+[Main Asset ID]
	Asset.BarCode	[Serial Number]
	Asset.dAcquisition	[Installation Date]
	Asset.Model.Name	[Item]
	Asset.Model.Nature.Name	[Category]
	Asset.Model.Parent.Name	[Type]
	Location.Name	[Site]
	Location.Parent.Name	[Region]
	Model.Name	[Item]
	Model.Nature.Name	[Category]
	Model.Parent.Name	[Type]
	Model.Parent.Nature.Name	[Category]
	Parent.fv_RemedAssetID	[Main Asset Eid]




The third scenario imports the data from AST:Workstation. In a Remedy implementation the additional information about workstation assets is stored in a separate table, AST:Workstation. This is similar to the data structure and relationship between amAsset and amComputer. This scenario will find the computer asset and link this additional information which will be stored in the amComputer table.

 Note:

The preintegration work to correct the storage of Hard Disk and RAM data must be done before running this scenario. See the preintegration setps for details.

Table 1.12. Workstation/Computer Asset Information

Scenario Name	ASTWorkstation
Mapping Name	AST:WorkstationSrc-amPortfolioDst
Source Document Type	AST:WorkstationSrc2
Destination Document Type	amPortfolioDst
Mapping constraint	

Rec. Key	Element	Mapping
	Asset Tag	[Asset ID+]
	Code	[Asset ID+]
	Asset.AssetTag	[Asset ID+]
	Asset.Computer.CPUType	[Processor]
	Asset.Computer.IMemTotalMb	[Total RAM]
	Asset.Computer.IpxSpxAddress	[IPX Address]
	Asset.Computer.TCPIP	[IP Address]
	Asset.Computer.IDiskSizeMb	[Total Hard Disk]
	Asset.Computer.IMemorySizeMb	[Total RAM]
	Asset.Computer.Name	[Node Name]
	Asset.Computer.OperatingSystem	[Operating System]
	Asset.Computer.OSBuildNumber	[Operating System Version]
	Asset.Computer.PhysicalAdress	[MacAddress]
	Asset.Computer.Workgroup	[Work Group]

This completes the initial phase of the data propagation between Remedy Service Management and AssetCenter. In the next phase of the project, we will be providing scenarios to integrate business processes between Helpdesk and AssetCenter workorders, and Change Request and Workorders.

