

HP OpenView Inventory Manager Using Radia

for the Windows operating system

Radia Release Version: 4.2i

Software Version: 4.0i

Installation and Configuration Guide

Document Release Date: January 2007



Legal Notices

Warranty

Hewlett-Packard makes no warranty of any kind with regard to this document, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Hewlett-Packard shall not be held liable for errors contained herein or direct, indirect, special, incidental or consequential damages in connection with the furnishing, performance, or use of this material.

A copy of the specific warranty terms applicable to your Hewlett-Packard product can be obtained from your local Sales and Service Office.

Restricted Rights Legend

Use, duplication, or disclosure by the U.S. Government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause in DFARS 252.227-7013.

Hewlett-Packard Company
United States of America

Rights for non-DOD U.S. Government Departments and Agencies are as set forth in FAR 52.227-19(c)(1,2).

Copyright Notices

© Copyright 1998-2007 Hewlett-Packard Development Company, L.P.

No part of this document may be copied, reproduced, or translated into another language without the prior written consent of Hewlett-Packard Company. The information contained in this material is subject to change without notice.

Trademark Notices

Linux is a registered trademark of Linus Torvalds.

Microsoft®, Windows®, and Windows® XP are U.S. registered trademarks of Microsoft Corporation.

OpenLDAP is a registered trademark of the OpenLDAP Foundation.

PREBOOT EXECUTION ENVIRONMENT (PXE) SERVER
Copyright © 1996-1999 Intel Corporation.

TFTP SERVER

Copyright © 1983, 1993

The Regents of the University of California.

OpenLDAP

Copyright 1999-2001 The OpenLDAP Foundation, Redwood City, California, USA.

Portions Copyright © 1992-1996 Regents of the University of Michigan.

OpenSSL License

Copyright © 1998-2001 The OpenSSLProject.

Original SSLeay License

Copyright © 1995-1998 Eric Young (eay@cryptsoft.com)

DHTML Calendar

Copyright Mihai Bazon, 2002, 2003

Support

You can visit the HP OpenView support web site at:

www.hp.com/managementsoftware/support

This Web site provides contact information and details about the products, services, and support that HP OpenView offers.

HP OpenView online software support provides customer self-solve capabilities. It provides a fast and efficient way to access interactive technical support tools needed to manage your business. As a valuable support customer, you can benefit by using the support site to:

- Search for knowledge documents of interest
- Submit enhancement requests online
- Download software patches
- Submit and track progress on support cases
- Manage a support contract
- Look up HP support contacts
- Review information about available services
- Enter discussions with other software customers
- Research and register for software training

Most of the support areas require that you register as an HP Passport user and sign in. Many also require a support contract.

To find more information about access levels, go to:

www.hp.com/managementsoftware/access_level

To register for an HP Passport ID, go to:

www.managementsoftware.hp.com/passport-registration.html

About this Guide

Who this Guide is for

This guide should be used by systems administrators who want to install and use the Radia Inventory Manager. You should be familiar with:

- Radia products such as the Radia Database and the Radia System Explorer.
- Web-Based Enterprise Management, also known as WBEM.
- With Microsoft implementations of WBEM, also known as Windows Management Instrumentation (WMI).

What this Guide is about

The *Radia Inventory Manager Guide for Windows*:

- Describes how to install and configure the Radia Inventory Manager.
- Discusses the Audit domain within the Radia Configuration Server Database.
- Discusses the different types of auditing.
- Discusses all of the features of auditing such as:
 - Configuring a supplied audit service.
 - Creating your own audit service.
 - Auditing using a timer.

This book contains information for the Windows platforms for the Radia Inventory Manager Server version 4.0 and the Radia Clients version 4.0.

Summary of Changes

This printing of the *Radia Inventory Manager Guide for Windows* is for use with the Radia Manager Inventory Server version 4.0 and the Radia Clients version 4.0. It contains the following changes to information and procedures for the following chapters:

Chapter 1: Introduction

- Page 18, *Overview*, added the following note regarding the role of the new Radia Messaging Server:
"As of Radia 4.0, the Radia Messaging Server handles the actual delivery of the inspection results to the Radia Integration Server, which frees up Radia Configuration Server resources. See the *Radia Messaging Server Guide* for more information."
- Page 19, *About the Radia Reporting Server*, new topic. The Radia Reporting Server offers a web-based interface for querying the combined data in existing Radia Inventory Manager, Radia Patch Manager, and Radia Usage Manager databases, with the ability to filter the data against your LDAP Directory levels.

Chapter 2: Installing the Radia Clients

- Page 43, *Installing the Radia 4.x Clients*, all figures in the chapter were updated to reflect the new Radia 4.0 Client Installation dialog boxes. The installation requires you to read and accept the Software License Agreement.

Chapter 3: Installing the Radia Administrator Workstation

- Page 69, *Installing the Radia Administrator Workstation*, all figures in the chapter were updated to reflect the new Radia 4.0 Administrative Workstation dialog boxes. The installation requires you to read and accept the Software License Agreement.

Chapter 4: Installing the Radia Inventory Manager

- Page 100, *Table 4.2 ~ rim.cfg Parameters*: corrected default value of **DL_DATEFMT** to %Y (not %V).
Added the following parameters to this table: BUILD, DSN_ATTEMPTS, DSN_DATEFMT, DSN_DELAY, DSN_PING, HOME, LABEL, MAXROWS, MODULE, QUERY_VISIBLE, URL, VERSION, and WBEM_AUTOCREATE.

Chapter 5: The AUDIT Domain

- Page 108, *Table 5.1 ~ AUDIT Domain*, Filescan and Filter class descriptions modified to clarify they can be used only for UNIX devices.
- Page 108, *Table 5.1 ~ AUDIT Domain*, Registry Class row added.
- Page 114, *REGISTRY Class* topic added. The new Registry class uses WMI to obtain a Registry scan of a Windows machine. Related sub-topics include:
- Page 115, *Implementing Registry Scans*.
- Page 115, *Updating the Radia Database for Windows Registry Scans*.
- Page 127, *Table 6.2 ~ FILEAUDT Object*: Added a description for the RESOLVE attribute.

Chapter 9: Configuring Timers for Audit Collection

- Page 175, *Table 9.1 ~ Scheduling (TIMER) Class*: Use ZNOPING when there is a possibility that the client will not be able to connect to the Radia Configuration Server.
- Page 182, *Specifying ZNOPING, PINGDLAY, and PINGCNT*: Added a sentence to the introductory paragraph of this section that explains to use ZNOPING when there is a possibility that the client will not be able to connect to the Radia Configuration Server.
- Page 182, *Specifying ZNOPING, PINGDLAY, and PINGCNT*: Added information on the **w** value for the ZNOPING parameter in **radskman**, as well as the use of the PINGDLAY and PINGCNT parameters if ZNOPING is set to N.

Chapter 10: Viewing Inventory from the Radia Integration Server

- Page 193, New chapter to hold topics related to viewing inventory through the Radia Integration Server. (As of Radia 4, the Radia Reporting Server is the preferred method of viewing inventory data).

Editorial Improvements

In addition to the changes listed above, this version contains various editorial and style updates to each chapter and section and the index.

Conventions

You should be aware of the following conventions used in this book.

Table P.1 ~ Styles

Element	Style	Example
References	<i>Italic</i>	See the <i>Publishing Applications and Content</i> chapter in this book.
Dialog boxes and windows	Bold	The Radia System Explorer Security Information dialog box opens.
Code	Andale Mono	radia_am.exe
Selections	Bold	Click Next to continue.

Table P.2 ~ Usage

Element	Style	Example
Drives (system, mapped, CD)	Italicized placeholder	<i>SystemDrive</i> :\Program Files\Novadigm might refer to C:\Program Files\Novadigm on your computer. <i>CDDrive</i> :client\radia_am.exe might refer to D:\client\radia_am.exe on your computer.
Files (in the Radia Database)	All uppercase	PRIMARY
Domains (in the Radia Database)	All uppercase	PRIMARY.SOFTWARE May also be referred to as the SOFTWARE domain in the PRIMARY file.
Classes (in the Radia Database)	All uppercase	PRIMARY.SOFTWARE.ZSERVICE May also be referred to as the ZSERVICE class in the SOFTWARE domain in the PRIMARY file.

The table below describes terms that may be used interchangeably throughout this book.

Table P.3 ~ Terminology*

* Depends on the context. May not always be able to substitute.

Term	May also be called
Application	software, service
Client	Radia Application Manager and/or Radia Inventory Manager
Computer	workstation, server
NOVADIGM domain	PRDMAINT domain Note: As of the 4.0 release of the database, the NOVADIGM domain is being renamed the PRDMAINT domain. Therefore, if you are using an earlier version, you will see the NOVADIGM domain in the database.
Radia Configuration Server	Manager, Active Component Server
Radia Database	Radia Configuration Server Database

Contents

- Preface 5**
 - About this Guide5
 - Who this Guide is for5
 - What this Guide is about5
 - Summary of Changes6
 - Conventions9

- 1 Introduction 17**
 - About the Radia Inventory Manager 18
 - Overview 18
 - About the Radia Reporting Server 19
 - Radia Inventory Manager Terminology 21
 - Radia Prerequisites 23
 - Necessary Skills 23
 - Radia Inventory Manager Technology 24
 - Common Information Model (CIM) 24
 - Web-Based Enterprise Management (WBEM) 24
 - Windows Management Instrumentation (WMI) 24
 - Radia and WBEM 25
 - The Radia Integration Server 25
 - Summary 27

- 2 Installing the Radia Clients 29**
 - System Requirements 30
 - About the Installation Process 30
 - Preparing INSTALL.INI 32
 - [PROPERTIES] Section of INSTALL.INI 34

[ARGS] Section of INSTALL.INI	38
[OBJECTS] Section of INSTALL.INI	42
Installing the Radia 4.x Clients	43
Initiating the Radia Client Installation from a Command Line	43
Specifying the Radia Client Features to Install	43
Additional Command Line Arguments	44
Initiating the Radia Client Installation from a Logon Script.....	45
Using the Radia Client Installation Wizard.....	47
Removing the Radia Clients.....	55
Using the Installation Wizard to Remove Radia Clients	55
Using a Command Line to Remove Radia Clients.....	56
Repairing the Radia Clients.....	57
Using the Installation Wizard to Repair Radia Clients.....	57
Using a Command Line to Repair Radia Clients	59
Modifying the Radia Client Installation	59
Using the Installation Wizard to Modify the Installation of Radia Clients.....	59
Using a Command Line to Modify the Installation of Radia Clients.....	62
Using a Pre-Install Script.....	63
Using a Post-Install Script	64
Summary	66
3 Installing the Radia Administrator Workstation	67
System Requirements	68
About the Installation Files	68
setup.exe.....	68
RADADMIN40.MSI.....	69
Installing the Radia Administrator Workstation	69
Using the Installation Wizard to Install the Radia Administrator Workstation.....	69
Using a Command Line to Install the Radia Administrator Workstation	74
Specifying the Features to Install	74
Additional Command Line Arguments	75
Removing the Radia Administrator Workstation	75
Using the Installation Wizard to Remove the Radia Administrator Workstation	75
Using a Command Line to Remove the Radia Administrator Workstation	77
Repairing the Radia Administrator Workstation	77
Using the Installation Wizard to Repair the Radia Administrator Workstation	78
Using a Command Line to Repair the Radia Administrator Workstation	79
Modifying the Radia Administrator Workstation Installation	79

Using the Installation Wizard to Modify the Radia Administrator Workstation	79
Using a Command Line to Modify the Radia Administrator Workstation Installation	82
Summary	83
4 Installing the Radia Inventory Manager Server	85
Installation Media	86
Installation	86
Configuring the Radia Configuration Server	91
Configure the EDMPROF.DAT	91
Limiting Access to Radia Inventory Manager Web-Pages	93
Installing the Radia Inventory Manager Sample Reporting Database (optional)	94
Radia Integration Server Configuration File: rim.cfg	99
Changing the DSN	102
Radia Inventory Manager Enhancements	102
Deploying the Radia Inventory Manager Client Modules to Radia Client	103
Summary	104
5 The AUDIT Domain	105
The AUDIT Domain in the Radia Configuration Server Database	106
AUDIT Domain Defined	107
RIMOPTS Class	109
REGISTRY Class	114
Implementing Registry Scans	115
Updating the Radia Database for Windows Registry Scans	115
Sample Inventory Database Tables	117
Summary	120
6 Software and Hardware Auditing	121
Auditing Types	122
File Auditing	122
WBEM Auditing	128
WBEM Objects and the Radia Configuration Server	131
Hardware Auditing	132
Summary	137

7 Successful Auditing	139
Sample Auditing	140
Configuring a Sample Audit	143
What Happened during the Scan?	149
Summary	152
8 Auditing – Creating Your Own Audit Packages.....	153
Audit Packages or PACKAGE Class	154
Using Radia System Explorer to Create/Maintain Audit Services	156
Summary	170
9 Configuring Timers for Audit Collection	171
The Scheduling (TIMER) Class	172
Creating a Timer Instance	176
Specifying Timer Settings.....	180
Specifying ZSCHDEF.....	180
Specifying ZSCHTYPE	181
Specifying ZSCHFREQ.....	181
Specifying ZRSCCMDL	181
Specifying ZNOPING, PINGDLAY, and PINGCNT	182
Connecting the Timer to a Service	183
Audit Execution Configuration.....	184
Radia Software Manager Users	189
Summary	192
10 Viewing Inventory from the Radia Integration Server.....	193
Accessing the Radia Integration Server	194
Maneuvering in the Radia Integration Server: Non-Radia Management Portal Users.....	197
Reporting	198
Summary Information.....	199
Detail Information	201
Subscriber	202
Subscriber Filtering	203
Maneuvering in the Radia Integration Server: Radia Management Portal Users	203
Administrator Hints and Tips.....	205
Viewing Audited Files Using the Radia Integration Server	211

Summary Reporting Examples 211
Detail Reporting Example 213
Summary 215

A Radia Inventory Manager Detail and Summary Reporting Tables 217

Lists 231

Figures 231
Tables 236
Procedures..... 238

Index 239



Introduction

At the end of this chapter, you will:

- Understand the components of the Radia Inventory Manager client.
- Understand the terminology associated with the Radia Inventory Manager client.
- Be familiar with supported platforms.
- Be familiar with WBEM and the Radia Client.
- Be familiar with the Radia Integration Server.
- Be familiar with related Radia Infrastructure components for processing Inventory client data, such as the Radia Messaging Server, the Radia Management Portal, and the Radia Reporting Server.

About the Radia Inventory Manager

The Radia Inventory Manager client is a utility used to discover configuration information on remote computers. It enables centralized reporting and administration based upon the discovery results.

The Radia Inventory Manager client is used with the Radia Inventory Manager Server. The Radia Inventory Manager Server stores and maintains the discovery information to be viewed within an ODBC-compliant (Open Database Connectivity) database. The preferred method for viewing the reported data from the Radia Inventory Manager is to use the Radia Reporting Server, discussed on page 19. The Radia Integration Server component of the Radia Inventory Manager Server provides an alternate method of viewing the reports via a Web browser interface.

This manual explains how to install and use the Radia Inventory Manager client and server components. Choose the appropriate strategies suited for your enterprise needs.

Overview

Systems administrators use the Radia System Explorer or the Radia Management Portal to manipulate the contents of the Radia Database. They specify what inventory management tasks to perform and on which client computers to perform them.

The collection of inventory information is performed on the Radia Inventory Manager computer when a subscriber connects to and installs the auditing software with the Radia Configuration Server as follows:

- **Radia Software Manager** installs the software when the user visits his Radia Web page.
- **Radia Application Manager** installs the software in one of the following ways:
 - through a logon script.
 - when the user double-clicks a desktop Radia Connect icon.
 - according to a schedule.
 - using the Notify capabilities of the Radia Configuration Server.

The results of the inspection are then sent back to the Radia Configuration Server. Any unwanted files discovered on a user's computer can be captured and/or deleted. This enables administrators to remove unauthorized content, such as games, from end users' computers.

The Radia Configuration Server can store these inspection results in the Radia Database PROFILE file and/or forward them to the Radia Inventory Manager Server for insertion into an ODBC-compliant database.

As of Radia 4.0, the Radia Messaging Server handles the actual delivery of the inspection results to the Radia Integration Server, which frees up Radia Configuration Server resources. See the *Radia Messaging Server Guide* for more information.

About the Radia Reporting Server

As part of the Radia extended infrastructure for Radia 4.0 Windows, the web-based Radia Reporting Server allows you to query the combined data in existing Radia Inventory Manager, Radia Patch Manager, and Radia Usage Manager databases and create detailed reports. In addition, you have the option of mounting an existing LDAP directory, which allows you to filter your data using your LDAP directory levels. The Radia Reporting environment is illustrated in Figure 1.1.




Figure 1.1 ~ Radia Reporting Environment.

The Radia Reporting Server interface provides a dynamic and intuitive way to use Radia SQL data for reporting and overall environmental assessment.

The screenshot displays the Radia Management Portal interface. On the left, there are sections for 'Search Controls' (LDAP Filters and Data Filters) and 'Display Controls' (Reporting Views). The main area shows a table of 'Radia Managed Devices' with columns for Details, Last Connect, Radia ID, Device, IP Address, Vendor, Model, Class, Operating System, and OS Level. The table lists 15 items, showing details for the first 15 of 22 total items.

Details	Last Connect	Radia ID	Device	IP Address	Vendor	Model	Class	Operating System	OS Level
	2003-12-07 19:55:04	UNIXNVFKVTCTLNING	bhadra	192.21.47.93	N/A	sparc SUNW/Ultra-60	Unknown	SunOS	N/A
	2003-12-07 14:51:24	UNIXMAPWVSVUGOGJ	tobor	192.169.8.12	N/A	sparc SUNW/Ultra-4	Unknown	SunOS	N/A
	2003-12-07 13:53:19	UNIXPUMOMATWUEHX	mince	199.6.22.58	N/A	sparc SUNW/Ultra-60	Unknown	SunOS	N/A
	2003-12-07 13:50:11	UNIXUESJUYLEWIGAL	ucunx003	192.169.23.228	N/A	sparc SUNW/Ultra-60	Unknown	SunOS	N/A
	2003-12-07 12:54:09	UNIXSWSXCSPQKECZ	ucunx010	192.169.23.115	N/A	sparc SUNW/Ultra-60	Unknown	SunOS	N/A
	2003-12-07 12:47:15	UNIXXJBAHRYLHNFE	explorer	192.169.68.162	N/A	sparc SUNW/Ultra-1	Unknown	SunOS	N/A
	2003-12-07 12:36:57	UNIXZSMOCIDMINDJ	oforce	192.169.23.169	N/A	sparc SUNW/Ultra-60	Unknown	SunOS	N/A
	2003-12-07 12:28:30	UNIXPHLKZBAHLJUZU	azalea	192.169.68.82	N/A	sparc SUNW/Ultra-60	Unknown	SunOS	N/A
	2003-12-07 09:20:03	UNIXRZJGFNMFBLVG	ear	199.6.22.216	N/A	sparc SUNW/Ultra-60	Unknown	SunOS	N/A
	2003-12-07 08:18:53	UNIXYFXBLRLOZDAMY	solaris7	199.6.22.149	N/A	sparc SUNW/Ultra-2	Unknown	SunOS	N/A

Figure 1.2 ~ Radia Reporting Server Web interface.

See the *Radia Reporting Server Guide* for more information on how to install the Radia Reporting Server and create a Radia Reporting environment for your SQL databases for Radia, such as inventory, patch, and usage databases, as well as an optional LDAP directory.

The *Radia Reporting Server Guide* also explains how to use the Radia Reporting Server interface to create, filter, and export reports, as well as browse reports for specific entries.

Radia Inventory Manager Terminology

CIM (Common Information Model)

(noun) a standardized framework for WBEM. It is an object oriented set of schemas for cross-platform network management. Some of these objects include computer systems, devices (like printers and batteries), controllers (for example, PCI and USB controllers), files, software, etc.

clean machine

(noun) a desktop computer on which the operating system has just been installed, and no further changes have been made.

client computer

(noun) the computer on the end user's desktop that has the Radia Client software installed on it.

Radia Client

(noun, capitalized) the Radia software component that is installed on the end user's desktop computer.

Radia Integration Server

The Radia Inventory Manager client is used with the **Radia Integration Server**. The Radia Integration Server stores and maintains the discovery information to be viewed within an ODBC (Open Database Connectivity) compliant database. The Radia Integration Server then provides the reports via a WEB-browser interface.

Radia Management Portal

The Radia Management Portal is a Web-based interface used to manage your Radia infrastructure. The core functionality of the Radia Management Portal includes: Authentication, Entitlement, Scheduling, Querying, Auditing/Logging, Policy Administration, and instance-level Radia Database Administration. See the *Radia Management Portal Guide* for additional information.

Radia Messaging Server

The Radia Messaging Server is the Radia Infrastructure component that provides a common routing and inter-server data delivery service, especially for report-bound data. When servicing a Radia Configuration Server, the Radia Messaging Server handles the delivery of Inventory, Operations, Patch, and Management Portal data collected from clients to the appropriate external location.

Radia Reporting Server

The Radia Reporting Server is a Web-based interface to the reportable data captured by the Radia extended infrastructure product suite. It allows you to query the combined data in existing Radia Inventory Manager, Radia Patch Manager, and Radia Usage Manager databases and create detailed reports. You have the option of mounting an existing LDAP directory, which allows you to filter your data using your LDAP directory levels.

Reporting Extensions for the Radia Integration Server

Any Open Database Connectivity (ODBC) compliant database used to view and manipulate the audited information obtained by the Radia Inventory Manager client.

subscriber

(noun) the person (end user) who uses Radia-managed applications on a remote desktop computer (client computer).

Web-Based Enterprise Management (WEBM)

Web-Based Enterprise Management enables information such as the amount of RAM in a computer, hard disk capacity, process type, and versions of operating systems to be extracted from computers, routers, switches, and other networked devices.

Windows Management Instrumentation (WMI)

Windows Management Instrumentation (WMI) is Microsoft's implementation of WBEM for Microsoft Windows platforms.

WMI Repository

WMI repository is a central storage area designed to hold managed information.

Radia Prerequisites

The Radia Inventory Manager 4.0 requires the following Radia components:

- Radia Configuration Server version 4.5.3 or higher
- Radia Client at version 3.1 or higher
 - Radia Application Managerand/or
 - Radia Software Manager
- Radia Messaging Server 2.0 is highly recommended. (It is installed automatically on a Radia Configuration Server with Radia 4.) See the *Radia Messaging Server Guide* for more information on installing or migrating to the Radia Messaging Server, and how the Radia Messaging Server transfers data to the Radia Inventory Manager server.

Note

If you are upgrading your Radia Management Server from Radia 3 to Radia 4, please refer to the chapter *Migrating Inventory Processing to Use QMSG and the Radia Messaging Server* in the *Radia Messaging Server Guide*.

Necessary Skills

WITH RADIA PRODUCTS

This document assumes that the reader is familiar with the Radia Database, with administering Radia using the Radia System Explorer, and with the Radia Management Portal. See the *Radia System Explorer Guide* and the *Radia Management Portal Guide* for more information.

WITH WEB-BASED ENTERPRISE MANAGEMENT

This document assumes that the reader is familiar with Web-Based Enterprise Management (WBEM). Resources for familiarizing yourself with WBEM can be found at the following Web site: <http://www.dmtf.org/spec/wbem.html>.

WITH MICROSOFT IMPLEMENTATIONS OF WBEM

This document also assumes that the reader is familiar with Windows Management Instrumentation (WMI). Information concerning WMI can be found at the following Web site: http://msdn.microsoft.com/library/default.asp?url=/library/en-us/w98ddk/hh/w98ddk/wmi_wp_03se.asp.

Radia Inventory Manager Technology

While an administrator with little Web-based knowledge can use the Radia Inventory Manager with success, it is important to understand some of the technology behind the product. The information that is provided below is intended to give you a preliminary understanding of the technology behind the Radia Inventory Manager client. As indicated in *Necessary Skills* on page 23, we recommend you become more familiar with web-based technology.

Common Information Model (CIM)

The Common Information Model (CIM) is an object-oriented model, or schema, that represents and organizes information within a managed environment. This includes:

- Defining **objects** such as computer systems, devices, controllers, software, files, people, and so forth.
- Allowing for the definition of **associations** such as describing relationships between object-dependencies, component relationships, and connections.
- Allowing for the definition of **methods** such as input/output parameters and return codes.

By using object-oriented designs and constructs, one of the goals of the CIM model is to consolidate and extend management standards. Some of these management standards include Simple Network Management Protocol (SNMP) and Desktop Management Interface (DMI).

Web-Based Enterprise Management (WBEM)

Web-Based Enterprise Management (WBEM) is a set of management and Internet standard technologies developed to unify the management of enterprise computing environments. The Distributed Management Task Force (DMTF) has developed a core set of standards that make up WBEM. The core set includes a data model, the CIM standard, an encoding specification, xmlCIM encoding specification, and a transport mechanism, (CIM Operations over HTTP).

Windows Management Instrumentation (WMI)

Windows Management Instrumentation (WMI) is the Microsoft implementation of the Web-Based Enterprise Management (WBEM) that supports the CIM model as well as Microsoft-specific extensions of CIM. To put it simply, it is a set of services designed to input data into a repository via WBEM providers.

The WMI repository is a central storage area designed to hold managed information. It is organized by a series of schemas that are loaded into namespaces. A namespace provides a container, or domain, for the instances of the classes in that schema.

WMI comes installed on Windows 2000 and Windows ME.

Note

For the purpose of this document, when we refer to WBEM, this includes WMI.

Radia and WBEM

The Radia Inventory Management client queries the WBEM namespace (that is, the WBEM database) and sends the results back to the Radia Configuration Server. All information collected by WBEM is available to the Radia Inventory Manager client. The collected information is then stored in the Radia Integration Server.

Note

WMI version 1.5 is available for download by licensed end users from the Microsoft download center at <http://www.microsoft.com/downloads/details.aspx?FamilyID=afe41f46-e213-4cbf-9c5b-fbf236e0e875&DisplayLang=en>. This download is for Windows 95, Windows 98, Windows 98 SE, and Windows NT4 SP4 or higher. Windows 2000 and Windows ME, WMI has been natively installed. The WMI installation program is available in the `\win32\WMI` folder on the Radia Management Applications CD-ROM. If WMI does not exist on the client computer, the WMI installation program runs automatically.

For client computers with WBEM (Web-Based Enterprise Management) installed, the Radia Inventory Manager executes an HP-proprietary method (RIMWBEM) to query the WBEM namespace.

For client computers that do not have WBEM installed, the Radia Inventory Manager executes HP proprietary methods to *directly* inspect the hardware (built into the Radia Client – ZCONFIG) and/or the file system (RIMSFSCAN).

Caution

HP Openview Inventory Manager using Radia for Windows leverages Microsoft's Windows Management Instrumentation (WMI) to collect hardware and software inventory data by using WMI queries. Some WMI queries can traverse the network contacting other servers in the enterprise to collect the requested information. This may result in large volumes of data being returned, and could have a significantly negative effect on network performance. An example of this would be querying all users on the network using the W32_UserAccount WMI class. Extreme caution must be taken to understand the scope of these queries to ensure unexpected results do not occur. While Radia Inventory Manager provides an interface to WMI and its providers, it cannot control how these queries are satisfied. It is the customer's responsibility to safeguard against using WMI queries that span the network, if this behavior is not desired.

The Radia Integration Server

The Radia Integration Server is a Tool Command Language (Tcl) based Web server that resides where the Radia Inventory Manager Server is installed. It builds and updates a structured query language (SQL) database of your choice via ODBC.

Introduction

The ODBC driver for the database you choose *must* be installed prior to installing the Radia Integration Server. Depending upon which database you choose, you may have to perform administrative tasks for allocating space and establish a user ID and password for the Radia Integration Server's use.

The Radia Integration Server will automatically create the necessary tables in the database you choose.

Note

For *demonstration purposes only*, a sample Access 97 database with predefined queries is provided on the Radia Inventory Manager. Use this sample to display the query results in a Web browser.

Summary

- The Radia Inventory Manager client is a utility used to discover hardware and software configuration on remote computers.
- The Radia Inventory Manager Server stores and maintains discovered information in an ODBC-compliant database.
- The collection and reporting of inventory information is performed on the Radia Inventory Manager when a subscriber/user connects to the Radia Configuration Server.
- The Radia Messaging Server delivers the data collected from subscribers to an external Radia Inventory Manager Server location.
- The ODBC driver for the database you choose *must* be installed prior to installing the Radia Inventory Manager Server.
- The Radia Inventory Manager Server will automatically create the necessary tables in the database you choose.
- The Radia Reporting Server offers a Web-based interface to the reportable data captured by the Radia Extended infrastructure product suite. It allows you to query the combined data in existing Radia Inventory Manager, Radia Patch Manager, and Radia Usage Manager databases, create detailed reports, and filter data using your LDAP directory levels.
- It is suggested that the administrator be familiar with Radia products, as well as Web-Based Enterprise Management, and Microsoft's implementations of WBEM.
- All information collected by WBEM is available to the Radia Inventory Manager.
- The Radia Inventory Manager queries the WBEM namespace (i.e., the WBEM database) and sends the results back to the Radia Configuration Server.
- RIMWBEM queries WBEM namespaces.
- RIMFSCAN directly inspects the software and/or the file system.

Installing the Radia Clients

At the end of this chapter, you will:

- Understand the system requirements for installing Radia Clients.
- Know how to customize the installation process.
- Be able to modify the [PROPERTIES] section of the INSTALL.INI in order to customize the behavior of the installation process.
- Be able to modify the [ARGS] section of the INSTALL.INI in order to customize the behavior of the Radia Software Manager.
- Be able to modify the [OBJECTS] section of the INSTALL.INI in order to specify Radia objects to be created on the client computer.
- Know how to use the Installation Wizard.
- Know how to remove and repair Radia Clients using the Installation Wizard and command lines.
- Know how to modify the installation of the Radia Clients using the Installation Wizard and command lines.
- Know how to use pre-install script to customize MSI properties that affect installation.
- Know how to use a post-install script to run processes after installing Radia Clients.

The Radia Client installation program uses the Microsoft MSI format for Windows Installer. The program consists of one MSI package with five feature sets—Radia Application Manager, Radia Software Manager, Radia Inventory Manager, Radia OS Manager and Radia Patch Manager.

Caution

Install only the Radia Clients for which you have licenses. If you do not have a license, the Radia Client will not authenticate with the Radia Configuration Server.

System Requirements

- Windows 2000 and above.
- Microsoft .NET runtime (*required for Radia Software Manager only*).
The .NET installation program is available in the **\DotNet** folder on the Radia Client CD-ROM. If .NET does not exist on the client computer, the .NET installation program runs automatically. Microsoft .NET requires Microsoft Internet Explorer 5.01 or later.
- MS Windows Installer Version 2.0 or higher.
The MSI 2.0 installation program is available in the **\MSI** folder on the Radia Client CD-ROM. If Windows Installer does not exist, or if an earlier version is detected on the client computer, the MSI 2.0 installation program runs automatically.
- TCP/IP connection to a computer running the Radia Configuration Server.
- WMI (*required for the Radia Inventory Manager only*).
The WMI installation program is available in the **\WMI** folder on the Radia Client CD-ROM. If WMI does not exist on the client computer, the WMI installation program runs automatically.
- You must have administrator rights to the computer to install the Radia Clients.

About the Installation Process

Whether the Radia Client installation program is distributed as an executable (setup.exe) or an Administrative Installation Point (AIP), the installation process is the same. You can customize many aspects of the installation including which Radia Clients to install and to what directory the installation files should be copied. If you want to customize the installation process, you should be familiar with the following files.

- **setup.exe**
setup.exe is stored in the **\win32** directory on the Radia Client CD-ROM. It accepts any standard Windows Installer command line parameters and passes them to the Windows Installer service.

You can also create an AIP for network installations.

Note

A Windows Installer Administrative Installation Point (AIP) is also known as an Administrative Control Point (ACP).

The AIP starts Windows Installer and passes any command line parameters to it. To create the Windows Installer AIP in a specified target directory, type:

```
SETUP.EXE /a TARGETDIR=drive:\targetdirectory /qb
```

The target directory contains RADIA40.MSI, the installation folders, setup.exe, and any files (such as INSTALL.INI or Visual Basic scripts) stored in the same directory as setup.exe. Next, copy the **\DotNet** and **\MSI** folders into the target directory.

Note

If you do not have Windows Installer version 2.0 installed, setup.exe looks for the standard MSI installation programs (INSTMSI.EXE or INSTMSIW.EXE) in the current directory and in the MSI subdirectory. If found, the appropriate MSI installation will run before the Radia Client installation.

- **RADIA40.MSI**

RADIA40.MSI is the MSI database file, which contains the default configuration information for the installation. This file is stored in the **\win32** directory on the Radia Client CD-ROM.

- **INSTALL.INI**

Use INSTALL.INI to customize the installation or the Radia Client arguments file, or to create or set attributes for Radia objects. Settings in INSTALL.INI override the defaults stored in RADIA40.MSI.

A sample INSTALL.INI is available in the **\win32\samples** directory on the Radia Client CD-ROM.

- **args.xml**

args.xml is the Radia Software Manager arguments file created from information stored in the [ARGS] section of INSTALL.INI. This file, stored in IDMLIB on the client computer, controls the behavior of the Radia Software Manager. The default directory for IDMLIB is *SystemDrive:\Program Files\Novadigm\Lib*.

- **Pre-install scripts**

(Recommended for experienced users only.)

Use custom Visual Basic scripts to customize MSI properties that affect the installation. For an example of a simple script, see *Using a Pre-Install Script* on page 63. This script is available in the **\win32\samples** directory on the Radia Client CD-ROM.

- **Post-install scripts**

(Recommended for experienced users only.)

Use custom Visual Basic, REXX, or Tcl scripts to run processes such as the first Client Connect. For an example, see *Using a Post-Install Script* on page 64. The complete version of this script is available in the **\win32\samples** directory on the Radia Client CD-ROM.




Figure 2.1 ~ Radia Client installation process.

Preparing INSTALL.INI

Create an installation file, INSTALL.INI. Use this file to:

- Customize the installation.
- Customize the Radia Software Manager.
- Create or set attributes for Radia objects.

Below is a sample INSTALL.INI. A description of the three sections and the attributes in each of these sections follows.

Notes

A semi-colon (;) at the beginning of attributes, properties, and object names indicates that this item is commented out and will be ignored. If you want to specify a value for any of these items, delete the semi-colon (;) and then type the appropriate value.

Table 2.1 ~ Sample INSTALL.INI

```

[Properties]
;MSI Property overrides (Novadigm properties have the "nvd" prefix)

;Uncomment and specify the installation directory to replace the default directory
;INSTALLDIR=

;Uncomment to prevent subscribers from using Add/Remove Programs in the Control Panel to remove the
Radia Client
;ARNOREMOVE=1

;Uncomment and specify the features that you want to install
;ADDLOCAL=NVDINSTALLRAM,NVDINSTALLRSM,NVDINSTALLRIM,NVDINSTALLROM,NVDINSTALLPATCH,
NVDINSTALLRLAE

;Uncomment to show/hide panels in the installation wizard (defaults shown below)
;NVDENABLEUSER=Y
;NVDENABLEIP=Y
;NVDENABLEPROXY=N
;NVDENABLESHORTCUT=Y
;NVDSHORTCUT=Y
;NVDSTARTMENUICON=Y
;NVDSTARTWMICFGMGR=Y

;Uncomment and specify the location of maintenance files
;NVDMAINTDIR=

;Uncomment to allow notifies only from the local host.
;NVDLOCALNOTIFYONLY=Y

;Uncomment to start the System Tray automatically if RAM is selected during the client install
process.
;NVDRADTRAYSTART=Y

;Uncomment to disable "Allow service to interact with desktop" flag for Radia Services
;NVDNOTIFYINTERACT=N
;NVDREDIRECTORINTERACT=N

;NVDSCHEULERINTERACT=N

;Uncomment and specify the file names of pre- and post-install custom action scripts
;NVDPRECAPATH=
;NVDPOSTCAPATH=

[Args]
; Tags to be placed into the Radia Software Manager ARGS.XML file
; A value of _NONE_ removes the tag from the file
;
;askconfirm=
;channelname=software
;dataurl=
;enterprisemanagement=
;identification=$USER
;log=connect.log
;logsize=
;logonpanel=
;managerurl=
;providername=Radia
;redirect=
;resolutionmanager=
;resolutionport=
;sslmanager=
;sslport=
;startdir=
;uioption=

```

```
[Objects]
; Set Radia object attribute values
; A value of _NONE_ will set the attribute to blank
;
; ZMASTER_ZDSTSOCK=3464
; ZMASTER_ZIPADDR=xxx.xxx.xxx.xxx
; ZMASTER_ZNTFPORT=3465
; ZMASTER_ZNTFYSEC=Y
; ZMASTER_ZTIMEO=240
; ZMASTER_ZTRACE=N
; ZMASTER_ZTRACEL=_NONE_
; ZMASTER_ZUSERID=
; ZMASTER_ZVRFYUID=N
;
; PROXYINF_USEPROXY=
; PROXYINF_DISCOVER=
; PROXYINF_PROXADDR=
;
; Uncomment to enable Client Operations Profile (COP)
; RADSETUP_COP=Y
; Uncomment to disable collection of AD information
; RADSETUP_ADINFO=N
; Uncomment to disable collection of NT Group information
; RADSETUP_ZGRPINFO=N
```

[PROPERTIES] Section of INSTALL.INI

Use the [PROPERTIES] section to modify Windows Installer properties or HP-specific properties to customize the behavior of the installation program. The values that you set in this section override the default values stored in the RADIA40.MSI database file.

Notes

All properties such as INSTALLDIR must be typed in all uppercase.

Argument	Description	Default Value*
----------	-------------	----------------

**These values are used even if the property is commented out.*

Table 2.2 ~ [PROPERTIES] Section of INSTALL.INI

Argument	Description	Default Value*
<i>*These values are used even if the property is commented out.</i>		
ADDLOCAL	<p>Specify the features that you want to install on the local hard drive. You must be properly licensed to use these products.</p> <p>The features may be:</p> <ul style="list-style-type: none"> • NVDINSTALLRAM = Radia Application Manager • NVDINSTALLRSM = Radia Software Manager • NVDINSTALLRIM = Radia Inventory Manager • NVDINSTALLROM = Radia OS Manager • NVDINSTALLPATCH = Radia Patch Manager • NVDINSTALLRLAE = Radia Local AIP Extension <p>Note: This must be installed to use the Local AIP Support for MSI Redirector feature. See the <i>Radia Software Manager Guide</i> for more information.</p>	N/A
ARNOREMOVE	<p>Set ARPNOREMOVE to 1 to indicate that you want to disable the ability to remove the Radia Client from the computer using Add/Remove Programs in the Control Panel.</p> <p>Note: Setting ARPNOREMOVE to 0 will <i>not</i> disable this option due to a Windows Installer issue. If you want to allow your subscribers to remove the Radia Client from the computer using Add/Remove Programs in the Control Panel, place a semi-colon (;) in front of the ARPNOREMOVE argument in INSTALL.INI.</p> <p>For Windows 2000 or XP, the Remove button is disabled.</p> <p>For earlier operating systems, the Radia Client will not be listed in Add/Remove Programs in the Control Panel.</p>	Subscribers can remove the Radia Client from the computer using Add/Remove Programs in the Control Panel.
INSTALLDIR	<p>Specify the directory where you want to install the Radia Client.</p> <p>This value will be overridden if a new directory is specified in the Destination Folder window in the Radia 4.x Client Installation Wizard.</p>	<i>SystemDrive:\Program Files\Novadigm</i>

Table 2.2 ~ [PROPERTIES] Section of INSTALL.INI

Argument	Description	Default Value*
<i>*These values are used even if the property is commented out.</i>		
NVDENABLEUSER	<p>Indicate whether to show or hide the Set User window in the Installation Wizard.</p> <p>Y – Show the window. N – Hide the window.</p> <p>Note: If you hide the window, the Create a Radia Software Manager icon on the desktop check box will no longer be available to your subscribers.</p> <p>D – Show the window, but disable the User Name field. The Create a Radia Software Manager icon on the desktop check box is still available.</p>	Y
NVDENABLEIP	<p>Indicate whether to show or hide the Radia Configuration Server window in the Installation Wizard.</p>	Y
NVDENABLEPROXY	<p>Indicate whether to show or hide the Proxy Information window in the Installation Wizard.</p> <p>If you want to use a Radia Proxy Server during the Radia Client Connect, show this window.</p> <p>The information entered in the Proxy Information window is stored, by default, in the PROXYINF object in the client computer's IDMLIB directory.</p>	N
NVDENABLESHORTCUT	<p>Indicate whether to show the Create a Radia Software Manager icon on the desktop check box in the Set User window.</p> <p>Selecting this check box installs a desktop shortcut for the Radia Software Manager on the subscriber's desktop.</p> <p>Reminder: This property does not apply to computers running Windows 95 because the Radia Software Manager 4.x client is not available for computers running Windows 95, as it requires Microsoft's .NET runtime.</p>	Y
NVDSHORTCUT	<p>Indicate whether to install a desktop shortcut for the Radia Software Manager on the subscriber's computer.</p> <p>Reminder: This property does not apply to computers running Windows 95 because the Radia Software Manager 4.x client is not available for computers running Windows 95, as it requires Microsoft's .NET runtime.</p>	Y
NVDSTARTMENUICON	<p>Indicate whether to install an icon in the Start Menu for the Radia Software Manager on the subscriber's computer.</p> <p>Reminder: This property does not apply to computers running Windows 95 because the Radia Software Manager 4.x client is not available for computers running Windows 95, as it requires Microsoft's .NET runtime.</p>	Y

Table 2.2 ~ [PROPERTIES] Section of INSTALL.INI

Argument	Description	Default Value*
<i>*These values are used even if the property is commented out.</i>		
NVDSTARTWMICFGMGR	Indicates whether to install the shortcuts for WMI on Windows NT and 9x systems.	Y
NVDRAMSHORCUT	Indicate whether to install a desktop shortcut for the Radia Application Manager on the subscriber's computer.	N
NVDRAMSTARTMENUSHORCUT	Indicate whether to install an icon in the Start Menu for the Radia Application Manager on the subscriber's computer.	N
NVDRAMCONNECT	Specify a command line to run if a Radia Application Manager shortcut is created on the desktop or the Start Menu.	Blank
NVDMAINTDIR	Specify a directory that stores the Radia Client maintenance files. Note: Type a value only if you want to store maintenance files in a directory other than the MAINT subdirectory in the folder containing setup.exe. If files exist in this directory that are newer than the installation files, they will be copied into the Radia Client's IDMSYS directory.	MAINT subdirectory in the folder containing setup.exe
NVDLOCALNOTIFYONLY	If set to Y , the Client will allow Radia Notifies only from the local host.	N
NVDRADTRAYSTART	Set to Y to start the System Tray automatically, if the Radia Application Manager is selected during the Client installation process.	N
NVDNOTIFYINTERACT	Set to Y to enable the Radia Notify Daemon to interact with the desktop.	N
NVDREDIRECTORINTERACT	Set to Y to enable the Radia MSI Redirector to interact with the desktop.	N
NVDSCHEDULERINTERACT	Set to Y to enable the Radia Scheduler to interact with the desktop.	N
NVDPRECAPATH	Specify the fully qualified path and filename of a custom Visual Basic pre-install script. Note: New objects or properties must be defined in INSTALL.INI. You can use a pre-install script to override a value for the object or property, but if you attempt to specify a new object or property in the pre-install script, it will be ignored. For an example of a simple script, see <i>Using a Pre-Install Script</i> on page 63.	N/A
NVDPOSTCAPATH	Specify the fully qualified path and filename of a custom Visual Basic or REXX post-install script. For an example, see <i>Using a Post-Install Script</i> on page 64.	N/A

[ARGS] Section of INSTALL.INI

Use the [ARGS] section to control the behavior of the Radia Software Manager. The information in this section is used to build the Radia Software Manager arguments file, args.xml, which is stored in IDMLIB on the client computer. The default directory for IDMLIB is *SystemDrive:\Program Files\Novadigm\Lib*.

Below is an example of args.xml.

```
<?xml version="1.0" ?>
<RADIA_ARGUMENTS>
<ARGUMENTS><CHANNELNAME>software</CHANNELNAME>
<IDENTIFICATION>jsmith</IDENTIFICATION>
<PROVIDERNAME>radia</PROVIDERNAME>
<RESOLUTIONMANAGER>10.10.10.1</RESOLUTIONMANAGER>
<LOG>connect.log</LOG>
<RESOLUTIONPORT>3464</RESOLUTIONPORT>
</ARGUMENTS>
</RADIA_ARGUMENTS>
```

Figure 2.2 ~ Sample args.xml.

Note

The XML tags (arguments) described in this section are not case-sensitive when you type them in INSTALL.INI. However, the arguments will automatically be converted to all uppercase in args.xml.

If you are using the Radia Application Manager, any of the parameters in the [ARGS] section can be added to the **radskman** command line.

Table 2.3 ~ [ARGS] Section of INSTALL.INI

Argument	Mandatory or Optional	Description	Default Value
askconfirm	Optional	Controls the display of a confirmation message to your subscribers. For example, some instances in which a confirmation message may display are: <ul style="list-style-type: none"> A reboot is required. There is insufficient disk space during deployment. A data download is interrupted. 	Y
channelname	Mandatory	The domain in the Radia Configuration Server Database from which applications are retrieved.	SOFTWARE

Table 2.3 ~ [ARGS] Section of INSTALL.INI

Argument	Mandatory or Optional	Description	Default Value
enterprisemanagement	Optional	<i>For use with the Radia Software Manager only.</i> Deploys mandatory applications from the Radia Software Manager. Set Enterprisemanagement=auto to deploy mandatory applications. Remove the Enterprisemanagement tag if you do not want to deploy mandatory applications.	N/A
identification	Optional	Identifies the client to the Radia Configuration Server by defining the value for the ZUSERID variable in the ZMASTER object. This value will be overridden if a different User Name is specified in the Set User window in the Radia 4.x Client Installation Wizard. If you do not want this value to be modified, set NVDENABLEUSER = N in the [PROPERTIES] section of INSTALL.INI. <ul style="list-style-type: none"> • \$MACHINE – The Radia user ID is the name of the subscriber's computer. • \$USER – The Radia user ID is the logon ID for the subscriber currently logged on. • CUSTOM – literal custom specification. 	\$USER
log	Optional	Specifies the name of the log stored in IDMLOG. IDMLOG is specified in NVD.INI. NVD.INI is stored in <i>SystemDrive:\Program Files\Novadigm\LIB</i> , by default.	Connect.log
logsize	Optional	Specifies the size of the log file in bytes. When the logsize is reached, a backup file (.BAK) is created. By default, this file is connect.bak. If a backup file already exists, it will be overwritten.	1000000
logonpanel	Optional	Controls the display of the logon panel.	Y
managerurl	Optional	Specifies the address of the Radia Configuration Server to be used for HTTP object transfer. The managerurl specification takes the form <i>http://hostname:port/nvdurl</i> .	N/A
providername	Mandatory	The name of the Radia Configuration Server, which is set during the standard installation. This is used to name the folder below the STARTDIR on the client computer. See <i>Startdir</i> on page 41 for more information.	Radia

Table 2.3 ~ [ARGS] Section of INSTALL.INI

Argument	Mandatory or Optional	Description	Default Value
redirect	Optional	<p><i>Used for the Radia Software Manager only.</i></p> <p>Specifies an alternate start-up file (<i>filename.xml</i>), which can be accessed via a network path or URL. If the redirect tag is set in args.xml, the Radia Software Manager uses the properties specified in the alternate file.</p> <p>For example, you might set redirect to point to a start-up file on the network that is shared by all users.</p>	N/A
resolutionmanager	Mandatory	<p>Identifies the IP address for the Radia Configuration Server. You can also use the server name.</p> <p>This value will be overridden if a different IP address is specified in the Radia Configuration Server window in the Radia 4.x Client Installation Wizard. If you do not want this value to be modified, set NVDENABLEIP = N in the [PROPERTIES] section of the INSTALL.INI.</p>	N/A
resolutionport	Mandatory	<p>Identifies the port for the Radia Configuration Server.</p> <p>This value will be overridden if a different port is specified in the Radia Configuration Server window in the Radia 4.x Client Installation Wizard. If you do not want this value to be modified, set NVDENABLEIP = N in the [PROPERTIES] section of the INSTALL.INI.</p>	N/A
sslmanager	Optional	<p>Specifies the address of the Radia Configuration Server to be used for SSL communications.</p> <p>If you want self-maintenance to use SSL communications, concatenate ::SM to the end of the specified IP address or host name. For example, sslmanager= <i>hostname::SM</i></p> <p>Warning: Use the ::SM switch with the following caveat in mind; the file (cacert.pem) that contains the CA root certificates cannot be maintained. If the corresponding CA root certificate for the certificate in use by the Radia Configuration Server should ever become expired, revoked, or corrupt, it will result in disabling SSL communications to the Radia Configuration Server.</p>	N/A
sslport	Optional	<p>Specifies the TCP/IP port that the SSL manager is listening on. This is normally 443. The sslport specification takes the form sslport=<i>port</i>.</p>	N/A

Table 2.3 ~ [ARGS] Section of INSTALL.INI

Argument	Mandatory or Optional	Description	Default Value
startdir	Optional	<p>Specifies the starting IDMLIB directory (by default, <i>SystemDrive:\Program Files\Novadigm\Lib\</i>).</p> <ul style="list-style-type: none"> • \$MACHINE – Uses the current computer name. • \$USER – Uses the subscriber who is logged on. • CUSTOM – Literal custom specification. Type <code>startdir=<i>foldername</i></code>. If the folder name contains embedded spaces, enclose the entire name in double quotes. <p>Note: You might want to do this to distribute a set of common applications to be shared by all subscribers of a multi-user computer.</p>	\$USER
uioption	Optional	Controls the display of the status window.	N

[OBJECTS] Section of INSTALL.INI

Use the [OBJECTS] section to specify Radia objects to be created on the client computer and to set their default values. The format is *clientobject_attribute*. For example, if you wanted to set the IP address for your Radia Configuration Server, set ZMASTER_ZIPADDR.

Table 2.4 ~ [OBJECTS] Section of INSTALL.INI

Argument	Description	Default Value
ZMASTER_ZDSTSOCK	The port setting for the Radia Configuration Server.	3464
ZMASTER_ZIPADDR	The IP address for the Radia Configuration Server.	N/A
ZMASTER_ZNTFPORT	The port that the Radia Client's notify daemon is 'listening' on.	3465
ZMASTER_ZNTFYSEC	This attribute allows a Notify operation to execute programs only from the IDMSYS directory. This is used for security during Notify operations.	Y
ZMASTER_ZTIMEO	Amount of time that the Radia Client will wait for a response from the Radia Configuration Server before the Radia Client program is deactivated (timed out). Numeric value between 0 and 3200, in seconds.	240
ZMASTER_ZTRACE	Enables log to include communications buffer information; also generates unique logs for create methods. Y Turns on Communication and Client Method Tracing. S Turns on Communication 'summary' information; Client Method Tracing is <i>not</i> enabled. N Communication Tracing and Client Method Tracing are disabled.	N
ZMASTER_ZTRACEL	Level of tracing generated in the Radia Client log files. 0 to 999, where 0=minimal tracing, 40=acceptable for most activity, and 999=maximum.	040
ZMASTER_ZUSERID	The subscriber's user ID.	The name of the user currently logged on to the computer.
ZMASTER_ZVRFYUID	Verify the user ID sent by the Radia Configuration Server's Notify command with the ZUSERID field found in the Radia Client's ZMASTER object.	N
PROXYINF_USEPROXY	Indicates whether you use a proxy server to connect to the Radia Configuration Server.	N
PROXYINF_DISCOVER	<i>For use with Microsoft's Internet Explorer.</i> Set to the proxy address and port that your Web browser is using.	N
PROXYINF_PROXADDR	The IP address and port number of your proxy server.	xxx.xxx.xxx.xxx:1080
RADSETUP_COP	Set this to Y to enable Radia Client Operations Profiles.	N

Installing the Radia 4.x Clients

Before installing the Radia Clients, you must decide whether to initiate the installation from:

- a command line that initiates the installation from a Web page, FTP site, mapped drive, CD-ROM, or e-mail. See *Initiating the Radia Client Installation from a Command Line* below.
- a logon script. See *Initiating the Radia Client Installation from a Logon Script* on page 45.
- the Radia Management Portal. This is recommended for mass rollouts in a Windows NT, 2000, or XP environment. See the *Radia Management Portal Guide* for more information.

After initiating the installation, the Radia Client 4.x Installation Wizard runs. This section describes some of the ways that you can initiate the Radia Client installation, and then describes the standard Radia Client 4.x Installation Wizard.

Initiating the Radia Client Installation from a Command Line

Before performing an installation from a command line, you must determine:

- how you are going to make the Radia Client installation program available to your subscribers. You can do this via a Web page, FTP site, mapped drive, CD-ROM, or e-mail.
- what Radia Client features (Radia Application Manager, Radia Software Manager, and Radia Inventory Manager) you want to install and pass any additional arguments to the command line.

EXAMPLE

The following is an example of a command line that will install the Radia Software Manager silently and create a detailed Windows Installer log.

```
SETUP.EXE ADDLOCAL=NVDINSTALLRSM /qn /L*v C:\Novadigm\install.log
```

The arguments in this command line, and others, are described in Table 2.5 below and Table 2.6 on page 44.

Specifying the Radia Client Features to Install

To specify the features that you want to install, use the appropriate feature state argument, such as ADDLOCAL, and specify the features that you want to install.

Table 2.5 ~ Radia Client Feature State Arguments

Specify the following arguments	To set the feature state
ADDLOCAL	Type a comma-delimited list of features that you want set to "Will be installed on local hard drive."

Specify the following arguments	To set the feature state
REMOVE	Type a comma-delimited list of features that you want set to "Entire feature will be unavailable." This only removes the features—not the entire product. Therefore, if you use the REMOVE property and type each of the feature names, the core product will still be stored on your computer. If you want to remove the entire product, type REMOVE=ALL.

When specifying features on the command line, reference the Radia Client features as follows:

- NVDINSTALLRAM
Installs the Radia Application Manager.
- NVDINSTALLRSM
Installs the Radia Software Manager.
- NVDINSTALLRIM
Installs the Radia Inventory Manager.
- NVDINSTALLROM
Installs the Radia OS Manager.
- NVDINSTALLPATCH
Installs the Radia Patch Manager.

For example, if you want to install the Radia Application Manager and the Radia Software Manager to the computer, the command line might be:

```
SETUP.EXE ADDLOCAL=NVDINSTALLRAM,NVDINSTALLRSM
```

Additional Command Line Arguments

Some additional arguments that you can pass to the installation program on the command line are described in Table 2.6 below.

Argument	Description
/qn	Performs a silent installation. Note: A silent installation is one that takes place without a user interface. Throughout our literature, the terms "silent installation," "quiet installation," and "unattended installation" are all used to refer to the same process.
/qb	Displays the progress bar only during the installation.
/L*v <i>drive:\install.log</i>	Creates a detailed Windows Installer log. Note: Using this option may impact the performance of the installation.

Argument	Description
<code>/a TARGETDIR= drive:\targetdirectory</code>	Creates a Windows Installer AIP in the specified target directory. Note: A Windows Installer Administrative Installation Point (AIP) is also known as an Administrative Control Point (ACP). The target directory contains RADIA.MSI, the installation folders, setup.exe, and any files (such as INSTALL.INI or Visual Basic scripts) stored in the same directory as setup.exe. Once you have created the AIP, you can run setup.exe and pass the appropriate command line parameters. This starts the Windows Installer and passes the specified parameters to it.
<code>NVDINIFILE=path\INIfilename</code>	If you want to rename the installation INI file, pass this parameter to the command line. Be sure to include the fully qualified path. By default, the installation program refers to INSTALL.INI located in the current directory.

If you initiate a Radia Client installation with a command line that does not contain the silent installation arguments (`/qn`), the Radia Client Installation Wizard opens. See *Using the Radia Client Installation Wizard* on page 47 for more information.

Initiating the Radia Client Installation from a Logon Script

You can use a logon script on a Windows 2000, Windows Server 2003, XP, or Netware client to automate installation of the Radia Clients.

The following is an example of code that can be added to your logon script that installs the Radia 4.x Clients. If the Radia Clients are *not* already installed when the subscriber logs on to the server, this logon script runs the Radia 4.x Client installation program.

```
:begin
@echo off
if exist C:\progra~1\Novadigm\LIB\zmaster.edm goto skipinst
    start setup.exe /qn
:skipinst
```

Figure 2.3 ~ Sample logon script.

```
if exist C:\progra~1\Novadigm\lib\zmaster.edm goto skipinst
```

To determine if the Radia Clients already exist, the script checks to see if the ZMASTER object (ZMASTER.EDM) exists in its default location on the local computer.

Note

The ZMASTER object begins the resolution process and is the first object exchanged during the Client Connect process.

If ZMASTER.EDM *exists*, the script skips the installation. If ZMASTER.EDM *does not* exist, the Radia 4.x Client installation program launches.

Installing the Radia Clients

```
start setup.exe /qn
```

This command line performs a silent installation of the Radia Clients.

Note

Modify this script to reflect your organization's needs.

If you initiate a Radia Client installation using a command line that does not contain the silent installation arguments, the Radia Client Installation Wizard opens. See *Using the Radia Client Installation Wizard* on page 47 for more information.

Using the Radia Client Installation Wizard

If you initiate a Radia Client installation without the arguments for a silent installation, the Radia Client Installation Wizard opens. The following steps describe the standard installation procedure. These steps may vary based on INSTALL.INI or any arguments passed when running the installation.

To install Radia Clients using the Installation Wizard

1. From the folder containing the Radia Client installation files, run **setup.exe**.

Reminder

You can initiate setup.exe from a command line, logon script, or from the Radia Management Portal. Go to the beginning of this chapter for more information.

The **Radia Client Installation Wizard** opens.

2. Click **Next**.

The **License Agreement** window opens.

3. After reading and accepting the license agreement, click **Next**.

The **Destination Folder** window opens. The default location for the Radia Clients is *SystemDrive:\Program Files\Novadigm*.




Figure 2.4 ~ Destination Folder window.

If you want to select a different destination for the Radia Client, click **Browse** and then navigate to the appropriate destination folder. This overrides the value set for `INSTALLDIR` in `INSTALL.INI`.

4. Click **OK** to continue.

5. Click **Next**.
The **Set User** window opens.




Figure 2.5 ~ Set User window.

6. In the **User Name** text box, type the name of the subscriber for whom you are installing the Radia Clients. This overrides the value set for IDENTIFICATION in INSTALL.INI.
7. Select the **Create a Radia Software Manager icon on the desktop** check box if necessary.

Note

This check box is not available in Windows 98. By default NVDSHORTCUT=Y, which means a shortcut will appear on the subscriber's desktop. Use NVDSHORTCUT=N to hide the shortcut. See the description of NVDSHORTCUT in the *Radia Software Manager Guide*.

8. Click **Next**.
The **Radia Configuration Server** window opens.




Figure 2.6 ~ Radia Configuration Server.

9. In the **IP Address** text box, type the IP address for the Radia Configuration Server. This overrides the value set for RESOLUTIONMANAGER in INSTALL.INI.
10. In the **Port** text box, type the port number. This overrides the value set for RESOLUTIONPORT in INSTALL.INI.

11. Click Next.

The **Select Features** window opens.





Figure 2.7 ~ Select Features window.

Note

The Radia Software Manager Client is not available for computers running Windows 95. If you use this installation program, the Radia Software Manager will not be an option.

12. Click  to select the features that you want to install.

Each time you click , a shortcut menu for that feature opens (see *Figure 2.8 ~ Feature set installation options* on page 52).

Note

Only install the Radia Clients for which you are licensed.





Figure 2.8 ~ Feature set installation options.

13. From the shortcut menu, select an installation option. These options are described in Table 2.7 below.

Option	Description
Will be installed on local hard drive	Installs the top-level feature on the local hard drive, but not any sub-features listed below.
Entire feature will be installed on local hard drive	Installs the entire feature, including any sub-features listed below. Note: In this installation program, selecting this option or the "Will be installed on local hard drive" option for the Radia Software Manager, Radia Application Manager, or Radia Inventory Manager results in the same installation because these features do not contain sub-features. Example: If you selected this option for the Radia Client feature in the Select Features window, all of the Radia Clients would be installed on the local hard drive.
Entire feature will be unavailable	The feature will not be installed. If previously installed this feature will be removed.

Tips

- If you want to set the same options for all of the features, you can click  **Radia Client** and select the appropriate option to apply the setting to all features.
- Click **Disk Cost** to see an overview of the disk space needed for the installation.

14. Click **Next**.

If .NET is not installed on the client computer and you have chosen to install the Radia Software Manager, .NET will be installed during the Radia Client installation. However, if you copied the installation program to your computer and did not include the \DotNet folder, the **DotNet Settings** message in Figure 2.9 on page 53 opens.




Figure 2.9 ~ DotNet Settings message.

15. Click **OK**.

If you do not want to install the Radia Software Manager, you can set this feature to be unavailable and then proceed. If you want to install the Radia Software Manager, you must copy the **\DotNet** folder to your computer. Be sure to copy this folder to the same directory where `setup.exe` is stored. Then, run `setup.exe` again.

16. If necessary, click **Next** again.

If .NET is not already installed on the computer, the **.NET Installation** window opens.




Figure 2.10 ~ .NET Installation window.

17. Click **Next**.

Caution
If you have installed .NET Beta, be sure to remove it before installing .NET.

The **Ready to Install the Application** window opens.

18. Click **Install** to begin the installation.

If necessary, the **.NET Framework Setup** wizard opens. Follow the prompts to install .NET on the client computer. After .NET is successfully installed, the Radia Client installation begins.

When the installation is done, the **Radia Client has been successfully installed** window (**Error! Reference source not found. Error! Bookmark not defined.**) opens.

19. Click **Finish** to close the Installation Wizard.

Removing the Radia Clients

The Windows Installer installation program offers the ability to remove your Radia 4.x Clients. This section describes how to remove the Radia Client using the Installation Wizard and using a command line.

Using the Installation Wizard to Remove Radia Clients

This section describes how to remove the Radia Client using the Installation Wizard.

Note

To remove specific features of the Radia Client, use the Modify option on the Application Maintenance window. This is discussed in *Modifying the Radia Client Installation* on page 59.

To remove Radia Clients using the Installation Wizard

1. From the folder containing the Radia Client installation files, double-click **setup.exe**. The **Application Maintenance** window opens.




Figure 2.11 ~ Application Maintenance window.

2. Select the **Remove** option.
3. Click **Next**.
The **Radia Client Uninstall** window opens.
4. Click **Remove**.
The files for all Radia Clients are removed from the computer.
The **Radia Client has been successfully uninstalled** window opens.
5. Click **Finish**.

Using a Command Line to Remove Radia Clients

This section describes how to remove Radia Clients using a command line.

To remove Radia Clients using a command line

- From the folder containing the Radia Client installation files, type the following command line:

```
SETUP.EXE REMOVE=ALL
```

See *Initiating the Radia Client Installation from a Command Line* on page 43 for additional arguments.

OR

If you would like to remove a single Radia Client, type a comma-delimited list of the features that you want to remove on the command line.

Note

Reference the features for the Radia 4.x Client installation as follows:

- Radia Application Manager NVDINSTALLRAM
- Radia Software Manager NVDINSTALLRSM
- Radia Inventory Manager NVDINSTALLRIM
- Radia OS Manager NVDINSTALLROM
- Radia Patch Manager NVDINSTALLPATCH

EXAMPLE

If you want to silently remove the Radia Software Manager and Radia Application Manager, type:

```
SETUP.EXE REMOVE=NVDINSTALLRSM,NVDINSTALLRAM /qn
```

Note

This only removes the features—not the entire product. Therefore, if you use the REMOVE argument and type each of the feature names, the core product will still be stored on your computer.

Repairing the Radia Clients

The Windows Installer installation program offers the ability to repair your Radia 4.x Clients. For example, if you have a missing Radia Client module, you can use this tool to repair the installation. This tool will not overwrite modules that exist on the client computer if they are newer than the ones provided with the installation.

This section describes how to repair Radia Clients using the Installation Wizard and using a command line.

Using the Installation Wizard to Repair Radia Clients

This section describes how to repair Radia Clients using the Installation Wizard.

To repair Radia Clients using the Installation Wizard

1. From the folder containing the Radia Client installation files, double-click **setup.exe**.
The **Application Maintenance** window opens.




Figure 2.12 ~ Application Maintenance window.

2. Select the **Repair** option.
3. Click **Next**.
The **Ready to Repair the Application** window opens.
4. Click **Next**.
When the repair is done, the **Radia Client has been successfully installed** window opens.
5. Click **Finish**.

Using a Command Line to Repair Radia Clients

This section describes how to repair Radia Clients using a command line.

To repair Radia Clients using a command line

- From the folder containing the Radia Client installation files, type the following command line:

```
msiexec /f RADIA40.MSI
```

Note

Additional parameters can be used with this command line. For more information, see your Windows Installer documentation.

Modifying the Radia Client Installation

The Windows Installer installation program offers the ability to modify your Radia 4.x Client installation by adding or removing individual features. This section describes how to modify the installation of Radia Clients using the Installation Wizard and using a command line.

Using the Installation Wizard to Modify the Installation of Radia Clients

This section describes how to modify the installation of Radia Clients using the Installation Wizard.

To modify the installation of Radia Clients using the Installation Wizard

1. From the folder containing the Radia Client installation files, double-click **setup.exe**.

The **Application Maintenance** window opens.




Figure 2.13 ~ Application Maintenance window.

2. Select the **Modify** option.
3. Click **Next**.

The **Select Features** window opens. See *Using the Radia Client Installation Wizard* on page 47 for information about how to use this window.




Figure 2.14 ~ Select Features window.

4. Click **Next**.
The **Ready to Modify the Application** window opens.
5. Click **Next**.
The **Radia Client has been successfully installed** window opens.
6. Click **Finish** to close the installation program.

Using a Command Line to Modify the Installation of Radia Clients

This section describes how to modify the installation of Radia Clients using a command line.

To modify the installation of Radia Clients using a command line

- From the folder containing the Radia Client installation files, type the following command line:

```
SETUP.EXE FeatureStateArgument=feature1,feature2
```

Table 2.8 ~ Radia Client Feature State Arguments

Specify the following arguments	To set the feature state
ADDLOCAL	Type a comma-delimited list of features that you want set to "Will be installed on local hard drive."
REMOVE	Type a comma-delimited list of features that you want set to "Entire feature will be unavailable." This only removes the features—not the entire product. Therefore, if you use the REMOVE property and type each of the feature names, the core product will still be stored on your computer. If you want to remove the entire product, type REMOVE=ALL.

Note

Reference the features for the Radia 4.x Client installation as follows:

- Radia Application Manager NVDINSTALLRAM
- Radia Software Manager NVDINSTALLRSM
- Radia Inventory Manager NVDINSTALLRIM
- Radia OS Manager NVDINSTALLROM
- Radia Patch Manager NVDINSTALLPATCH

EXAMPLE

If you want to install the Radia Software Manager, and to make the Radia Inventory Manager and Radia Application Manager unavailable, you would use the following command line:

```
SETUP.EXE ADDLOCAL=NVDINSTALLRSM REMOVE=NVDINSTALLRIM,NVDINSTALLRAM
```

See *Initiating the Radia Client Installation from a Command Line* on page 43 for additional arguments.

Using a Pre-Install Script

Use Visual Basic scripts to customize MSI properties that affect the installation. The following is a very simple Visual Basic script, which is intended to be an example only. This script is available in the `\win32\samples` directory on the Radia Client CD-ROM.

Caution

Be sure to use the `NVDPRECAPATH` argument to specify the fully qualified path and filename of a custom Visual Basic pre-install script in `INSTALL.INI` or on the command line. See the description of `NVDPRECAPATH` in *Table 2.2 ~ [PROPERTIES] Section of INSTALL.INI* on page 34.

```
' The following sample demonstrates fetching an MSI property, then setting the
same property.
' The property values are displayed in message boxes for debugging purposes.
Option Explicit
msgbox Session.Property("ALLUSERS")
Session.Property("ALLUSERS") = "1"
msgbox Session.Property("ALLUSERS")
```

Figure 2.15 ~ Sample pre-install script.

You can use a pre-install script to override the property settings of the arguments that control the behavior of the Radia Software Manager, such as those in the `[ARGS]` section of `INSTALL.INI`, as well as the attribute values for Radia objects, such as those specified in the `[OBJECTS]` section of `INSTALL.INI`.

Caution

New objects or properties must be defined in `INSTALL.INI`.

You can use a pre-install script to override a value for the object or property, but if you attempt to specify a new object or property in the pre-install script, it will be ignored.

To override property settings or attributes for objects

Caution

Be sure to type the name of the property or the object and its attribute such as NVDOBJZMASTER_ZDSTSOCK in all uppercase.

- Use the prefix **NVDARG** to override property settings.

For example, if you want to override the value set for the identification property, which identifies the subscriber session to the Radia Configuration Server, type:

```
Session.Property("NVDARGIDENTIFICATION")="jenns"
```

- Use the prefix **NVDOBJ** to override object attributes.

For example, if you want to override the value set for the ZDSTSOCK attribute of the ZMASTER object, which is the port setting for the Radia Configuration Server, type:

```
Session.Property("NVDOBJZMASTER_ZDSTSOCK")="3462"
```

Using a Post-Install Script

Use custom Visual Basic, REXX, or Tcl scripts to run processes after installing Radia Clients. For example, your post-install script can initiate a connection to the Radia Configuration Server in order to process mandatory applications. A sample script is available in the **\win32\samples** folder on the Radia Client installation CD-ROM.

Caution

Be sure to use the NVDPOSTCAPATH argument to specify the fully qualified path and filename of the custom Visual Basic or REXX post-install script in INSTALL.INI or on the command line. See the description of NVDPOSTCAPATH in *Table 2.2 ~ [PROPERTIES] Section of INSTALL.INI* on page 34. For example, if you want to run a script called redstart.rex, uncomment and set NVDPOSTCAPATH=C:\Progra~1\Novadigm\radstart.rex

Include the script in the \maint folder of the client install. It will automatically get copied into IDMSYS. A script example is shown below:

```
/* ***** */
/** RADSTART.REX                               **/
/**                                           **/
/** DESCRIPTION:                               **/
/** Client Rexx will perform a Radia connection to an RCS defined in the **/
/** install.ini to process all mandatory applications.           **/
/**                                           **/
/** AUTHOR:          HP                        **/
/** LANGUAGE:       REXX                       **/
/**                                           **/
/* ***** */
/* trace i */

fullcmd = 'HIDE radntfyc localhost wait radskman
context=m,log=connect_initial.log'
call edmcmd fullcmd;
```

Figure 2.16 ~ Sample REXX code from a post-install script.

Summary

- The Radia Client installation program consists of one MSI package with five feature sets: Radia Application Manager, Radia Inventory Manager, Radia Software Manager, Radia OS Manager and Radia Patch Manager.
- You can install the Radia Clients using a command line or using the Installation Wizard.
- Customize your installation to suit your enterprise.
- Create pre-install and post-install scripts to run processes before or after the clients are installed.

Installing the Radia Administrator Workstation

At the end of this chapter, you will:

- Understand the system requirements for installing the Radia Administrator Workstation.
- Be familiar with the installation files.
- Know how to install the Radia Administrator Workstation using the Installation Wizard and command lines.
- Understand the feature settings of the Radia Administrator Workstation.
- Know how to remove and repair the Radia Administrator Workstation using the Installation Wizard and command lines.

The Radia Administrator Workstation installation program uses the Microsoft MSI format for Windows Installer. The program consists of one MSI package with four feature sets—Radia Packager, Radia System Explorer, Radia Client Explorer, and Radia Screen Painter.

System Requirements

- Clean computer. (A *clean computer* is a computer with only the target subscriber's operating system installed.)
- Windows 2000 and above.
- TCP/IP connection to the Radia Configuration Server.
- Minimum resolution of 800 x 600.
- MS Windows Installer Version 2.0 or higher.
The MSI 2.0 installation program is available in the **management_infrastructure\administrator_workstation\win32\msi** folder on the Radia Infrastructure CD-ROM. If Windows Installer does not exist, or if an earlier version is detected on the computer, the MSI 2.0 installation program runs automatically.
- For Windows NT, 2000, Server 2003, or XP, you must have administrator rights to the computer to install the Radia Administrator Workstation.

About the Installation Files

setup.exe

setup.exe is stored on the Radia Infrastructure CD-ROM in the **management_infrastructure\administrator_workstation\win32** folder. It accepts any command line parameters and passes them to Windows Installer.

You can also create a Windows Installer Administrative Installation Point (AIP) for network installations.

Note

A Windows Installer Administrative Installation Point (AIP) is also known as an Administrative Control Point (ACP).

The AIP starts Windows Installer and passes any command line parameters to it. To create the Windows Installer Administrative Installation Point (AIP) in a specified target directory, type:

```
SETUP.EXE /a TARGETDIR=drive:\targetdirectory /qb
```

The target directory contains RADADMIN40.MSI, the installation folders, and setup.exe.

RADADMIN40.MSI

RADADMIN40.MSI is the MSI database file, which contains the default configuration information for the installation. This file is stored on the Radia Infrastructure CD-ROM in the `management_infrastructure\administrator_workstation\win32\` folder.

Installing the Radia Administrator Workstation

This section describes how to install the Radia Administrator Workstation using the Installation Wizard and using a command line.

Using the Installation Wizard to Install the Radia Administrator Workstation

This section describes how to install the Radia Administrator Workstation for Windows using the Installation Wizard.

To install the Radia Administrator Workstation using the Installation Wizard

1. From the folder containing the Radia Administrator Workstation installation files, run **setup.exe**.

The **Welcome to the Radia Administrator Workstation** window opens.

2. Click **Next**.

The License Agreement window opens.

3. After reading and accepting the license agreement, click **Next**.

If the Radia Client is not installed on the computer, the **Destination Folder** window opens.

Note

If the Radia Client is already installed on the computer, this window will not open and the Radia Administrator Workstation is installed in the same location as the Radia Client.





Figure 3.1 ~ Destination Folder window.

If you want to select a different destination for the Radia Administrator Workstation, click **Browse**, and then navigate to the appropriate destination folder.

Click **OK** to continue.

4. Click **Next**.

The **Radia Configuration Server** window opens.



The screenshot shows a window titled "Radia Administrator Workstation" with a sub-header "Radia Configuration Server". Below the sub-header, the text "Provide an IP Address and Port to proceed." is displayed. There are two text input fields: "IP Address" with a placeholder "xxx.xxx.xxx.xxx" and "Port" with the value "3464". At the bottom of the window, there are three buttons: "< Back", "Next >", and "Cancel". The Hewlett-Packard Company logo is visible at the bottom left.

Figure 3.2 ~ Radia Configuration Server window.

5. In the **IP Address** text box, type the IP address for the Radia Configuration Server.
6. In the **Port** text box, type the port number (default is 3464).
7. Click **Next**.

The **Select Features** window opens.






Figure 3.3 ~ Select Features window.

8. Click  to select the features that you would like to install.

Tips

- If you want to set the same options for all of the features, you can click  next to **Radia Administrator Workstation** and select the appropriate option to apply the setting to all features.
- Click **Disk Cost** to see an overview of the disk space needed for the installation.

Each time you click  a shortcut menu for that feature opens.




Figure 3.4 ~ Feature set installation options.

9. From the shortcut menu, select an installation option. These options are described in Table 3.1 below.

Option	Description
Will be installed on local hard drive	Installs the top-level feature on the local hard drive, but not any sub-features listed below.
Entire feature will be installed on local hard drive	Installs the entire feature, including any sub-features listed below. Note: In this installation program, selecting this option or the "Will be installed on local hard drive" option for any of the features results in the same installation because these features do not contain sub-features.
Entire feature will be unavailable	The feature will not be installed. If previously installed, this feature will be removed.

10. Click **Next**.

The **Ready to Install the Application** window opens.

11. Click **Install** to begin the installation.

When the installation is done, the **Radia Administrator Workstation has been successfully installed** window opens.

12. Click **Finish** to exit the installation.

Using a Command Line to Install the Radia Administrator Workstation

You can also use the command line to run the Radia Administrator Workstation installation program. For example, if you want to install only the Radia Packager on a computer, the command line that you run from the directory containing the Radia Administrator Workstation installation files might be:

```
SETUP.EXE ADDLOCAL=NVDINSTALLPACKAGER
```

Specifying the Features to Install

To specify the features that you want to install, use the appropriate feature state argument, such as ADDLOCAL, and specify the features that you want to install.

Specify the following arguments	To set the feature state
ADDLOCAL	Type a comma-delimited list of features that you want set to "Will be installed on local hard drive."
ADDSOURCE	Type a comma-delimited list of features that you want set to "Will be installed to run from network."
ADVERTISE	Type a comma-delimited list of features that you want set to "Feature will be installed when required."
REMOVE	Type a comma-delimited list of features that you want set to "Entire feature will be unavailable." This only removes the features—not the entire product. Therefore, if you use the REMOVE property and type each of the feature names, the core product will still be stored on your computer. If you want to remove the entire product, type REMOVE=ALL.

When specifying features on the command line, reference the Radia Administrator Workstation features as follows:

- NVDINSTALLPACKAGER Radia Packager
- NVDINSTALLPUBLISHER Radia Publisher
- NVDINSTALLSYSTEMEXPLORER Radia System Explorer
- NVDINSTALLCLIENTEXPLORER Radia Client Explorer
- NVDINSTALLSCREENPAINTER Radia Screen Painter

For example, if you want to install the Radia System Explorer and the Radia Client Explorer to the computer, the command line might be:

```
SETUP.EXE ADDLOCAL= NVDINSTALLSYSTEMEXPLORER,NVDINSTALLCLIENTEXPLORER
```

If you run the installation from a command line, be sure to pass the IP address for the Radia Configuration Server to the installation. For example:

```
SETUP.EXE NVDOBJZMASTER_ZIPADDR=10.10.10.1
```

Additional Command Line Arguments

Some additional arguments that you can pass to the installation program on the command line are described in Table 3.3 below.

Table 3.3 ~ Command Line Arguments

Argument	Description
/qn	Performs a silent installation.
/qb	Displays the progress bar only during the installation.
/l*v <i>drive:\install.log</i>	Creates a detailed Windows Installer log. Note: Using this option may impact the performance of the installation.
/a TARGETDIR= <i>drive:\targetdirectory</i>	Creates a Windows Installer AIP in the specified target directory. Note: A Windows Installer Administrative Installation Point (AIP) is also known as an Administrative Control Point (ACP). The target directory contains RADADMIN40.MSI, the installation folders, and setup.exe. Once you have created the AIP, you can run setup.exe and pass the appropriate command line parameters. This starts the Windows Installer and passes the specified parameters to it.

Removing the Radia Administrator Workstation

The Windows Installer installation program offers the ability to remove the Radia Administrator. This section describes how to remove the Radia Administrator Workstation using the Installation Wizard and using a command line.

Using the Installation Wizard to Remove the Radia Administrator Workstation

This section describes how to remove (uninstall) the Radia Administrator Workstation using the Installation Wizard.

Note

To remove specific features of the Radia Administrator Workstation, use the Modify option on the Application Maintenance window. This is discussed in *Modifying the Radia Administrator Workstation Installation* on page 79.

To remove the Radia Administrator Workstation using the Installation Wizard

1. From the folder containing the Radia Administrator Workstation installation files, double-click **setup.exe**.

The **Application Maintenance** window opens.




Figure 3.5 ~ Application Maintenance window.

2. Select the **Remove** option.

3. Click **Next**.

The **Radia Administrator Workstation Uninstall** window opens.

4. Click **Next**.

The files for the Radia Administrator Workstation are removed from the computer.

The **Radia Administrator Workstation has been successfully uninstalled** window opens.

5. Click **Finish**.

Using a Command Line to Remove the Radia Administrator Workstation

This section describes how to remove (uninstall) the Radia Administrator Workstation using a command line.

To remove the Radia Administrator Workstation using a command line

- From the folder containing the Radia Administrator Workstation installation files, type the following command line:

```
SETUP.EXE REMOVE=ALL
```

OR

If you would like to remove a single Radia Administrator Workstation feature, type a comma-delimited list of the features that you want to remove on the command line.

EXAMPLE

If you want to silently remove the Radia System Explorer and Radia Client Explorer, type:

```
SETUP.EXE REMOVE=NVDINSTALLSYSTEMEXPLORER,NVDINSTALLCLIENTEXPLORER /qn
```

Note

Reference the features for the Radia 4.x Administrator Workstations as follows:

- | | |
|-------------------------|--------------------------|
| • Radia Packager | NVDINSTALLPACKAGER |
| • Radia Publisher | NVDINSTALLPUBLISHER |
| • Radia System Explorer | NVDINSTALLSYSTEMEXPLORER |
| • Radia Client Explorer | NVDINSTALLCLIENTEXPLORER |
| • Radia Screen Painter | NVDINSTALLSCREENPAINTER |

Caution

This only removes the features—not the entire product. Therefore, if you use the REMOVE property and type each of the feature names, the core product will still be stored on your computer.

Repairing the Radia Administrator Workstation

The Windows Installer installation program offers the ability to repair the Radia Administrator Workstation. For example, if you have a missing Radia Administrator Workstation module, you

can use this tool to repair the installation. This tool will not overwrite modules that exist on the computer if they are newer than the ones provided with the installation.

This section describes how to repair the Radia Administrator Workstation using the Installation Wizard and using a command line.

Using the Installation Wizard to Repair the Radia Administrator Workstation

This section describes how to repair the Radia Administrator Workstation using the Installation Wizard.

To repair the Radia Administrator Workstation using the Installation Wizard

1. From the folder containing the Radia Administrator Workstation installation files, double-click **setup.exe**.

The **Application Maintenance** window opens.




Figure 3.6 ~ Application Maintenance window.

2. Select the **Repair** option.

3. Click **Next**.

The **Ready to Repair the Application** window opens.

4. Click **Next**.

When the repair is done, the **Radia Administrator Workstation has been successfully installed** window opens.

5. Click **Finish**.

Using a Command Line to Repair the Radia Administrator Workstation

This section describes how to repair the Radia Administrator Workstation using a command line.

To repair the Radia Administrator Workstation using a command line

- From the folder containing the Radia Administrator Workstation installation files, type the following command line:

```
msiexec /f radadmin40.msi
```

Note

Additional parameters can be used with this command line. For more information, see your Windows Installer documentation.

Modifying the Radia Administrator Workstation Installation

The Windows Installer installation program offers the ability to modify the Radia 4.x Administrator Workstation installation by adding or removing individual features. This section describes how to modify the installation of the Radia Administrator Workstation using the Installation Wizard and using a command line.

Using the Installation Wizard to Modify the Radia Administrator Workstation

This section describes how to modify the installation of the Radia Administrator Workstation using the Installation Wizard.

To modify the Radia Administrator Workstation installation using the Installation Wizard

1. From the folder containing the Radia Administrator Workstation installation files, double-click **setup.exe**.

The **Application Maintenance** window opens.




Figure 3.7 ~ Application Maintenance window.

2. Select the **Modify** option.
3. Click **Next**.

The **Select Features** window opens. See *Installing the Radia Administrator Workstation* on page 69 for information about how to use this window.




Figure 3.8 ~ Select Features window.

4. Click **Next**.
The **Ready to Modify the Application** window opens.
5. Click **Next**.
The **Radia Administrator Workstation 4.x has been successfully installed** window opens.
6. Click **Finish** to close the installation program.

Using a Command Line to Modify the Radia Administrator Workstation Installation

To modify the Radia Administrator Workstation installation using a command line

- From the folder containing the Radia Administrator Workstation installation files, type the following command line:

```
SETUP.EXE FeatureStateArgument=feature1,feature2
```

See Table 3.2 on page 74 for more information.

EXAMPLE

If you want to install the Radia Packager to the local hard drive, and to make the Radia System Explorer and Radia Client Explorer unavailable, use the following command line:

```
SETUP.EXE ADDLOCAL=NVDINSTALLPACKAGER REMOVE=NVDINSTALLSYSTEMEXPLORER,NVDINSTALLCLIENTEXPLORER
```

See *Additional Command Line Arguments* on page 75 for additional arguments.

Summary

- The Radia Administrator Workstation consists of one MSI package with five feature sets: Radia Client Explorer, Radia Packager, Radia Publisher, Radia Screen Painter, and Radia System Explorer.
- Install the Radia Administrator Workstation on a clean computer.
- You can install the Radia Administrator Workstation using a command line or using the Installation Wizard.

Installing the Radia Inventory Manager Server

At the end of this chapter, you will:

- Understand the installation media.
 - Have installed the Radia Inventory Manger Server.
 - Have installed the Radia Sample Reporting Database (optional).
- OR**
- Have installed your own reporting database.

Installation Media

The Radia Inventory Manager Server is one of the Extended Infrastructure products provided on the Radia Infrastructure CD.

Tips

- Click **Cancel** in any of the windows to exit the installation. If you click **Cancel** accidentally, there are prompts that enable you to return to the installation program.
- Click **Back** at any time to return to previous windows. All the information that you have entered thus far will remain unchanged.
- Most windows have an error message associated with them. If your specifications are not acceptable, an error message will appear. Click **OK**, and enter the correct information.

Installation

The installation CD-ROM contains an installation process that will install the Radia Inventory Manager.

There are a few important points to remember prior to installing the Radia Inventory Manager.

- If a current installation of the Radia Integration Server (httpd.tkd) exists on the drive where you are installing the Radia Inventory Server, the product is automatically installed to the existing Radia Integration Server location. The Radia Integration Server is a foundation component of various Radia products.
- If you *have not* already installed a Radia product with your current license to the selected directory, you *must* install the license file, license.nvd, during the Radia Inventory Manager installation.
- If your current Radia license exists in the selected installation directory from a previous install, you will not need to install the license.nvd file.

Caution

If you are currently running Radia as a service, you must stop the service prior to this installation.

Close all other applications prior to beginning installation of the Radia Inventory Manager.

To install the Radia Inventory Manager

1. Insert the installation CD-ROM for the Radia Inventory Manager into the CD-ROM drive.
2. Using the Windows Explorer, select and open your CD-ROM drive.
3. Open the **extended_infrastructure** folder.
4. Expand the **inventory_manager_server** folder.

- Expand the **win32** folder.




Figure 4.1 ~ The location of the *setup.exe* modules for the Radia Inventory Manager.

- Double-click **setup.exe** (in the list view).




Figure 4.2 ~ Double-click *setup.exe* to begin the Radia Inventory Manager installation.

The **Welcome** window opens.

- Click **Next** to proceed.

The **End-User License Agreement** window opens for you to read the licensing terms for this product. You must accept the terms before the Radia Proxy Server can be installed.

- Click **Accept** to agree to the terms of the software license and continue with the installation.

If this is the first installation of a Radia product containing the foundation Radia Integration Server component, the **Radia Inventory Manager Location** window opens.




Figure 4.3 ~ Select the folder to which you want to install the Radia Inventory Manager.

In this window, you are prompted to enter or accept the location for the files that will install the Radia Inventory Manager, and the foundation Radia Integration Server component.

Note

The window to select an install folder is bypassed when an existing Radia Integration Server component exists on the target directory. In this case, the Radia Inventory Manager is installed automatically to the location of the existing Radia Integration Server.

9. After selecting the installation location, click **Next**.
The **Select Location of License File** window opens.




Figure 4.4 ~ Indicate where the license file is located.

In this window, you are asked to enter the location of your License File. Use the **Browse** button to identify the location of your **LICENSE.NVD** file.

Note

The License File window is bypassed when a valid Radia license exists on the target machine due to a previous Radia product install.

10. After locating your license file, click **Next**.

The **Installation Settings** window opens.




Figure 4.5 ~ Installation Settings window.

This window contains all the information that you specified during the Radia Inventory Manager installation process. This is your final opportunity to review and modify the settings you have indicated.

Note

The Install Radia Inventory Manager summary window may appear slightly different if you have not entered the license file location.

If you discover any errors, or want to modify any of your entries, click **Back**. After making your changes, click **Next** to review your installation changes in the **Installation Settings** window.

11. Click **Install** to begin the installation.

Figure 4.6 on page 91 shows the installation in progress.




Figure 4.6 ~ Installation is in progress window.

Upon completion of the installation, the **Finish** window opens.

12. Click **Finish** to exit the installation program.

The Radia Integration Server will be started automatically.

Configuring the Radia Configuration Server

Once the Radia Inventory Manager components have been installed, it is necessary to configure two additional options on the Radia Configuration Server.

Configure the EDMPROF.DAT

The [MGR_RIM] section of the EDMPROF.DAT file specifies the HTTP HOST for the Radia Integration Server. As shipped from HP, the assumption is that the Radia Integration Server and the Radia Configuration Server will be running on the same computer.

If the Radia Integration Server is running on a computer other than the one running the Radia Configuration Server, you must edit the [MGR_RIM] section of the EDMPROF.DAT file to direct the HOST and PORT to the proper URL.

Installing the Radia Inventory Manager Server

The format for this addition is:

```
HTTP_HOST= Localhost  
HTTP_PORT= 3466
```

OR

```
HTTP_HOST= IPADDRESS  
HTTP_PORT= 3466
```

The default setting are:

```
HTTP_HOST = Localhost  
HTTP_PORT = 3466.
```

To change the MGR_RIM section of the edmprof.dat file, use the procedures outlined below.

To edit the EDMPROF.DAT file

1. Using your Windows Explorer, navigate to the bin file of your Radia Configuration Server.
2. Expand the bin file and locate the edmprof.dat file.




Figure 4.7 ~ Locate the edmprof.dat file in the bin file.

3. Using the text editor of your choice, open the edmprof.dat file.

4. Locate the [MGR_RIM] section.

```
[MGR_RIM]
HTTP_HOST = localhost
HTTP_PORT = 3466

*-----*
* Manager Radia Management Portal Section *
* HTTP_HOST = Host name of Radia Management Portal (RMO) *
* Multiple hosts may be specified (space or comma separated) *
* for fail over *
* HTTP_PORT = IP Port number of RMP *
* NO restart required *
*-----*
```

Figure 4.8 ~ [MGR_RIM] section of the edmprof.dat file.

5. Enter the location of the HTTP_HOST. This can be either local host or the IP address of the host machine.

```
[MGR_RIM]
HTTP_HOST = 111.111.111.111
HTTP_PORT = 3466
```

Figure 4.9 ~ You can enter either the IP address or the host name.

In the example shown in Figure 4.9 above, the IP address of the Radia Integration Server has been used. Instead of an IP address, you can use the **host name**. The **port**, 3466, is the default port number attended by the Radia Integration Server.

6. When you have completed editing the edmprof.dat file, save your changes and exit the text editor.

Limiting Access to Radia Inventory Manager Web-Pages

Caution

Use the following information *only* if you would like to restrict access to a specific Radia Integration Server URL.

In some situations, it may be desirable for a Radia administrator to want to restrict access to specific Radia Inventory Manager Web pages. To restrict access to a specific Radia Integration Server URL, edit the **httpd.rc** file. This file is located in the **etc** folder at the root of the Radia Integration Server directory.

For example, if you would like to restrict access to a specific Radia Integration Server URL such as /rim (this is the top URL for the Radia Inventory Manager), add the following line to the **Examples of Setting URL Security** section of the httpd.rc file:

```
SetAccess /rim "" NTLM/Group Administrators
```

This particular command restricts access of the Radia Inventory Manager to members of the Administrators group on the local machine.

The httpd.rc file that is shipped with the Radia Integration Server has additional examples built into it.

Installing the Radia Inventory Manager Sample Reporting Database (optional)

After installing the Radia Inventory Manager, you may choose to install the sample reporting database. The sample database provided is Microsoft's Access database. Other ODBC databases supported for production are SQL, Oracle, and Sybase.

To install the sample database (through the Radia Management Portal)

1. In **Services**, ensure that the Radia Integration Server is started.




Figure 4.10 ~ Starting the Radia Integration Server in Services.

2. Start your Web browser and type the address and port number of the Radia Integration Server into the address text box:

`http://<I/P Address or Hostname>:<Port>.`

- The *I/P Address* is the IP address of the computer running the Radia Integration Server.
- The *Hostname* is the host name of the computer running the Radia Integration server.
- The *Port* is the port number of the Radia Integration Server. This default port number is 3466.

Address

Figure 4.11 ~ Enter the IP address and port number in your Web browser.

The Logon screen opens.

3. Enter the **User Name** and **Password** and click **Login**.

Note

As shipped from HP, the User Name is **admin** and the Password is **secret**. This may have been changed. It may be necessary to obtain your own User Name and Password from your Radia administrator.

If your Radia Inventory Manager will be running from the Radia Management Portal, the following screen opens:




Figure 4.12 ~ The home page of the Radia Management Portal.

4. In the upper right corner, click **INVENTORY**.

Note

It is possible that the Radia Inventory Manager is not running from the same location as the Radia Management Portal. If this is the case, then the home page of the Radia Integration Server is displayed. See *To install the sample database (Non-Radia Management Portal Installation)* on page 97 for information on how to complete the installation of the sample database.

The **Radia Inventory Manager Setup/Configuration** window opens.

Radia Inventory Manager Setup/Configuration

Figure 4.13 ~ Radia Inventory Manager Setup/Configuration.

The **Radia Inventory Manager Setup/Configuration** window opens upon the first connection to the Reporting section.

- Use Table 4.1 below to complete the configuration information for the Radia Inventory Manager Setup/Configuration.

Table 4.1 ~ Radia Inventory Manager Setup/Configuration

Item	Description
Auto-Create Demo Database	Select Yes to create the reporting database sample.
Data Source Name	This is a unique name used to create a data connection to a database using open ODBC. The data source name is used by applications that need to access or manage data in the database. The default, RIMDEMO, is automatically filled in for you. If you wish to use the sample database installed with the Radia Integration Server, leave this entry. If you wish to use an ODBC driver for a different database, enter that data source name here. Note: The ODBC driver for the database you choose must be installed prior to installing the Radia Integration Server.
DSN: User ID	If the data source database requires a user ID, enter that ID here. The sample data source does not require a user ID.
DSN: Password	If the data source requires a password, enter that here. The sample data source does not require a password.

If you accept the default of **Auto Create**, the Integration Server will create a Microsoft Access 97 DSN named RIMDEMO automatically.

Note
As received from HP, the Sample data source does not require a user ID or a password.

- Select **Yes** for the **Auto-Create Demo Database** option to create the demo database, and then click **Submit**.

An alert message is displayed indicating a successful installation.




Figure 4.14 ~ Alert message indicates a successful installation.

The Radia Integration Server is now ready to process data received from the Radia Configuration Server.

- Click on the **INVENTORY** button to exit setup.

To install the sample database (non-Radia Management Portal installation)

- In **Services**, ensure that the Radia Integration Server is started.




Figure 4.15 ~ Starting the Radia Integration Server in Services.

- Start your Web browser and type the address and port number of the Radia Integration Server into the address field:

`http://<I/P Address or Hostname>:<Port>.`

- The *I/P Address* is the IP address of the computer running the Radia Integration Server.
- The *Hostname* is the host name of the computer running the Radia Integration server.
- The *Port* is the port number of the Radia Integration Server. This port number is usually 3466.

Address	http://111.111.111.11:3466
---------	----------------------------

Figure 4.16 ~ Enter the IP address and port number in your Web browser.

The **Radia Integration Server** home page opens.




Figure 4.17 ~ Radia Integration Server home page.

-
3. Click the **Reporting** tab.

The **Radia Inventory Manager Setup/Configuration** window opens.

Radia Inventory Manager Setup/Configuration

Auto-Create Demo Database Yes No

Data Source Name

DSN: User ID

DSN: Password

Figure 4.18 ~ Radia Inventory Manager Setup/Configuration page.

The **Radia Inventory Manager Setup/Configuration** page opens upon the first connection to the Reporting section.

Use Table 4.1 on page 96 to complete the configuration information for the Radia Inventory Manager Setup/Configuration.

If you accept the default of **Auto Create**, the Radia Integration Server will create a Microsoft Access 97 DSN named RIMDEMO automatically.

Note

As received from HP, the sample data source does not require a User ID or a Password.

4. Select **Yes** for the **Auto-Create Demo Database** option to create the demo database, and then click **Submit**.

An alert message is displayed indicating a successful installation.



rim.cfg has been updated, click on reporting tab to continue...

Figure 4.19 ~ Alert message indicates a successful installation.

The Radia Integration Server is now ready to process data received from the Radia Configuration Server.

Radia Integration Server Configuration File: rim.cfg

The Radia Inventory Manager configuration file, **rim.cfg**, contains parameters you can use to adjust specific Radia Inventory Manager settings. The configuration file is located in the Radia Integration Server **/etc** directory. Some parameters may vary depending on your configuration.

```

# $Header: /cvs/nvd/rim/default.rc,v 1.11 2003/04/09 16:16:28 lfu Exp $
# Copyright (c) 1997-2000 Novadigm Inc. All Rights Reserved.
#
# RIM Module (Radia Inventory Manager)
#
# This section provides the core configuration for the
# RIM Sub-system. Please take care when hand-editing this.
#
rim::init {
    BUILD                403
    COMMIT_INTERVAL     5000
    DB_AUTOCREATE       0
    DL_DATEFMT          {%m/%d/%Y %I:%M:%S %p}
    DSN                 RIMDEMO
    DSN_ATTEMPTS        3
    DSN_DATEFMT         {%Y-%m-%d %H:%M:%S}
    DSN_DELAY           10
    DSN_PASSWD          {{DES}:0}
    DSN_PING            60
    DSN_USER            ""
    HOME                C:/Novadigm/IntegrationServer/modules/rim.tkd
    LABEL               Reports
    MAXROWS             500000
    MODULE              RIM
    N_WORKERS           2
    QUERY_VISIBLE       0
    ROWS_PER_PAGE       10
    STATUS_INTERVAL     600
    STATUS_RESET        {12:00 am}
    TITLE               {Radia Inventory Module}
    URL                 /rim
    VERSION             4.0
    WBEM_AUTOCREATE     0
    WBEM_AUTOLOAD       0
    WORKER_RETRY        3
    WORKER_TIMEOUT      180}
#
# END OF CONFIG
#

```

Figure 4.20 ~ Sample rim.cfg file.

Table 4.2 ~ rim.cfg Parameters		
Parameter	Default Value	Description
BUILD	N/A	Build number of rim.tkd, the Radia Inventory Manager module.
COMMIT_INTERVAL	5000	Number of transactions successfully processed to the backend database between each commit of the temporary queue used to hold all incoming data (odbc_queue.mk). Not usually modified.

Parameter	Default Value	Description
DB_AUTOCREATE	0	Controls the loading of the demo database: 1- Will automatically load the sample database. 0 – Will not automatically load the sample database.
DL_DATEFMT	(%m/%d/%Y %I:%M:%S %p)	Date format displayed on the Radia Integration Server web pages.
DSN	RIMDEMO	Data Source Name (DSN).
DSN_ATTEMPTS	3	Number of attempts to connect to the Radia Inventory Manager database DSN.
DSN_DATEFMT	{%Y-%m-%d %H:%M:%S}	Date format for the storage of the date string in the Radia Inventory Manager database.
DSN_DELAY	10	Delay in seconds between attempts to connect to the RIM DSN.
DSN_PASSWD	N/A	DSN password.
DSN_PING	60	Delay in seconds between pinging the database connection to verify the DSN is available.
DSN_USER	N/A	User name used to connect to the DSN.
HOME	C:/Novadigm/IntegrationServer/modules/rim.tkd	Home directory for the Radia Inventory Manager module, rim.tkd.
LABEL	Reports	Label for this module.
MAXROWS	500000	<i>Do not modify.</i> Maximum number of rows to retrieve from the RIM database to display.
MODULE	RIM	<i>Do not modify.</i> Name of this module.
N_WORKERS	4	Number of open ODBC connections.
QUERY_VISIBLE	0	Specify 0 or 1 to determine whether the UNIX Query function is to be displayed. 1 – UNIX Query hyperlink is visible. Set to 1 if tables in the database have been populated with UNIX clients. 0 – UNIX Query hyperlink is not visible.
ROWS_PER_PAGE	10	Number of rows displayed on each Radia Integration Server query result page.
STATUS_INTERVAL	600	Time interval (seconds) used to display the status message.
STATUS_RESET	{12:00 am}	Time status is rolled over.
URL	/rim	<i>Do not modify.</i> Url of this module.
VERSION	4.0	Version.

Parameter	Default Value	Description
WBEM_AUTOCREATE	0	The switch to enable the creation of a new sql file and table in the database when a new object class is received. 1 – Will create a new SQL file and table entry for a new object class. 0 – Does not create a file or table entry for a new object class. Note: If WBEM_AUTOCREATE is set to 1, set WBEM_AUTOLOAD to 0.
WBEM_AUTOLOAD	0	Controls the WBEM Autoload 1 - Will load WBEM audit objects on demand. 0 - Audit objects are loaded at startup. Note: If WBEM_AUTOLOAD is set to 1, set WBEM_AUTOCREATE to 0.
WORKER_RETRY	3	Number of times to retry before a message is discarded.
WORKER_TIMEOUT	180	Wait time (seconds) before an ODBC connection is dropped.

The default values for each **rim.cfg** parameter are set for optimal performance. Changing any of these settings will alter the performance of your Radia Inventory Manager.

Changing the DSN

If you would like to change the Data Source Name (DSN) to a different database at any time, change the correct parameters in the **rim.cfg**. Edit this text file using any text editor and update the following parameters at a minimum:

- **DSN** with the appropriate Data Source Name.
- **DSN_USER** with the user name you will be using to connect to the DSN.
- **DSN_PASSWD** with the required password.

Radia Inventory Manager Enhancements

Previous versions of the Radia Inventory Manager supported only one ODBC connection to the Radia Integration Server. With only one open connection, the inventory collection process could, in some cases, be slow. Running multiple sessions of the Radia Integration Server was one way to increase production and remedy this problem. With Radia version 3.0 and higher, the Radia Inventory Manager supports multiple concurrent ODBC connections, which optimizes throughput, and eliminates any need to run multiple sessions of the Radia Integration Server. These connections are represented in the **rim.cfg** by the parameter **N_WORKERS**. The default number of connections is four. Along with this parameter, other parameters are available in **rim.cfg** to maximize performance. Refer to *Table 4.2 ~ rim.cfg Parameters* on page 100, for further explanations.

Deploying the Radia Inventory Manager Client Modules to Radia Client

There are two ways to deploy the client modules to end users.

- Deploy the modules using the Radia Management Portal. See the *Radia Management Portal Guide* for information.
- Deploy the modules by using the Radia Client installation. See *Chapter 2: Installing the Radia Clients* beginning on page 29.

Summary

- The installation CD-ROM contains a single installation process that will install the Radia Inventory Manager Server. The foundation Radia Integration Service is installed automatically.
- The Radia Inventory Manager Server is generally installed on a separate computer from the Radia Configuration Server.
- Determine ahead of time the best method of installation for your enterprise.
- The Radia Inventory Manager is installed to the IntegrationServer (RIS) subdirectory of the target location. The default is: *SystemDrive:\Novadigm\IntegrationServer*.
- We recommend installing the Radia Messaging Server on the Radia Configuration Server to offload the work of forwarding inventory and other client-collected data to the Radia Inventory Manager Server.
- If you accept the default of Auto Create, the Radia Integration Server will automatically create a Microsoft Access 97 DSN named RIMDEMO.
- We also recommend installing the Radia Reporting Server for viewing the inventory reports.

The AUDIT Domain

At the end of this chapter, you will:

- Understand the AUDIT domain in the Radia Database.
- Understand the Radia Inventory Manager database.

This manual is provided to assist you with installing and using the Radia Inventory Manager. Choose the appropriate strategies suited for your enterprise needs.

The **AUDIT** Domain in the Radia Configuration Server Database

The **AUDIT** domain is located in the PRIMARY file of the Radia Database.




Figure 5.1 ~ Radia Database.PRIMARY.AUDIT domain.

The **AUDIT** domain contains the classes required to:

- Configure the tasks needed to collect the inventory information.
- Manage the client computers' assets.

AUDIT Domain Defined

The AUDIT domain is structured very much like the SOFTWARE domain. Figure 5.2 below shows its tree structure in the Radia System Explorer.




Figure 5.2 ~ The AUDIT domain.

Table 5.1 below describes the classes in the AUDIT domain.

Table 5.1 ~ AUDIT Domain	
Class	Description
Application (ZSERVICE)	These are sample services distributed with the Radia Inventory Manager. The AUDIT.ZSERVICE instance is connected to a policy instance. A policy instance can be an instance of the Users, Departments, or Workgroups class. It can also be a customer-defined class within the POLICY domain. Each of the sample ZSERVICE classes is connected to the PACKAGE instances.
Audit Packages (PACKAGE)	Defines what information to collect, and then what actions to take. These packages would contain various audit components. A good example is an audit of running services on a desktop. The AUDIT.ZSERVICE instance must contain a connection to an AUDIT.PACKAGE instance.
Behavior Services (BEHAVIOR)	Defines instances that enable the execution of auditing on the client. Normally, there is no need to add or modify instances in this class.
Client Methods (CMETHOD)	This class is used to configure method points for Tcl inventory scans. The base instance of the SCANNER class is connected to the CMETHOD.INV_FULL instance. This instance can be used for all inventory scans defined in the SCANNER class.
Desktop (DESKTOP)	This class is reserved for future use.
File (FILE)	Defines file scans, such as auditing system DLLs.
File Scanner (FILESCAN)	For UNIX devices only, persistent component class used to configure an inventory scan. Adding File Scanner components to an audit package creates instances of the FILESCAN class.
File Scanner Filters (FILTER)	For UNIX devices only, persistent component class used to configure an inventory scan. Adding FILE Scanner Filters components to an audit package creates instances of the FILTER class
Inventory Options (RIMOPTS)	Contains the attributes that offer options that control an inventory management task. For additional information, see <i>RIMOPTS Class</i> on page 109.
Inventory Scanners (SCANNER)	This persistent component class is used to configure an inventory scan. Create instances of the SCANNER class by adding Inventory Scanners components to an audit package.
Path (PATH)	This class stores the drive and directory required to install a resource. Packages can be relocated by updating instances of this class.
Registry (REGISTRY)	This class uses WMI to obtain a Registry scan of a Windows machine. Create instances of the REGISTRY class to run scans of the Windows Registry and obtain a Registry Scan report.
Scheduling (TIMER)	This class contains the instances that enable the Radia administrator to set a timer on end users' computers. One or multiple auditing services can be processed whenever the timer expires.
Virtual Mgr Location (MGRVLOC)	This class is used to specify the initial path for files being transferred to the Radia Configuration Server during a FILE audit.

Table 5.1 ~ AUDIT Domain

Class	Description
WBEM (WBEM)	This class contains instances that define Radia Inventory Manager scans of WMI classes. These can include any class in the WMI database such as Win32_Services. This example would provide information on Windows NT or Windows 2000 services.

RIMOPTS Class

The RIMOPTS class is also known as the **Inventory Options Class**. This class contains the attributes that control an inventory management task. Table 5.2 below describes these attributes.

Table 5.2 ~ RIMOPTS Class

Attribute	Usage
COLLECT	<p>Audit Collection Type by selecting Diff or Full</p> <ul style="list-style-type: none"> Select Diff to report the difference between the previous information collected for the service and the information collected during the current client audit. This is the default setting. <p>Note: The first or initial scan of the DIFF setting will be a FULL scan as defined below. All subsequent scans will then be differenced unless the administrator changes the setting to FULL.</p> <ul style="list-style-type: none"> Select Full to report the information collected for the service during the current Client Connect process without differencing against the previous collection for that service.
RUNEXEC	<p>This string indicates what actions the Radia Inventory Manager will take upon connection:</p> <ul style="list-style-type: none"> Select I to invoke collection of information when the service is installed Select U to invoke collection of information when the service is updated. Select V to invoke collection of information when the service is verified. <p>The default settings are I and U.</p>
ZSVCTYPE	<p>Contains code that is used internally by the Radia Inventory Manager client. In all cases, this value should remain I.</p>
NAME	<p>Contains the friendly name of the instance. It is the name displayed for the instance in the tree view of the Radia System Explorer.</p>

To apply an option expressed in the RIMOPTS instance to the inventory management task, the RIMOPTS instance must contain a connection to an audit service.

Prior to beginning any tasks using the Radia Inventory Manager, you must enable the drag-and-drop feature for the newly created RIMOPTS class instances. For additional information about editing instances, see the *Radia System Explorer Guide, Chapter 3: Radia Database Overview*.

To enable drag-and-drop connections for RIMOPTS class instances

1. If you have not done so already, navigate to and open the Radia System Explorer.
2. Expand the **PRIMARY** file and the **ADMIN** domain.




Figure 5.3 ~ PRIMARY.ADMIN domain.

3. Expand the **ZLIST** class.




Figure 5.4 ~ Expanded ZLIST class.

4. Expand the **CONNECT_** instance.




Figure 5.5 ~ Expanded CONNECT_ instance.

5. Expand the **CONNECT_ZSERVICE_** attribute and double-click on **CONNECT_ZSERVICE_TO_RULES**.




Figure 5.6 ~ CONNECT_ZSERVICE_TO_RULES.

The **Editing Instance** dialog box opens.




Figure 5.7 ~ Adding RIMOPTS as an attribute.

6. Set the value of the **ZNAME *n*** attribute to **RIMOPTS**.

The drag-and-drop feature is now available for all attributes in **RIMOPTS**.

REGISTRY Class

The Registry class uses WMI to obtain a Registry scan of a Windows machine. Most of the attributes are copied from the existing WBEM class of the AUDIT domain, with descriptions adjusted for registry-specific needs. For example, the PROPERTY and CNDITION attributes define the current Registry hive and subkey to scan, respectively. Three new Registry-specific attributes have been added to the class. They include:

- **RPTCLASS** – The Report Class Name in RIM.
- **FORMAT** – The Output format- requires REGISTRY (do not change).
- **DEPTH** – Defines the levels below the current subkey to scan.

Table 5.3~ Registry Class Instance Attributes summarizes the attributes and values for the Registry class instances. Attributes in bold are new to this class (not in the WBEM class).

Attribute	Description	Default Value	Valid Values
ACTION	Report Flags (I, N, C, D, S, D, C)	YYYYXXN	Y, X, or N for each flag.
NAMESPACE	Name Space	root\default	root\default – Do not change.
CLASS	WBEM Class	StdRegProv	StdRegProv – Do not change.
RPTCLASS	Report Class Name	Registry	A valid table name. If blank "StdRegProv" will be used.
PROPERTY	Registry hive.	HKEY_LOCAL_MACHINE	Any Windows registry hive: HKEY_CLASSES_ROOT HKEY_CURRENT_USER HKEY_LOCAL_MACHINE HKEY_USERS HKEY_CURRENT_CONFIG HKEY_DYN_DATA
CNDITION	Registry subkey	SOFTWARE\Microsoft\Internet Explorer	Any Windows registry subkey.
FORMAT	Output format.	REGISTRY	REGISTRY – Do not change.

Attribute	Description	Default Value	Valid Values
DEPTH	Starting at the registry subkey named in the CNDITION attribute, depth specifies the number of descendent key levels to include in the scan: 0 = Only scan current subkey -1 = Scan all subkey levels 1 to <i>n</i> = Scan current subkey and the specified subkeys levels deep	0	0, -1, or <i>n</i> See Description.
OUTPUT	Output Object Name	WBEMAUDT	WBEMAUDT
TYPE	Scan Type (WBEM)	WBEM	WBEM – Do not change.
NAME	Friendly Name	Default	Friendly name for this instance displayed in System Explorer.

Implementing Registry Scans

Use the following high-level procedures to create and run scans of the Windows Registry using the REGISTRY class in the AUDIT domain.

1. Create an AUDIT.REGISTRY scan instance and modify the attributes, as necessary. The PROPERTY, CNDITION and DEPTH attributes define the hive, registry subkey and depth of the scan, respectively.
2. Attach the registry scan instance to an audit service package.
3. Entitle the audit service for the registry scan to the appropriate machines or users.
4. The registry scan service is deployed during the first connection to an entitled client. Upon the next connection, the registry scan inventory is collected and passed to the Radia Inventory Manager server.
5. View the Registry Scan report from Radia Inventory Manager.

Updating the Radia Database for Windows Registry Scans

To be able to scan the Registry of Windows machines using WMI, HP introduced a new Registry class to the AUDIT domain of the Radia Database. If your existing database does not include the Registry class, see the following import procedure to add the class to your database.

The import deck is available as enhancement fix: ER3201044, available from HP OpenView Technical Support.




Figure 5.8~ REGISTRY class added to the AUDIT domain.

To install the Radia Database update for the AUDIT Registry class

Caution

Do not use this procedure to add a class already on your Radia Database.

1. Stop the Radia Configuration Server.
2. From the downloaded installation media, go to the **db_import** directory. This folder contains the import deck for the new class to be added to the Radia Database.

Import Deck Filename	Domain and Class
REGISTRY.XPC	AUDIT.Registry (REGISTRY)

3. Copy the `REGISTRY.XPC` file into the Radia Configuration Server's bin subdirectory. The default location of the bin directory is:
<System Drive>\Novadigm\ConfigurationServer\bin.
4. Open a command prompt and navigate to the Radia Configuration Server's bin directory.
5. Execute the following command from the bin directory to import the `AUDIT.REGISTRY` class to your database.

Caution

Do not import classes already on your database.

```
ZEDMAMS VERB=IMPORT_CLASS, FILE=REGISTRY.XPC, PREVIEW=NO
```

A return code of 0 indicates that there were no errors reported during the import, and the updates are applied to the database. If there were errors, you can type **zedmams.log** to open and view that log.

6. Restart the Radia Configuration Server. The Registry class is newly available in the `AUDIT` domain, as shown in Figure 5.8 on page 116.

Sample Inventory Database Tables

As previously discussed, when you install the Radia Inventory Manager Server, you have the option of installing the sample reporting database. HP provides a Microsoft Access '97 Database, `RIMDEMO`, to sample the features of the Radia Inventory Manager. If installed, the information obtained by auditing client computers is stored here. An administrator can then view the information obtained in an easy to read format.

Whether you have installed the sample reporting database or your own ODBC-compliant database, the same tables with the same names and data field names will be created in any database indicated by the DSN supplied.

The sample reporting database contains the tables shown in Figure 5.9 below.











































































 Create table in Design view	 rWin32_DisplayConf	 rWin32_Process
 Create table by using wizard	 rWin32_DisplayControllerConf	 rWin32_Processor
 Create table by entering data	 rWin32_DMAChannel	 rWin32_Product
 AppEvent	 rWin32_Environment	 rWin32_SerialPort
 DeviceConfig	 rWin32_FloppyController	 rWin32_Service
 DeviceErrors	 rWin32_FloppyDrive	 rWin32_Share
 DeviceMap	 rWin32_Group	 rWin32_SoftwareElement
 DeviceNotify	 rWin32_IDEController	 rWin32_SoftwareFeature
 DeviceServices	 rWin32_IRQResource	 rWin32_SoundDevice
 DeviceState	 rWin32_Keyboard	 rWin32_StartupCommand
 DeviceStatus	 rWin32_LoadOrderGroup	 rWin32_SystemDriver
 FileAudit	 rWin32_LogicalDisk	 rWin32_SystemEnclosure
 HAppEvent	 rWin32_LogicalMemoryConf	 rWin32_TimeZone
 HDeviceErrors	 rWin32_LogicalProgramGroup	 rWin32_USBController
 HDeviceState	 rWin32_MemoryArray	 rWin32_UserAccount
 HDeviceStatus	 rWin32_MemoryDevice	 rWin32_VideoController
 rCIM_Product	 rWin32_MotherboardDevice	
 rWin32_BIOS	 rWin32_NetworkAdapter	
 rWin32_BootConf	 rWin32_NetworkAdapterConf	
 rWin32_Bus	 rWin32_NetworkConnection	
 rWin32_CacheMemory	 rWin32_OperatingSystem	
 rWin32_CDROMDrive	 rWin32_PageFile	
 rWin32_ComputerSystem	 rWin32_PageFileSetting	
 rWin32_ComputerSystemProduct	 rWin32_PageFileUsage	
 rWin32_Desktop	 rWin32_ParallelPort	
 rWin32_DesktopMonitor	 rWin32_PnPEntity	
 rWin32_DeviceMemoryAddress	 rWin32_PointingDevice	
 rWin32_DiskDrive	 rWin32_PortResource	
 rWin32_DiskPartition	 rWin32_Printer	

Figure 5.9 ~ Sample Inventory Database – Tables.

The table names denote the origin of the data that they contain. For example, the **rWin_LogicalMemoryConf** table will be populated with data from the Win32_LogicalMemoryConfiguration WBEM class.

Tables that begin with rWin32_ are populated with the data from WBEM queries. Tables that do not start with rWin32_ are populated with data from non-WEBM sources.

The recommended product for viewing Radia Inventory is the Radia Reporting Server. See the *Radia Reporting Server Guide* for more information.

Alternatively, you can view Radia Inventory tables through the Radia Integration Server, with or without the Radia Management Portal. See *Chapter 10: Viewing Inventory from the Radia Integration Server* starting on page 193 for more information.

Summary

- The AUDIT domain contains the classes required to configure the tasks needed to collect the inventory information and to manage the client computer's assets.
- The RIMOPTS class is also known as the Inventory Options class. This class contains the attributes that control an inventory management task.
- Prior to beginning any tasks using the Radia Inventory Manager, you must enable the drag-and-drop functionality for the newly created RIMOPTS class instances.
- If installed, use the Radia Reporting Server for viewing the information obtained by auditing client computers. Alternatively, inventory reports can also be viewed from the Radia Integration Server, with or without the Radia Management Portal.

Software and Hardware Auditing

At the end of this chapter, you will:

- Understand file auditing.
- Understand WBEM auditing.
- Understand hardware auditing and the ZCONFIG object.

This manual is provided to assist you with installing and implementing the Radia Inventory Manager. Choose the appropriate strategies suited for your enterprise needs.

Auditing Types

When configuring your audits, it is beneficial for the administrator to understand exactly what types of things can be audited and what the expected results from an audit will be.

The Radia Inventory Manager allows for three types of audits:

- File auditing
- WBEM auditing
- Hardware auditing

File Auditing

The `AUDIT.FILE` class instances in an audit package control the auditing function for files on the client computer. The `RIMFSCAN` and the `RIMDIFF` methods on the client computer perform the actual file auditing operations by specifying what files to look for. There can be one or more `AUDIT.FILE` instances in an audit package. Each `AUDIT.FILE` instance can specify a scan for one or more files.

See *What Happened during the Scan* on page 149 for additional information on the `RIMFSCAN` and the `RIMDIFF` methods.

The following table summarizes the attributes in an `AUDIT.FILE` class instance and their effects on the `RIMFSCAN` method.

Table 6.1 ~ AUDIT.FILE Class Instances

Attribute	Description Examples
SCANFOR	Indicate a fully qualified path and file name to search for. Wildcards are permitted. <i>systemdrive:\WinNt**.dll</i>
ACTION	<p>The RIMDIFF method performs actions on the files discovered on the user's computer during the Client Connect.</p> <ul style="list-style-type: none"> • Y configures RIMDIFF to perform the action. • N configures RIMDIFF to not perform the action. <p>The first four flags determine <i>when</i> to report that the files were found: Report on: Initial, New, Changed, Deleted</p> <ul style="list-style-type: none"> • Initial means that the file was found during the first scan of the client computer. • New means that the file was found during the current scan. The file was not present during the previous scan. • Changed means that the file was present during the previous scan and is different from the file found during the current scan. • Deleted means that the file was found during the previous scan. The file is not present for the current scan. <p>The last three flags control the <i>actions to take</i> on the files detected during the current scan. Action to take on discovery: Send, Delete, Custom</p> <ul style="list-style-type: none"> • Send means to send the files to the Radia Configuration Server and store them in the location indicated by the ZRSCVLOC attribute (see ZRSCVLOC in this table). • Delete means to delete the files from the user's computer. • Custom means to execute the method indicated in the CUSTOM attribute. <p>YYYYNYN – Report whenever encountered and delete the files. NNYYNNN – Report when changed or deleted and take no action. NYYNYYN – Report when the files are new or changed. Then send and delete the files.</p>
OUTPUT	Output object name.
TYPE	Scan different file locations. Available scans are Behavior Services, Desktop, File, Path, Registry, and WBEM. File.
GROUP	Optional way to identify a set of scan results. This maybe useful for querying and reporting on the audited files from the database where audit results can be stored. Games, MPEGs.

Table 6.1 ~ AUDIT.FILE Class Instances

Attribute	Description Examples
ZVERINFO	<p>Collect extended information.</p> <ul style="list-style-type: none"> • Set the value to 1 to collect additional information for a file. • Set the value to 0 to not collect additional information. <p>In order for this data to be collected, the associated attribute must exist in the AUDIT.FILE class template.</p> <p>You can limit the scan to only those files that have some particular values in their extended information. You do so by supplying a value (either 1 or 0) for any of the associated attributes in an AUDIT.FILE instance. This causes the scan to be filtered. Only those files whose extended information data element contains the value you specify in its associated attribute will be scanned.</p> <p>Extended file information consists of one or more of the following data elements. The associated attribute name for the data element is in parentheses:</p> <ul style="list-style-type: none"> • (VENDOR) – The seller of the file/product • (PRODUCT) – The name of the item for which the file is a part. • (PRODVERS) – The version of the product which the file is a part. • (ORGNAME) – The name of the organization. • (INTERNAL) – The internal data element encoded in the file. • (VERSION) – The version of the file. • (LANGUAGE) – The language of the file.
ZRSCSTYP	Server file type. This can be either Binary or Text . The administrator does not set this.
ZRSCMFIL	Manager directory location.
ZRSCVLOC	<p>The location on the Radia Configuration Server where the files are stored because of the Send Action (see ACTION in this table). This variable needs to be configured when sending a file back to the Configuration Server. The variable should contain the name of the MGRVLOC instance that will be used to resolve the location to store the uploaded file.</p> <p><i>systemdrive:\Data\&(ZOBJPID)\&(name)</i></p>
ZRSCMMEM	PDS member name. This field is optional.
PRODUCT	<p>The product name.</p> <p>See ZVERINFO above for more detail.</p>
PRODVERS	<p>The product version.</p> <p>See ZVERINFO above for more detail.</p>
ORGNAME	<p>The organization name.</p> <p>See ZVERINFO above for more detail.</p>
INTERNAL	<p>The internal data element encoded in the file.</p> <p>See ZVERINFO above for more detail.</p>
VERSION	<p>The version of the file.</p> <p>See ZVERINFO above for more detail.</p>
LANGUAGE	<p>The language of the file.</p> <p>See ZVERINFO above for more detail.</p>

Table 6.1 ~ AUDIT.FILE Class Instances

Attribute	Description Examples
VENDOR	The product vendor. See ZVERINFO on page 124 for more detail.
ZRSCCRC	Resource CRC.
ZCRCINFO	Collect file CRC.
ZRSCOBJN	Persistent object name.
ZRSCPADM	Administrator ID.
ZRSCSRC	Resource Source, i.e. Publisher.
ZINIT	Not applicable at this time.
NAME	Not applicable at this time.
LOCATION	Not applicable at this time.

Use the Radia Client Explorer to view the FILEAUDT object results as shown in Figure 6.1 on page 126.

The FILEAUDT object contains one heap for each file discovered during the scan for the audit service. It contains the attributes from the AUDIT.FILE class instance that controlled the scan, as described above. It also contains the following attributes:

Table 6.2 ~ FILEAUDT Object	
Attribute	Description
ACCESSDT	The date of the most recent access of this file.
ACCESSTM	The time of the most recent access of this file.
ATTRIBUTE	A string listing the attributes of the file: R = Read only A = Archive S = System H = Hidden C = Compressed
DATE	The date of the most recent modification to this file.
DIRPATH	The directory path of the file.
DRIVE	The system drive location of the file.
FULLPATH	Fully qualified path and file name of the file.
PATHCRC	A unique number that indicates the CRC path used for differencing.
RESOLVE	The value of M indicates that the Radia Configuration Server resolves each heap of the FILEAUDT object individually. This value cannot be modified.
SIZE	File size in bytes.
STATUS	Indicates the status of the file on the client computer. Possible values are: <ul style="list-style-type: none"> • Exists This is the first time scanning for this file and it was found. • New This file was added to the file system of the client computer since the last scan was performed. • Update This file exists in the new and previous scans. There have been changes to the date, time, size, and/or version. • Deleted This file was present in the previous scan but is missing in the new scan. • Not found No files were found that matched this request.
TIME	The time of the most recent modification to this file.
XTENSION	The file extension. This is useful for sorting and querying back-end database tables that store the data found in this object.

WBEM Auditing

Use the RIMWBEM method to query the WBEM namespaces to retrieve information about how a system's hardware and software is used. The RIMWBEM method constructs a query from the information contained in an instance of the AUDIT.WBEM class. WBEM has a query engine that processes the query statement and returns the query results to RIMWBEM. There is one heap in the query result object for every discovered instance.

Caution

HP Openview Inventory Manager using Radia for Windows leverages Microsoft's Windows Management Instrumentation (WMI) to collect hardware and software inventory data by using WMI queries. Some WMI queries can traverse the network contacting other servers in the enterprise to collect the requested information. This may result in large volumes of data being returned, and could have a significantly negative effect on network performance. An example of this would be querying all users on the network using the W32_UserAccount WMI class. Extreme caution must be taken to understand the scope of these queries to ensure unexpected results do not occur. While Radia Inventory Manager provides an interface to WMI and its providers, it cannot control how these queries are satisfied. It is the customer's responsibility to safeguard against using WMI queries that span the network, if this behavior is not desired.

An AUDIT.WBEM class instance defines a query into the WBEM namespace.

Database Tree View:

- AUDIT
 - Application (ZSERVICE)
 - Audit Packages (PACKAGE)
 - Behavior Services (BEHAVIOR)
 - Client Methods (CMETHOD)
 - Desktop (DESKTOP)
 - File (FILE)
 - File Scanner (FILESCAN)
 - File Scanner Filters (FILTER)
 - Inventory Options (RIMOPTS)
 - Inventory Scanners (SCANNER)
 - Path (PATH)
 - Scheduling (TIMER)
 - Virtual Mgr Location (MGRVLDC)
 - wBEM (WBEM)**
 - Default
 - NVDM Discovery of Applications:NVDM Discover Applications
 - RIM Reporting\Win32_Bios
 - RIM Reporting\Win32_ComputerSystem
 - RIM Reporting\Win32_ComputerSystemProduct
 - RIM Reporting\Win32_Environment
 - RIM Reporting\Win32_Keyboard
 - RIM Reporting\Win32_LogicalDisk
 - RIM Reporting\Win32_LogicalMemoryConfiguration
 - RIM Reporting\Win32_NetworkAdapter
 - RIM Reporting\Win32_NetworkAdapterConfiguration
 - RIM Reporting\Win32_OperatingSystem
 - RIM Reporting\Win32_PointingDevice
 - RIM Reporting\Win32_Printer
 - RIM Reporting\Win32_Processor
 - RIM Reporting\Win32_Product
 - RIM Reporting\Win32_SerialPort
 - RIM Reporting\Win32_Service
 - RIM Reporting\Win32_SoftwareElement
 - RIM Reporting\Win32_VideoController

wBEM (WBEM) Class Instances:

Name	Instance Name	Type
Default	_BASE_INSTANCE_	AUDIT.WBEM Instance
NVDM Discovery of Applications:NVDM Discover Applications	D001D4398CF7_5337A6F	AUDIT.WBEM Instance
RIM Reporting\Win32_Bios	DABCABEB29EA_94A8341D	AUDIT.WBEM Instance
RIM Reporting\Win32_ComputerSystem	DABCABEB29EA_CB33B8AB	AUDIT.WBEM Instance
RIM Reporting\Win32_ComputerSystemProduct	DABCABEB29EA_7CB2B421	AUDIT.WBEM Instance
RIM Reporting\Win32_Environment	DABCABEB29EA_BD5DB3DF	AUDIT.WBEM Instance
RIM Reporting\Win32_Keyboard	DABCABEB29EA_B43DB82F	AUDIT.WBEM Instance
RIM Reporting\Win32_LogicalDisk	DABCABEB29EA_B54E6D05	AUDIT.WBEM Instance
RIM Reporting\Win32_LogicalMemoryConfiguration	DABCABEB29EA_079AE58C	AUDIT.WBEM Instance
RIM Reporting\Win32_NetworkAdapter	DABCABEB29EA_E7D9E023	AUDIT.WBEM Instance
RIM Reporting\Win32_NetworkAdapterConfiguration	DABCABEB29EA_F1910AC7	AUDIT.WBEM Instance
RIM Reporting\Win32_OperatingSystem	DABCABEB29EA_4FC77675	AUDIT.WBEM Instance
RIM Reporting\Win32_PointingDevice	DABCABEB29EA_34C5B38C	AUDIT.WBEM Instance
RIM Reporting\Win32_Printer	DABCABEB29EA_1C4C3306	AUDIT.WBEM Instance
RIM Reporting\Win32_Processor	DABCABEB29EA_02435F9	AUDIT.WBEM Instance
RIM Reporting\Win32_Product	DABCABEB29EA_424A4E46	AUDIT.WBEM Instance
RIM Reporting\Win32_SerialPort	DABCABEB29EA_EAF7FEDF	AUDIT.WBEM Instance
RIM Reporting\Win32_Service	DABCABEB29EA_709DD039	AUDIT.WBEM Instance
RIM Reporting\Win32_SoftwareElement	DABCABEB29EA_FD85FF2C	AUDIT.WBEM Instance
RIM Reporting\Win32_VideoController	DABCABEB29EA_5EEBA462	AUDIT.WBEM Instance
Unix Hardware Inventory: CIM_CDROMDrive	D1230ABD31DF_1C7A84F5	AUDIT.WBEM Instance
Unix Hardware Inventory: CIM_Directory	D1230ABD31DF_D58A6D7C	AUDIT.WBEM Instance
Unix Hardware Inventory: CIM_DiskDrive	D1230ABD31DF_6BAD4E89	AUDIT.WBEM Instance
Unix Hardware Inventory: CIM_DVDDrive	D1230ABD31DF_4167F3C4	AUDIT.WBEM Instance
Unix Hardware Inventory: CIM_EthernetController	D1230ABD31DF_8DAE4FB6	AUDIT.WBEM Instance
Unix Hardware Inventory: CIM_IDEController	D1230ABD31DF_3D18EEAE	AUDIT.WBEM Instance
Unix Hardware Inventory: CIM_LogicalDisk	D1230ABD31DF_F4DA1039	AUDIT.WBEM Instance
Unix Hardware Inventory: CIM_LogicalDisk	D1230ABD31DF_6CB0713E	AUDIT.WBEM Instance
Unix Hardware Inventory: CIM_MediaDrive	D1230ABD31DF_9B92F7E0	AUDIT.WBEM Instance
Unix Hardware Inventory: CIM_NFS	D1230ABD31DF_DD902035	AUDIT.WBEM Instance
Unix Hardware Inventory: CIM_ParallelController	D1230ABD31DF_70BFC817	AUDIT.WBEM Instance

48 WBEM instance(s) displayed 3/5/2002 2:26 PM

Figure 6.2 ~ AUDIT.WBEM class instances.

The following table describes the attributes of the AUDIT.WBEM instance.

Table 6.3 ~ AUDIT.WBEM Instance

Attribute Name	Description
ACTION	<p>The RIMDIFF method performs actions on the WBEM namespaces (s) instances discovered on the user's computer during the Client Connect.</p> <ul style="list-style-type: none"> • Y configures RIMDIFF to perform the reporting action. • N configures RIMDIFF to not perform the reporting action. <p>The first four flags determine <i>when</i> to report that the WBEM namespace instance was found: Report on: Initial, New, Changed, Deleted, Scan, Delete, Custom</p> <ul style="list-style-type: none"> • Initial means that the file was found during the first scan of the client computer. • New means that the file was found during the current scan. The file was not present during the previous scan. • Changed means that the file was present during the previous scan and is different from the file found during the current scan. • Deleted means that the file was found during the previous scan. The file is not present for the current scan. • Scan means that the file was found during the current scan. • Delete means that the file was found during the previous scan. The file is not present for the current scan. • Custom means that the file was found during a custom scan. <p>The last three flags are not applicable to WBEM audits.</p>
NAMESPACE	The name of the WBEM namespace to query or HARDWARE.
CLASS	The name of the WBEM class to query or HARDWARE.
PROPERTY	Specify one or more property names to be queried and reported. Use commas to separate more than one property name. If this attribute is blank, all properties in the class will be queried and reported.
CNDITION	An optional condition to narrow results of an audit.
OUTPUT	This is the name of the object to send to the Radia Configuration Server.
TYPE	Indicates that WBEM scan is to be employed for this audit package.
NAME	Friendly name for this instance. This name will appear in the Radia System Explorer's tree view to identify this instance.

Note

When the keyword HARDWARE is used in the NAMESPACE and/or CLASS attributes of AUDIT.WBEM, hardware information is collected. This information is essentially the same as the ZCONFIG object.

The Radia Inventory Manager client stores the results of a WBEM scan in a WBEM object. This object can be found in the service node of the client object tree. The results are also sent to the Radia Configuration Server.

In addition to the attributes described in Table 6.3 on page 130, the WBEM object also contains the following:

Table 6.4 ~ WBEM Object Attributes in the Client

Attribute	Description
ZOBJCID	Object child ID.
ZOBJCLAS	The targeted class for the audit such as ZRSOURCE or ZSERVICE.
ZOBJCRC	The CRC of all persistent and transient objects under the current node.
ZOBJDATE	The last date under the current node.
ZOBJDOMN	The domain name of the object.
ZOBJID	The object ID of the instance used to obtain information from the Resource file.
ZOBJNAME	The instance name of the object.
ZOBJPCLS	The parent class name.
ZOBJPID	The parent class ID.
ZOBJRCRC	The resource CRC maintained by the Radia Configuration Server.
ZOBJRSIZ	The resource size maintained by the Radia Configuration Server.
ZOBJTIME	The latest time under the current node.
ZRSCSRC	The name of the program promoted the resource.

WBEM Objects and the Radia Configuration Server

When the Radia Inventory Manager client sends a WBEMAUDT object to the Radia Configuration Server, the processing is defined by the SYSTEM.PROCESS.WBEMAUDT instance in the Radia Database.

Radia Processes class WBEMAUDT Instance Attributes:		
Name	Attribute Description	Value
<input type="checkbox"/> _ALWAYS_	Method	SYSTEM.ZMETHOD.POST_WBEM
<input type="checkbox"/> _ALWAYS_	Method	
<input type="checkbox"/> _ALWAYS_	Connect To	
<input type="checkbox"/> _ALWAYS_	Connect To	
<input type="checkbox"/> _ALWAYS_	Method	
<input type="checkbox"/> _ALWAYS_	Method	
<input type="checkbox"/> _ALWAYS_	Method	
<input type="checkbox"/> _ALWAYS_	Method	
<input type="checkbox"/> _ALWAYS_	Method	
<input type="checkbox"/> _ALWAYS_	Method	
<input checked="" type="checkbox"/> DESCRIPT	Process Description	Processing Client Request for &ZCUIROBJ
<input checked="" type="checkbox"/> ZMAXOKRC	Max acceptable method Return Code	008

Figure 6.3 ~ SYSTEM.PROCESS.WBEMAUDT instance.

This instance calls upon the method in the SYSTEM.ZMETHOD.POST_WBEM instance.

Name	Attribute Description	Value
ZMTHPRMS	Parameters Passed to Method	post: /proc/wbem &ZCURINDB
ZMTHTYPE	Method Type [REXX/ASM/EXE]	EXE
ZMTHNAME	Member Name of Method	radish
DESCRIPT	Method Description	Manager Method %ZMTHNAME
ZMTHMODE	Mode [INTERNAL] or [EXTERNAL]	EXTERNAL
ZMTHSYNC	Synchronization Flag [Y] [N]	Y
ZMTHDSC1	Method Description 1	
ZMTHDSC2	Method Description 2	
ZMUSTRUN	Return Code critical to Resolution?	Y

Figure 6.4 ~ SYSTEM.ZMETHOD.POST_WBEM instance.

The method executed in the Radia Configuration Server is RADISH.EXE. This method is responsible for performing the following tasks:

- Compressing and encoding the information in the WBEMAUDT object and sending it to RIS for processing.
- Issuing an HTTP POST to transmit information to the Radia Integration Server.

The HTTP POST is specified in the MGR_RIM section of the edmprof.dat. As shipped from HP, this instance assumes that the Radia Integration Server is running on the same computer as the Radia Configuration Server. By default, the RADISH.EXE method will issue the POST to:

<http://localhost:3466>.

The Radia Integration Server receives the information from the HTTP POST. It processes this information by executing SQL statements to append or update the information to the ODBC-compliant database.

The new information is immediately available for query and reporting purposes.

Hardware Auditing

Each time a client connects to the Radia Configuration Server, information about the Radia Client's hardware configuration is stored in the ZCONFIG object. The ZCONFIG object is calculated and stored in the application service directory of the Radia Client's object directory tree as follows:




Figure 6.5 ~ ZCONFIG object.

A separate ZCONFIG object is calculated and stored for each service installed or updated during the Client Connect. To force the transfer of the hardware information, the ZCONFIG attribute *must* be set to **Y** in the POLICY.USER class.




Figure 6.6 ~ POLICY.USER Class – ZCONFIG attribute.

The ZCONFIG object contains a wealth of information about the client computer's hardware.

Variable	Length	1 of 1
GATEWAY03	013	208.244.231.1
IPADDR01	007	0.0.0.0
IPADDR02	007	0.0.0.0
IPADDR03	015	208.244.231.104
LADAPT01	012	444553540000
LADAPT02	012	444553540001
LADAPT03	012	0050da644154
REBOOTD	008	20010608
REBOOTT	008	11:15:40
SUBNET01	007	0.0.0.0
SUBNET02	007	0.0.0.0
SUBNET03	013	255.255.255.0
ZGATEWAY	011	&(GATEWAY03)
ZHDWBIOS	037	04/22/99 PhoenixBIOS 4.0 Release 6.0
ZHDWCDDR	002	E:
ZHDWCOMP	009	ctanzillo
ZHDWCPU	007	Pentium
ZHDWCPU\$	006	450MHz
ZHDWD00	002	C:
ZHDWD00C	005	Fixed
ZHDWD00F	014	10,109,403,136
ZHDWD00S	005	FAT32
ZHDWD00T	014	13,689,888,768
ZHDWD01	002	E:
ZHDWD01C	005	CDROM
ZHDWD02	002	F:
ZHDWD02C	006	Remote
ZHDWD02F	011	541,196,288
ZHDWD02S	007	NWCOMPA
ZHDWD02T	013	1,048,576,000
ZHDWD03	002	G:
ZHDWD03C	006	Remote
ZHDWD03F	014	51,560,579,072
ZHDWD03S	004	NTFS

Figure 6.7 ~ ZCONFIG object.

The ZCONFIG object stores hardware information discovered by the Radia Client's standard hardware auditing method. Certain types of hardware can occur multiple times. The ZCONFIG object automatically expands to allow additional information to be stored.

The following table describes the attributes that are stored in the ZCONFIG object.

Table 6.5 ~ ZCONFIG Object

Attribute	Description
GATEWAY	Router for your subnet.
HALCOMP	Company of HAL.DLL
HALDATE	Date and time of HAL.DLL
HALFNAME	Original name of HAL.DLL
HALFVER	Internal version of HAL.DLL
HALINAME	Name of HAL.DLL
HALLANG	Language of HAL.DLL
HALPNAME	Product name of HAL.DLL
HALPVER	Product version of HAL.DLL
HALSIZE	Size of HAL.DLL
IPADDR##	IP address of network adapter (there can be multiple addresses).
LADAPT##	Network card (there can be multiple network cards).
REBOOTD	Last re-boot date.
REBOOTT	Last re-boot time.
SUBNET##	Subnet mask.
ZGATEWAY	Looks at GATEWAY attribute.
ZHDWBIOS	BIOS type.
ZHDWCDDR	Radia Client's CD-ROM drive letter.
ZHDWCOMP	Computer name.
ZHDWCPU	Current CPU type.
ZHDWCPUS	Current CPU speed.
ZHDWCTYP	Computer Type (Desktop or Laptop)
ZHDWD##	Drive identification.
ZHDWD##C	Drive classification.
ZHDWD##F	Current free space on the drive.
ZHDWD##S	File system on the drive.
ZHDWD##T	Total space for the drive.
ZHDWDF_A	Information for a floppy drive.
ZHDWDLST	A listing of assigned drive letters.
ZHDWNUM	The number of assigned drive letters.
ZHDWFPU	Current FPU type.
ZHDWIPAD	The IP address of the computer.
ZHDWKYBD	Keyboard type.
ZHDWLANA	LAN adapter.

Table 6.5 ~ ZCONFIG Object

Attribute	Description
ZHDWLANG	Language setting.
ZHDWMEM	Total physical memory (RAM).
ZHDWMEMF	Total free memory (RAM).
ZHDWMOUS	Mouse type.
ZHDWNET#	Network card information (can be multiple cards).
ZHDWNNET	Number of network cards.
ZHDWOS	Computer's operating system and version.
ZHDWOSCL	Operation system classification (Workstation or Server)
ZHDWOSDB	Operating system's build number.
ZHDWOSOG	Organization.
ZHDWOSOW	Owner.
ZHDWOSSR	Windows 9x Sub-Version Number (i.e. A, B, C)
ZHDWPA##	Printer information.
ZHDWPPAR	Number of parallel ports.
ZHDWPPRN	Number of printers available.
ZHDWPSER	Number of serial ports.
ZHDWVIDO	Video type.
ZHDWVMSI	MSI Version
ZHDWVRES	Video resolution.
ZHDWXPAG	Page size.
ZHWCPU01	CPU type.
ZHWFPU01	FPU type.
ZMODEM	Modem present? Y or N
ZOBJDATE	The date of the Client Connect for this particular service.
ZOBJNAME	HARDWARE_SCAN (hard coded).
ZOBJTIME	The time of the Client Connect.
ZSUBNET	The subnet mask.
ZUSERID	The name of the user who connected.

Whenever a client connects to the Radia Configuration Server, certain hardware information concerning the subscriber is automatically forwarded to the Radia Integration Server.

Summary

- The Radia Inventory Manager allows for file auditing, WBEM auditing, and hardware auditing.
- The RIMFSCAN and the RIMDIFF methods on the client computer perform the actual file auditing operations by specifying what files to look for.
- The FILEAUDT object contains one heap for each file discovered during the scan for the audit service.
- The RIMWBEM method constructs a query from the information contained in an instance of the AUDIT.WBEM class.
- Each time a client connects to the Radia Configuration Server, information about the subscriber's hardware configuration is stored in the ZCONFIG object.
- To force the transfer of the hardware information, the ZCONFIG attribute *must* be set to Y in the POLICY.USER class.
- The ZCONFIG object stores hardware information discovered by the Radia Client's standard hardware auditing method.



Successful Auditing

At the end of this chapter, you will:

- Know how to use the pre-packaged Audit Applications (ZSERVICE).
- Know how to design your own Audit Packages (PACKAGE).

This manual is provided to assist you with installing and implementing the Radia Inventory Manager. Choose the appropriate strategies suited for your enterprise needs.

Sample Auditing

To illustrate the concepts of inventory information collection, the Radia Inventory Manager installation contains a set of representative audit service examples. These samples are located in the PRIMARY.AUDIT.Audit Application (ZSERVICE) class as follows:




Figure 7.1 ~ Sample Auditing services.

These sample services represent common scenarios for inventory collection and management. The best way to develop your own audit services is to study the samples that were installed with the Radia Inventory Manager upgrade.

The sample audit services are described in the following table:

Table 7.1 ~ Sample of Auditing Services		
Service	Connected to Audit Package (PACKAGE)	Description
_BASE_INSTANCE_		This service instance is the base instance for the Audit Application (ZSERVICE) class.
Audit Multi Files	Audit to find and Capture Multiple Files	This service scans for a file name or pattern and reports that information back to the administrator.
CE PDA XML Inventory	CE PDA XML Inventory	This service scans for and reports back information on installed Windows CE PDA devices. Will only report back if a device is found.
Delete Discovered Application Component	Audit to Find and Remove Local File	This service looks for a specific file on the user's computer. If it is found, it will be deleted.
Individual File Audit	Audit to Find and Capture Local File	This service performs an NVDM scan of the user's computer for a specified file of an instance of the AUDIT.FILE classes.
NVDM Discovery of Applications	NVDM Discovery of Applications	Used to discover software applications that are installed on a client machine.
Palm PDA XML Inventory	Palm PDA XML Inventory	This service scans for and reports back information on installed Palm PDA devices. Will only report back if a device is found.
RIM Reporting	RIM Reporting	This service performs a scan of a systems Win32 devices such as: Bios, Computer System, environment, keyboard, logical disk, logical memory configuration, network adapter, operating system, pointing device, printer, processor product, serial port, service, software element, and video controller. Note: This is a very large scan and may take several minutes to complete.
Unix File Scan Audit	UNIX File Scan Audit	This service performs a NVDM scan of the user's computer for a specified file of an instance of the AUDIT.FILE classes on UNIX platforms.

Table 7.1 ~ Sample of Auditing Services

Service	Connected to Audit Package (PACKAGE)	Description
Unix Hardware Inventory	Unix Hardware Inventory	This service scans for and reports on a user's hardware on UNIX computers.
Unix Software Inventory	Unix Software Audit	This service performs an audit to find UNIX-based software.
WBEM MSI Based Applications	WBEM Scan for Windows Installer Applications	This service performs a WBEM scan of the user's computer for components registered in the WMI database that have been installed by Microsoft Windows Installer.
WBEM Running Services	WBEM Scan for Running Services	This service scans the users computer for system services that are running at the time of the scan.
WBEM Scan for Hardware	WBEM Scan for System Software	This service scans for and reports on a user's hardware.
WBEM Scan with Condition Statement	WBEM Scan with Condition Statement	This service performs scans based on a conditional statement set in the CONDITION attribute.
WBEM Stopped Services	WBEM Scan for STOPPED Services	This service scans the user's computer for system services that are stopped at the time of the scan.
WBEM System Drivers	WBEM Scan for Windows System Drivers	This service scans the user's computer for Win 32 system drivers.
WBEM Windows Services	WBEM Scan for Windows Services	This service scans for and reports on Windows Services.
Windows System DLL	Audit System DLL	This service scans for system DLLs and reports on them.

Configuring a Sample Audit

All of the examples presented can be configured for individuals, departments, work-groups, and so forth. See the *Radia System Explorer Guide* for additional information on manipulating the database components.

For documentation purposes, we will configure the sample audit service **Audit Multi Files**. The file type we will be auditing is indicated in the SCANFOR attribute within the instance. This instance directs the Radia Inventory Manager client to scan for any ***:\program files**.exe** files on the client computer. The ACTION attribute indicates that the discovery of the file will be reported and sent to the Radia Configuration Server for storage.




Figure 7.2 ~ SCANFOR attribute of the Audit Multi Files instance.

To configure a sample Audit package

1. If you have not already done so, start the Radia System Explorer.
2. Navigate to and expand the PRIMARY.AUDIT domain.
3. Double-click on Application (ZSERVICE) to expand the class.




Figure 7.3 ~ AUDIT.ZSERVICE

4. Scroll to and expand the POLICY domain.

For our example, we would like all users that are members of the Workgroup class to select this audit package from their Radia Software Manager.

5. Expand the POLICY.WORKGROUPS class.




Figure 7.4 ~ Expanded POLICY.WORKGRP class.

6. Select the **Audit Multi Files** package from the ZSERVICE class and drag it to the POLICY.WORKGROUPS class and drop it on the **Default** instance.

The **Select Connections Attribute** window opens.




Figure 7.5 ~ Select Connection Attribute dialog box.

7. Click **Copy** to add this package.
The **Confirm Connection** dialog box opens.
8. Click **Yes** to confirm the connection.

The **Audit Multi Files** package is added to WORKGRP class.




Figure 7.6 ~ Audit Multi Files package has been added to the WORKGRP class.

The collection of inventory information occurs on the Radia Inventory Manager client computer when a user connects to the Radia Configuration Server as follows:

- Through the Radia Software Manager Client Connect when the user visits a Radia Web page.

OR

- Through the Radia Application Manager client when the user double-clicks the Radia Connect icon on his desktop, or is scheduled or notified to connect.

A Radia Software Manager client would see the following when connecting:




Figure 7.7 ~ Audit Multi Files in the Radia Software Manager.

When the subscriber selects and installs the Audit Multi Files package from his Radia Software Manager, there are really two connections. The first connection downloads the Audit service. The second connection sends the audit results back to the Radia Configuration Server. The audit-related scans are done between the two connections.

Note

Some scans may take several minutes to complete. This is a normal behavior of the audit scanning process.

What Happened during the Scan?

Use the Radia Client Explorer to locate the ZSERVICE for the **Audit Multi Files** package in the LIB directory.




Figure 7.8 ~AUDIT_MULTI_FILES in the LIB directory.

Within the ZSERVICE, note the two objects, **FILEAUDT** and **FILEPREV**. These objects are created and stored in the ZSERVICE of the LIB directory whenever an audit package is installed. The **FILEAUDT** object contains one heap for each file discovered during the auditing scan. It also contains the attributes from the AUDIT.FILE instance that controlled the scan.

The AUDIT.FILE class instances in an audit package control the auditing for files on the client computer. The **RIMFSCAN** and the **RIMDIFF** methods on the client computer perform the actual file auditing operations by specifying what files to look for.




Figure 7.9 ~ The RIMFSCAN and the RIMDIFF methods on the client computer perform the actual file auditing operations by specifying what files to look for.

- The **RIMFSCAN** method scans the client's computer file system based upon the values contained in the **AUDIT.FILE** class instance in the audit package. It constructs an object

called **FILENEW**. The **FILENEW** object contains one heap per file discovered during the current scan.

- The **RIMDIFF** method compares the scan results from the current scan (the scan done during the current Client Connect stored in the **FILENEW** object) with the scan results from a previous scan (the scan done during a previous Client Connect process stored in the **FILEPREV** object). It will construct the **FILEAUDT** object that is then sent to the Radia Configuration Server. The **RIMDIFF** method then deletes the **FILEPREV** object and will rename the **FILENEW** object to **FILEPREV**.

For our particular example, there were 486 instances for both the **FILEAUDT** and the **FILEPREV** object located on the Radia Client's computer.

Summary

- To illustrate the concepts of inventory information collection, the Radia Inventory Manager installation contains a set of representative audit service examples.
- The best way to develop your own audit services is to study the samples that were installed with the Radia Inventory Manager.
- Inventory information is collected on the Radia Inventory Manager client computer when a user connects to the Radia Configuration Server.
- The first connection downloads the audit service. The second connection sends the audit results back to the Radia Configuration Server. The audit-related scans are done between the two connections.
- The RIMFSCAN method scans the client's computer file system based upon the values contained in the AUDIT.FILE class instance in the audit package. It constructs an object called FILENEW.
- The RIMDIFF method compares the scan results from the current scan (the scan done during the current Client Connect process stored in the FILENEW object) with the scan results from a previous scan (the scan done during a previous Client Connect process stored in the FILEPREV object). It constructs the FILEAUDT object that is then sent to the Radia Configuration Server.

Auditing – Creating Your Own Audit Packages

At the end of this chapter, you will:

- Have created a new file audit package.
- Have created a new ZSERVICE for your package.

This manual is provided to assist you with installing and implementing the Radia Inventory Manager. Choose the appropriate strategies suited for your enterprise needs.

Audit Packages or PACKAGE Class

Once you are comfortable auditing using the sample packages provided by HP, you will probably want to take the next step in designing your own audit packages.

By expanding the **Audit Packages (PACKAGE)** class, you will see the audit package instances.




Figure 8.1 ~ Audit Package (PACKAGE) class.

A complete audit service consists of several connected instances in the AUDIT domain. The audit package instance is a container that "owns" the instances connected to it. For example, open the AUDIT.ZSERVICE class and double-click on the **Individual File Audit** instance.



Figure 8.2 ~ Individual File Audit instance.

In the example, the **Individual File Audit** ZSERVICE instance "owns" the **Audit to Find and Capture a Local File** instance. The fact that a package instance owns a component class instance means that all of the instances are managed as a package unit. If the package instance is deleted, all of its owned class instances are automatically deleted as well.

Caution

Sound database management practices dictate that the component class instances owned by a package are not connected to any other package instance.

The audit service instance must also contain a connection to an instance of the RIMOPTS class. Connecting an instance of the RIMOPTS class to an audit service instance causes the expressed behavior to be performed. Specified behaviors are listed in the following table.

Table 8.1 ~ Inventory Options (RIMOPTS) Class

Instance	Description
Default	Contains the base instance attributes for the RIMOPTS class. <ul style="list-style-type: none"> Collect attribute is set to Diff. Runexec attribute is set to IU. ZSVCTYPE attribute is set to I.
Differenced Audit on Install and Update	When connected to an audit service will difference the audited information on installation and when the audited target is updated. <ul style="list-style-type: none"> Collect attribute is set to Diff. Runexec attribute is set to IU. ZSVCTYPE attribute is set to I.
Differenced Audit on Install, Verify, and Update	When connected to an audit service, will difference the audited information in initial installation, on subsequent connects, and when updated. <ul style="list-style-type: none"> Collect attribute is set to Diff. Runexec attribute is set to IVU. ZSVCTYPE attribute is set to I.

Table 8.1 ~ Inventory Options (RIMOPTS) Class

Instance	Description
Full Audit on Install and Update	When connected to an audit service, will difference the audited information on installation and update. <ul style="list-style-type: none"> • Collect attribute is set to Full. • Runexec attribute is set to IU. • ZSVCTYPE attribute is set to I.
Full Audit on Install, Verify and Update	When connected to an audit service, will <ul style="list-style-type: none"> • Collect attribute is set to Full. • Runexec attribute is set to IVU. • ZSVCTYPE attribute is set to I.

See *The AUDIT Domain* starting on page 105 for additional information about RIMOPTS attributes.

Finally, a connection to an auditing behavior is needed.




Figure 8.3 ~ Connection to an Audit Behavior.

The audit behavior owned by the Individual File Audit ZSERVICE is connected to the Behavior Services (BEHAVIOR) class within the AUDIT domain.

The BEHAVIOR class in the AUDIT domain remains unchanged from the BEHAVIOR class within the SOFTWARE domain. See the *Radia Database Manual, Chapter 8: The SOFTWARE Domain* for the description of the attributes found within this class.

Using Radia System Explorer to Create/Maintain Audit Services

By using the Radia System Explorer, we will walk through the construction of a file audit. An instance of the AUDIT domain's Audit Package (PACKAGE) class contains information about the inventory information to collect, and what action to take with that collected information.

Prior to beginning the creations package, you should ask yourself the following questions:

- What am I auditing for? Will it be a hardware audit, a file audit, or a WBEM object audit?
- Will I be deploying to all users, or a select few?

- Will I want this to be connected to a timer for scheduled deployment? (See *Configuring Timers for Audit Collection* starting on page 171 for information concerning timers.)

By viewing and deploying the sample audits provided by HP, system administrators will be able to create and use their own auditing packages.

Caution

If you are creating a WBEM Audit Package, be aware that HP Openview Inventory Manager using Radia for Windows leverages Microsoft's Windows Management Instrumentation (WMI) to collect hardware and software inventory data by using WMI queries. Some WMI queries can traverse the network contacting other servers in the enterprise to collect the requested information. This may result in large volumes of data being returned, and could have a significantly negative effect on network performance. An example of this would be querying all users on the network using the W32_UserAccount WMI class. Extreme caution must be taken to understand the scope of these queries to ensure unexpected results do not occur. While Radia Inventory Manager provides an interface to WMI and its providers, it cannot control how these queries are satisfied. It is the customer's responsibility to safeguard against using WMI queries that span the network, if this behavior is not desired.

To create a new Audit package

1. From the **Start** menu, select **Programs, Radia Administrator, Radia System Explorer**. The **Radia System Explorer Security Information** dialog box opens.

Note

The **User ID**, as shipped from HP, is **RAD_MAST**. No password is necessary. This may have been changed during installation. Check with your Radia security administrator to obtain your own **User ID** and **Password**, if necessary.

2. If necessary, type a **User ID** and **Password**, and then click **OK**. The **Radia System Explorer** window opens.
3. Double-click **PRIMARY**.
4. Expand the **AUDIT** domain.
5. Double-click on **Audit Packages (PACKAGE)** class.




Figure 8.4 ~ AUDIT. Audit Packages (PACKAGE) class.

As an example, we will create a new auditing package called **Log Finder**. This package will scan a user's computer for .log files, capture them, and return the results to the administrator.

6. Right-click on the **Audit Packages (PACKAGE)** class.

A shortcut menu opens.




Figure 8.5 ~ New Instance option.

7. Select **New Instance** from the shortcut menu.

The **Create Instance** dialog box opens.




Figure 8.6 ~ Create Instance dialog box.

8. Enter a new display name for the package instance. This friendly name will appear in the tree view.

9. Enter a name for the **Create a new Audit Packages (PACKAGE)** instance name. This name appears in the title bar of the list view of the Radia System Explorer window when the instance is selected and opened in the tree view.
10. Click **OK** to continue.

The new **Log Finder** package is added to the **AUDIT.PACKAGE** class.




Figure 8.7 ~ Log Finder AUDIT.PACKAGE.

Once the Log Finder package is created, you will need to add its components.

To add a component to an Audit package

1. Right-click on the Log Finder package.
2. A shortcut menu opens.




Figure 8.8 ~ Add Components option.

3. Select **Add Component** from the shortcut menu.

The **Add Components** dialog box opens.




Figure 8.9 ~ The Add Components dialog box.

4. Click on the **Available Components** drop-down arrow, and select **File**.
-




Figure 8.10 ~ Add Components – Available Components list.

5. In the **New Component Name** text box, enter the new component name.
-




Figure 8.11 ~ Add Components dialog box.

6. Click **Add+Edit**. The component is added to the package and the **Editing Instance** dialog box opens.




Figure 8.12 ~ Editing Log Finder Instance dialog box.

In the **Editing Instance** dialog box, you can edit the instances that will be used in your audit.

Note

Use the AUDIT.FILE class instances to help you decide which instances you may want to edit.

For our example, we changed the SCANFOR attribute to **C:**.log**.

Continue to edit, line-by-line, as necessary.

7. Click **OK** when you are done with your edit.

8. Click **Yes** to save your changes.

Next, you will need to create a ZSERVICE instance to contain the Log Finder package.

To create a ZSERVICE instance

Note

While working in the Audit domain, note that the New Application Wizard is *not* available to connect a package to a service. You need to either copy an existing instance or create a new one.

1. In the Radia System Explorer, expand the AUDIT.ZSERVICE class in the tree view.
2. Right-click **Audit Application (ZSERVICE)** and a shortcut menu opens.




Figure 8.13 ~ Create a New Instance.

3. Select **New Instance** from the shortcut menu.

The **Create Instance** dialog box opens.




Figure 8.14 ~ Create Instance dialog box.

4. Type a **Display** and an **Instance** name.
5. Click **OK**. The ZSERVICE **Log Finder** is added to the **AUDIT.ZSERVICE** class.




Figure 8.15 ~ Log Finder ZSERVICE.

6. Use the Radia System Explorer to connect the Log Finder package to the Log Finder service.




Figure 8.16 ~ Log Finder package connected to Log Finder service.

Once the connection to the ZSERVICE has been completed, various optional steps can be taken.

You might want to ask yourself the following questions:

- Will the service appear in the Radia Software Manager? Should the ZSVCNAME be changed? Should I enter additional information that may appear in the Radia Software Manager?
- Will this be a mandatory or optional service?
- Will the service have a certain length of time to be active?
- Do I want to confirm if the service is installed or not?

The answers to these questions can help you decide how to customize the service.

For our example, we wanted to change the service name from **Unknown** to **Log Finder**. We also wanted to make this service available to users in the Radia Software Manager, so we have changed the ZSVCMO attribute from mandatory to mandatory *and* optional. We would like the Radia Configuration Server to report back and store any .log files that are found. Therefore, we will change the ZRSCMFIL attribute to capture and store this information on the Radia Configuration Server's directory.

Application class Log Finder Instance Attributes:		
Name	Attribute Description	Value
ZSTOP000	Expression Resolution Method	
ZSTOP001	Expression Resolution Method - 001	
ZSTOP002	Expression Resolution Method - 002	
ZSTOP999	Stop Unless Radia Connect	
ZSVCNAME	Service Name/Description	Log Finder
ZSVCTTYP	Application Target Type [A/S]	
ZSVCMO	Mandatory or Optional Service [M/O]	MO
ZSVCCSTA	Service Status on Client (999)	999
ZSVCPRI	Service Create Ordering [01-99]	
ig_ALWAYS_	Contains	AUDIT.PACKAGE.LOG_FINDER
ic_ALWAYS_	Contains	
ic_ALWAYS_	Contains	
ic_ALWAYS_	Contains	
it_ALWAYS_	Contains	
it_ALWAYS_	Contains	AUDIT.RIMOPTS.DIFF_INSTALL_UPD...
it_ALWAYS_	Contains	AUDIT.PACKAGE.AUDIT_EXECUTE_B...
ALWAYS	Utility Resolution Method	
ZCREATE	Service Installation Method	
ZINIT	Service Initialization Method	
ZDELETE	Service Delete Method	
ZUPDATE	Service Update Method	
ZVERIFY	Service Verify Method	
ZREPAIR	Service Repair Method	
ZAVIS	Available,Verified,Installed,Sync F	YXNX
PUBDATE	Published Date of Service	
VERDATE	Verified Date of Service	
UPGDATE	When Application was Upgraded on De	
UPDDATE	Upgrade Date (Programmatic)	
INSTDATE	Installed Date	
DELDATE	Delete Date	
AUTHOR	Author Name	
DESCRIPT	Application Description	

Figure 8.17 ~ Log Finder ZSERVICE attributes.

Use the Radia System Explorer to connect and deploy the Log Finder audit service. In this particular example, the user sees the new audit service in his Radia Software Manager.




Figure 8.18 ~ Log Finder as it appears in the Radia Software Manager.

Summary

- A complete audit service consists of several connected instances in the AUDIT domain.
- The audit package instance is a container that "owns" the instances connected to it. The fact that a package instance owns a component class instance means that all of the instances are managed as a package unit.
- By viewing and deploying the sample audits provided by HP, system administrators will be able to create and use their own auditing packages.
- The New Application Wizard is *not* available to connect a package to a service in the Audit domain. You need to either copy an existing instance or create a new one.

Configuring Timers for Audit Collection

At the end of this chapter, you will:

- Have created an Audit TIMER instance for an audit package.
- Have created an Audit TIMER ZSERVICE for an audit package.

This manual is provided to assist you with installing and implementing the Radia Inventory Manager. Choose the appropriate strategies suited for your enterprise needs.

The Scheduling (TIMER) Class

The Scheduling (TIMER) class enables the Radia administrator to set a timer on the client computer that will cause one or more audit services to be processed whenever the timer expires. The administrator can use this method to process mandatory audit services automatically according to a pre-determined schedule.

Note

As distributed by HP, the SOFTWARE domain also contains a Scheduling (TIMER) class. Timers can be specified in instances of either of these Scheduling (TIMER) classes and can be connected to an Application (ZSERVICE) class instance in either the SOFTWARE or AUDIT domain.

Housed within the AUDIT.Scheduling (TIMER) class are sample Timer packages:

- **Daily**
which will deploy a ZSERVICE everyday at the time specified.
- **Weekday**
which will deploy a ZSERVICE on Mondays, Wednesdays, and Fridays at a specified time.
- **Weekly**
which will deploy a ZSERVICE every seven days at a specified time.
- **Discover Installed Software Timer**
executes a ZSERVICE weekly between 8:30 am and 10:30 pm. Use this particular timer in conjunction with the ZSERVICE Discovery of Applications that audits the ADD/REMOVE PROGRAM part of the OS.

These sample packages can be copied and modified, changing the time parameters to suit your needs. See the *Radia System Explorer Guide* for information on copying an instance. Or, you can create a new timer instance by following the instructions in *Creating a Timer Instance* beginning on page 176.




Figure 9.1 ~ AUDIT Scheduling (TIMER) class.

Timers can be set to expire periodically (hourly, daily, weekly, monthly, or at defined intervals), on a specific date, or at a specific time. Each Radia Client is installed with the Radia Scheduler service. This service contains an executable timer component that executes any program on the end-user desktop when a timer expires.

Typically, the Radia Scheduler service lies dormant in the background, and wakes up once per minute to see if a timer has expired. When a timer expires, the command line associated with the expired timer is executed. Normally, this command line invokes a connection to the Radia Configuration Server to deploy or maintain a service.

The following table contains descriptions of the Scheduling (TIMER) class attributes:

Table 9.1 ~ Scheduling (TIMER) Class	
Attribute	Description
ZOBJPRI	Sets the priority for deployment of the ZTIMEQ object. The ZTIMEQ object is deployed relative to the other elements being deployed during the Client Connect. The elements with a priority number less than the value of ZOBJPRI are deployed <i>before</i> the ZTIMEQ object. A value of 90 is inherited from the base instance and should not be changed.
ZSTOP	Used to assign timer conditions. Indicate true to cause resolution of the instance to be skipped. The timer is not deployed for end users. Leave <i>blank</i> for the instance to be accepted, and resolution will continue.

Table 9.1 ~ Scheduling (TIMER) Class

Attribute	Description
ZSCHMODE	Specifies the timer owner. We recommend you leave the default configuration of USER.
ZSCHDEF	Indicates when the timer expires. The syntax varies depending on the frequency of expiration that can be DAILY, HOURLY, INTERVAL, NUMDAY, WEEKDAY, WEEKLY.
ZSCHTYPE	<p><i>Used only when ZSCHFREQ = PERIODIC.</i></p> <p>Set ZSCHTYPE to DEFERRED to indicate that the first time an event is attempted to be launched, it will be deferred until the <i>next</i> scheduled time, no matter when the timer instance is evaluated. This was designed to handle the case of a daily 4am (non-peak) scheduled event that is sent to the client computer during the day. If it was not deferred, it would launch during the day instead of "waiting" until the next morning.</p> <p>Example 1:</p> <p>Suppose you create and deploy a timer with the ZSCHDEF = DAILY(&ZSYSDATE,4:00:00). If ZSCHTYPE = IMMEDIATE and it is:</p> <ul style="list-style-type: none"> • Before 4:00:00, the command in the instance will be executed the same day at 4:00:00. • After 4:00:00, the command in the instance will be executed immediately. <p>If ZSCHTYPE = DEFERRED and it is:</p> <ul style="list-style-type: none"> • Before 4:00:00, the command in the instance will be executed the <i>next</i> day at 4:00:00. • After 4:00:00, the command in the instance will be executed the <i>next</i> day at 4:00:00. <p>Example 2:</p> <p>Suppose you create and deploy a timer with the ZSCHDEF = WEEKDAY(FRIDAY,4:00:00) If ZSCHTYPE = IMMEDIATE and it is:</p> <ul style="list-style-type: none"> • Not Friday or Friday and before 4:00:00, the command in the instance will be executed on Friday at 4:00:00. • Friday and after 4:00:00, the command in the instance will be executed immediately. <p>If ZSCHTYPE = DEFERRED and it is:</p> <ul style="list-style-type: none"> • Not Friday or Friday and before 4:00:00, the command in the instance will be executed a week later on Friday at 4:00:00. • Friday and after 4:00:00, the command in the instance will be executed a week later on Friday at 4:00:00.
ZSCHFREQ	<p>This attribute indicates how often the timer should expire according to the frequency specified in the ZSCHDEF attribute.</p> <ul style="list-style-type: none"> • Once for a one-time expiration. • Periodic for a repeated expiration. • Random for random intervals.
ZRSCCMDL	This attribute indicates the command line that is executed on the subscriber's computer when the timer expires.
ZSVCOID	Specifies the object ID of the Application instance that this Scheduling instance is connected to. This value is inherited from the base instance and should not be modified.
_ <u>ALWAYS</u> _	Stores the connections to other instances.
NAME	Friendly name for this instance.

Table 9.1 ~ Scheduling (TIMER) Class

Attribute	Description
APPSVC	Application.
REQUEST	Application request.
DOMAIN	Server's domain name.
IPADDR	Server's IP address/name.
SOCKET	Server's socket number.
MGRNAME	Server's name.
ZCREATE	Scheduler CREATE method that runs on the client computer. This value is inherited from the base instance and should not be changed.
ZVERIFY	Scheduler VERIFY method that runs on the client computer. This value is inherited from the base instance and should not be changed.
ZUPDATE	Scheduler UPDATE method that runs on the client computer. This value is inherited from the base instance and should not be changed.
ZDELETE	Scheduler DELETE method that runs on the client computer. This value is inherited from the base instance and should not be changed.
RUNSYNC	Sets the value of Yes or No for the synchronous timer execution. The default value is Yes.
ZNOPING	Controls the automatic sensing of a network connection between the client computer and the Radia Configuration Server. An expired time will continually evaluate whether communications with the Radia Configuration Server can be established. When communications are established, the command line associated with the time is executed. After executing the command line, the Scheduler service resumes normal evaluation of whether the timer has expired again. Use this attribute when there is a possibility that the client will not be able to connect with the Radia Configuration Server. This attribute is especially useful for mobile users. Note: In order to use this attribute, you must add it to the TIMER class template.
PINGDLAY	Sets the amount of time between pings in milliseconds. The default setting is 2000 milliseconds.
PINGCNT	Sets the number of ping attempts to be made by the Radia Configuration Server. The default setting is 3.

This section describes how to create and configure a timer, and connect it to the service that you want to deploy. Prior to creating and configuring a timer, consider the following:

- What time of day should the timer expire?
- How often do you want the timer to expire?
- Does the timer need to expire more than once?
- What should happen when the timer expires?

Creating a Timer Instance

To create a timer in the Radia Database, use the Radia System Explorer to create a Scheduling (TIMER) instance in the AUDIT domain.

Note

As distributed by HP, the SOFTWARE domain also contains a Scheduling (TIMER) class. Timers can be specified in instances of either of the Scheduling (TIMER) classes and can be connected to an Application (ZSERVICE) class instance in either the SOFTWARE or AUDIT domains.

For the purposes of documentation, the timer created will be created from within the AUDIT domain.

For additional information concerning the Scheduling (TIMER) class, see the *Deploying Applications* in the *Radia Application Manager Guide*.

To create a new timer in the AUDIT domain

1. From the **Start** menu, select **Programs, Radia Administrator Workstation, Radia System Explorer**. The **Radia System Explorer Security Information** dialog box opens.

Note

The **User ID**, as shipped from HP, is **RAD_MAST**. No password is necessary. This may have been changed during installation. Check with your Radia security administrator to obtain your own **User ID** and **Password**, if necessary.

2. If necessary, type a **User ID** and **Password**, and then click **OK**. The **Radia System Explorer** window opens.
3. Double-click **PRIMARY**.
4. Double-click **AUDIT**.
5. Right-click **Scheduling (TIMER)**.




Figure 9.2 ~ Timer shortcut menu.

6. Select **New Instance**. The **Create Instance** dialog box opens.




Figure 9.3 ~ Create Instance dialog box.

7. Type a name for the new timer instance, such as Log Audit Timer.
8. Click **OK**. The timer instance appears in the Scheduling (TIMER) class.




Figure 9.4 ~ Log Audit Timer instance.

Specifying Timer Settings

Whether you have copied an existing timer or you have created a new Timer instance, you need to review and/or customize your timer settings. See the *Radia Application Manager Guide* and the *Radia Software Manager Guide* for more information on how to specify the client timer settings.

Specifying ZSCHDEF

Use the **ZSCHDEF** attribute to define the time interval and date and time to execute the command line. The syntax varies depending upon the interval chosen. When configuring ZSCHDEF, the attribute is set in the following form depending on the interval.

```
DAILY (<DATE>, <TIME>[, <LIMIT>])
HOURLY (<DATE>, <TIME>[, <LIMIT>])
WEEKLY (<DATE>, <TIME>[, <LIMIT>])
WEEKDAY (<DAY of Week>, <TIME>[, <LIMIT>])
NUMDAYS (<DATE>, <TIME>[, <LIMIT>], <Number of Days>)
INTERVAL (<DATE>, <TIME>[, <LIMIT>], <Number of Seconds>)
```

Note

Note in the case of NUMDAYS and Interval the Optional parameter <Limit> is between mandatory parameters. If the optional parameter is omitted the place must be held with a double comma. Example:

```
NUMDAYS: NUMDAYS (20000803, 08:00:00, 12:00:00, 14)
NUMDAYS: NUMDAYS (20000803, 08:00:00, , 14)
```

- The value of **freq** can be:

```
DAILY, WEEKLY, WEEKDAY, HOURLY, INTERVAL, NUMDAYS
```

- If the value of **freq** is DAILY, WEEKLY, HOURLY, INTERVAL, or NUMDAYS, the **date** is then specified in the following form:

```
YYYYMMDD
```

- If the value of **freq** is WEEKDAY, the **date** is then specified as the name of a day of the week in all uppercase letters. This would be one of the following:

```
MONDAY, TUESDAY, WEDNESDAY, THURSDAY, FRIDAY, SATURDAY, SUNDAY
```

- The values for **time** and **limit_time** are optional. They are specified in the following form:

```
HH:MM:SS
```

- The value for **count** is optional. It is specified as an integer.

The timer expiration can also be configured on the value of ZSCHFREQ. Use Table 9.2 on page 181 to help you determine the appropriate syntax.

Table 9.2 ~ Syntax of ZSCHDEF Attributes

Type	Syntax	Timer Expires
DAILY	DAILY(&ZSYSDATE,24:00:00)	Daily at midnight by the system's date.
WEEKLY	WEEKLY(&ZSYSDATE,01:00:00)	Every seven days at 1:00 am.
WEEKDAY	WEEKDAY (<i>Name of Weekday*</i> , 01:00:00)	Every <i>Name of Weekday*</i> at 1:00 AM. The weekday must be specified in uppercase.
HOURLY	HOURLY(&ZSYSDATE,08:41:00)	Hourly starting at 8:41 AM on the system's date.
INTERVAL	INTERVAL(&ZSYSDATE,08:41:00,,30)	Every 30 minutes starting at 8:41 AM based on system's date.
NUMDAYS	NUMDAYS(20000803,08:00:00,,14)	Every 14 days starting on August 3, 2000 at 8:00 AM.

Specifying ZSCHTYPE

The **ZSCHTYPE** controls how the timer handles the scheduled event when the client receives the initial **TIMER** definition for a service. There are two valid controls:

- **IMMEDIATE**
will execute the command specified in the **ZRSCCMDL** attribute immediately if the date and time indicated in the **ZSCHDEF** attribute has passed when the **ZTIMEQ** object is initially created.
- **DEFERRED**
will defer the execution if the date and time defined in the **ZSCHDEF** has passed and will wait until the next occurrence to execute. This is the recommended setting.

If the time and date indicated in **ZSCHDEF** has not passed when the **ZTIMEQ** object is deployed, this setting has no effect.

Specifying ZSCHFREQ

Use the **ZSCHFREQ** to specify whether the timer should expire once (**ONCE**) or repeatedly (**PERIODIC**) according to the frequency specified in **ZSCHDEF**.

Specifying ZRSCCMDL

Use the **ZRSCCMDL** to execute a command on the subscriber's computer when the timer expires.

Use the following command line to run the audit service when the scheduled time occurs:

```
Radskman uid=&(ZMASTER.ZUSERID), startdir=&(ZMASTER.LOCALUID),
mname=&(ZMASTER.ZMGRNAME), dname=&(ZMASTER.ZDOMNAME), sname=&(ZSERVICE.ZOBJNAME)
```

Note

Execution causes the Radia to launch the AUDIT service behavior, (EXECUTE.REXX) attached to the AUDIT service.

Note

The parameters indicated in the **radskman** command may differ depending upon customer specific implementations.

Specifying ZNOPING, PINGDLAY, and PINGCNT

Use the **ZNOPING** attribute to control automatic sensing of a network connection between the client computer and the Radia Configuration Server. The default is **Y**. Use this attribute when there is a possibility that the client will not be able to connect with the Radia Configuration Server such as a mobile user.

See the *Radia Software Manager Guide* for more information about the **ZNOPING** attribute.

- If the **ZNOPING** attribute is not in the **ZTIMEQ** object, or if **ZNOPING** is not equal to **N**, the Scheduler service does not ping the Radia Configuration Server.
- If **ZNOPING** = **N**, the Scheduler service will ping the Radia Configuration Server.
 - If the Radia Configuration Server is pinged successfully, the command in the **ZRSCCMDL** attribute is executed. The **PENDING** attribute in the client's **ZTIMEQ** object is then set to **N**. This indicates that the Scheduler service does not need to ping the Radia Configuration Server again.
 - Set **ZNOPING** to **W** if you are specifying an end limit in the **ZCHDEF** attribute. The Scheduler pings the Radia Configuration Server before executing the command. If the Radia Configuration Server is unavailable, the **ZPENDING** flag is set to "W". If the **ZSCHEDEF** has a limit time, then when that time passes, the **ZPENDING** flag is set to **N**, and the Scheduler will not attempt to execute the command until its next scheduled time.
 - If the Radia Configuration Server is not pinged successfully, the timer is not processed any further. The **ZPENDING** attribute value remains set to **Y**. The next time the Scheduler service expires, it should ping the Radia Configuration Server again.

If **ZNOPING** is set to **N**, also use the **PINGDLAY** and **PINGCNT** attributes to further specify the timing and number of pings between the client computer and the Radia Configuration Server.

- If **ZNOPING** is set to **N**, **PINGDLAY** specifies the time in milliseconds between pings. The default is 2000.
- If **ZNOPING** is set to **N**, **PINGCNT** specifies number of ping attempts. The default is 3 attempts.

Connecting the Timer to a Service

Once you have created your timer, you must connect it to a service. Each subscriber that receives the ZSERVICE to which the timer is connected, will receive the timer information in the ZTIMEQ object the next time the Radia Client connects to the Radia Configuration Server.

Use the Radia System Explorer to connect the **Log Audit Timer** to the **Log Finder** ZSERVICE created earlier in this document.




Figure 9.5 ~ Log Audit Timer instance connected to the Log Finder service.

Then connect the AUDIT.ZSERVICE .Log Finder to a user or group of users in the POLICY domain.



Figure 9.6 ~ Log Finder attached to a user.

Audit Execution Configuration

By default, when an Audit service is installed on an end user's computer, it executes immediately and reports to the Radia Configuration Server. This can be time consuming, especially if the audit service type is WBEM, File Scan, or an MSI request. The audit service definition may also be installed at a time when an audit scan is not desirable. For example, when an end user visits the Radia Software Manager and mandatory applications are processed as defined in the embed tag **enterprisemanagement=auto**.

The easiest way to approach this issue is to manipulate how and when the audit actually executes. This can be accomplished by:

- Customizing the Inventory Options (RIMOPTS) attribute.
and
- Updating the embed tags in the html file for the Radia Software Manager.

The following describes the steps necessary to customize RIMOPTS and update the embed tag to prevent audit execution during mandatory application processing.

To customize the RIMOPTS instance

1. From the **Start** menu, select **Programs, Radia Administrator Workstation, Radia System Explorer**. The **Radia System Explorer Security Information** dialog box opens.

Note

The **User ID**, as shipped from HP, is **RAD_MAST**. No password is necessary. This may have been changed during installation. Check with your Radia security administrator to obtain your own **User ID** and **Password** if necessary.

2. If necessary, type a **User ID** and **Password**, and then click **OK**. The **Radia System Explorer** window opens.
3. Expand the **PRIMARY** file and the **AUDIT** domain.




Figure 9.7 ~ PRIMARY.AUDIT.Inventory Options (RIMOPTS) class.

4. Create a new instance in the **Inventory Options (RIMOPTS)** class called **NVDM_AUDIT_NO_EXECUTE**, and click **OK**.




Figure 9.8 ~ New Inventory Options instance: NVDM Audit No Execute.

Next, you will need to edit the **NVDM Audit No Execute** instance.

- Expand the **Inventory Options (RIMOPTS)** class and double-click the **NVDM Audit No Execute** instance.




Figure 9.9 ~ Attributes of the NVDM Audit No Execute instance.

- Double-click the **RUNEXEC** attribute in the list view to edit it. Remove any attribute information. This will ensure that the audit service will not run during the installation, verification, or update function.




Figure 9.10 ~ Clear the RUNEXEC attribute.

Next, determine which AUDIT service you will be adding the new RIMOPTS service to. For example, select the RIM_REPORTING service.

7. Right-click on **RIM_REPORTING** Service in the AUDIT class.
8. Select **Edit Instance**.




Figure 9.11 ~ RIM Reporting: Edit Instance.

9. Locate the **_ALWAYS_ Contains** attribute with the value of **AUDIT.RIMOPTS.DIFF_INSTALL_UPDATE** and change it to a value of **AUDIT.RIMOPTS.NVDM_NO_EXECUTE**.




Figure 9.12 ~ RIM Reporting: Editing the ALWAYS connection.

- Next, to define the audit service as **Mandatory**, locate the **ZSVCMO** field and set it to **M**. This will cause the initial **TIMER** definition associated with the audit service to be created on the client.




Figure 9.13 ~ RIM Reporting: Editing the ZSVCMO instance.

The **NVDM Audit No Execute** instance is now connected to the RIM Reporting service.




Figure 9.14 ~ NVDM Audit No Execute added to the RIM Reporting instance.

Radia Software Manager Users

If enterprise users use the Radia Software Manager to install applications, by default, all mandatory Audit Services will execute when enterprise-management is performed. This is the case when the embed tag **enterprisemanagement** is set to **AUTO** or if the end user visiting the Radia Software Manager selects the **Enterprise Management** button from the Radia Software Manager.

The following steps prevent mandatory Audit services from executing during Enterprise Management processing.

To prevent Mandatory Audit Services from executing in the Radia Software Manager

1. Use the Windows Explorer to navigate to the html page that serves up the Radia Software Manager.




Figure 9.15 ~ RADIA1.HTM.

- Using an ASCII editor, open the html page. By default, this is the **radia1.htm** file located on your Web server.
- Add the following line:
`execonupdt=0`

```

RADIA1.HTM - Notepad
File Edit Format Help
<html>
<head>
<meta http-equiv="Content-Type" content="text
<meta name="GENERATOR" content="Microsoft Fro
</title></title>
</head>

<body background="gifs/stars1.jpg">
<div align="center"><center>

<table border="0" width="100%" cellspacing="0"
  <tr>
    <td width="100%" height="21" bgcolor="#00
      <embed src=aservice.ext
      height=300
      width=550
      pluginspage=getplugn.htm
      providername=RADIA
      bannerimage=radia.bmp
      channelname=SOFTWARE
      resolutionmanager=208.244.231.61
      resolutionport=3464
      installedhelpurl=http://208.244.231.61/radia/
      cataloghelpurl=http://208.244.231.61/radia/do
      execonupdt=0
      usercontext=y
      autorun>
      <align="middle"> <!--webbot bot="HTMLMarkup"
        <div align="center"><center><table border
          <tr>
            <td width="100%"></td>
          </tr>
        </table>
        </center></div></td>
      </tr>
    </table>
  </center></div>
</body>
</html>

```

Figure 9.16 ~ Adding the EXECONUPDT=0 to the RADIA1.HTM.

4. Save and exit the radia1.htm file.

When the client visits the Radia Software Manager and the **Enterprise Management** button is selected, the following occurs:

- **radskman** will *not* execute the EXECUTE.REXX associated with mandatory services.
- The previously configured RIMOPTS will prevent the audit service from executing except when launched via a scheduled (TIMER) event.

Summary

- The Scheduling (TIMER) class enables the Radia administrator to set a timer on the client computer. The timer will cause one or more audit services to be processed whenever the time expires.
- As distributed by HP, the SOFTWARE domain also contains a Scheduling (TIMER) class. Timers can be specified in instances of either Scheduling (TIMER) class and can be connected to an Application (ZSERVICE) class instance in either the SOFTWARE or AUDIT domains interchangeably.
- Typically, the Radia Scheduler service lies dormant in the background, and wakes up once per minute to see if a timer has expired.
- Use the **ZSCHDEF** to indicate when the timer should expire.
- Use the **ZRSCMDL** to execute a command on the subscriber's computer when the timer expires.

Viewing Inventory from the Radia Integration Server

At the end of this chapter, you will:

- Know how to access and use the *Radia Integration Server* pages to view the inventory information obtained from client computers. The web pages can be accessed whether or not you have the Radia Management Portal installed.
- Know how to use the **Summary** link in the Radia Integration Server to view information about *all* Radia Clients.
- Know how to use the **Detail** link in the Radia Integration Server to view in-depth information about a *single* subscriber.
- Be able to navigate through the information collected by clicking on hyperlinks embedded within any table.

Accessing the Radia Integration Server

To access the Radia Integration Server (via the Radia Management Portal)

1. In **Services**, ensure that the Radia Integration Server (httpd) is started.




Figure 10.1 ~ Starting the Radia Integration Server in Services.

2. Start your Web browser and type the address and port number of the Radia Integration Server into the text box in the following format:

`http://<I/P Address or hostname>:<Port>.`

- The *IP Address* is the IP address of the computer running the Radia Integration Server.
- The *hostname* is the name of the computer running the Radia Integration Server.
- The *Port* is the port number of the Radia Integration Server. This port number is usually 3466.




Figure 10.2 ~ Sample IP address and port number of the RIS entered in a Web browser.

If your Radia Inventory Manager is running from the Radia Management Portal, the web page shown in Figure 10.3 opens.




Figure 10.3 ~ The home page of the Radia Management Portal.

3. In the upper right corner, click **INVENTORY**.

Note

If the Radia Inventory Manager is not running from the same location as the Radia Management Portal, the home page opens with the Radia Integration Server banner. See *To access the Radia Integration Server (non-Radia Management Portal)* below for information on how to access the Radia Integration Server if you are not using the Radia Management Portal.

To access the Radia Integration Server (non-Radia Management Portal)

1. In **Services**, ensure that the Radia Integration Server is started.




Figure 10.4 ~ Starting the Radia Integration Server in Services.

2. Start your Web browser and type the IP address and port number of the Radia Integration Server into the text box in the following format:

`http://<I/P Address or hostname>:<Port>.`

- The *I/P Address* is the IP address of the computer running the Radia Integration Server.
- The *hostname* is the name of the computer running the Radia Integration Server.
- The *Port* is the port number of the Radia Integration Server. This port number is usually 3466.




Figure 10.5 ~ Sample IP address and port number of the RIS entered in a Web browser.

The home page of the Radia Integration Server opens.




Figure 10.6 ~ Radia Integration Server home page.

Maneuvering in the Radia Integration Server: Non-Radia Management Portal Users

The Radia Integration Server home page is a Web page designed to facilitate your use of various Radia products such as the Radia Inventory Manger, the Radia Policy Server, and the Radia Policy Manager (also known as the Push Manager).

Note

For more information on any of these add-on features, contact your sales representative.

The tabs and links across the top of the page access the following:

Table 10.1 ~ Radia Integration Server – Tabs and Links

Tab/Link	Information
MANAGER ADMIN	Clicking on the MANAGER ADMIN tab allows the administrator to view and navigate through the Radia Database. Note: In order to use this feature, the Radia Integration Server must be installed to the same computer as the Radia Configuration Server.
REPORTING	Clicking on the REPORTING tab takes you to the Web-based reports that show the information collected through the Radia Inventory Manager. This area is specific to and is the primary focal point for the Radia Inventory Manager.
SITE	Clicking on the SITE tab takes you to a place where custom HTML can be stored. This area is specific to the Radia Integration Server.
Server Admin	Click on the SERVER ADMIN tab to change the settings of the Web-server itself. This area is specific to the Radia Integration Server.
HOME	Clicking on the HOME link will return you to the Radia Integration Server home page.

Table 10.1 ~ Radia Integration Server – Tabs and Links

Tab/Link	Information
SUPPORT	Clicking on the SUPPORT link opens another web browser pointing at the HP Home Page. From here, you can access Support, Technical Publications, as well as our corporate information. Alternatively, go directly to the HP OpenView web site.
INFO	Clicking on the INFO link will bring you to more Radia Integration Server documentation.

Note

Information specifically related to the Radia Integration Server can be found on the HP OpenView web site.

Reporting

Click on the **REPORTING** tab to access the queries page.



Figure 10.7 ~ Accessing the REPORTING tab.

At the top of the page, select:

- **Summary**
which will show information about *all* subscribers or Radia Clients.
- OR
- **Detail**
which will show in-depth information about a *single* subscriber or Radia Client.

Summary Information

Click the **Summary** link to display the following:




Figure 10.8 ~ Reporting tab – Summary.

Click the drop-down arrow for **Action** to make a selection from a drop-down menu.

Summary




Figure 10.9 ~ Summary tab – Action drop-down menu.

Table 10.2 below indicates the information that can be accessed from the **Action** drop-down menu.

Table 10.2 ~ Reporting Tab – Actions Drop-down Selections

Action	Reporting Available
--------	---------------------

Table 10.2 ~ Reporting Tab – Actions Drop-down Selections

Action	Reporting Available
Show - Subscribers	Lists all of the Radia Clients that have connected to the Radia Configuration Server; the most recent date and time the subscriber connected, and the number of applications that a subscriber has installed. Use this in conjunction with the Limit To drop-down menu to control the number of subscribers/clients to be viewed. You can access the subscribers/clients system configurations and application information.
Show - Applications	Lists the applications available to Radia Clients. It also shows how many users have subscribed to a particular application.
Show - System Drivespace	List the end users' system drive space. Includes the drive indicator (such as C: drive), the drive size in megabytes, the systems free drive space in megabytes, and the free drive space expressed in a percentage.
Show - IP Addresses	Lists the IP address and MAC (Machine) addresses for each subscriber.
WBEM - Configuration	A summary of configuration information for all Radia Clients.
Status - Application Events	Will show the last event (install, uninstall, verify, repair, etc.) for all Radia Clients and all applications.
Status - WBEM Events	Not applicable at this time.
Status - Connect	Shows statistics concerning the last connect for all Radia Clients.
Status - Multicast Server Statistics	Shows statistics for all client downloaded resources in your network. This is useful for obtaining a network profile of your client downloads, as well as debugging client download problems. Includes the following information for all client downloaded resources: the exact source of a resource delivery (for example, a Radia Proxy Server, Stager, Radia Configuration Server, or Radia Multicast Server), how many files were delivered from each source, how long the delivery took from each source, and the total size of resources downloaded from each source. For a sample of fields reported, see Table A.4 ~ Summary Reporting on page 227.
Status - Client Download Statistics	Shows statistics for all client downloaded resources in your network. This is useful for obtaining a network profile of your client downloads, as well as debugging client download problems. Includes the following information for all client downloaded resources: the exact source of a resource delivery (for example, a Radia Proxy Server, Stager, Radia Configuration Server, or Radia Multicast Server), how many files were delivered from each source, how long the delivery took from each source, and the total size of resources downloaded from each source. For a sample of fields reported, see Table A.4 ~ Summary Reporting on page 227.
Status - Notify	This report is not applicable for the Radia Inventory Manager.
Errors – Connect	Summary of error information for all Radia Clients.
Errors – Notify	This report is not applicable for the Radia Inventory Manager.
Admin - Configuration	Lists current configuration setting of the Radia Inventory Manager module.

For most of the Summary Reports, it is possible to obtain more detailed reports by clicking on buttons and hyperlinks embedded within the reporting tables. For more information on Detail Reports, see *Detail Information* beginning on page 201.

Detail Information

Click on the **Detail** link to display the following page:




Figure 10.10 ~ Reporting tab – Detail Report.

Use the buttons and drop-down menus to configure what you would like to see reported. The type of **Report** you select directly impacts the **Action** you can take. For example, if you would like to see the General Reporting items, select **General Reporting** option. Then click on the **Action** drop-down arrow to see what Action items are available to you.

Table 10.3 below indicates the information that can be accessed from each of the drop-down menus.

Table 10.3 ~ Reporting Tab – Detail Reporting – Type

Type	Action Available
Inventory Reporting	<p>Allows you to select the following Actions:</p> <ul style="list-style-type: none"> • WBEM Applications For WBEM audited applications. • WBEM Features Displays the software features for a particular subscriber. • WBEM Elements Displays the software elements for a particular subscriber. • Configuration - Summary Displays OS configuration, hardware, disk drive information, environment, and Windows services. • Applications For managed and audited applications. • Installed Applications Displays the information for the audited files, installed applications and applications that have been added or removed. • Audited Files Displays audited files information such as name, version, status, etc. • PDA Devices Displays any found PDA devices for a particular subscriber. • WBEM PDA Config Displays the configuration and any installed products for a subscribers PDA device.

Table 10.3 ~ Reporting Tab – Detail Reporting – Type

Type	Action Available
General Reporting	<p>Allows you to select the following Actions:</p> <ul style="list-style-type: none"> • Show – Config Detailed reporting on such things as devices, hardware, and software for a particular subscriber. • Status – Application Events Displays the Application Events (application packages) for a specific subscriber. • Status – Connect Displays the connection status for a specific subscriber. This also includes a report on any errors. • Status – Services Displays the service state of the devices. • Status – Notify Displays the notification status of the devices. • Status – Summary Displays connection status for a specific user. • Status – Detailed Displays the connection status as well as errors for a specific subscriber.
History Reporting	<p>Allows you to select the following Actions:</p> <ul style="list-style-type: none"> • Application Events Displays application event history. • Connect Displays connect history. • Errors Displays error history. • State Displays state history.

Subscriber

The **Subscriber** drop-down menu lists all of the subscribers (clients and or end users) that reporting is available for.

Note

Remember, the Detail reporting functions focus on individual users. If you wish to view more than one user, click on the **Summary** link to enable viewing multiple users.

To view a specific user, click on the **Subscriber** drop-down menu as follows:

Subscriber Detail - 3 subscribers in database

Reporting: Inventory General History **Action:**

Subscriber Filtering: **Subscriber:**

CTANZILLO
SAMPLE1
UNIX_FILE_AUDIT

Figure 10.11 ~ Details – Subscriber drop-down menu.

To select a Subscriber, simply hold your cursor over the list item and click on the desired user.

Subscriber Filtering

Before you use the **Subscriber** drop-down menu, you can filter the available subscribers list by entering all or part of a subscriber's name in the **Subscriber Filtering** text box. If you enter only part of a subscriber's name, be sure to use the asterisk (*), which acts as a wild-card variable, before or after the text you typed. For example, to filter all subscribers containing **TEST** in their names, you would type *TEST* in the **Subscriber Filtering** text box.

Maneuvering in the Radia Integration Server: Radia Management Portal Users

The Radia Management Portal is a Web-based interface used to manage your Radia infrastructure. The Radia Management Portal consists of the Radia Integration Server service, the Radia Management Portal service, and the Radia Management Portal Directory. You can perform administrative and operational tasks to objects in your infrastructure.

Actions performed in Radia Management Portal are accessed through one interface. Accessing the inventory functions in the Radia Management Portal by clicking on the INVENTORY button, located in the upper right hand corner of the Radia Management Portal interface.




Figure 10.12 ~ The home page of the Radia Management Portal.

For specific information about the features of the Radia Management Portal, see the *Radia Management Portal Guide*.

Once you have accessed the Radia Integration Server from within the portal, the functionality of the interface is the same as non-portal users.




Figure 10.13 ~ The Radia Inventory Server homepage viewed from within the Radia Management Portal.

Administrator Hints and Tips

When viewing reports, you are able to navigate through the information collected by clicking on hyperlinks embedded within any table. These links can be in a table header or in the actual body of a particular report.

The following example shows how an administrator might navigate through a Summary report for **Show – Applications**.

To navigate through a Summary report for Show - Applications

1. Access the Radia Integration Server via the Radia Management Portal or the Radia Integration Server home page.
2. Click the **Reporting** tab.
3. Click the **Summary** link.
4. From the **Action** drop-down menu, select **Show – Applications**.
When the screen refreshes, the **Applications** table is displayed.

Summary - 1 subscriber in database

Action:

Application Name	Subscribers
Amortize	1
RIM Reporting	1
Sales Information	1
WBEM Hardware & Software	1

[Back to top](#)

Figure 10.14 ~ Summary Reporting – Applications Table.

This table shows all the applications that are available to all subscribers. There is a variety of actions and information that can now be accessed.

5. To sort a column:
 - Click on the **Applications** column heading to list the applications in reverse alphabetical order.

Note

▲ indicates the column heading that the table is currently sorted by and designates whether the table is sorted in ascending order ▲ or descending order ▼.



Figure 10.15 ~ Sort in reverse alphabetical order by Application Name.

- Click on the **Subscribers** column heading to sort the list in ascending order.

Home > Inventory > [Summary] | [Detail]

Summary - 3 subscribers in database

Action:

Applications

Application Name	Subscribers
Amortize	1
ITAAudit Cim_LogicalDisk	1
Sales Information	1
Unknown Service	1
WBEM Hardware & Software	1
RIM Reporting	2

Back to top

Figure 10.16 ~ Sample Sort by Subscribers (ascending number of subscribers shown).

6. Sorting within a row:

- Click on any of the **Applications** to view the Radia Clients for that particular application.

Home > Inventory > [Summary] | [Detail]

Summary - 3 subscribers in database

Action:

Status - Application Events > RIM Reporting >

Application Events

Subscriber	Service	Created	Modified	Application Name	Event	Status	Date Deleted	Date Verified	Date Installed	Date Fix
CTANZILLO	RIM_REPORTING	2002-02-07 10:20:35	2002-02-07 10:23:22	RIM Reporting	Install	Successful		2002-02-07 10:17:52	2002-02-07 10:17:52	2002-02-07 10:17:52
SAMPLE1	RIM_REPORTING	2000-11-02 15:59:20	2000-11-02 15:59:20	RIM Reporting	Install	Successful		2000-11-02 15:59:23	2000-11-02 15:59:23	2000-11-02 15:59:23

Back to top

Figure 10.17 ~ Click on the Amortize application.

CTANZILLO and SAMPLE1 are the only two Radia Clients for the Amortize application.

From here, it is possible to access even more information. Just as on the Applications page, clicking on any of the column headers will result in a sort process. Click on any of the hyperlinks within the rows to provide additional information for that item.

7. Click on the subscriber, CTANZILLO.

The **Application Events** for CTANZILLO opens.

Home> Inventory> [Summary] | [Detail]

Subscriber Detail - 3 subscribers in database

Reporting: Inventory General History Action: Status - Application Events

Subscriber Filtering: * GO Subscriber: CTANZILLO

Status - Application Events>

Application Events (CTANZILLO, running Windows_NT Version 5.0 [Build 2195])

Subscriber	Service	Created	Modified	Application Name	Event	Status	Date Deleted	Date Verified	Date Installed	Date Fixed
CTANZILLO	RIM_REPORTING	2002-02-07 10:20:35	2002-02-07 10:23:22	RIM Reporting	Install	Successful		2002-02-07 10:17:52	2002-02-07 10:17:52	2002-02-07 10:17:52

[Back to top](#)

Figure 10.18 ~ Application Events for CTANZILLO.

This report displays all of the applications CTANZILLO has downloaded.

Note

Notice that since we are accessing information on a specific user, the mode of reporting has refreshed to the options available through Detail reporting.

The administrator can continue to access additional information about a particular subscriber, application, and so forth, simply by clicking on the embedded hyperlinks.

Table 10.4 on page 209 shows the results of clicking on specific links.

Table 10.4 ~ Summary Links – All Actions

Action	Embedded Links
Show - Subscribers	<ul style="list-style-type: none"> Click Config to show a detailed report for a specific user such as O/S configuration, hardware, disk drive information, environment, and Windows services. Click Application to show a detailed report for a specific user including managed and audited applications.
Show - Applications	<ul style="list-style-type: none"> Click a specific application to show Status Application Events for that particular application. Click on a specific subscriber to view detailed Application Events for that particular subscriber.
WBEM – Configuration	<ul style="list-style-type: none"> Click on a Subscriber to obtain a detailed report for that user such as O/S configuration, hardware, disk drive information, environment, and windows services. This is the same as clicking on Config in the Show – Subscribers summary report.
Status – Application Events	<ul style="list-style-type: none"> Click on a Subscriber to obtain a detailed report of application events for that particular subscriber. Click on either Install or Uninstall in the Event column to filter. Click on either Successful or Unsuccessful to filter in the Status column.
Status – Connect	<ul style="list-style-type: none"> Click on a subscriber to obtain detailed reports on a specific user's connect status and any errors encountered.
Status – Notify	<ul style="list-style-type: none"> Notify Status for use with Push Manager.
Errors – Connect	<ul style="list-style-type: none"> Click on a subscriber to display detailed information concerning a specific user's connect and error information.
Errors – Notify	<ul style="list-style-type: none"> Used by the Push Manager.
Admin - Configuration	<ul style="list-style-type: none"> There are no embedded hyperlinks for this report.

Table 10.5 ~ Detail – Inventory Reporting

Action	Embedded Links
Applications	<p>Managed Applications</p> <ul style="list-style-type: none"> Click on a subscriber to see a detailed report of all of the applications for that particular subscriber. Click on a service to see a summary report of Application Events. <p>Audited Applications</p> <ul style="list-style-type: none"> No embedded links.
WBEM Audited Applications	<ul style="list-style-type: none"> No embedded links.
Audited Files	<ul style="list-style-type: none"> No embedded links.
Configuration	<ul style="list-style-type: none"> No embedded links.
WBEM Audited Files	<ul style="list-style-type: none"> No embedded links.

Table 10.6 ~ Detail – General Reporting

Action	Embedded links
Show - Config	<ul style="list-style-type: none"> No embedded links.
Status - Application Events	<ul style="list-style-type: none"> Click on Subscriber to display the detailed history of this particular application. Click on a service to display the summarized report for a particular application event. Click on either Install or Uninstall in the Event column to filter. Click on either Successful or Unsuccessful to filter in the Status column.
Status - Connect	<ul style="list-style-type: none"> No embedded links.
Status - Services	<ul style="list-style-type: none"> EDM service status.
Status - Notify	<ul style="list-style-type: none"> Notify Status for use with Push Manager.
Status - Summary	<ul style="list-style-type: none"> No embedded links.
Status - Detailed	<ul style="list-style-type: none"> No embedded links.

Viewing Audited Files Using the Radia Integration Server

In this section, the Audit Multi Files example illustrated in *Configuring a Sample Audit* on page 179 is used to examine how the collected information is presented within some of the Radia Integration Server reports.

Summary Reporting Examples

To view a sample Summary report

1. In Services, ensure that the Radia Integration Server is started.
2. Start your Web browser and type the address and port number of the Radia Integration Server into the address field: **http://IP Address or hostname>:<Port>**.

The home page of the Radia Integration Server is displayed.




Figure 10.19 ~ Radia Integration Server home page.

3. Click the **REPORTING** tab.

The **Summary** page opens.




Figure 10.20 ~ Show Applications.

4. On the **Action** drop-down menu, select **Show Applications**.
Here you can see the Radia Clients that have selected to download Audit Multi Files.
5. In the **Application Name** column, click on **Audit Multi Files**.
The **Status - Application Events** page opens.




Figure 10.21 ~ Application Events for Audit Multi Files.

Here you can see the Radia Clients that have selected the Audit Multi Files.
To see more detailed reporting for specific users, see the next section, *Detail Reporting Example* on page 213.

Detail Reporting Example

To view a sample Detail report

1. In Services, ensure that the Radia Integration Server is started.
2. Navigate to the Radia Integration Server's home page.




Figure 10.22 ~ Radia Integration Server home page.

3. Click the **REPORTING** tab.
The **Subscriber Detail** page opens.



Figure 10.23 ~ Detail Reporting.

4. Click on the **Detail** link.
5. From the **REPORTING** options (Inventory, General, and History), select what type of reporting you would like to view. For our example, select **Inventory Reporting**.
6. From the **Action** drop-down menu, select the **Action**. For our example, select **Audited Files**.

7. From the **Subscriber** drop-down menu, select **CTANZILLO**.

You are presented with all of the audited **.exe** files for the user **CTANZILLO**.

The screenshot shows the 'Subscriber Detail' page for 'CTANZILLO'. The page title is 'Subscriber Detail - 3 subscribers in database'. The 'Reporting' section has radio buttons for 'Inventory' (selected), 'General', and 'History'. The 'Action' dropdown is set to 'Audited Files'. The 'Subscriber' dropdown is set to 'CTANZILLO'. Below this is a 'Status - Audited Files' section with a table of audited files for 'CTANZILLO, running Windows_NT Version 5.0 [Build 2195]'. The table has columns: Name, Version, Status, Vendor, Product, Product Version, Scanned, File Date, File Size, Modified, and File Type. One file is listed: 'logagent.exe' with version '4.1.00.3917', status 'EXISTS', vendor 'Microsoft Corporation', product 'Microsoft Windows Media Services', product version '4.1.00.3917', scanned path '~/program files/~/EXE', file date '1999-12-07 07:00:00', file size '64 KB', modified date '2002-02-07 14:48:51', and file type 'FILE'. A 'Back to top' link is at the bottom left.

Name	Version	Status	Vendor	Product	Product Version	Scanned	File Date	File Size	Modified	File Type
logagent.exe	4.1.00.3917	EXISTS	Microsoft Corporation	Microsoft Windows Media Services	4.1.00.3917	~/program files/~/EXE	1999-12-07 07:00:00	64 KB	2002-02-07 14:48:51	FILE

Figure 10.24 ~ Audited files for a subscriber

You can continue to view the audited information in various formats by using the drop-down menus to specify the reporting configuration.

Summary

- If installed, the information obtained by auditing client computers is stored in the Radia Integration Server.
- The **Summary** link in the Radia Integration Server will show information about *all* Radia Clients.
- The **Detail** link in the Radia Integration Server will show in-depth information about a *single* subscriber.
- When viewing reports within the Radia Integration Server, you are able to navigate through the information collected by clicking on hyperlinks embedded within any table.



Radia Inventory Manager Detail and Summary Reporting Tables

Table A.1 ~ Inventory Reporting – Detailed Reports			
Action	Displayed Table Title	Columns Queried /Display Name	Tables Queried
Applications	Managed Applications	device_id/Subscriber	AppEvent
		service_id/Service	
		ctime/Created	
		mtime/Modified	
		app_name/Application Name	
		event/Event	
		del_time/Date Deleted	
		ver_time/Date Verified	
		inst_time/Date Installed	
		fix_time/Date Fixed	
Audited Applications	Cim-show-apps.tsp		
Installed Applications	Installed-apps.tsp		
Add/Remove Applications	Installed-uninstalled-apps.tsp		
WBEM Applications	Installed Products	wName/Tag	rCIM_Product
		wVendor/Vendor	
		wVersion/Version	
		wIdentifyingNumber/Software Spec	
	Installed Filesets /	wCaption/Caption	rCIM_SoftwareFeatureElements
		wPartComponent/Fileset	
		Packages	
	Audited Applications	wName/Tab	rCIM_SoftwareElement
		wVersion/Version	
		wSoftwareElementID/SoftwareSpec	
wTargetOperatingSystem/TargetOS			
wManufacturer/Vendor			
wCaption/Caption			
wInstallDate/Install Date			
wCaption/Application Name	rNVD_Product		
mtime/Modified			
CIM_Product.wDescription/type			
wName/Name			
wVendor/Vendor			
wVersion/Version			
wInstallState/Installed			
wInstallDate/Date Installed			
Audited Files	Audited Files	name/Name version/Version	FileAudit

Table A.1 ~ Inventory Reporting – Detailed Reports

Action	Displayed Table Title	Columns Queried /Display Name	Tables Queried
		status/Status vendor/Vendor product/Product prodvers/Product Version scanfor/Scanned file_date/File Date file_size/File Size mtime/Modified file_type/File Type path/Path	
Configuration Summary for Windows	O/S Configuration	mtime/Modified	rWin32_OperatingSystem
		_wOS/OS wRegisteredUser/Registered User wOrganization/Organization wSerialNumber/S/N wSystemDirectory/Sys Dir WtotalPageFileSpace/PageFileSize (mb)	
	Hardware	manufacturr/Manufacturer	rWin32_ComputerSystemProduct
		_model/Model _wSNTag/S/N wManufacturer,wCurrentClockSpeed/Processor wTotalPhysicalMemory/Physical Memory (MB) wSystemType/System _wBios / Bios _wKybd/keyboard _wMouse/Mouse _wVideo/Video/Video _wDriverName/Printer _WSerialPort/Serial Ports _wParallelPort/Parallel Ports	RWin32_systemEnclosure RWin32_Processor RWin32_LogicalMemoryConf rWin32_Computer System rWin32_Bios
	Network Adapter information	Wbem-show-network.tsp	
	Disk Drive Information	Wbem-show-drives.tsp	
	Environment	Wbem-show-environment.tsp	
	Windows Services	Wbem-show-services.tsp	
	Device Configuration	Ctime/Created	Device Config

Table A.1 ~ Inventory Reporting – Detailed Reports

Action	Displayed Table Title	Columns Queried / Display Name	Tables Queried
		Mtime/modified Os/OS Os_level/ OS Level Sysdrv/Sys Drive Sysdrv_total/ Sys Drive Size (MB) Sysdrv_free/Sys Drive Free (MB)	
	Software (CLIENT and	Person/Person Organization/Organization Language/Language Protocol/Protocol Timeout/Timeout Trace/Trace Edmsys/Sys Dir Edmlib/Lib Dir Edmlog/Log Dir	Device Config
	Hardware	Ipaddr/ IP Address Macaddr/ MAC Adress Bios/ Bios Cpu/CPU Memory/Mem (MB) Keyboard/Keyboard Mouse/Mouse Video/Video N_serial/Serial(#) N_Parallel/Parallel (#) N_PRINTER/printer (#)	Device Config
WBEM Features	Audited Features	wProductName/Product Name mtime/Modified WInstallDate/Date Installed wVendor/Vendor wVersion/Version	RWind32_SoftwareFeature
Installed Applications	Audited Files	Show-fileaudit.tsp	
	Installed Applications	WFileDescription / Application Name Mtime / Modified WPath / Path WoriginalFileName / Executable WFileVersion / Executable Version	RNVD_Installed_Apps

Table A.1 ~ Inventory Reporting – Detailed Reports

Action	Displayed Table Title	Columns Queried / Display Name	Tables Queried
	Add/Remove Applications	WcompanyName ? Vendor WproductName / Product Name WproducttVersion / Version Installed-uninstall-apps.tsp	
WBEM Elements	Audited Elements	mtime/Modified wName/Name wVersion/Version wInstallDate/Date Installed wManufacturer/Manufacturer wPath/Path	rWin32_SoftwareElement
PDA Devices	PDA Devices	mtime/Modified wName/Name wDescription/Type wStatus/Status	rNVD_PDASystem
WBEM PDA Config	Configuration	Mtime/Modified wCaption, wVersion / OS wFreePhysicalMemory/Free Physical Memory (MB) wTotalVirtualMemorySize/Total Virtual Memory (MB) wFreeVirtualMemorySize/Free Virtual Memory (MB)	rCIM_OperatingSystem
	PDA Installed Products	Show-pda-inst-prod.tsp	RCIM_OperatingSystem
wbem-show-environment.tsp	Environment	mtime / Modified wUserName / Account WsystemVariable / System Variable wName / Name wAttributeValue / Value	rWin32_Environment
wbem-show-services.tsp	Window Services	mtime / Modified wDisplayName / Services wState / Status wStartMode / Startup wName / Name wStartName / Logon wDesktopInteract / Interact with Desktop wPathName / Path	rWin32_Services
Wbem-show-	Network Adapter	Mtime / Modified	RWin32_NetworkAdapterConf

Table A.1 ~ Inventory Reporting – Detailed Reports

Action	Displayed Table Title	Columns Queried / Display Name	Tables Queried
network.tsp	Information	Wdescription / Type WIPAddress / IP Address WMACAddress / MAC Address	
Wbem-show-drives.tsp	Disk Drive Information	Mtime / Modified WDeviceID / Drive Letter WDescription/Type WfileSystem / File System WSize / Size (MB) WFreeSpace / Free Space (MB) WProviderName / Provider Name WvolumeSerialNumber / Serial Number	RWin32_LogicalDisk
Installed-uninstall-apps.tsp	Add/Remove Applications	WDisplayName / Application Name Mtime / Modified WUninstallString / Uninstall String	RNVD_Installed_Uninstall
Show-pda-inst-prod.tsp	PDA Installed Products	Mtime / Modified Wdescription/ Type WStatus / Status WVersion / Version	Rnvd_Product

Table A.2 ~ General Reporting – Detailed Reports

Action	Displayed Table Title	Columns Queried/Display Name	Tables Queried
Show-Config	Device Configuration	ctime/Created mtime/Modified os/OS os_level/OS Level sysdrv/Sys Drive sysdrv_total/Sys Drive Size (MB) sysdrv_free/Sys Drive Free (MB)	DeviceConfig
	Software	person/Person organization/Organization language/Language protocol/Protocol timeout/Timeout trace/Trace edmsys/Sys Dir edmlib/Lib Dir edmlog/Log Dir	
	Hardware	ipaddr/IP Address macaddr/MAC Address bios/Bios cpu/CPU memory/Mem (MB) keyboard/Keyboard mouse/Mouse video/Video n_serial/Serial (#) n_parallel/Parallel (#) n_printer/Printer (#)	
Status - Application Events	Application Events	device_id/Subscriber service_id/Services ctime/Created mtime/Modified app_name/Application Name event/Event status/Status del_time/Date Deleted ver_time/Date Verified inst_time/Date Installed fix_time/Date Fixed	AppEvent

Table A.2 ~ General Reporting – Detailed Reports

Action	Displayed Table Title	Columns Queried/Display Name	Tables Queried
Status - Connect	Connect Status	mtime/Modified duration/Duration mrc/Return Code reason/Reason svc_count/Services (#) rsrc_count/Files (#) rsrc_transfer/Files Tx (#) rsrc_transfer_size/Files Tx (Sz) ctime/Created	DeviceStatus
	Errors	mtime/Modified type/Type code/Code reason/Reason module/Module object/Object component/Component	DeviceErrors
Status - Services	Service State	mtime/Modified serviceid/Service svc_actv/Svc Actv rsrc_active/Files Active (#) rsrc_inactive/Files Inactive (#) ver_error/Vers Err reason/Reason	DeviceServices
Status - Notify	Notification Status	device_id/Subscriber nfy_status/Status mtime/Modified nfy_reason/Reason nfy_cmd/Command ctime/Created nfy_type/CommsType nfy_attempts/Attempts (#) nfy_userid/User Id nfy_addr/Address nfy_port/Port nfy_maxretry/Max (#) nfy_delay/Delay (s) nfy_timeout/Timeout (s) nfy_retry2/Retry2 (#) nfy_retry2/Retry2 (#)	DeviceNotify

Table A.2 ~ General Reporting – Detailed Reports

Action	Displayed Table Title	Columns Queried/Display Name	Tables Queried
		nfy_timeout2/Timeout2 (s)	
Status - Summary	Connect Status	mtime/Modified mrc/Return Code duration/Duration svc_count/Services (#) rsrc_count/Files (#) reason/Reason	DeviceState
	Client State	mtime/Modified state/State svc_count/Services (#) rsrc_count/Files (#) rsrc_error/File Err ver_error/Vers Err reason/Reason	
	Service State	Status-services.tsp	
Status - Detailed	Connect Status	<i>same as</i> Status Connect <i>entries</i>	
	Client State	Mtime / Modified State / State Svc_count / Services (#) Rsrc_count / Files (#) Rsrc_error / File Err Ver_error / Vers Err Reason / Reason	
	Service State	Status-services.tsp	
	Errors	<i>same as</i> Status Connect <i>entries</i>	

Table A.3 ~ History Reporting – Detailed Reports

Action	Displayed Table Title	Columns Queried/Display Name	Tables Queried
Application Events	Application Event History	device_id/Subscriber service_id/Service mtime/Modified app_name/Application Name event/Event status/Status del_time/Date Deleted ver_time/Date Verified inst_time/Date Installed fix_time/Date Fixed nvd_domain/Domain nvd_class/Class	HAppEvent
Connect	Connect History	mtime/Modified duration/Duration mrc/Return Code reason/Reason svc_count/Services (#) rsrc_count/Files (#) rsrc_transfer/Files Tx (#) rsrc_transfer_size/Files Tx (Sz)	HDeviceStatus
Errors	Error History	mtime/Modified type/Type code/Code reason/Reason module/Module object/Object	HDeviceErrors
State	State History	mtime/Modified state/State svc_count/Services (#) ver_error/Vers Error rsrc_count/Files (#) rsrc_error/File Err rsrc_active/Files Active (#) rsrc_active_size/Files Active (Sz) rsrc_inactive/Files Inactive (#) rsrc_inactive_size/Files Inactive (Sz) reason/Reason	HDeviceState

Table A.4 ~ Summary Reporting

Action	Displayed Table Title	Columns Queried/Display Name	Tables Queried
Show - Subscribers	Application Subscribers	device_id/subscriber	DeviceStatus
		mtime/Modified llength [*]/InstalledApps (#)	AppEvent
Show - Applications	Applications	app_name or service_id / Application Name	AppEvent
		count (device_id)/Subscribers	DeviceServices
Show - System Drivespace	Subscribers System Drive Space	device_id/Subscriber	DeviceConfig
		sysdrv/Sys Drive	
		sysdrv_total/Sys Drive Size (MB)	
		sysdrv_free/Sys Drive Free (MB)	
		(sysdrv_free*100)/sysdrv_total / Percent Free	
Show - IP Addresses	Subscribers IP Addresses	device_id/Subscriber	DeviceConfig
		ipaddr/IP Address	
		macaddr/MAC Address	
WBEM Configuration	Configuration	userid/Subscriber	rWin32_Bios
		mtime/Modified	rWin32_OperatingSystem
		wCaption, wBuildNumber, wCSDVersion/OS	rWin32_LogicalDisk
		wSystemDirectory/System Drive	rWin32_ComputerSystem
		wSize/System Drive Size (MB)	rWin32_Processor
		wFreeSpace/System Drive Free (MB)	rWin32_LogicalMemoryConf
		wSystemType/System	
		wManufacturer,	
		wCurrentClockSpeed/Processor	
		wTotalPhysicalMemory/Physical Memory (MB)	
wVersion/Bios			
Status - Application Events	Application Events	device_id/Subscriber	AppEvent
		service_id/Service	
		ctime/Created	
		mtime/Modified	
		app_name/Application Name	
		event/Event	
		status/Status	
		del_time/Date Deleted	

Table A.4 ~ Summary Reporting

Action	Displayed Table Title	Columns Queried/Display Name	Tables Queried
		ver_time/Date Verified inst_time/Date Installed fix_time/Date Fixed	
Status - Connect	Connections	mtime/Modified device_id/Subscriber duration/Duration mrc/Return Code reason/Reason rsrc_transfer/File Tx (#) rsrc_transfer_size/Files Tx (Sz)	DeviceStatus
Status - Notify	Notify Queue	mtime/Modified device_id/Subscriber nfy_status/Status nfy_reason/Reason nfy_type/CommsType nfy_attempts/Attempts (#)	DeviceNotify
Errors - Connect	Connect Errors	mtime/Modified device_id/Subscriber type/Type code/Code reason/Reason	DeviceErrors
Errors - Notify	Notify Errors	mtime/Modified device_id/Subscriber nfy_attempts/Attempts (#) nfy_status/Status nfy_reason/Reason nfy_type/Comms Type	DeviceNotify

Table A.5 ~ Inventory Reporting – Multicast Detail Reporting

Action	Displayed Table Title	Columns Queried /Display Name	Tables Queried
Status – Multicast Server Statistics	Multicast Server Statistics	mtime userid wDuration/Transmit Duration wNamespace wNbytesRej wNbytesReq wNbytesXmt/Bytes Transmitted wNclients/Clients Connected wNdevices wNfilesRej/Files Rejected wNfilesReq/Files Requested wNfilesXmt/Files Transmitted wServiceID/Service wSourceID/Multicast Session wSourceType wStartTime/Transmit Start	rNVD_MulticastStatistics
Status – Client Download Statistics	Client Download Statistics	mtime userid/Subscriber wDuration/Transmit Duration (sec) wNamespace wNbytesRcv/Bytes Received wNbytesRej wNbytesReq wNfilesRej/FilesRejected wNfilesRcv/Files Received wNfilesReq/Files Requested wNpktsDrp wNpktsRcv wServiceID/Service wSourceID wSourceType/Source Type wStartTime/Transmit Start	RNVD_DownloadStatistics

Figures

Figure 1.1 ~ Radia Reporting Environment.	19
Figure 1.2 ~ Radia Reporting Server Web interface.	20
Figure 2.1 ~ Radia Client installation process.	32
Figure 2.2 ~ Sample args.xml.	38
Figure 2.3 ~ Sample logon script.	45
Figure 2.4 ~ Destination Folder window.	48
Figure 2.5 ~ Set User window.	49
Figure 2.6 ~ Radia Configuration Server.	50
Figure 2.7 ~ Select Features window.	51
Figure 2.8 ~ Feature set installation options.	52
Figure 2.9 ~ DotNet Settings message.	53
Figure 2.10 ~ .NET Installation window.	54
Figure 2.11 ~ Application Maintenance window.	56
Figure 2.12 ~ Application Maintenance window.	58
Figure 2.13 ~ Application Maintenance window.	60
Figure 2.14 ~ Select Features window.	61
Figure 2.15 ~ Sample pre-install script.	63
Figure 2.16 ~ Sample REXX code from a post-install script.	65
Figure 3.1 ~ Destination Folder window.	70
Figure 3.2 ~ Radia Configuration Server window.	71
Figure 3.3 ~ Select Features window.	72
Figure 3.4 ~ Feature set installation options.	73
Figure 3.5 ~ Application Maintenance window.	76
Figure 3.6 ~ Application Maintenance window.	78
Figure 3.7 ~ Application Maintenance window.	80

Figure 3.8 ~ Select Features window..... 81

Figure 4.1 ~ The location of the setup.exe modules for the Radia Inventory Manager..... 87

Figure 4.2 ~ Double-click setup.exe to begin the Radia Inventory Manager installation..... 87

Figure 4.3 ~ Select the folder to which you want to install the Radia Inventory Manager..... 88

Figure 4.4 ~ Indicate where the license file is located. 89

Figure 4.5 ~ Installation Settings window..... 90

Figure 4.6 ~ Installation is in progress window. 91

Figure 4.7 ~ Locate the edmprof.dat file in the bin file..... 92

Figure 4.8 ~ [MGR_RIM] section of the edmprof.dat file..... 93

Figure 4.9 ~ You can enter either the IP address or the host name. 93

Figure 4.10 ~ Starting the Radia Integration Server in Services..... 94

Figure 4.11 ~ Enter the IP address and port number in your Web browser. 95

Figure 4.12 ~ The home page of the Radia Management Portal..... 95

Figure 4.13 ~ Radia Inventory Manager Setup/Configuration..... 96

Figure 4.14 ~ Alert message indicates a successful installation. 97

Figure 4.15 ~ Starting the Radia Integration Server in Services..... 97

Figure 4.16 ~ Enter the IP address and port number in your Web browser. 98

Figure 4.17 ~ Radia Integration Server home page. 98

Figure 4.18 ~ Radia Inventory Manager Setup/Configuration page..... 98

Figure 4.19 ~ Alert message indicates a successful installation. 99

Figure 4.20 ~ Sample rim.cfg file. 100

Figure 5.1 ~ Radia Database.PRIMARY.AUDIT domain. 106

Figure 5.2 ~ The AUDIT domain..... 107

Figure 5.3 ~ PRIMARY.ADMIN domain..... 110

Figure 5.4 ~ Expanded ZLIST class. 111

Figure 5.5 ~ Expanded CONNECT_ instance. 112

Figure 5.6 ~ CONNECT_ZSERVICE_TO_RULES..... 113

Figure 5.7 ~ Adding RIMOPTS as an attribute..... 113

Figure 5.8~ REGISTRY class added to the AUDIT domain..... 116

Figure 5.9 ~ Sample Inventory Database – Tables. 118

Figure 6.1 ~ FILEAUDT object. 126

Figure 6.2 ~ AUDIT.WBEM class instances..... 129

Figure 6.3 ~ SYSTEM.PROCESS.WBEMAUDT instance..... 131

Figure 6.4 ~ SYSTEM.ZMETHOD.POST_WBEM instance. 132

Figure 6.5 ~ ZCONFIG object.	133
Figure 6.6 ~ POLICY.USER Class – ZCONFIG attribute.	133
Figure 6.7 ~ ZCONFIG object.	134
Figure 7.1 ~ Sample Auditing services.	140
Figure 7.2 ~ SCANFOR attribute of the Audit Multi Files instance.	143
Figure 7.3 ~ AUDIT.ZSERVICE.	144
Figure 7.4 ~ Expanded POLICY.WORKGRP class.	145
Figure 7.5 ~ Select Connection Attribute dialog box.	146
Figure 7.6 ~ Audit Multi Files package has been added to the WORKGRP class.	147
Figure 7.7 ~ Audit Multi Files in the Radia Software Manager.	148
Figure 7.8 ~ AUDIT_MULTI_FILES in the LIB directory.	149
Figure 7.9 ~ The RIMFSCAN and the RIMDIFF methods on the client computer perform the actual file auditing operations by specifying what files to look for.	150
Figure 8.1 ~ Audit Package (PACKAGE) class.	154
Figure 8.2 ~ Individual File Audit instance.	155
Figure 8.3 ~ Connection to an Audit Behavior.	156
Figure 8.4 ~ AUDIT. Audit Packages (PACKAGE) class.	158
Figure 8.5 ~ New Instance option.	159
Figure 8.6 ~ Create Instance dialog box.	159
Figure 8.7 ~ Log Finder AUDIT.PACKAGE.	160
Figure 8.8 ~ Add Components option.	161
Figure 8.9 ~ The Add Components dialog box.	162
Figure 8.10 ~ Add Components – Available Components list.	162
Figure 8.11 ~ Add Components dialog box.	163
Figure 8.12 ~ Editing Log Finder Instance dialog box.	163
Figure 8.13 ~ Create a New Instance.	164
Figure 8.14 ~ Create Instance dialog box.	165
Figure 8.15 ~ Log Finder ZSERVICE.	166
Figure 8.16 ~ Log Finder package connected to Log Finder service.	167
Figure 8.17 ~ Log Finder ZSERVICE attributes.	168
Figure 8.18 ~ Log Finder as it appears in the Radia Software Manager.	169
Figure 9.1 ~ AUDIT Scheduling (TIMER) class.	173
Figure 9.2 ~ Timer shortcut menu.	177
Figure 9.3 ~ Create Instance dialog box.	178
Figure 9.4 ~ Log Audit Timer instance.	179

Figure 9.5 ~ Log Audit Timer instance connected to the Log Finder service.	183
Figure 9.6 ~ Log Finder attached to a user.	183
Figure 9.7 ~ PRIMARY.AUDIT.Inventory Options (RIMOPTS) class.	185
Figure 9.8 ~ New Inventory Options instance: NVDM Audit No Execute.	185
Figure 9.9 ~ Attributes of the NVDM Audit No Execute instance.	186
Figure 9.10 ~ Clear the RUNEXEC attribute.	186
Figure 9.11 ~ RIM Reporting: Edit Instance.	187
Figure 9.12 ~ RIM Reporting: Editing the ALWAYS connection.	188
Figure 9.13 ~ RIM Reporting: Editing the ZSVCMO instance.	188
Figure 9.14 ~ NVDM Audit No Execute added to the RIM Reporting instance.	189
Figure 9.15 ~ RADIA1.HTM.	190
Figure 9.16 ~ Adding the EXECONUPDT=0 to the RADIA1.HTM.	191
Figure 10.1 ~ Starting the Radia Integration Server in Services.	194
Figure 10.2 ~ Sample IP address and port number of the RIS entered in a Web browser.	194
Figure 10.3 ~ The home page of the Radia Management Portal.	195
Figure 10.4 ~ Starting the Radia Integration Server in Services.	196
Figure 10.5 ~ Sample IP address and port number of the RIS entered in a Web browser.	196
Figure 10.6 ~ Radia Integration Server home page.	197
Figure 10.7 ~ Accessing the REPORTING tab.	198
Figure 10.8 ~ Reporting tab – Summary.	199
Figure 10.9 ~ Summary tab – Action drop-down menu.	199
Figure 10.10 ~ Reporting tab – Detail Report.	201
Figure 10.11 ~ Details – Subscriber drop-down menu.	203
Figure 10.12 ~ The home page of the Radia Management Portal.	204
Figure 10.13 ~ The Radia Inventory Server homepage viewed from within the Radia Management Portal.	204
Figure 10.14 ~ Summary Reporting – Applications Table.	205
Figure 10.15 ~ Sort in reverse alphabetical order by Application Name.	206
Figure 10.16 ~ Sample Sort by Subscribers (ascending number of subscribers shown).	207
Figure 10.17 ~ Click on the Amortize application.	207
Figure 10.18 ~ Application Events for CTANZILLO.	208
Figure 10.19 ~ Radia Integration Server home page.	211
Figure 10.20 ~ Show Applications.	212
Figure 10.21 ~ Application Events for Audit Multi Files.	212
Figure 10.22 ~ Radia Integration Server home page.	213

Figure 10.23 ~ Detail Reporting213
Figure 10.24 ~ Audited files for a subscriber.....214

Tables

Table P.1 ~ Styles.....	9
Table P.2 ~ Usage.....	9
Table P.3 ~ Terminology*	10
Table 2.1 ~ Sample INSTALL.INI	33
Table 2.2 ~ [PROPERTIES] Section of INSTALL.INI	34
Table 2.3 ~ [ARGS] Section of INSTALL.INI	38
Table 2.4 ~ [OBJECTS] Section of INSTALL.INI	42
Table 2.5 ~ Radia Client Feature State Arguments.....	43
Table 2.6 ~ Command Line Arguments	44
Table 2.7 ~ Feature Settings for Radia Clients	52
Table 2.8 ~ Radia Client Feature State Arguments.....	62
Table 3.1 ~ Feature Settings for the Radia Administrator Workstation	73
Table 3.2 ~ Radia Administrator Workstation Feature State Arguments	74
Table 3.3 ~ Command Line Arguments	75
Table 4.1 ~ Radia Inventory Manager Setup/Configuration	96
Table 4.2 ~ rim.cfg Parameters	100
Table 5.1 ~ AUDIT Domain	108
Table 5.2 ~ RIMOPTS Class	109
Table 5.3~ Registry Class Instance Attributes.....	114
Table 5.4 ~ Available Import Deck for Adding Registry Class	117
Table 6.1 ~ AUDIT.FILE Class Instances	123
Table 6.2 ~ FILEAUDT Object	127
Table 6.3 ~ AUDIT.WBEM Instance.....	130
Table 6.4 ~ WBEM Object Attributes in the Client.....	131
Table 6.5 ~ ZCONFIG Object.....	135
Table 7.1 ~ Sample of Auditing Services.....	141
Table 8.1 ~ Inventory Options (RIMOPTS) Class	155
Table 9.1 ~ Scheduling (TIMER) Class	173
Table 9.2 ~ Syntax of ZSCHDEF Attributes.....	181
Table 10.1 ~ Radia Integration Server – Tabs and Links.....	197
Table 10.2 ~ Reporting Tab – Actions Drop-down Selections	199
Table 10.3 ~ Reporting Tab – Detail Reporting – Type.....	201
Table 10.4 ~ Summary Links – All Actions	209

Table 10.5 ~ Detail – Inventory Reporting210
Table 10.6 ~ Detail – General Reporting210
Table A.1 ~ Inventory Reporting – Detailed Reports218
Table A.2 ~ General Reporting – Detailed Reports223
Table A.3 ~ History Reporting – Detailed Reports226
Table A.4 ~ Summary Reporting227
Table A.5 ~ Inventory Reporting – Multicast Detail Reporting.....229

Procedures

To install Radia Clients using the Installation Wizard	47
To remove Radia Clients using the Installation Wizard.....	55
To remove Radia Clients using a command line	57
To repair Radia Clients using the Installation Wizard.....	58
To repair Radia Clients using a command line	59
To modify the installation of Radia Clients using the Installation Wizard.....	59
To modify the installation of Radia Clients using a command line	62
To override property settings or attributes for objects	64
To install the Radia Administrator Workstation using the Installation Wizard	69
To remove the Radia Administrator Workstation using the Installation Wizard.....	76
To remove the Radia Administrator Workstation using a command line	77
To repair the Radia Administrator Workstation using the Installation Wizard.....	78
To repair the Radia Administrator Workstation using a command line	79
To modify the Radia Administrator Workstation installation using the Installation Wizard	80
To modify the Radia Administrator Workstation installation using a command line	82
To install the Radia Inventory Manager	86
To edit the EDMPROF.DAT file.....	92
To install the sample database (through the Radia Management Portal).....	94
To install the sample database (non-Radia Management Portal installation).....	97
To enable drag-and-drop connections for RIMOPTS class instances	109
To install the Radia Database update for the AUDIT Registry class	117
To configure a sample Audit package	143
To create a new Audit package.....	157
To add a component to an Audit package	160
To create a ZSERVICE instance	164
To create a new timer in the AUDIT domain	176
To customize the RIMOPTS instance	184
To prevent Mandatory Audit Services from executing in the Radia Software Manager	189
To access the Radia Integration Server (via the Radia Management Portal)	194
To access the Radia Integration Server (non-Radia Management Portal)	195
To navigate through a Summary report for Show - Applications.....	205
To view a sample Summary report	211
To view a sample Detail report.....	213

Index

\$

\$MACHINE..... 39, 41
 \$USER..... 39, 41

.

.NET 52
 installing 52
 .NET Beta 54
 .NET cannot be located 52
 .NET Framework Setup wizard 54
 .NET Installation window 54
 .NET runtime..... 30, 36

:

::SM switch..... 40

A

access levels 4
 ACCESSDT attribute 127
 ACCESSTM attribute 127
 ACP..... *See* AIP
 ACTION attribute 123, 130, 143
 Action drop-down menu 199, 201
 Add Components dialog box..... 162
 ADDLOCAL argument..... 35, 43, 62, 74
 ADDSOURCE argument..... 74
 Admin - Configuration..... 200, 209
 Administrative Control Point *See* AIP
 Administrative Installation Point *See* AIP
 ADVERTISE argument..... 74
 AIP30, 68
 ALWAYS attribute 174

Application class..... 108
 Application Events 208
 Application Maintenance window
 modifying
 Radia Administrator Workstation 80
 Radia Client 60
 removing
 Radia Administrator Workstation 76
 Radia Client 56
 repairing
 Radia Administrator Workstation 78
 Radia Client 58
 APPSVC attribute..... 175
 ARGS section of INSTALL.INI..... 38
 args.xml 31, 38, 40
 sample..... 38
 ARPNOREMOVE argument 35
 askconfirm argument..... 38
 ATTRIBUTE attribute 127
 AUDIT domain 106, 107
 AUDIT file class instances..... 123
 Audit Multi Files 141
 Audit Multi Files package 145
 Audit Packages class..... 108
 AUDIT.FILE class
 ACTION..... 123
 GROUP 123
 INTERNAL..... 124
 LANGUAGE..... 124
 LOCATION..... 125
 NAME 125
 ORGNAME..... 124
 OUTPUT..... 123

PRODUCT.....	124	Unix File Scan Audit.....	141
PRODVERS.....	124	Unix Hardware Inventory.....	142
SCANFOR.....	123	Unix Software Inventory Audit.....	142
TYPE.....	123	WBEM MSI Based Applications.....	142
VENDOR.....	125	WBEM Running Services.....	142
VERSION.....	124	WBEM Scan For Hardware.....	142
ZCRCINFO.....	125	WBEM Scan with Condition Statement.....	142
ZINIT.....	125	WBEM Stopped Services.....	142
ZRSCCRC.....	125	WBEM System Drivers.....	142
ZRSCMFIL.....	124	WBEM Windows Services.....	142
ZRSCMMEM.....	124	Windows System DLL.....	142
ZRSCOBJN.....	125	Auto Create.....	98
ZRSCPADM.....	125	Auto-Create Demo Database.....	96
ZRSCSRC.....	125	B	
ZRSCSTYP.....	124	BEHAVIOR class.....	108
ZRSCVLOC.....	124	Behavior Services class.....	108
ZVERINFO.....	124	BUILD parameter.....	100
AUDIT.FILE class instance.....	122	C	
AUDIT.FILE instance.....	124	cacert.pem.....	40
AUDIT.PACKAGE class.....	160	CE PDA XML Inventory.....	141
AUDIT.PACKAGE instance.....	108	channelname argument.....	38
AUDIT.WBEM class.....	128	CIM.....	<i>See</i> Common Information Model
AUDIT.WBEM instance.....	130	CLASS attribute.....	130
ACTION.....	130	clean computer, definition.....	68
CLASS.....	130	clean machine, definition.....	21
CNDITION.....	130	client computer, definition.....	21
NAME.....	130	Client Methods class.....	108
NAMESPACE.....	130	Clistats.....	<i>See</i> Status - Client Download Statistics
OUTPUT.....	130	CMETHOD class.....	108
PROPERTY.....	130	CNDITION attribute.....	130
TYPE.....	130	COLLECT attribute.....	109
AUDIT.ZSERVICE class.....	165	command line	
AUDIT.ZSERVICE instance.....	108	installing	
auditing files.....	122	Radia Administrator Workstation.....	74
Auditing Services		Radia Client.....	43
Audit Multi Files.....	141	modifying	
CE PDA XML Inventory.....	141	Radia Administrator Workstation installation.....	82
default.....	141	Radia Client installation.....	62
Delete Discovered Application Component.....	141	removing	
Individual File Audit.....	141	Radia Administrator Workstation.....	77
NVDM Discovery of Applications.....	141		
Palm PDA XML Inventory.....	141		
RIM Reporting.....	141		

- Radia Client..... 57
- repairing
 - Radia Administrator Workstation 79
 - Radia Client..... 59
- silent installation 46
- command line arguments
 - Radia Administrator Workstation installation ... 75
 - Radia Client installation..... 44
- COMMIT_INTERNAL parameter 100
- Common Information Model 24
 - definition 21
- CONNECT instance 111
- connect.bak 39
- Create Instance dialog box 159, 165, 178
- CREATE method 175
- CUSTOM..... 39, 41
- customer support 4

D

- Data Source Name, changing..... 102
- DATE attribute 127
- DB_AUTOCREATE parameter 101
- db_import directory 117
- DEFERRED 174
- Delete Discovered Application Component 141
- DELETE method 175
- Desktop class 108
- DESKTOP class 108
- Destination Folder window 48, 70
- detail information 201
- Detail link 198, 201, 213
- Detail Reporting types
 - General Reporting 202
 - History Reporting 202
 - Inventory Reporting 201
- detail reporting, subscriber 202
- Differenced Audit on Install and Update 155
- Differenced Audit on Install, Verify, and Update.. 155
- DIRPATH attribute 127
- DISCOVER attribute 42
- Disk Cost 52, 72
- Distributed Management Task Force..... 24
- DL_DATEFMT parameter 101

- DOMAIN attribute 175
- DotNet Settings message..... 53
- DRIVE attribute..... 127
- DSN *See* Data Source Name
- DSN parameter 101
- DSN_ATTEMPTS parameter 101
- DSN_DATEFMT parameter..... 101
- DSN_DELAY parameter..... 101
- DSN_PASSWD parameter..... 101
- DSN_PING parameter 101
- DSN_USER parameter 101

E

- EDMPROF.DAT file, editing 92
- Enterprise Management button 189
- enterprisemanagement argument..... 39
- Errors - Connect 200, 209
- Errors - Notify 200, 209
- EXECUTE.REXX 182, 191

F

- feature set installation options
 - Radia Administrator Workstation 73
 - Radia Client 52
- feature settings
 - Radia Administrator Workstation 73
 - Radia Client installation 52
- feature state arguments
 - Radia Administrator Workstation 74
 - Radia Client 43, 62
- file auditing 122
- File class 108
- FILE class 108
- File Scanner class..... 108
- File Scanner Filters class 108
- FILEAUDT object 125, 126, 127, 149, 151
 - ACCESSDT 127
 - ACCESSTM..... 127
 - ATTRIBUTE 127
 - DATE 127
 - DIRPATH 127
 - DRIVE 127

FULLPATH	127
PAHTCRC	127
RESOLVE	127
SIZE	127
STATUS	127
TIME	127
XTENSION	127
FILENEW object	151
FILEPREV object	149
FILESCAN class	108
FILTER class	108
filtering subscribers	203
Full Audit on Install and Update	156
Full Audit on Install, Verify and Update	156
FULLPATH attribute	127
G	
GATEWAY attribute	135
General Reporting	202
Status - Notify	210
General Reporting - detail	
Show - Config	210
Status - Application Events	210
Status - Connect	210
Status - Detailed	210
Status - Service	210
Status - Summary	210
General Reporting option	201
GROUP attribute	123
H	
HALCOMP attribute	135
HALDATE attribute	135
HALFNAME attribute	135
HALFVER attribute	135
HALINAME attribute	135
HALLANG attribute	135
HALPNAME attribute	135
HALPVER attribute	135
HALSIZE attribute	135
History Reporting	202
HOME link	197
HOME parameter	101
HTTP HOST	91
HTTP object transfer	39
HTTP POST	132
HTTP_PORT	92
httpd.rc file	93
I	
identification argument	39, 49
IDMLIB directory	36, 38
starting	41
IDMLOG	39
IDMSYS directory	37
IMMEDIATE	174
Individual File Audit	141
INFO link	198
INSTALL.INI	31, 37, 45
ARGS section	38
OBJECTS section	42
preparing	32
PROPERTIES section	34, 40
installation program	
Radia Administrator Workstation	68
Radia Client	30
Installation Settings window	90
installation wizard	
installing	
Radia Administrator Workstation	69
Radia Client	47
modifying	
Radia Administrator Workstation	79
Radia Client	59
removing	
Radia Administrator Workstation	76
Radia Client	55
repairing	
Radia Administrator Workstation	78
Radia Client	58
INSTALLDIR argument	35, 48
installed .NET	52
installing	
Radia Administrator Workstation	
command line	74

Installation Wizard	69
Radia Client	
command line	43
Installation Wizard	47
logon script	45
INSTMSI.EXE	31
INSTMSIW.EXE	31
INTERNAL attribute	124
INVENTORY button	95, 195, 203
Inventory Options class	108, 109, 120
Inventory Reporting	201
Inventory Reporting - detail	
Applications	210
Audited Files	210
Configuration	210
WBEM Audited Applications	210
WBEM Audited Files	210
Inventory Scanners	108
IPADDR attribute	175
IPADDR## attribute	135
L	
LABEL parameter	101
LADAPT## attribute	135
LANGUAGE attribute	124
license.nvd	86
Limit To drop-down menu	200
LOCATION attribute	125
log argument	39
logon script	
installing the Radia Client	45
sample code	45
logonpanel argument	39
logsize argument	39
M	
MANAGER ADMIN tab	197
managerurl argument	39
MAXROWS parameter	101
MGR_RIM	91, 132
MGRNAME attribute	175
MGRVLOC class	108

MGRVLOC instance	124
Modify option	60, 80
modifying	
Radia Administrator Workstation installation	
command line	82
Installation Wizard	79
Radia Client installation	
command line	62
Installation Wizard	59
MODULE parameter	101
MS Windows Installer	30, 68
MSI 2.0 installation program	30
MSIEXEC	59, 79

N

N_WORKERS	102
N_WORKERS parameter	101
NAME attribute	109, 125, 130, 174
NAMESPACE attribute	130
NVD.INI	39
NVDARG	64
NVDARGIDENTIFICATION	64
NVDENABLEIP argument	36, 40
NVDENABLEPROXY argument	36
NVDENABLESHORTCUT argument	36
NVDENABLEUSER argument	36
NVDINSTALLCLIENTEXPLORER	74
NVDINSTALLPACKAGER	74
NVDINSTALLPATCH	44
NVDINSTALLPUBLISHER	74
NVDINSTALLRAM	35, 44
NVDINSTALLRIM	35, 44
NVDINSTALLROM	44
NVDINSTALLRSM	35, 44
NVDINSTALLSCREENPAINTER	74
NVDINSTALLSYSTEMEXPLORER	74
NVDM Discovery of Applications	141
NVDMINTDIR argument	37
NVDOBJ	64
NVDPOSTCAPATH argument	37, 64
NVDPRECAPATH argument	37, 63
NVDSHORTCUT argument	36, 49

O

object	
overriding property settings.....	64
OBJECTS section of INSTALL.INI.....	42
odbc_queue.mk). Not usually modified.....	100
ORGNAME attribute.....	124
OUTPUT attribute.....	123, 130

P

PACKAGE class.....	108
Palm PDA XML Inventory.....	141
passport registration.....	4
Path class.....	108
PATH class.....	108
PATHCRC attribute.....	127
PENDING attribute.....	182
PERIODIC.....	174
PINGCNT attribute	
specifying.....	182
PINGDLAY attribute.....	175
specifying.....	182
post-install script.....	31, 37, 64
sample.....	65
pre-install script.....	31, 37, 63
sample.....	63
PRIMARY.AUDIT.....	140
PRODUCT attribute.....	124
PRODVERS attribute.....	124
progress bar, displaying.....	75
PROPERTIES section of INSTALL.INI.....	34, 40
PROPERTY attribute.....	130
providername argument.....	39
PROXADDR attribute.....	42
PROXYINF object.....	36
Push Manager.....	197, 209, 210

Q

QUERY_VISIBLE parameter.....	101
------------------------------	-----

R

RADADMIN40.MSI.....	69, 75
Radia Administrator Workstation	

feature settings.....	73
feature state arguments.....	74
installation	
command line arguments.....	75
installation program.....	68
installing	
command line.....	74
Installation Wizard.....	69
modifying the installation	
command line.....	82
Installation Wizard.....	79
removing	
command line.....	77
Installation Wizard.....	76
repairing	
command line.....	79
Installation Wizard.....	78
system requirements.....	68
Radia Application Manager.....	18
Radia Client	
feature settings.....	52
installation command lines.....	44
installation program.....	30
installing.....	47
command line.....	43
logon script.....	45
modifying the installation	
command line.....	62
Installation Wizard.....	59
removing	
command line.....	57
Installation Wizard.....	55
repairing	
command line.....	59
Installation Wizard.....	58
system requirements.....	30
Radia Client Installation Wizard.....	47
.NET Installation window.....	54
Destination Folder window.....	48
Radia Configuration Server.....	50
Select Features window.....	51
Set User window.....	49
Radia Client Operations Profiles.....	42

Radia Client, description.....	21	removing	
Radia Configuration Server window	50	Radia Administrator Workstation	
Radia Integration Server	21, 25	command line	77
accessing	194, 195	Installation Wizard.....	76
description	18	Radia Client	
HOME Link	197	command line	57
home page	197	Installation Wizard.....	55
INFO link.....	198	Repair option	58, 79
MANAGER/ADMIN tab.....	197	repairing	
REPORTING tab	197	Radia Administrator Workstation	
SERVER ADMIN tab.....	197	command line	79
SITE tab.....	197	Installation Wizard.....	78
SUPPORT link.....	198	Radia Client	
Radia Inventory Manager		command line	59
description	18	Installation Wizard.....	58
sample database	117	Reporting	198
Radia Management Portal		REPORTING options	213
description	21	REPORTING tab.....	98, 197, 198, 211
home page	195	Admin - Configuration	200
Radia Messaging Server.....	21	detail information	201
overview	6, 18	Errors - Connect.....	200
Radia Policy Manager	197	Errors - Notify	200
Radia Policy Server	197	Show - Applications	200
Radia Reporting Server.....	19, 22	Show - IP Addresses	200
environment.....	19	Show - Subscribers.....	200
overview	19	Show - System Drivespace.....	200
Radia Software Manager.....	18	Status - Application Events.....	200
RADIA.MSI	45	Status - Client Download Statistics	200
RADIA1.HTM	190	Status - Connect.....	200
RADIA40.MSI	31, 34, 59	Status - Multicast Server Statistics	200
RADIADMIN40.MSI	79	Status - Notify	200
RADISH.EXE.....	132	Status - WBEM Events.....	200
radskman	182	summary information	199
radskman	191	WBEM - Configuration	200
REBOOT attribute	135	REQUEST attribute.....	175
REBOOTD attribute.....	135	resolutionmanager argument.....	40, 50
redirect argument.....	40	resolutionport argument.....	40, 50
redirect tag.....	40	RESOLVE attribute	127
Registry class	108	RIM Reporting.....	141
REGISTRY class.....	108	rim.cfg	99
registry.xpc.....	117	parameters	100
REMOVE argument	44, 57, 62, 74	RIM_REPORTING service	187
Remove option.....	35, 56, 76	RIMDEMO.....	96, 98

Index

RIMDIFF method.....	122, 123, 149, 151
RIMFSCAN method.....	122, 149, 150
RIMOPTS	155
customizing.....	184
Default	155
Differenced Audit on Install and Update	155
Differenced Audit on Install, Verify, and Update	155
Full Audit on Install and Update.....	156
Full Audit on Install, Verify and Update	156
RIMOPTS class	108, 109
attributes	109
RIMOPTS instance	109
RIMSFSCAN	25
RIMWBEM	25
RIMWBEM method.....	128
ROWS_PER_PAGE parameter	101
RUNEXEC attribute	109, 186
RUNSYNC attribute	175

S

sample reporting database	94, 117
SCANFOR attribute.....	123, 143
SCANNER class	108
Scheduling (TIMER) class	172, 173
ALWAYS.....	174
APPSVC.....	175
DOMAIN.....	175
IPADDR.....	175
MGRNAME	175
NAME	174
PINGDLAY.....	175
REQUEST	175
RUNSYNC.....	175
SOCKET	175
ZCREATE.....	175
ZDELETE.....	175
ZNOPING	175
ZOBJPRI	173
ZRSCMDL.....	174
ZSCHDEF.....	174
ZSCHFREQ.....	174
ZSCHMODE.....	174

ZSCHTYPE	174
ZSTOP	173
ZSVCOID	174
ZUPDATE	175
ZVERIFY.....	175
Scheduling class.....	108
script	
post-install	64
pre-install.....	63
Select Connection Attribute dialog box	146
Select Features window	
Radia Administrator Workstation.....	72, 81
Radia Client	51, 61
SERVER ADMIN tab	197
Set User window.....	39, 49
setup.exe.....	30, 68
location	45
Show - Applications	200, 209
Show - IP Addresses	200
Show - Subscribers.....	200, 209
Show - System Drivespace	200
silent installation.....	44, 75
command line.....	46
SITE tab	197
SIZE attribute.....	127
SOCKET attribute.....	175
sslmanager argument.....	40
sslport argument.....	40
startdir argument	41
STARTDIR folder.....	39
Status - Application Events	200, 209
Status - Client Download Statistics.....	200
Status - Connect.....	200, 209
Status - Multicast Server Statistics.....	200
Status - Notify.....	200, 209
Status - WBEM Events	200
STATUS attribute.....	127
STATUS_INTERVAL parameter.....	101
STATUS_RESET parameter.....	101
SUBNET## attribute.....	135
Subscriber Detail page	213
Subscriber drop-down menu	202
Subscriber Filtering text box	203

subscriber, definition	22
summary information	199
Summary link	198, 199
Summary links	
Admin - Configuration	209
Errors - Connect	209
Errors - Notify	209
Show - Applications	209
Show - Subscribers	209
Status - Application Events	209
Status - Connect	209
Status - Notify	209
WBEM Configuration	209
support	4
SUPPORT link	198
system requirements	
Radia Administrator Workstation	68
Radia Client installation	30

T

target directory	68, 75
technical support	4
TIME attribute	127
TIMER class	108, 172
TYPE attribute	123, 130

U

UIOPTION attribute	41
Unix File Scan Audit	141
Unix Hardware Inventory	142
Unix Software Inventory Audit	142
UPDATE method	175
URL parameter	101
USEPROXY attribute	42

V

VENDOR attribute	125
VERIFY method	175
VERSION attribute	124
VERSION parameter	101
Virtual Mgr Location class	108

W

WBEM - Configuration	200, 209
WBEM auditing	128
WBEM class	109
WBEM MSI Based Applications	142
WBEM namespace	25, 128
WBEM object variables	
ZOBJCID	131
ZOBJCLAS	131
ZOBJCRC	131
ZOBJDATE	131
ZOBJDOMN	131
ZOBJID	131
ZOBJNAME	131
ZOBJPCLS	131
ZOBJPID	131
ZOBJRCRC	131
ZOBJRSIZ	131
ZOBJTIME	131
ZRSCSRC	131
WBEM Running Services	142
WBEM Scan for Hardware	142
WBEM Scan with Condition Statement	142
WBEM Stopped Services	142
WBEM System Drivers	142
WBEM Windows Services	142
WBEM_AUTOCREATE parameter	102
WBEM_AUTOLOAD parameter	102
Web-Based Enterprise Management	24
WEBM	<i>See</i> Web-Based Enterprise Management
Windows Installer	30, 68
installation program	30
Windows Installer AIP, creating	75
Windows Installer log	44
creating	75
Windows Management Instrumentation	24
description	22
Windows Registry	
scanning	108
Windows System DLL	142
WMI	<i>See</i> Windows Management Instrumentation
used for registry scan	108

Index

WMI installation program	30
WMI repository.....	24
WORKER_RETRY parameter.....	102
WORKER_TIMEOUT parameter.....	102

X

XML tags	38
xmlCIM	24
XTENSION attribute	127

Z

ZCONFIG object.....	132, 135
ZCONFIG variable.....	133
ZCRCINFO attribute	125
ZCREATE attribute	175
ZDELETE attribute	175
ZDSTOCK attribute.....	42, 64
ZGATEWAY attribute.....	135
ZHDWBIOS attribute	135
ZHDWCDDR attribute	135
ZHDWCOMP attribute	135
ZHDWCPU attribute	135
ZHDWCPU attribute	135
ZHDWCTYP attribute	135
ZHDWD## attribute	135
ZHDWD##C attribute.....	135
ZHDWD##F attribute	135
ZHDWD##S attribute	135
ZHDWD##T attribute	135
ZHDWDF_A attribute.....	135
ZHDWDLST attribute	135
ZHDWFPU attribute.....	135
ZHDWIPAD attribute.....	135
ZHDWKYBD attribute.....	135
ZHDWLANA attribute.....	135
ZHDWLANG attribute.....	136
ZHDWMEM attribute.....	136
ZHDWMEMF attribute	136
ZHDWMOUS attribute.....	136
ZHDWNET# attribute	136
ZHDWNET attribute	136
ZHDWNUM attribute.....	135

ZHDWOS attribute.....	136
ZHDWOSCL attribute.....	136
ZHDWOSDB attribute	136
ZHDWOSOG attribute	136
ZHDWOSOW attribute	136
ZHDWOSSR attribute.....	136
ZHDWPA## attribute.....	136
ZHDWPPAR attribute.....	136
ZHDWPPRN attribute.....	136
ZHDWPSER attribute.....	136
ZHDWVIDEO attribute	136
ZHDWVMSI attribute	136
ZHDWVRES attribute.....	136
ZHDWXPAG attribute.....	136
ZHWCPU01 attribute.....	136
ZHWFPU01 attribute.....	136
ZINIT attribute.....	125
ZIPADDR attribute.....	42
ZLIST class.....	110
ZMASTER object.....	45
ZMASTER.EDM	45
ZMODEM attribute	136
ZNOPING attribute.....	175
specifying	182
ZNTFPORT attribute	42
ZNTFYSEC attribute	42
ZOBJCID attribute.....	131
ZOBJCLAS attribute.....	131
ZOBJCRC attribute	131
ZOBJDATE attribute	131, 136
ZOBJDOMN attribute.....	131
ZOBJID attribute.....	131
ZOBJNAME attribute	131, 136
ZOBJPCLS attribute	131
ZOBJPID attribute	131
ZOBJPRI attribute	173
ZOBJPRI attribute	173
ZOBJRCRC attribute	131
ZOBJRSIZ attribute	131
ZOBJTIME attribute.....	131, 136
ZRSCCMDL attribute.....	174, 181, 182
specifying	181
ZRSCCRC attribute.....	125

ZRSCMFIL attribute	124, 167	ZSUBNET attribute	136
ZRSCMMEM attribute	124	ZSVCMO attribute	188
ZRSCOBJN attribute	125	ZSVCMO attribute	167
ZRSCPADM attribute	125	ZSVCOID attribute	174
ZRSCSRC attribute	125, 131	ZSVCTYPE attribute	109, 155
ZRSCSTYP attribute	124	ZTIMEO attribute	42
ZRSCVLOC attribute	123, 124	ZTIMEQ object	173, 181, 182
ZSCHDEF attribute	174, 180, 181	ZTRACE attribute	42
ZSCHFREQ attribute	174	ZTRACEL attribute	42
specifying	181	ZUPDATE attribute	175
ZSCHMODE attribute	174	ZUSERID attribute	42, 136
ZSCHTYPE attribute	174	ZVERIFY attribute	175
specifying	181	ZVERINFO attribute	124
ZSERVICE class	108	ZVRFYUID attribute	42
ZSTOP attribute	173		

