

HP Project and Portfolio Management Center

Software Version: 9.10

Creating Portlets and Modules

Document Release Date: September 2010

Software Release Date: September 2010



Legal Notices

Warranty

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

The information contained herein is subject to change without notice.

Restricted Rights Legend

Confidential computer software. Valid license from HP required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

Copyright Notices

© Copyright 1997-2010 Hewlett-Packard Development Company, L.P.

Trademark Notices

Adobe® is a trademark of Adobe Systems Incorporated.

Intel®, Intel® Itanium®, Intel® Xeon®, and Pentium® are trademarks of Intel Corporation in the U.S. and other countries.

Java™ is a U.S. trademark of Sun Microsystems, Inc.

Microsoft®, Windows®, Windows® XP, and Windows Vista® are U.S. registered trademarks of Microsoft Corporation.

Oracle® is a registered trademark of Oracle Corporation and/or its affiliates.

UNIX® is a registered trademark of The Open Group.

Documentation Updates

This manual's title page contains the following identifying information:

- Software version number, which indicates the software version
- Document release date, which changes each time the document is updated
- Software release date, which indicates the release date of this version of the software

To check for recent updates, or to verify that you are using the most recent edition of a document, go to:

h20230.www2.hp.com/selfsolve/manuals

You will also receive updated or new editions if you subscribe to the appropriate product support service. Contact your HP sales representative for details.

Why version number 9.10?

PPM Center is an integrated part of the HP BTO Operations version 9 portfolio. Using this version number aligns PPM Center with other products that are releasing in the same time frame. PPM Center 9.10 builds on PPM Center 8.0x and is an extension of that product version family. Product releases within the HP BTO Operations version 9 portfolio will feature shared technology, common platforms, integrations, solutions, upgrade tools, and professional services offerings.

Support

You can visit the HP Software Support Web site at:

hp.com/go/hpsoftwaresupport

HP Software Support Online provides an efficient way to access interactive technical support tools. As a valued support customer, you can benefit by using the support site to:

- Search for knowledge documents of interest
- Submit and track support cases and enhancement requests
- Download software patches
- Manage support contracts
- Look up HP support contacts
- Review information about available services
- Enter into discussions with other software customers
- Research and register for software training

Most of the support areas require that you register as an HP Passport user and sign in. Many also require a support contract.

To find more information about access levels, go to:

h20230.www2.hp.com/new_access_levels.jsp

To register for an HP Passport ID, go to:

h20229.www2.hp.com/passport-registration.html

Contents

1	Getting Acquainted with the Standard Interface	9
	Introduction to the Standard Interface	9
	Overview of Creating Portlets and Modules	11
	Standards-Based Portlet Support	14
	The Configuration Process	15
	Related Information	15
2	Creating and Maintaining Portlet Data Sources	17
	Overview of Portlet Data Sources	17
	Searching For and Viewing Existing Portlet Data Sources	19
	Creating or Modifying Portlet Data Sources	21
	Completing the General Information Section	24
	Completing the Data Source Tab	25
	Completing the Select/From Tab	27
	Completing the Where/Filter Tab	29
	Completing the Group By/Order By Tab	32
	Completing the Filter Fields Tab	33
	Completing the Ownership Tab	36
	Copying Portlet Data Sources	37
	Deleting Portlet Data Sources	39
	Viewing Portlet Definition Usage	40
	Supplemental Details for the Data Source Column Window	41
	Text-Based Column Types Details	41
	Hyperlink Column Type Details	43
	Currency Column Type Details	45

3	Creating and Maintaining Portlet Definitions	47
	Overview of Portlet Definitions	47
	HP-Supplied Portlet Definitions	48
	HP-Imported Portlet Definitions	49
	Imported Java and WSRP Portlet Definitions	49
	Standard Portlet Definitions	49
	Searching for Existing Portlet Definitions	50
	Creating New Portlet Definitions	53
	Copying Portlet Definitions	64
	Modifying Portlet Definitions	65
	Deleting Portlet Definitions	68
	Importing Java Portlet Definitions	69
	Importing WSRP Portlet Definitions	73
	Migrating Portlet Definitions	77
	Defining a Drill-down Page	78
	Usage Example	78
	Defining a Drill-down Page	80
	Usage Samples	84
	DEMO - Pie Chart Portlet	84
	DEMO - Request List Portlet - 1	88
	DEMO - Request List Portlet - 2	91
	Defining a Portlet Event	94
	Managing Portlet Categories	96
	Adding Portlet Categories	96
	Deleting Portlet Categories	97
	Supplemental Details for the Set Up Display Option Step	98
	List Portlet	98
	Adding Columns	100
	Editing Columns	106
	Deleting Columns	107
	Pivot Table Portlet	107
	Adding a Pivot Table Row, Column, or Paging Filter Data Column	110
	Adding a Pivot Table Measurement Data Column	112
	Bar Chart Portlet	113
	Clustered Bar Chart Portlet	115
	Stacked Bar Chart Portlet	118
	Pie Chart Portlet	120

Line Chart Portlet	122
XY (Scatter) Line Chart Portlet.....	124
Radar (Spider) Line Chart Portlet.....	127
Bubble Chart Portlet	129
Setting the Displayed Color Label Length for a Bubble Chart.....	131
Selecting Portlet Colors.....	131
Defining Color Maps in the Portlet Data Source.....	131
Specifying the Color Map in the Portlet Definition	134
4 Creating and Maintaining PPM Dashboard Pages and Modules.....	137
About PPM Dashboard Pages and Modules	137
Preconfigured Dashboard Pages	137
HP-Provided Preconfigured Pages	137
Application Administrator-Provided Preconfigured Pages.....	138
Shared Dashboard Pages.....	139
Landing Page (Default PPM Dashboard Page).....	139
Searching for Modules	140
Creating Modules	143
Sharing Modules	146
Copying Modules	147
Modifying Modules.....	148
Deleting Modules	149
Configuring the Landing Page (Default PPM Dashboard Page).....	150
Changing the Landing Page	151
Disabling the Landing Page	152
A Color Names.....	153
Index.....	161

1 Getting Acquainted with the Standard Interface


Introduction to the Standard Interface

Most HP Project and Portfolio Management Center (PPM Center) users work solely in the standard interface, although some may use the PPM Workbench as well. The standard interface opens in your Web browser, and from it, you can run reports, create requests, and search for packages, among other things.

A key feature of PPM Center is the PPM Dashboard, which provides you with a real-time view into your PPM Center–based activities.

Using the PPM Dashboard’s portlets, you can view almost anything, from the status of requests assigned to you, to comparisons between current projects and staffing profiles. *Figure 1-1* shows a PPM Dashboard page that relies on two HP-supplied portlets: Request List and Current Portfolio Map.

Figure 1-1. Personalized PPM Dashboard page



When you first log on to PPM Center, you are presented with a PPM Dashboard page. The PPM Dashboard page displayed is determined by the system administrator (if your system administrator has configured a default landing page) or how you personalized your pages. HP provides a PPM Dashboard page named Front Page (Standard PPM Dashboard).

For more information about logging on to PPM Center, see the *Getting Started* guide.

Overview of Creating Portlets and Modules

Managers (or other lead personnel) can create, maintain, and share *configured* Dashboard pages and portlets to facilitate communication and coordination for their own projects. For example, your recruiting organization might share the list of current job openings.

Configuring the standard interface in this manner provides a mechanism for managers to share real-time information up and/or down the chain of command.



The individuals who plan, set up, and maintain HP-based applications are generally called application administrators (or configurators) and their responsibilities may also include configuring PPM Dashboard pages.

Figure 1-2 provides a visual overview of the different types of Dashboard pages. This document focuses on the application administrator-configured Dashboard pages; however, [Chapter 4, *Creating and Maintaining PPM Dashboard Pages and Modules*, on page 137](#) briefly describes how users can add preconfigured Dashboard pages.

Figure 1-2. Various types of PPM Dashboard pages





Figure 1-3 details the major components that make up configured Dashboard pages and depicts their relationships.

Figure 1-3. PPM Dashboard components



- **Dashboard.** The PPM Dashboard is one of the key applications provided with PPM Center.

In addition to the pre-installed Front Page and optional user-personalized Dashboard pages, the PPM Dashboard can include one or more modules.

- **Module.** A module is the container for one or more Dashboard pages.

Modules are created much like a Dashboard page is personalized by an individual user. Modules are created by application administrators.

- **Dashboard page.** A Dashboard page is the container for one or more portlets.

Dashboard pages within a module can be added, modified, and deleted. Similarly, on each Dashboard page, portlets can be added, modified, or deleted.

- **Portlet.** Portlets are the key visualization component of the PPM Dashboard and display information relevant to your PPM Center data. HP provides numerous portlets and additional (personalized or configured) portlets can be created.

In general, portlets rely on the following:

- **Portlet data sources.** For some portlets, these are typically the SQL queries used to gather the information from the PPM Center database. Other data sources include Web pages and RSS feeds.
- **Portlet definitions.** These define the look and feel of a portlet and can be customized. Portlet definitions can include such information as the type of portlet, data source, display options such as labels and columns to display, layout, user and group access to the portlet, and filter field definitions.

Standards-Based Portlet Support

PPM Center is a Java™-compliant portal, and provides support for Java-compliant portlets that are not included with PPM Center. Java portlets can be developed using the Java API, purchased from vendors (such as Sun Microsystems), or obtained with products (such as WebLogic Portal).

WSRP-compliant portlets are also supported by PPM Center. Web Services for Remote Portlets (WSRP) allows portals to publish portlets so that other portals can “consume” them. Use of WSRP portlets simplifies integration between systems and can reduce programming overhead as well as provide continuity for users of multiple systems.

PPM Center provides support for JSR 168 and WSRP standards-compliant portlets. This support is based on the Apache Reference implementations of two specifications: Pluto and WSRP4J. However, the specifications may not be complete in all areas or may be open to interpretation. HP has made design decisions to cover these areas.



HP is committed to provide support for customers implementing these types of portlets, including debugging and diagnosing problems related to the PPM Dashboard. HP does not extend that support to cover the debugging of custom portlet code or configuration files.

To facilitate diagnosis, customers reporting problems to the HP Software Support Web site (hp.com/go/hpsupport) are required to provide a simple, reproducible case that demonstrates the error in the PPM Dashboard.

The Configuration Process

Configuring the standard interface requires steps relating to both creating portlets and making them available. In general, the process is as follows:

Step 1: Create a portlet.

1. Create a portlet data source. See [Chapter 2, *Creating and Maintaining Portlet Data Sources*, on page 17](#), for specifics.
2. Create a portlet definition. See [Chapter 3, *Creating and Maintaining Portlet Definitions*, on page 47](#), for more information.

Step 2: Create and share a module and its Dashboard page(s).

See [Chapter 4, *Creating and Maintaining PPM Dashboard Pages and Modules*, on page 137](#), to learn more about these topics.

Related Information

The following documents also include information related to creating and sharing portlets and modules:

- *Commands, Tokens, and Validations Guide and Reference*
- *Reports Guide and Reference*
- *Security Model Guide and Reference*

The following documents also provide insights into the user experience with PPM Dashboard pages:

- *Customizing the Standard Interface*
- *Getting Started*

2 Creating and Maintaining Portlet Data Sources

Overview of Portlet Data Sources

Portlet data sources contain the following components:

- The filter fields found on the edit page for the portlet.
- The permissions allowing editing of the portlet data source.
- The SQL query used by the portlet definition to retrieve data from the PPM Center database.

A portlet data source SQL query consists of the following:

- **SELECT/FROM.** This statement is used to select columns from the designated database table.

These columns are used by the portlet definition, such as a column in a list portlet or the x-axis in a bubble chart portlet.

For example:

```
SELECT OBJECT_TYPE, OBJECT_NAME, REVISION_NUMBER  
FROM KACC_PSFT_VC_V
```

- **WHERE.** This clause is used to specify selection criterion.

For example:

```
WHERE LOCKED_FLAG="Y"
```

- **GROUP BY or ORDER BY.** These keywords are used to aggregate or sort the result.

For example:

```
ORDER BY OBJECT_TYPE
```

The following is a complete SQL query for a portlet data source:

```
SELECT OBJECT_TYPE, OBJECT_NAME, REVISION_NUMBER  
FROM KACC_PSFT_VC_V  
WHERE LOCKED_FLAG="Y"  
ORDER BY OBJECT_TYPE
```

Portlet definitions and portlet data sources have the following relationships:

- A portlet definition can be linked to only one portlet data source.
- A portlet data source can be linked to multiple portlet definitions.

Portlet data sources are constructed using the Data Source Workbench (sometimes called the Data Source Builder).

From the Data Source Workbench you can:

- Search for and view portlet data sources; see *Searching For and Viewing Existing Portlet Data Sources*
- Create new portlet data sources or modify existing ones; see *Creating or Modifying Portlet Data Sources* on page 21
- Use existing portlet data sources as the basis for new portlet data sources; see *Copying Portlet Data Sources* on page 37
- Delete existing portlet data sources; see *Deleting Portlet Data Sources* on page 39
- View portlet definition usage; see *Viewing Portlet Definition Usage* on page 40



HP-supplied portlet data sources can be copied but cannot be modified or deleted.

Searching For and Viewing Existing Portlet Data Sources


To search for a portlet data source:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Open Workbench**.

The PPM Workbench opens.

3. From the shortcut bar, select **Dashboard > Data Sources**.

The Data Source Workbench opens.




4. On the **Query** tab, provide the search criteria.



To display all portlet data sources, click **List** without providing any search criteria.

5. Click **List**.

The **Results** tab appears, displaying the results of the search.



Query	Data Source Name	Description	Enabled
	My Packages	Displays all Packages created by or assigned to t...	Y
	My Requests	Displays all Requests created by or assigned to t...	Y
	My Tasks	Displays all Project Tasks currently assigned to y...	Y
	My Time Sheets	Displays the Time Sheets for the user during the ...	Y
	My Work Items	Displays all the Work Items on open Time Sheet...	Y
	Package List	Package List	Y
	Program Issue List	Portlet listing open issues associated with a Pro...	Y
	Program List	Displays the programs and their summary condit...	Y
	Program Project List	Displays projects within a specified program	Y
	Program Risk List	Portlet listing open Risks associated with a Progr...	Y
	Program Scope Change List	Portlet listing open Scope Change requests ass...	Y
	Resource Assignments	Displays the packages, requests, and tasks assi...	Y
	Resource Pool List	Resource Pool List Portlet	Y
	Staffing Profile List	Staffing Profile List Portlet	Y

Buttons: New, Open, Copy, Delete, Refresh

72 Record(s) loaded.


6. (Optional) To view a portlet data source, either:

- Double-click a portlet data source.
- Select a portlet data source and click **Open**.



Use the **shift** or **ctrl** keys to select multiple portlet data sources.

The Data Source : *<Data Source Name>* window opens.



Data Source Name: Program List Time-out: Use Default 20 Seconds

Reference Code: PROGRAM_LIST_1

Description: Displays the programs and their summary conditions

Enabled: Yes No

Data Source | Filter Fields | Portlet Definitions | Ownership

Full Query for the Data Source

```
group by program_name,
p.program_id,
relative_priority,
program_state_meaning,
program_manager_full_name,
program_manager_email_address,
program_manager_phone_number,
issue_summary,
risk_summary,
cost_summary,
scope_change_summary,
resource_request_summary,
show_issues_flag,
show_risks_flag,
show_scope_changes_flag
```

View Query Use Bind Variables? Yes No

Verify OK Save Cancel

Ready (Read-Only, Seed Data)

Creating or Modifying Portlet Data Sources

To update an existing portlet data source, or to create an entirely new portlet data source:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Open Workbench**.

The PPM Workbench opens.

3. From the shortcut bar, select **Dashboard > Data Sources**.

The Data Source Workbench opens.

4. To:
 - Create an entirely new portlet data source, either:
 - On the **Query** tab, click **New Data Source**.
 - On the **Results** tab, click **New**.
 - Modify an existing portlet data source:
 - View the portlet data source (as described in *Searching For and Viewing Existing Portlet Data Sources* on page 19).



HP-supplied portlet data sources cannot be modified.

The Data Source : *<Data Source Name>* window opens.

Data Source : Untitled1

Data Source Name: Time-out Use Default 20 Seconds

Reference Code:

Description:

Enabled: Yes No

Data Source | Filter Fields | Portlet Definitions | Ownership

Full Query for the Data Source

```
SELECT
```

Edit Query Use Bind Variables?

Yes No

Verify OK Save Cancel

Ready

5. Provide information for each of the following areas before proceeding to the next step.
- **General information.** Use these fields to set general information regarding the portlet data source, such as the name of the portlet data source, reference code, and its description. See [Completing the General Information Section on page 24](#) for details.
 - **Data Source.** Use this tab to define the columns of the portlet data source and create the SQL query. See [Completing the Data Source Tab on page 25](#) for details.
 - **Filter Fields.** Use this tab to create the filter fields found on a portlet's edit page. See [Completing the Filter Fields Tab on page 33](#) for details.
 - **Ownership.** Use this tab to set who can edit the portlet data source. See [Completing the Ownership Tab on page 36](#) for details.



The **Portlet Definitions** tab is used to identify which portlet definitions rely on this portlet data source. A new portlet data source will not have any portlet definitions associated with it.

This tab is detailed in [Viewing Portlet Definition Usage on page 40](#).

6. (Optional) At any time, you can click **Save** to commit your changes. See the tip following *Table 2-1* for additional considerations and suggestions.

You can also click **Cancel** to discard any changes. However, if you have provided a unique **Data Source Name** and clicked **Save** (at least once), the portlet data source has been created with the information provided as of the last **Save**.

7. (Optional, although highly recommended) On the Data Source : *<Data Source Name>* window, click **Verify** to validate the SQL statement.

Make any necessary corrections to the SQL by clicking **Edit Query** on the **Data Source** tab.

8. Click **OK** to save your changes and close the window.

The Data Source : *<Data Source Name>* window closes and the Data Source Workbench is updated.



On the **Results** tab, click **Data Source Name** to have the portlet data sources appear in alphabetical sequence. Clicking **Data Source Name** a second time reverses the sort order.



If your PPM Center instance supports multiple languages, any data source you create is defined in the language you selected at logon (your session language). After the data source is created, it can be modified only in its definition language. For more information, see *Multilingual User Interface Guide*.

Completing the General Information Section

To complete (or update) the general information area of the Data Source : <Data Source Name> window:

1. Provide the settings using the information from the following table.

Table 2-1. Portlet data source general information field descriptions

Field Name (*Required)	Description
*Data Source Name	Specify a unique name for the portlet data source. Type any alphanumeric string.
*Reference Code	A default value is provided, but you may specify a unique name for the data source reference code. PPM Center uses this code to identify specific entity types. This code does not change, regardless of whether its name is changed or translated.
Time-out	Select the timeout to use. Choices include: <ul style="list-style-type: none">• Use Default• Data Source Specific
Seconds	The number of seconds to wait before the portlet data source's query times out. If the Time-out field has a value of Use Default , this field displays the default time-out value used. If the Time-out field has a value of Data Source Specific , specify the time-out value. Type any integer greater than zero.
Description	Specify a description for the portlet data source. Type any alphanumeric string.
Enabled	Indicate whether or not this portlet data source is available for use.



To allow incremental saving of your settings without impacting any users, set the **Enabled** field to **No** when initially defining the portlet data source. Once the portlet data source definition is complete, reset this field to **Yes**.

2. (Optional) Click **Save** to commit these changes.

Completing the Data Source Tab

Figure 2-1. Data Source tab for portlet data sources

The screenshot shows a dialog box titled "Data Source : Untitled1". It has several input fields: "Data Source Name", "Reference Code", and "Description". Below these is an "Enabled" section with radio buttons for "Yes" and "No", where "No" is selected. There are four tabs: "Data Source", "Filter Fields", "Portlet Definitions", and "Ownership", with "Data Source" being the active tab. A large text area labeled "Full Query for the Data Source" contains the text "SELECT". Below this text area is an "Edit Query" button. To the right of the text area is a section labeled "Use Bind Variables?" with radio buttons for "Yes" and "No", where "No" is selected. At the bottom of the dialog are "Verify", "OK", "Save", and "Cancel" buttons. The status bar at the bottom left says "Ready".

To complete (or update) the **Data Source** tab of the Data Source : *<Data Source Name>* window:


1. Set **Use Bind Variables**.

The **Use Bind Variables** option should be set to **Yes**, except when:

- Any of the filter fields are multi-select-enabled
- The portlet query statement includes tokens

2. Click **Edit Query**.

The Query Definition window opens.



3. Provide the following information before proceeding to the next step.

- **Select/From.** Use this tab to create the columns and add the SELECT and FROM clauses for the SQL query. See [Completing the Select/From Tab](#) for details.
- **Where/Filter.** (Optional) Use this tab to add WHERE clauses to the SQL query. See [Completing the Where/Filter Tab on page 29](#) for details.
- **Group By/Order By.** (Optional) Use this tab to add GROUP BY or ORDER BY clauses. See [Completing the Group By/Order By Tab on page 32](#) for details.

4. (Optional) Click **View Full Query** to see the entire SQL query—the composite of the information from each of the tabs.
5. Click **Apply** to commit any interim changes. Click **OK** to save your changes and close the window.

Completing the Select/From Tab

The **Select/From** tab allows you to construct the SQL query the portlet data source executes.

- **Select.** This statement identifies one or more columns to be included in the query.

For example, the following shows a complete SQL query for a portlet data source (the SELECT statement portion of the SQL query is shown in italics):

```
SELECT OBJECT_TYPE, OBJECT_NAME, REVISION_NUMBER  
FROM KACC_PSFT_VC_V  
WHERE LOCKED_FLAG="Y"  
ORDER BY OBJECT_TYPE
```

- **From.** This clause selects the table from which the columns are selected.

For example, the following shows a complete SQL query for a portlet data source (the FROM clause portion of the SQL query is shown in italics):

```
SELECT OBJECT_TYPE, OBJECT_NAME, REVISION_NUMBER  
FROM KACC_PSFT_VC_V  
WHERE LOCKED_FLAG="Y"  
ORDER BY OBJECT_TYPE
```

To complete (or update) the **Select** section on the **Select/From** tab in the Query Definition window:

1. (Optional) To change the settings for any existing column:
 - a. Select a column.
 - b. Click **Edit** in the **Select** section.

The Data Source Column. <Column Name> windows opens.

- c. The information that should be provided depends on the Column Type. See *Supplemental Details for the Data Source Column Window on page 41* for the details associated with each column type.
 - d. Click **Save** to commit any interim changes. Click **OK** to save your changes and close the window.
2. (Optional) To include a new column.
 - a. Click **Add** in the **Select** section.

The Data Source Column: New window opens.
 - b. The information that should be provided depends on the Column Type. See *Supplemental Details for the Data Source Column Window on page 41* for the details associated with each column type.
 - c. Click **Save** to commit any interim changes. Click **OK** to save your changes and close the window.
3. Repeat [step 1](#) and [step 2](#) until all the desired columns are included.
4. In the **From Clause** section of the **Select/From** tab of the Query Definition window, complete the associated clause.

This is a free-form SQL entry area.



Click **Enlarge** to create a larger text entry field.

5. Click **Apply** to commit your changes. Click **OK** to save your changes and close the window.

Completing the Where/Filter Tab

The **Where/Filter** tab allows you to construct the SQL query the portlet data source executes.

- **Where.** This clause is used to specify the selection criteria.

For example, the following shows a complete SQL query for a portlet data source (the WHERE clause portion of the SQL query is shown in italics):

```
SELECT OBJECT_TYPE, OBJECT_NAME, REVISION_NUMBER
FROM KACC_PSFT_VC V
WHERE LOCKED_FLAG="Y"
ORDER BY OBJECT_TYPE
```


- **Filter.** This clause is used to specify the filter fields that appear on the portlet's edit page.

Each filter field is appended to the WHERE clause of the portlet query, but only when the filter field is being used by a PPM Dashboard user.

Filter field values can be used in the SQL by using the token name `P.TOKEN_NAME` or `VP.TOKEN_NAME`.



Figure 2-2. Where/Filter tab of the Query Definition window



To complete (or update) the **Where Clause** section on the **Where/Filter** tab in the Query Definition window:

1. Complete the associated clause.

The **Where Clause** section defines the WHERE clause of the portlet query.

This is a free-form SQL entry area.



Click **Enlarge** to create a larger text entry field.

2. (Optional) To change the settings for an existing filter field:

- a. Select a filter field.
- b. Click **Edit** in the **Filter Fields** section.

The Filter: <Filter Field> window opens.

- c. Provide the data as detailed in [Completing the Filter Fields Tab on page 33](#).
- d. Click **Apply** to commit any interim changes. Click **OK** to save your changes and close the window.

3. To include a new filter field:

- a. Click **New** in the **Filter Fields** section.

The Filter: New window opens.

Adding filter fields here has the same results as adding filter fields using the **Filter Fields** tab as the Data Source : <Data Source Name> window.

The difference in the two areas is how the information is visually displayed.



- In the **Filter Fields** section of the Query Definition window, the SQL clauses are displayed.
- On the **Filter Fields** tab of the Data Source : <Data Source Name> window, the PPM Center entities are displayed.

- b. Provide the data as detailed in [Completing the Filter Fields Tab on page 33](#).

- c. Click **Add** to commit any interim changes. Click **OK** to save your changes and close the window.

4. Repeat [step 2](#) and [step 3](#) until all the desired filter fields are included.

5. Click **Apply** to commit your changes. Click **OK** to save your changes and close the window.

Completing the Group By/Order By Tab


The **Group By/Order By** tab allows you to refine the SQL query the portlet data source executes.

- **GROUP BY.** Adds a keyword to aggregate the result.
- **ORDER BY.** Adds a keyword to sort the result.

For example, the following shows a complete SQL query for a portlet data source (the ORDER BY portion of the SQL query is shown in *italics*):

```
SELECT OBJECT_TYPE, OBJECT_NAME, REVISION_NUMBER
FROM KACC_PSFT_VC_V
WHERE LOCKED_FLAG="Y"
ORDER BY OBJECT_TYPE
```

Figure 2-3. Group By/Order By tab of the Query Definition window



To complete (or update) the **Group By/Order By** tab in the Query Definition window:

1. In the **Group By Clause** section, provide the GROUP BY or ORDER BY terms.

This is a free-form SQL entry area.

2. In the **Having Clause** section, provide the HAVING terms.

This is a free-form SQL entry area.

3. In the **Default Order By Clause** section, provide the default ORDER BY terms.

This is a free-form SQL entry area.

4. Click **Apply** to commit your changes. Click **OK** to save your changes and close the window.

Completing the Filter Fields Tab

Figure 2-4. Filter Fields tab for portlet data source

Data Source Name: Program List Time-out: Use Default 20 Seconds

Reference Code: _PROGRAM_LIST_1

Description: Displays the programs and their summary conditions

Enabled: Yes No

Seq	Name	Token	Validation	Required	Enabled
1	Created By:	CREATED_BY	PPM - User Id - Enabled	N	Y
2	Creation Date From:	CREATION_DATE_FROM	Date	N	Y
3	Creation Date To:	CREATION_DATE_TO	Date	N	Y
4	Program Name:	PROGRAM_NAME	PMO - Programs	N	Y
5	Relative Priority To:	RELATIVE_PRIORITY_TO	Numeric Text Field (Positive)	N	Y
6	Relative Priority From:	RELATIVE_PRIORITY_FR...	Numeric Text Field (Positive)	N	Y
7	Program Status:	PROGRAM_STATE	PMO - Program State AC	N	Y
8	Program Manager:	PROGRAM_MANAGER	PPM - User Names - Enabled	N	Y
9	Contains Contents:	CONTAINS_PROJECTS	PPM - Lifecycle Entities	N	Y
10	Business Objectives:	BUSINESS_OBJECTIVES	PMO - Business Objectives	N	Y


Verify OK Save Cancel

Ready (Read-Only, Seed Data)

To complete (or update) the Filter Fields tab in the Data Source : <Data Source Name> window:

1. (Optional) To change the settings for an existing filter field:
 - a. Select a filter field.
 - b. Click **Edit**.

The Filter: <Filter Field> window opens.



- c. Provide the filter criteria using the information from the following table.

Each filter field is appended to the WHERE clause of the portlet query, but only when the filter field is being used by a PPM Dashboard user.

Filter field values can be used in the SQL by using the token name `P . TOKEN_NAME` or `VP . TOKEN_NAME`.

Field Name (*Required)	Description
*Field Name	Specify a name for the filter field that should be shown in the portlet's edit page. Type any alphanumeric string.
*Token	Specify the token for the filter field.
Description	Specify a description for the filter field. Type any alphanumeric string.

Field Name (*Required)	Description
*Validation	Select the validation for the filter field. Choices are limited to those validations available on your PPM Center instance.
Multiselect	Indicate whether or not the filter field is enabled for multi-select.
Required	Indicate whether or not the filter field is required on the portlet's edit page.
Enabled	Indicates whether or not the filter field is enabled.
*When this filter has a value, append to Where Clause	Provide the AND clause that is appended to the portlet's WHERE clause if you provide a value in this filter field.

- d. Click **Apply** to commit any interim changes. Click **OK** to save your changes and close the window.
2. (Optional) To include a new filter field:
 - a. Click **New**.
The Filter: New window opens.
 - b. Provide the filter criteria using the information from the previous table.
 - c. Click **Add** to commit any interim changes. Click **OK** to save your changes and close the window.
 3. Repeat [step 1](#) and [step 2](#) until all the desired filter fields are included.
 4. Click **Save** to commit your changes. Click **OK** to save your changes and close the window.

Completing the Ownership Tab

Only members of the security groups specified in the Ownership window can edit, copy, or disable a specific portlet. If a security group is disabled or the System: Edit Portlet Definition access grant is removed, that group no longer has access to the portlet.

If no ownership groups are associated with the entity, the entity is considered global and any user with the proper edit access grant for the entity can edit, copy, or disable it. Users with the System: Ownership Override access grant can access configuration entities even if the user is not a member of one of the ownership groups and does not have the specific edit access grant.



For more information concerning access grants, refer to the *Security Model Guide and Reference*.

Figure 2-5. Ownership tab for the portlet data source

Data Source : Program List

Data Source Name: Program List Time-out: Use Default 20 Seconds

Reference Code: _PROGRAM_LIST_1

Description: Displays the programs and their summary conditions

Enabled: Yes No

Data Source | Filter Fields | Portlet Definitions | **Ownership**

Give ability to edit this Data Source to :

All users with the Edit Portlet Definition Access Grant

Only groups listed below that have the Edit Portlet Definition Access Grant

Security Group	Description
----------------	-------------

Add Remove

Verify OK Save Cancel

Ready (Read-Only, Seed Data)

To complete (or update) the **Ownership** tab in the Data Source : <*Data Source Name*> window:

1. Indicate whether to allow changes to the portlet data source to be made by:
 - All users with the System: Edit Portlet Definition access grant
 - Only groups listed below that have the System: Edit Portlet Definition access grant


Use the **Add** and **Remove** buttons to refine the list of allowed users.
2. Click **Save** to commit your changes. Click **OK** to save your changes and close the window.

Copying Portlet Data Sources

To create a new portlet data source using an existing portlet data source as the basis:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Open Workbench**.
The PPM Workbench opens.
3. From the shortcut bar, select **Dashboard > Data Sources**.
The Data Source Workbench opens.
4. Search for and select a portlet data source (see *Searching For and Viewing Existing Portlet Data Sources* on page 19).

5. Click **Copy**. The Copy Data Source window opens.




6. In the **Data Source Name** field, specify a unique name for the portlet data source.

In the Reference Code field, specify a unique reference code for the portlet data source.

If your PPM Center instance supports multiple languages and the data source is defined in a language other than your session language, the **Copy existing translations** checkbox is enabled. To copy all of the content that is translated for the data source, select this checkbox. To copy only the content that has been translated to your session language, do not select the checkbox. For more information, see *Multilingual User Interface Guide*.

7. Click **Copy**. The Question window opens.



8. Click **Yes** if you would like to edit the portlet data source. Otherwise, click **No**.
9. (Optional) If you clicked **Yes** in the previous step, modify the portlet data source using the information described in *Creating or Modifying Portlet Data Sources* on page 21.

Deleting Portlet Data Sources

- ▶ HP-supplied portlet data sources cannot be deleted.

To delete an existing portlet data source:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Open Workbench**.

The PPM Workbench opens.


3. From the shortcut bar, select **Dashboard > Data Sources**.

The Data Source Workbench opens.

4. Search for and select one or more portlet data sources (see [Searching For and Viewing Existing Portlet Data Sources](#) on page 19).

5. Click **Delete**.

The Question window opens.



6. Click **Yes** to remove the portlet data source(s). Otherwise, click **No**.

If you clicked **Yes**, the Data Source Workbench is updated (and the deleted portlet data source no longer appears in the list).


Viewing Portlet Definition Usage

The **Portlet Definitions** tab allows you to view all of the portlet definitions currently linked to the portlet data source.

From the Portlet Data Source window, on the **Portlet Definitions** tab, you can:

- View all of the portlet definitions linked to the portlet data source.
Remember that portlet definitions and portlet data sources have the following relationships:
 - A portlet definition can be linked to only one portlet data source.
 - A portlet data source can be linked to multiple portlet definitions.
- Open the portlet definition by clicking on the portlet definition name. This opens the Portlet Definition wizard. The Portlet Definition wizard is populated with the information for the selected portlet definition.
- Create a new portlet definition by clicking **New Portlet Definition**. This opens the Portlet Definition wizard.

Figure 2-6. Portlet Data Source window, Portlet Definitions tab



Supplemental Details for the Data Source Column Window

Adding columns to the Query Definition window relies on the Data Source Column window. The fields of the Data Source Column window vary, depending on the column type selected.

See the associated details for the following column types:

- Text, Date, Number, or Summary Condition/Exception, see [Text-Based Column Types Details](#)
- Hyperlink, see [Hyperlink Column Type Details](#)
- Currency, see [Currency Column Type Details](#) on page 45

Text-Based Column Types Details

Figure 2-7. Text-based column types in Data Source Column window




Table 2-2. Text-based column types field descriptions

Field Name (*Required)	Description
*Column Name	Specify the name of the column. Type any alphanumeric string.
*Column Type	Select one of the following: <ul style="list-style-type: none"> • Text • Date • Number • Summary Condition/Exception
Description	Specify a brief description of the column. Type any alphanumeric string.
*Column	Specify the database column name used for the column. Choices are limited to the column names available on your PPM Center instance. Note: The type of the database column specified should match the Column Type selected. If the types do not match, sorting of this column in the portlet may not behave as expected (sorting is based on the type of the database column). For example, if you select a Column Type of Number, but the type of the database column is text, sorting of this column in the portlet is based on text rather than numbers. Use a function, such as <code>to_number</code> , to change the database column type to match the selected Column Type.

Hyperlink Column Type Details

Figure 2-8. Hyperlink column type in the Data Source Column window




Table 2-3. Hyperlink column type field description (page 1 of 2)

Field Name (*Required)	Description
*Column Name	Specify the name of the column. Type any alphanumeric string.
*Column Type	Select Hyperlink .
Description	Specify a brief description of the column. Type any alphanumeric string.
*Hyperlink Type	<p>Select the type of hyperlink to create from this column.</p> <p>Choices include:</p> <ul style="list-style-type: none"> • Request Detail Page • Package Detail Page • Task Detail Page • Project Detail Page • Project Overview Page • Custom Hyperlink <p>When Custom Hyperlink is selected, the Hyperlink field becomes editable and required. Otherwise, the Hyperlink field is read-only and displays a preview of the link that is created (for example, /itg/crt/RequestDetail.jsp?REQUEST_ID=[PRT.ENTITY_ID]).</p>

Table 2-3. Hyperlink column type field description (page 2 of 2)

Field Name (*Required)	Description
*Entity ID Column	<p>Specify the SQL expression used to make a column in the final query.</p> <p>This column should contain values which are Request IDs (such as, Request Detail Page type Hyperlinks).</p> <p>In the case of the Custom Hyperlink, the values from this column are used to resolve the token <code>PRT.ENTITY_ID</code>, which can be used in the text of the hyperlink.</p>
*Hyperlink	<p>Specify the actual hyperlink text, which should be of one of the following forms:</p> <ul style="list-style-type: none"> • <code><PPM_Home>/some/page</code> • <code>http://machine.server.com/page.html</code> <p>The valid tokens are <code>DSH.PRT.ENTITY_ID</code>, <code>DSH.PRT.ENTITY_ID.TO_URL</code>, and <code>SYS.USERNAME</code>.</p>

Currency Column Type Details

Figure 2-9. Currency column type in the Data Source Column window




Table 2-4. Currency column type field descriptions (page 1 of 2)

Field Name (*Required)	Description
*Column Name	Specify the name of the column. Type any alphanumeric string.
*Column Type	Select Currency .
Description	Specify a brief description of the column. Type any alphanumeric string.

Table 2-4. Currency column type field descriptions (page 2 of 2)

Field Name (*Required)	Description
*Base Value Column	<p>Specify the column (that displays in the currency column) whose values are costs in the base currency.</p> <p>These values are displayed if the user has configured their PPM Dashboard to show costs in the system's base currency.</p> <p>For this column to sort correctly, it must be a number. If necessary, use the function <code>to_number</code> to change the value to a number.</p>
Currency ID Column	<p>Specify the column whose values are the ID of the local currency.</p> <p>This value is never displayed; however, it is used to determine how the local currency value (see Local Value Column) is formatted.</p>
Local Value Column	<p>Specify the column (that displays in the currency column) whose values are costs in the local currency.</p> <p>These values are displayed (and formatted appropriately for the specified currency) if the user has configured their PPM Dashboard to show costs in the local currency. That is, the user must select Local Currency from the Dashboard Cost Display section from the Edit My Profile page (Open > Administration > Edit My Profile).</p> <p>For this column to sort correctly, it must be a number. If necessary, use the function <code>to_number</code> to change the value to a number.</p>

3 Creating and Maintaining Portlet Definitions

Overview of Portlet Definitions

PPM Center portlets include:

- **Builder Portlets.** These are portlets created with the Portlet Definition wizard and Data Source Workbench.

HP supplies several builder portlets as part of PPM Center. You can create your own custom builder portlets using the Portlet Definition wizard and Data Source Workbench.
- **Java Portlets.** These portlets are written in Java and imported into PPM Center using the Portlet Definition wizard. Java portlets consist of a Java portlet definition and the Java code.
- **WSRP Portlets.** These portlets are defined by a producer Web service and imported into PPM Center using the Portlet Definition wizard. WSRP portlets have a WSRP portlet definition that references the URL of the WSRP portlet. That is, WSRP portlet definitions are a proxy to a remote portlet definition maintained by the producer and accessible through a Web service.

These PPM Center portlets rely on the following types of portlet definitions:

- **HP-supplied portlet definitions.** These portlet definitions are provided by HP as part of a PPM Center application.
- **HP-imported portlet definitions.** These portlet definitions are imported by HP as part of a PPM Center application.

- **Standard portlet definitions.** These portlet definitions are created using the Portlet Definition wizard (see *Creating New Portlet Definitions on page 53*).
- **Java portlet definitions.** These portlet definitions are imported using the Import Portlet Definition wizard (see *Importing Java Portlet Definitions on page 69*), maintained using the Portlet Definition wizard (see *Creating New Portlet Definitions on page 53*), and include portlet definitions such as RSS Reader and URL.
- **WSRP portlet definitions.** These portlet definitions are imported using the Import Portlet Definition wizard (see *Importing WSRP Portlet Definitions on page 73*) and maintained using the Portlet Definition wizard (see *Creating New Portlet Definitions on page 53*).

HP-Supplied Portlet Definitions

PPM Center applications, such as HP Portfolio Management and HP Demand Management, may include their own portlet definitions.

These HP-supplied portlet definitions:

- Cannot be deleted
- Cannot have their displays or preferences changed in any way
- Can be modified by:
 - Copying portlet definitions
 - Changing user and administrator access
 - Changing user help (for builder portlets only)

HP-Imported Portlet Definitions

PPM Center applications may include their own imported Java or WSRP portlet definitions.

These HP-imported portlet definitions:

- Cannot be deleted
- Can be modified by:
 - Changing user and administrator access
 - Changing general information

Imported Java and WSRP Portlet Definitions

Any Java portlet definitions or WSRP portlet definitions that you have imported using the Import Portlet Definition wizard:

- Can be deleted
- Can be modified by:
 - Configuring user and administrator access
 - Changing general information

Standard Portlet Definitions

Any standard portlet definitions that you have created using the Create Portlet Definition wizard:

- Can be deleted
- Can have *any* of their settings changed




These portlet definitions are sometimes termed “builder portlet definitions” since they are *built* using the Create Portlet Definition wizard.

Searching for Existing Portlet Definitions

To search for an existing portlet definition.

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Portlet Definitions > Configure Portlet Definitions**.

The Configure Portlet Definitions page appears.



The screenshot shows the 'Configure Portlet Definitions' page. At the top, there is a title bar 'Configure Portlet Definitions' and a 'Reset Form' button. Below this is a search form titled 'Search for a Portlet Definition to Configure'. The form contains several input fields and dropdown menus: 'Name starts with:' (text input), 'Type:' (dropdown), 'Category:' (text input with a search icon), 'Enabled:' (dropdown), 'Created By:' (text input with a search icon), 'Sort By:' (dropdown set to 'Name'), 'Ascending' (radio button, selected), 'Descending' (radio button), and 'Results Displayed Per Page:' (text input set to '50'). A 'Search' button is located at the bottom right of the form.

3. Provide the search criteria using the information from the following table.

Field Name (*Required)	Description
Name starts with	Specify a string. The search results display all portlets whose name starts with the specified string. Type any alphanumeric string (up to 255 characters in length).

Field Name (*Required)	Description
Type	Select the type of portlet definition: <ul style="list-style-type: none"> • List • Pivot Table • Bar Chart • Clustered Bar Chart • Stacked Bar Chart • Pie Chart • Line Chart • XY Chart • Radar Chart • Bubble Chart • Java • WSRP
Category	Select one or more categories. Choices are limited to the categories available on your PPM Center instance.
Enabled	Indicated whether or not the portlet definition is enabled.
Created By	Select the user who created the module.
Sort By	Select the sort criteria. Choices include: <ul style="list-style-type: none"> • Name • Type • Category • Enabled
Ascending/Descending	Indicate the sorting sequence.
*Results Displayed Per Page	Specify the maximum number of search results to display on a page. Type any positive integer.



Click **Reset Form** if you would like to clear your current search criteria.

4. Click **Search**.

The Configure Portlet Definitions page is updated to include the search results which are displayed in the **Configure Portlet Definitions** section.

Configure Portlet Definitions

Configure Portlet Definitions							Showing 1 to 18 of 81		Prev	Next
Name	Description	Type	Category	Last Updated On	Enabled					
<input checked="" type="checkbox"/> Analyze Assignment Load	Analyze Assignment Load Portlet.	Java	Resource Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Analyze Resource Pools	Analyze Resource Pools Portlet	Java	Resource Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Approve Time Sheets	Displays Time Sheets that need approval by the current user.	Java	Time Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Assignment Queue	Provides quick assignment capabilities from the Dashboard for Demand Managers.	Java	Requests	4/20/09	Yes					
<input checked="" type="checkbox"/> Budget by Asset Class	A graphical view that shows the breakdown of budget by Asset Class for a what-if scenario from an existing Scenario Comparison.	Java	Portfolio Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Budget by Business Objective	A graphical view that shows the breakdown of budget by Business Objective for a what-if scenario from an existing Scenario Comparison.	Java	Portfolio Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Budget by Project Class	A graphical view that shows the breakdown of budget by Project Class for a what-if scenario from an existing Scenario Comparison.	Java	Portfolio Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Budget Summary	A graphical view that shows the budget summary of a what-if scenario from an existing Scenario Comparison.	Java	Portfolio Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Capitalized Project Breakdown	Can be set up to show the source data for (capitalized) projects displayed in graphical portlets (Total Exposure, Impairment Risks and Capitalized Project Timelines).	Java	Portfolio Management, Financial Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Capitalized Project Timelines	A graphical display of projects with capitalized costs showing their start date, end date and health.	Java	Portfolio Management, Financial Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Consolidated Demand	Provides a graphical overview of the Demand placed on your organization.	Java	Requests	4/20/09	Yes					
<input checked="" type="checkbox"/> Cost Benefit Analysis	A graphical view that shows cost-benefit analysis for a what-if scenario from an existing Scenario Comparison.	Java	Portfolio Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Current Portfolio Map	This portlet gives a graphical view of the current portfolio of Projects and Assets.	Java	Portfolio Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Demand by Category	Provides a graphical summary of the Demand placed on an organization that can be grouped by common Demand Categories.	Java	Requests	4/20/09	Yes					
<input checked="" type="checkbox"/> Demand List	Provides a personalizable list of the Demand placed on an organization or individual.	Java	Requests	4/20/09	Yes					
<input checked="" type="checkbox"/> EV Summary	Displays work plan-level Earned Value metrics for the project.	Java	Project Overview	4/20/09	Yes					
<input checked="" type="checkbox"/> Impairment Risks	A graphical view of active projects that have capitalized costs, chosen by project health and broken out project.	Java	Portfolio Management, Financial Management	4/20/09	Yes					
<input checked="" type="checkbox"/> Issue List	Portlet listing open issues associated with a Program	List	Requests, Program Management	4/20/09	Yes					

Showing 1 to 18 of 81 [Prev](#) [Next](#)

Search for a Portlet Definition to Configure [Reset Form](#)

Name starts with: Type:

Category: Enabled:

Created By:

Sort By: Ascending Descending *Results Displayed Per Page:

[Search](#)

From the Configure Portlet Definitions page you can:

- Select a portlet definition by clicking the link associated with the desired portlet definition (in the **Configure Portlet Definitions** section).
- Refine your search by providing additional search criteria as detailed in [step 3 on page 50](#).

Creating New Portlet Definitions

To create an entirely new standard portlet definition, use the Create Portlet Definition wizard.









1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Portlet Definitions > Create a Portlet Definition**.

The Choose Portlet Type step of the Create Portlet Definition page appears.

Create Portlet Definition

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. Set up Display Options ▶ 4. Define Preferences
5. Configure Portlet Communication ▶ 6. Configure Access ▶ 7. Add User Help

Choose Portlet Type

<input checked="" type="radio"/> List		Displays data in rows and columns.
<input type="radio"/> Pivot Table		Displays multidimensional aggregations over tabular data.
<input type="radio"/> Bar Chart		Displays data in either vertical or horizontal bars.
<input type="radio"/> Clustered Bar Chart		Displays data in either vertical or horizontal bars; bars can be grouped into clusters.
<input type="radio"/> Stacked Bar Chart		Displays data in either vertical or horizontal bars; each bar can be subdivided into categories.
<input type="radio"/> Pie Chart		Typically used to show percentages of a whole.
<input type="radio"/> Line Chart (including subtypes)		Typically used to show changes in data over time. Subtypes include an XY Chart (also known as a Scatter Chart) and a Radar Chart (also known as a Spider Chart which is often used for data that have a natural cycle of change).
<input type="radio"/> Bubble Chart		Typically used to plot points on two axes such as "value" vs. "risk." Bubble size and color indicate additional dimensions of information.

Cancel < Back Next >

3. Select the type of portlet to create.

Portlet Type	Description
List	Data is presented in tabular form using rows and columns.
Pivot Table	Data is aggregated in a table. Rows, columns, tables, and measurements can be grouped into categories.
Bar Chart	Data is displayed as vertical or horizontal bars. Each bar represents a single item.
Clustered Bar Chart	Data is displayed as vertical or horizontal bars. Bars can be grouped into categories.
Stacked Bar Chart	Data is displayed as vertical or horizontal bars. Each bar can be subdivided into categories.
Pie Chart	Data is displayed as a percentage of a whole.
Line Chart	Data is displayed to show changes over time.
Bubble Chart	Four dimensions of data are displayed on an x-y axis. The x-y axis location pinpoints a spot while the size and color of the bubble indicates additional dimensions of the information.

4. Click **Next** (found near the bottom of the page).

The Enter Portlet Information step of the Create Portlet Definition (<Portlet Type>) page appears.

Create Portlet Definition (List)

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. Set up Display Options ▶ 4. Define Preferences
5. Configure Portlet Communication ▶ 6. Configure Access ▶ 7. Add User Help

Portlet Information

Name:

Category: [Manage Categories](#)

Description:

Default Width:

Enabled: Yes No

Portlet Information

Data Source: [New Data Source](#)

5. Provide the portlet details using the information from the following table.

Field Name (*Required)	Description
Portlet Information section	
*Name	Specify a unique name for the portlet. Type any alphanumeric string (up to 80 characters in length).
Category	Select one or more categories. Choices are limited to those categories available on your PPM Center instance.
Manage Categories	Click to add or delete portlet categories. See Managing Portlet Categories on page 96 for details.
Description	Specify the portlet definition. Type any alphanumeric string (up to 1,800 characters in length).
Default Width	Select the default width of the portlet. Choices include: <ul style="list-style-type: none"> • Narrow • Wide Note that the default width can be changed when the portlet is personalized.
Enabled	Indicate whether or not the portlet can be added to the Dashboard page. If a portlet is added to a PPM Dashboard, then disabled, the portlet remains on the Dashboard page.
Data Source section	
*Data Source	Select the data source for the current portlet. The portlet data source defines the columns or chart entity, and preferences fields for a portlet definition.
New Data Source	Click to open the PPM Workbench and create a new portlet data source.

6. Click **Next**.

The Set up Display Options step of the Create Portlet Definition (<Portlet Type>) page appears.

Create Portlet Definition (List)

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. Set up Display Options ▶ 4. Define Preferences
5. Configure Portlet Communication ▶ 6. Configure Access ▶ 7. Add User Help

Display Columns

Columns may be displayed in the portlet by Default (in the user's initial view) or in the Maximized view only. Columns may be made optionally available for the user's selection.

Add Column **Edit** **Delete**

Click on a column to select User Sortable

Columns Displayed by Default:

▲ Tasks ▲ OPEN_TASKS ▼

Columns Displayed by Default in Maximized View Only:

▲ ▼

Columns Available for Display:

Arrange Data

Default Sort By: ▼ Ascending Descending

*Default Rows Displayed: In Normal View
 In Maximized View

Cancel **Back** **Next**

7. Provide the appropriate information on the Create Portlet Definition (<Portlet Type>) page.

The information needed to create the different portlet types vary significantly. Field descriptions are provided in the *Supplemental Details for the Set Up Display Option Step* on page 98 section.


- For list portlets, see *List Portlet* on page 98.
- For pivot table portlets, see *Pivot Table Portlet* on page 107.
- For bar charts, see *Bar Chart Portlet* on page 113.
- For clustered bar charts, see *Clustered Bar Chart Portlet* on page 115.
- For stacked bar charts, see *Stacked Bar Chart Portlet* on page 118.
- For pie charts, see *Pie Chart Portlet* on page 120.

- For line charts, see *Line Chart Portlet* on page 122.
- For bubble charts, see *Bubble Chart Portlet* on page 129.

8. Click **Next**.

The Define Preferences step of the Create Portlet Definition (<Portlet Type>) page appears.

Initially, all preference fields are mapped from the portlet data source, which indicates the name of the field, type of the field (such as auto-complete or text field), and any default value. Note that preferences requiring default values are shown with a red asterisk.

- (Optional) To change the width of preferences, click the **Sizing** icon ()
- (Optional) To rearrange preferences:
 - Select a preference.
 - Drag and drop the preference into the desired location.

c. (Optional) To edit preferences:

- i. Select a preference.
- ii. Click **Edit**.

The Edit Portlet Preference: *<Preference>* dialog box opens.

hp Close Window X

Edit Portlet Preference: TASK_STATE_ID

Field Prompt: Limit by Task State:

Component Type: Multi-Select Auto Complete

Display:

- Editable - Allow user to edit
- Required and Editable - Require user to enter a value
- Non-Editable - Only allow user to view
- Hidden - Not visible to user

Default Value: [] [icon]

Done Cancel

Close Window X

- iii. Provide the preference details using the information from the following table.

Field Name (*Required)	Description
*Field Prompt	Specify the prompt that will appear on the Portlet Preference page. Type any alphanumeric string (up to 200 characters in length).
Display	Select the manner in which this preference is displayed. Choices could include one or more of the following (depending on the component type): <ul style="list-style-type: none"> • Editable. Allows the user to edit the field. • Required and Editable. Requires the user to provide a value. • Non-Editable. Allows user to view, but not edit the field. • Hidden. The information is not viewable (or editable) by the user. This field is required if a default value is required by the portlet data source.
Default Value	Specify the default value that is shown when editing the portlet. This field is required if a default value is required by the portlet data source.

- iv. Click **Done**.

The changes to preference are saved and the Edit Portlet Preference: <Preference> dialog box closes.

- d. (Optional) Select **Show Preferences summary on this portlet (user can choose to hide it)** if you want the user to have this capability.
- e. (Optional) Select **Require user to edit preferences before viewing portlet for the first time** if you want to force the user to edit their preferences.

9. If you do not want to change any of the remaining default values, click **Finish**. Otherwise, click **Next**.

The Configure Portlet Communication step of the Create Portlet Definition (<Portlet Type>) page appears.

Create Portlet Definition (List)

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. Set up Display Options ▶ 4. Define Preferences

5. Configure Portlet Communication ▶ 6. Configure Access ▶ 7. Add User Help

Portlet Communication Subscribers

Define whether this portlet definition enables portlet communication. If yes, select event topic names to subscribe portlet definition for published portlet event.

Enable portlet communication (user can choose to disable it)

*Event topic: Manage event topics

Cancel ◀ Back Next ▶ Preview Finish

- a. (Optional) Select **Enable portlet communication (user can choose to disable it)** if you want the user to have this capability.
- b. If portlet communication is enabled, you must provide an event topic. Use the auto-complete button to provide an existing event topic or click **Manage event topics** to add a new topic or delete an existing topic.

10. If you do not want to change any of the remaining default values, click **Finish**. Otherwise, click **Next**.

The Configure Access step of the Create Portlet Definition (<Portlet Type>) page appears.

Create Portlet Definition (List)

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. Set up Display Options ▶ 4. Define Preferences
5. Configure Portlet Communication ▶ 6. **Configure Access** ▶ 7. Add User Help

Configure Access

User Access

Users specified below will have access to add this Portlet to their dashboards.

Require users to have one of these privileges:

Allow access to only the following users and groups:

Security Type	Name
All Users	

Give Access to:

Administrator Access

Users specified below will have access to modify this Portlet Definition.

Security Type	Name
All Portlet Definition Administrators	

Give Access to:

WSRP Access

Make Portlet available to WSRP Consumers

Drilldown Access

This portlet supports drilling into

a. (Optional) In the **User Access** section:

- i. Select one or more access grants (privileges) a user must have in order to add the portlet to a Dashboard page.
- ii. Select one or more users or security groups allowed to add the portlet to a Dashboard page.

By default, access is given to all users belonging to the PPM User security group.



Whenever there is no specific (individual or group) user access, this setting reverts to its default.

b. (Optional) In the **Administrator Access** section:

- Select one or more users or security groups allowed to modify the portlet.

By default, access is given to all users belonging to the PPM User Admin security group.



Whenever there is no specific (individual or group) administrator access, this setting reverts to its default.

c. (Optional) In the **WSRP Access** section:

- Select if you want to make the portlet available to WSRP consumers.
- Click **Preview** to review the layout and make sure that you have presented the information as desired.

d. (Optional) In the Drilldown Access section:

- Select if you want the portlet to support drill-down access.

11. Click **Next**.

The changes are added to the new portlet definition and the Add User Help step of the Create Portlet Definition (<Portlet Type>) page appears.

Create Portlet Definition (List)

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. Set up Display Options ▶ 4. Define Preferences
5. Configure Portlet Communication ▶ 6. Configure Access ▶ 7. Add User Help

Portlet Help

Help content will be available to end users when viewing this portlet on their dashboard, and when adding portlets during Dashboard Personalization.

Portlet Help Text:

Preview Help

Cancel Back Next Preview Finish

12. In the **Portlet Help Text** field, type the help text.

This field supports HTML. Use valid HTML tagging when typing the information that defines the functionality of the portlet and lists and describes all of the portlet fields.

Click **Preview Help** to review the help content make sure that you have presented the information as desired.



Click **Preview** to review the layout and make sure that you have presented the information as desired.

13. Click **Finish**.

The help data is saved, the portlet definition is created, and a status message displayed.

Create Portlet Definition

Sample has been successfully created.

[Configure Sample](#)
[Create another Portlet Definition](#)
[Search for other Portlet Definitions to configure](#)

14. Review the information to make determine if your portlet definition was successfully created.



If your PPM Center instance supports multiple languages, any portlet definition you create is defined in the language you selected at logon (your session language). After the portlet definition is created, it can be modified only in its definition language. For more information, see *Multilingual User Interface Guide*.

Copying Portlet Definitions

You can copy a portlet definition to use as the basis for another portlet definition.



Java portlet definitions and WSRP portlet definitions cannot be copied.

To copy a portlet definition:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Portlet Definitions > Configure Portlet Definitions**.

The Configure Portlet Definitions page appears, as shown in [step 2 on page 50](#).

3. Search for and select a portlet definition.

For detailed instructions on how to search for and select portlet definitions, see [Searching for Existing Portlet Definitions on page 50](#).

The Configure Portlet Definition: *<Portlet Definition>* page appears.



If your PPM Center instance supports multiple languages and the portlet definition is defined in a language other than your session language, you cannot edit the portlet definition. For more information, click **here** in the header or see *Multilingual User Interface Guide*.

4. Click **Copy**.

The Configure Portlet Definition: <Portlet Definition> page is updated with the copied information.

5. Provide the portlet information using the information available from the following steps: Enter Portlet Information ([step 4 on page 54](#)), Set up Display Options ([step 6 on page 56](#)), Define Preferences ([step 8 on page 57](#)), Configure Portlet Communication ([step 9 on page 60](#)), Configure Access ([step 10 on page 61](#)), and Add User Help ([step 11 on page 63](#)).



Click **Preview** to review the layout and make sure that you have presented the information as desired.

6. Click **Create**.

7. (Optional) Make any additional modifications and click **Save**.

8. Click **Done** to return to the Configure Portlets Definitions window.

Modifying Portlet Definitions

To change an existing portlet definition:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Portlet Definitions > Configure Portlet Definitions**.

The Configure Portlet Definitions page appears, as shown in [step 2 on page 50](#).

3. Search for and select a portlet definition.

For detailed instructions on how to search for and select portlet definitions, see [Searching for Existing Portlet Definitions](#) on page 50.



If your PPM Center instance supports multiple languages and the portlet definition is defined in a language other than your session language, you cannot edit the portlet definition. For more information, click **here** in the header or see [Multilingual User Interface Guide](#).

The Configure Portlet Definition: *<Portlet Definition>* page appears.

Configure Portlet Definition: Time Sheet Totals for Direct Reports

This is a built-in Portlet Definition. It cannot be deleted. Preview Save Done Cancel

Portlet Type: [List](#) Data Source: [Time Sheet Totals for Direct Reports](#)

Created By: seed_data seed_data Last Modified By: seed_data seed_data Last Modification Date: 2/20/2008

Name: Time Sheet Totals for Direct Reports

Category: Time Management

Description: Shows the total time entered by all the direct reports for a specific manager or set of managers

Default Width: Narrow

Enabled: Yes No In use by 1 user(s), 0 module(s), and 0 hyperlink(s). View Usage Copy

Display Preference Fields Portlet Communication Access User Help

Display Columns

Columns may be displayed in the portlet by Default (in the user's initial view) or in the Maximized view only. Columns may be made optionally available for the user's selection.

User Sortable

Columns Displayed by Default:

Name	RESOURCE_FULL_NAME	Tooltip: RESOURCE_INFO
Period Type	PERIOD_TYPE_NAME	Tooltip: PERIOD_TYPE_NAME
Current Period (hrs)	ACTUALS_CURRENT	
Unsubmitted Time (hrs)	UNRELEASED_TIME	
Previous Period (hrs)	ACTUALS_PREVIOUS	

Columns Displayed by Default in Maximized View Only:

Columns Available for Display:

Arrange Data

Default Sort By: Ascending Descending

*Default Rows Displayed: 5 In Normal View
50 In Maximized View

Preview Save Done Cancel

4. For non-Java portlets:

- a. (Optional) At any time, you can click **Save** to commit your changes.
- b. (Optional) Provide the general information using the details from the **Portlet Information** section of the table included in [step 5 on page 55](#).
- c. (Optional) Click the link associated with **Data Source** to view the details of the data source in the PPM Workbench.
- d. (Optional) Click the appropriate tab to make changes to the other settings. The content of the tabs varies based on the portlet type. Field descriptions are provided in [Chapter 3, *Creating New Portlet Definitions*, on page 53](#).

For Display tab content, refer to the following sections based on the portlet type:

- For list portlets, see [List Portlet on page 98](#).
- For bar charts, see [Bar Chart Portlet on page 113](#).
- For clustered bar charts, see [Clustered Bar Chart Portlet on page 115](#).
- For stacked bar charts, see [Stacked Bar Chart Portlet on page 118](#).
- For pie charts, see [Pie Chart Portlet on page 120](#).
- For line charts, see [Line Chart Portlet on page 122](#).
- For bubble charts, see [Bubble Chart Portlet on page 129](#).

5. For Java portlets:

- a. (Optional) Provide the general information using the details from the **Portlet Information** section of the table included in [step 5 on page 55](#).
- b. (Optional) Configure portlet communication subscribers using the details provided in [step 9 on page 60](#).
- c. (Optional) Configure the user and administrator access using the details provided in [step 10 on page 61](#).

6. Click **Done**.



Click **Preview** to review the layout and make sure that you have presented the information as desired.

Deleting Portlet Definitions

To delete a portlet definition:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Portlet Definitions > Configure Portlet Definitions**.

The Configure Portlet Definitions page appears, as shown in [step 2 on page 50](#).

3. Search for and select a portlet definition.

For detailed instructions on how to search for and select portlet definitions, see [Searching for Existing Portlet Definitions on page 50](#).

The Configure Portlet Definition: *<Portlet Definition>* page appears.

4. Click the delete icon next to the name of the portlet definition to delete.
A confirmation dialog box opens.
5. Click **Delete**.

The confirmation dialog box closes and the Configure Portlet Definitions page is updated.

Importing Java Portlet Definitions

The WAR files used for Java portlet definitions must be placed on the server file system in the `<PPM_Home>/server/<PPM_Server_Name>/deploy` directory.

To import a Java portlet definition using the Import Portlet Definition wizard:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Portlet Definitions > Import a Portlet Definition**.

The Choose Portlet Type step of the Import Portlet Definition page appears.

The screenshot shows the 'Import Portlet Definition' wizard interface. At the top, the title is 'Import Portlet Definition'. Below the title, there are five steps in a progress bar: 1. Choose Portlet Type (highlighted), 2. Select from Available Portlets, 3. Enter Portlet Information, 4. Configure Portlet Communication, and 5. Configure Access. Below the progress bar, there are two radio button options: 'Java Portlet - Created according to the Java Portlet specification' (which is selected) and 'WSRP Portlet - Created according to WSRP specifications'. At the bottom of the wizard, there are three buttons: 'Cancel', 'Back', and 'Next'.

3. Select **Java Portlet - Created according to the Java Portlet specification**.

4. Click **Next**.

The Select from Available Portlets step of the Import Portlet Definition page appears.

Import Portlet Definition (Java)

1. Choose Portlet Type ▶ 2. **Select from Available Portlets** ▶ 3. Enter Portlet Information

4. Configure Portlet Communication ▶ 5. Configure Access

Select from Available Portlets

The Dashboard has found the Java portlets listed below. Please select one of these portlets to import.

Portlet Display Name	Description
<input checked="" type="checkbox"/> Project List	Displays general information about PPM Projects, such as how close they are to completion and their scheduled finish date.
<input checked="" type="checkbox"/> Summary Task List	Displays general information about Summary Tasks, such as how close they are to completion and their scheduled finish date.
<input checked="" type="checkbox"/> Package List	Displays general information about PPM Packages, such as their description and status.
<input checked="" type="checkbox"/> Request Activity	Displays general activity information about PPM Requests, such as the number of Requests opened and closed during the last two weeks, and the number of open Requests.
<input checked="" type="checkbox"/> Package Activity	Displays activity information about the number of deployments (Package Line execution step transactions) completed during the last three weeks. Provides drill down to any Object Type or Environment to view the included Packages.
<input checked="" type="checkbox"/> Request Summary	Displays information about groups of PPM Requests, such as their priority, type, status and the total number of Requests for each category. Additionally provides drill down capabilities to detailed requests.
<input checked="" type="checkbox"/> Open Requests by Priority	A bar chart that displays the number of Requests currently open, grouped by priority.
<input checked="" type="checkbox"/> Request List	Displays general information about PPM Requests, such as their description and status.
<input checked="" type="checkbox"/> Project Gantt	Displays Projects, Tasks and Milestones in Gantt chart format. This portlet can be configured based on such criteria as Project and Task status, schedule and resource assignments. It also allows drilling down into Project and Task details.
<input checked="" type="checkbox"/> Capitalized Project Timelines	A graphical display of projects with capitalized costs showing their start date, end date and health.
<input checked="" type="checkbox"/> Project Timelines	Displays project level information in a gantt format for multiple projects, based on the planned start and finish periods.
<input checked="" type="checkbox"/> Resource Gantt	Displays information about Work Items (including Requests, Tasks, Milestones, and Staffing Profiles) assigned to selected Resources in Gantt chart format. Additionally, this portlet provides the ability to drill down into Work Item details.
<input checked="" type="checkbox"/> Capitalized Project Breakdown	Displays relevant information about capitalized projects. This portlet can be filtered so show the same projects as Total Exposure, Impairment Risks and Capitalized Project Timelines, showing the source data for those graphical portlets.
<input checked="" type="checkbox"/> Impairment Risks	A graphical view of active projects that have capitalized costs, chosen by project health and broken out project.
<input checked="" type="checkbox"/> Total Exposure	A graphical view of active projects that have capitalized costs grouped by the health of the project.
<input checked="" type="checkbox"/> Project Current Cost Metrics	Analyze Current Cost Metrics for Projects.
<input checked="" type="checkbox"/> Analyze Assignment Load	Analyze Assignment Load Portlet.
<input checked="" type="checkbox"/> Project Cost Summary	Displays a list of cost information for a Project.
<input checked="" type="checkbox"/> Program Cost Summary	Displays a list of cost information for a Program.
<input checked="" type="checkbox"/> Analyze Resource Pools	Analyze Resource Pools Portlet
<input checked="" type="checkbox"/> Budget by Project Class	A graphical view that shows the breakdown of budget by Project Class for a what-if scenario from an existing Scenario Comparison.
<input checked="" type="checkbox"/> Budget by Asset Class	A graphical view that shows the breakdown of budget by Asset Class for a what-if scenario from an existing Scenario Comparison.
<input checked="" type="checkbox"/> Budget by Business Objective	A graphical view that shows the breakdown of budget by Business Objective for a what-if scenario from an existing Scenario Comparison.
<input checked="" type="checkbox"/> Consolidated Demand	Provides a graphical overview of the Demand placed on your organization.
<input checked="" type="checkbox"/> Demand By Category	Provides a graphical summary of the Demand placed on an organization that can be grouped by common Demand Categories.
<input checked="" type="checkbox"/> Pending Deployment	Displays general information about Packages which have not been deployed. This portlet provides visibility into scheduled or required Package migration.
<input checked="" type="checkbox"/> Package References	Display the References that are attached to the Package based on filters such as Reference Types, Relationship, and the time period when they were added.
<input checked="" type="checkbox"/> Total Budget	A graphical view that shows budget requirement and availability for all what-if scenarios from an existing Scenario Comparison.
<input checked="" type="checkbox"/> Total Resource	A graphical view that shows resource requirement and availability for all what-if scenarios from an existing Scenario Comparison.
<input checked="" type="checkbox"/> Budget Summary	A graphical view that shows the budget summary of a what-if scenario from an existing Scenario Comparison.
<input checked="" type="checkbox"/> Cost Benefit Analysis	A graphical view that shows cost-benefit analysis for a what-if scenario from an existing Scenario Comparison.
<input checked="" type="checkbox"/> Request References	Display the References that are attached to the Request based on filters such as Reference Types, Relationship, and the time period when they were added.
<input checked="" type="checkbox"/> Assignment Queue	Provides quick assignment capabilities from the Dashboard for Demand Managers.
<input checked="" type="checkbox"/> SLA Exception Rollup	Displays the open Requests that have triggered SLA exceptions.
<input checked="" type="checkbox"/> Demand List	Provides a personalizable list of the Demand placed on an organization or individual.
<input checked="" type="checkbox"/> Portfolio By Category	Provides a graphical view of monetary metrics of Projects and Assets in the current portfolio, striped by a selected category.
<input checked="" type="checkbox"/> My Tasks	Displays all Project Tasks currently assigned to you that have a scheduled finish date two weeks from the current date.
<input checked="" type="checkbox"/> Current Portfolio Map	This portlet gives a graphical view of the current portfolio of Projects and Assets.
<input checked="" type="checkbox"/> Project Health Pie Chart	Pie chart summary of Projects by health.
<input checked="" type="checkbox"/> Package Summary Bar Chart	Bar chart summary of Packages.
<input checked="" type="checkbox"/> Package Summary Pie Chart	Pie chart summary of Packages.
<input checked="" type="checkbox"/> Request Summary Bar Chart	Bar chart summary of Requests.
<input checked="" type="checkbox"/> Request Summary Pie Chart	Pie chart summary of Requests.
<input type="radio"/> RSS Portlet	RSS Reader Portlet
<input type="radio"/> URL Portlet	URL Portlet
<input type="radio"/> HTML Portlet	HTML Portlet
<input checked="" type="checkbox"/> Financial Summary to Financial Data Comparison	Compares FS to FDTs.
<input checked="" type="checkbox"/> Financial Comparison	Displays a stacked Bar Chart format of Financial Comparisons
<input checked="" type="checkbox"/> Previously imported	

5. Select a portlet.

Note that only one portlet can be selected at a time.

If no portlet definitions are available (that is, all of the portlet definitions are selected):

- Click **Back** to return to the previous page.
- Click **Cancel** to stop.

6. Click **Next**.

The Enter Portlet Information step of the Import Portlet Definition page appears.

The screenshot shows the 'Import Portlet Definition (Java)' page at step 3, 'Enter Portlet Information'. The breadcrumb trail is: 1. Choose Portlet Type > 2. Select from Available Portlets > 3. Enter Portlet Information > 4. Configure Portlet Communication > 5. Configure Access. The main section is titled 'Portlet Information' and contains the following fields: 'Name' (text input with 'URL Portlet'), 'Category' (text input with a 'Manage Categories' button), 'Description' (text input with 'URL Portlet'), 'Default Width' (dropdown menu with 'Narrow'), and 'Enabled' (radio buttons for 'Yes' and 'No', with 'Yes' selected). At the bottom are buttons for 'Cancel', 'Back', 'Next', and 'Finish'.

7. (Optional) Provide the general information using the details from the **Portlet Information** section of the table included in [step 5 on page 55](#).

8. Click **Next**.

The Configure Portlet Communication step of the Import Portlet Definition page appears.

The screenshot shows the 'Import Portlet Definition (Java)' page at step 4, 'Configure Portlet Communication'. The breadcrumb trail is: 1. Choose Portlet Type > 2. Select from Available Portlets > 3. Enter Portlet Information > 4. Configure Portlet Communication > 5. Configure Access. The main section is titled 'Portlet Communication Subscribers' and contains the following text: 'Define whether this portlet definition enables portlet communication. If yes, select event topic names to subscribe portlet definition for published portlet event.' Below this is a checkbox for 'Enable portlet communication (user can choose to disable it)'. There is also an 'Event topic' field (text input) with a 'Manage event topics' button. At the bottom are buttons for 'Cancel', 'Back', 'Next', and 'Finish'.

If portlet communication is enabled, you must provide an event topic.

Use the auto-complete button to provide an existing event topic or click **Manage event topics** to add a new topic or delete an existing topic.

9. Click **Next**.

The Configure Access step of the Import Portlet Definition page appears.

Import Portlet Definition (Java)

1. Choose Portlet Type ▶ 2. Select from Available Portlets ▶ 3. Enter Portlet Information
4. Configure Portlet Communication ▶ 5. Configure Access

Configure Access

User Access

Users specified below will have access to add this Portlet to their dashboards.

Require users to have one of these privileges:

Allow access to only the following users and groups:

Security Type	Name
All Users	

Give Access to: User

Administrator Access

Users specified below will have access to modify this Portlet Definition.

Security Type	Name
All Portlet Definition Administrators	

Give Access to: User

WSRP Access

Make Portlet available to WSRP Consumers

Cancel Back Next Finish

(Optional) Configure the user and administrator access using the details provided in [step 10 on page 61](#).

10. Click **Finish**.

The confirmation page appears.

Import Portlet Definition

Package List (Copy) has been successfully imported.

[Configure Package List \(Copy\)](#)
[Import another Portlet Definition](#)
[Create new Portlet Definition](#)
[Search for other Portlet Definitions to configure](#)

11. Review the Import Portlet Definition page and verify that the import was successful.

12. (Optional) Select the link of your choice.

Importing WSRP Portlet Definitions

To import a WSRP portlet definition using the Import Portlet Definition wizard:

1. Make sure that the producer Web URL is available.
2. Log on to PPM Center.
3. From the menu bar, select **Open > Administration > Portlet Definitions > Import a Portlet Definition**.

The Choose Portlet Type step of the Import Portlet Definition page appears.

The screenshot shows the 'Import Portlet Definition' wizard. The title is 'Import Portlet Definition'. Below the title is a progress bar with five steps: 1. Choose Portlet Type (selected), 2. Select from Available Portlets, 3. Enter Portlet Information, 4. Configure Portlet Communication, and 5. Configure Access. Below the progress bar are two radio button options: 'Java Portlet - Created according to the Java Portlet specification' (unselected) and 'WSRP Portlet - Created according to WSRP specifications' (selected). At the bottom of the form are three buttons: 'Cancel', 'Back', and 'Next'.

4. Select **WSRP Portlet - Created according to WSRP specifications**.
5. Click **Next**.

The Define Producer Web Service step of the Import Portlet definition page appears.

The screenshot shows the 'Import Portlet Definition (WSRP)' wizard. The title is 'Import Portlet Definition (WSRP)'. Below the title is a progress bar with six steps: 1. Choose Portlet Type, 2. Define Producer Web Service (selected), 3. Select from Available Portlets, 4. Enter Portlet Information, 5. Configure Portlet Communication, and 6. Configure Access. Below the progress bar is a section titled 'Define Producer Web Service'. The text in this section reads: 'In this step you can either: select a predefined producer (new producers can be defined using the Manage WSRP Producer button) or type a free URL of a WSRP producer. When you click Next, the Dashboard will contact the web service to determine what portlets are available. You will then be able to choose one of the portlets that it offers.' Below this text are two radio button options: 'Predefined Producer URL' (selected) and 'Producer URL'. The 'Predefined Producer URL' option has a text input field and a 'Manage WSRP Producers' button. The 'Producer URL' option has a text input field. Below the input fields is an example URL: 'Example: http://www.myserver.com/dashboard/wsrp4producer.wsdl'. At the bottom of the form are three buttons: 'Cancel', 'Back', and 'Next'.

6. Select either a **Predefined Producer URL** (define new producers by clicking the **Manage WSRP Producers** button) or **Producer URL** (provide the URL for the Web service providing portlet definitions using WSRP).



If you are importing a portlet from another PPM Center instance, use the following URL: `http://<Host>:<Port>/dashboard/wsrp4jproducer.wsdl`.

7. Click **Next**.

The Web service is contacted to determine what portlet definitions are available.

The Select from Available Portlets page appears.

Import Portlet Definition (WSRP)

1. Choose Portlet Type ▶ 2. Define Producer Web Service ▶ 3. **Select from Available Portlets** ▶ 4. Enter Portlet Information

5. Configure Portlet Communication ▶ 6. Configure Access

Select from Available Portlets

The Dashboard has found the portlets listed below from the WSRP producer at `http://labmvtg25-46300/dashboard/wsrp4jproducer.wsdl`. Please select one of these portlets to import.

Portlet Display Name	Description
<input checked="" type="radio"/> My Requests	Displays all Requests created by or assigned to the current user. This portlet provides a critical view into your most pressing Requests and nearing deadlines.
<input type="radio"/> My Tasks	Displays all Project Tasks currently assigned to you that have a scheduled finish date two weeks from the current date.
<input type="radio"/> Project List	Displays general information about PPM Projects, such as how close they are to completion and their scheduled finish date.

Cancel ◀ Back Next ▶ Finish

8. Select a portlet.

Note that only one portlet can be selected at a time.

If no portlet definitions are available (that is, all of the portlet definition are selected):

- Click **Back** to return to the previous page.
- Click **Cancel** to stop.

9. Click **Next**.

The Enter Portlet Information step of the Import Portlet Definition page appears.

The screenshot shows the 'Import Portlet Definition (WSRP)' page with the progress bar indicating step 4, 'Enter Portlet Information'. The main section is titled 'Portlet Information' and contains the following fields:

- Name:** Project List
- Category:** [Empty dropdown] **Manage Categories**
- Description:** Displays general information about PPM Projects, such as how close they are to completion and their schedule
- Default Width:** Narrow
- Enabled:** Yes No

At the bottom, there are four buttons: Cancel, Back, Next, and Finish.

10. Provide the general information using the details from the **Portlet Information** section of the table included in [step 5 on page 55](#).

11. Click **Next**.

The Configure Portlet Communication step of the Import Portlet Definition page appears.

The screenshot shows the 'Import Portlet Definition (WSRP)' page with the progress bar indicating step 5, 'Configure Portlet Communication'. The main section is titled 'Portlet Communication Subscribers' and contains the following elements:

- Define whether this portlet definition enables portlet communication. If yes, select event topic names to subscribe portlet definition for published portlet event.
- Enable portlet communication (user can choose to disable it)
- *Event topic:** [Empty dropdown] **Manage event topics**

At the bottom, there are four buttons: Cancel, Back, Next, and Finish.

- If portlet communication is enabled, you must provide an event topic. Use the auto-complete button to provide an existing event topic or click **Manage event topics** to add a new topic or delete an existing topic.

12. Click **Next**.

The Configure Access step of the Import Portlet Definition page appears.

Import Portlet Definition (WSRP)

1. Choose Portlet Type ▶ 2. Define Producer Web Service ▶ 3. Select from Available Portlets ▶ 4. Enter Portlet Information
5. Configure Portlet Communication ▶ 6. **Configure Access**

Configure Access

User Access

Users specified below will have access to add this Portlet to their dashboards.

Require users to have one of these privileges:

Allow access to only the following users and groups:

Security Type	Name
All Users	

Give Access to: User

Administrator Access

Users specified below will have access to modify this Portlet Definition.

Security Type	Name
All Portlet Definition Administrators	

Give Access to: User

Drilldown Access

This portlet supports drilling into

Cancel Back Next Finish

13. (Optional) Configure the user and administrator access using the details provided in [step 10 on page 61](#).

14. Click **Finish**.

The confirmation page appears.

15. Review the Import Portlet Definition page and verify that the import was successful.

16. (Optional) Select the link of your choice.

Migrating Portlet Definitions

Use the PPM Portlet Definition Migrator object type to migrate portlet definitions. The following are things to consider when migrating portlet definitions:

- When migrating an HP-supplied portlet definition, the portlet's data source file is automatically migrated at the same time as the portlet definition.
- When migrating a standard portlet definition, the portlet's data source file is automatically migrated at the same time as the portlet definition.
- When migrating a Java portlet definition, you must configure the source and destination servers with the same set of Web applications (such as WARs) before migrating the Java portlet definition.
- When migrating a WSRP portlet definition, the migration of the portlet definition is sufficient for the WSRP portlet to work. Migrating a WSRP portlet definition might fail under the following conditions:
 - **If the URL uses a port number.** If you move that portlet to a different machine whose WSRP provider runs on a different port number, the portlet stops working.
 - **If a WSRP portlet definition shares a firewall or a private network with a WSRP producer.** You cannot migrate the portlet definition outside of that private network or firewall protected area (because the machine is not accessible).

Defining a Drill-down Page

Portlet drill-down is a powerful feature that allows you to access and view the details of the information displayed in a portlet.

When you create a portlet, you can specify one or more drill-to portlets (these are sometimes called drill-down pages). Clicking a portlet that contains a drill-to portlet results in the display of the corresponding portlet. A drill-to portlet typically offers a view of the data with more details or the information is filtered differently.

- Prior to being added to a portlet, these drill-to portlets must already exist on your PPM Center instance.
- Drill-to portlets must be builder portlets (created using the Portlet Definition wizard).
- Only selected HP-supplied portlets can be used as drill-to portlets. These include: Issue List, Program Risk List, Program Scope Change List, and Program Contents List.



Usage Example


In some cases you may want to view the data in more than one way. Whenever you want to do this, specify one or more drill-to portlets.

For example, suppose you have a portlet that shows a collection of requests. However, you would like to be able to view the breakdown of requests sorted by priority and have insight into some of the requests' details. To provide this information, you would create two drill-to portlets, one showing the requests sorted by priority and the other showing the selected details of the requests. Then you would configure your portlet such that it is linked to these drilldown pages (drill-to portlets).

When you click key areas within the portlet having the drilldown pages, the appropriate data from the drill-to portlets is displayed.

The following figure shows an example of this kind of scenario.

Figure 3-1. Portlet having drilldown pages



If you click either the amber (25%) wedge or the **Critical** link, the drill-to pages having requests with critical priorities are shown (see *Figure 3-2*). Note that the drill-to page on the left shows the list of requests having the selected priority, whereas the drill-to page on the right shows the selected details of the request.

Figure 3-2. Drill-to portlets showing critical priority requests

Drill Down From DEMO - Pie Chart Back Export to PDF

Priority	Request #	Request #	Request Type	Description	Priority
Critical	30667	30667	Application Issues	Getting stock from front.	Critical
Critical	30649	30649	Application Issues	External Website - Job updates.	Critical
Critical	30641	30641	Application Issues	Replace cartridge in Brother labeler.	Critical
Critical	30622	30622	Application Issues	Tom called about his printer.	Critical
Critical	30612	30612	Application Issues	Research massive port scan/probe on cti.com	Critical

Showing 1 to 5 of 25 Prev Next

Showing 1 to 5 of 25 Prev Next

Alternatively, if you click either the red (38%) wedge or the **Low** link, the drill-to pages having requests with low priorities appear (see *Figure 3-3*).

Figure 3-3. Drill-to portlets showing low priority requests

Drill Down From DEMO - Pie Chart Export to PDF

Priority	Request #	Request #	Request Type	Description	Priority
Low	30672	30672	Application Issues	Make space on full volume on Pearl	Low
Low	30654	30654	Application Issues	Corporate Affiliate	Low
Low	30644	30644	Application Issues	Morning mail and phone support.	Low
Low	30636	30636	Application Issues	Move briefing.	Low
Low	30617	30617	Application Issues	Morning mail / phone msg support.	Low

Showing 1 to 5 of 38 Prev Next

Defining a Drill-down Page

The following procedure describes how to define a drilldown page. These instructions are applicable to the third step of the Portlet Definition wizard.



The page from which the drill-to portlets are accessed is sometimes referred to as the drill-from page.

To define a drill-down page for a column:

1. On the Set up Display Options step of the Create Portlet Definition (<Portlet Type>) page, select **Drilldown to Portlet**.

Create Portlet Definition (Pie Chart)

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. Set up Display Options ▶ 4. Define Preferences
5. Configure Portlet Communication ▶ 6. Configure Access ▶ 7. Add User Help

Data Source Mapping to Chart

Select a data source column to map to each chart property:

Chart Title:

*Wedge Source: ASSIGNED_TO

*Wedge Size Source: ASSIGNED_TO

Wedge Label: ASSIGNED_TO

Color Source:

Tooltip Source:

Hyperlink Options:

No Hyperlink

Hyperlink Source: ASSIGNED_TO

Drilldown to Portlet: (None) Edit

Portlet Event:

Sample Pie Chart

Wedge Label	Percentage
20% Wedge A	20%
25% Wedge B	25%
45% Wedge C	45%
8% Wedge D	8%
2% Wedge E	2%


Total: N (Wedge Source Value Total)

45% (Wedge Size)

Cancel Back Next

2. Click **Edit**.

The Edit Drilldown: <Name> dialog box appears.




3. Click **Add**.

The list of available portlet definitions appears.

4. Select one or more portlet definitions from the list presented.

5. Click **OK**.

The portlet definition are added to the **Drill-to Portlets** list and the list of available portlet definitions disappears.



Use the up- and down-pointers to rearrange the order of the drill-to portlets. When displayed, the drill-to portlets appear in the order your selected, in a top to bottom fashion. Narrow portlets will not be displayed side by side.

6. (Optional) To change the default mapping between the current portlet definition and the drill-to portlet definition:
 - a. Select a portlet definition from the **Drill-to Portlets** list.
 - b. Click **Add Data Mapping**.

The Add Data Mapping dialog box appears.

- c. Provide the mapping details using the information from the following table.



The examples shown in [Usage Samples on page 84](#) include annotations that identify the data mappings used in the example.

Field Name (*Required)	Description
*Map Value From	<p>Indicate the data to use. Choices include:</p> <ul style="list-style-type: none"> • Data Source Column. Select a column. Choices are limited to the columns available in your data source. • Preference of Drill-From Portlet. Select the desired preference for the portlet. • Text. Provide an alphanumeric string up to 200 characters in length.
*Map Value To	<p>Select the desired preference from the drill-to portlet. Choices are limited to the preference fields in the drill-to portlet.</p>

d. Click **Add**.

The information is added to the Edit Drilldown: <Name> dialog box and the Add Data Mapping dialog box disappears.

7. (Optional) To delete a mapping between the current portlet definition and the drill-to portlet definition:

- a. Select a portlet definition from the **Drill-to Portlets** list.
- b. In the **Drill-To Preference Values (<Drill-to Portlet>)** section, select from the following techniques:
 - Click the **Delete** icon next to the unwanted mapping
 - Click **Delete All** to remove all the mappings at one time



Occasionally it is easier to delete the existing mappings, then remap the current portlet and drill-to portlet definitions.

8. Once the drilldown is correctly defined, click **Done**.

The Edit Drilldown: <Name> dialog box disappears.

Continue with the configuration (and sharing) of your portlet as you normally would.

Usage Samples

The following images provide details about the data source and portlet configuration used to create the portlets used in the examples shown in this document.



The annotations identify each of the three data mappings.

DEMO - Pie Chart Portlet

This is the drill-from portlet and its various components.

Create Portlet Definition (Pie Chart)

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. Set up Display Options ▶ 4. Define Preferences
5. Configure Portlet Communication ▶ 6. Configure Access ▶ 7. Add User Help

Data Source Mapping to Chart

Select a data source column to map to each chart property:

Chart Title:

*Wedge Source:

*Wedge Size Source:

Wedge Label:

Color Source:

Tooltip Source:

Hyperlink Options:

No Hyperlink

Hyperlink Source:

Drilldown to Portlet: (None)

Portlet Event:

Sample Pie Chart

Chart Title

Total: N (Wedge Source Value Total)

Wedge Label
20% Wedge A
25% Wedge B
45% Wedge C
8% Wedge D
2% Wedge E

Data Source

Data Source : DEMO - Pie Chart

Data Source Name: DEMO - Pie Chart Time-out Use Default 20 Seconds

Reference Code: DEMO_PIE_CHART

Description:

Enabled: Yes No

Data Source | Filter Fields | Portlet Definitions | Ownership 1

Full Query for the Data Source

```
SELECT PRIORITY_MEANING COLUMN_VISIBLE PRIORITY_CODE COLUMN_HIDDEN COUNT(*) VALUE,
length(priority_code)||length(priority_meaning)||length(priority_meaning) AS STRLEN
FROM KORT_REQUESTS_V
WHERE f=1
AND batch_number 1
group by priority_code, priority_meaning
```

Edit Query Use Bind Variables?
 Yes No

Verify OK Save Cancel

Ready

Data Source : DEMO - Pie Chart

Data Source Name: DEMO - Pie Chart Time-out Use Default 20 Seconds

Reference Code: DEMO_PIE_CHART

Description:

Enabled: Yes No

Data Source | Filter Fields | Portlet Definitions | Ownership

Seq	Name	Token	Validation	Required	Enabled
1	Created By:	CREATED_BY	SPM - User Names - Enabled	N	Y
2	Request Type(s)	REQUEST_TYPE_ID_LIST	CRT - Request Types - Enabled	N	Y

New Edit Remove

Verify OK Save Cancel

Ready

Portlet Definition

Configure Portlet Definition: DEMO - Pie Chart

Preview Save Done Cancel

Portlet Type: Pie Chart Data Source: My Packages

Created By: Admin User Last Modified By: Admin User Last Modification Date: 2/22/2008

Name: DEMO - Pie Chart

Category: Manage Categories

Description:

Default Width: Narrow

Enabled: Yes No Not in use.

Copy Delete

Display Preference Fields Portlet Communication Access User Help

Data Source Mapping to Chart

Select a data source column to map to each chart property:

Chart Title:

*Wedge Source: ASSIGNED_TO

*Wedge Size Source: ASSIGNED_TO


Wedge Label: ASSIGNED_TO

Color Source:

Tooltip Source:

Hyperlink Options:
 No Hyperlink
 Hyperlink Source: ASSIGNED_TO
 Drilldown to Portlet: Resource Assignments Edit
 Portlet Event: Edit

Sample Pie Chart



Preview Save Done Cancel

hp Close Window X

Edit Drilldown: DEMO - Pie Chart

The following lists the portlets drilled-to by this hyperlink. You may add portlets to the list or remove them as well as edit the drilldown mappings for each portlet. The drilldown mappings of the selected portlet can be viewed in the table below.

Drill-to Portlets

DEMO - Request List Portlet - 1
 DEMO - Request List Portlet - 2

▲
▼

Add Remove

Drill-To Preference Values (DEMO - Request List Portlet - 1)

Preferences of the Drill-From portlet have been automatically mapped to preferences with the same name in the Drill-To portlet. To create additional mappings, click Add Data Mapping. In the Add Data Mapping window, use the data source column or preference of the drill-from portlet or enter text to define the mapping.

Map From	Map To
<input checked="" type="checkbox"/> Source Column: COLUMN_HIDDEN	<input type="checkbox"/> PTP_RL_PRIORITY
<input checked="" type="checkbox"/> Preference: CREATED_BY	<input type="checkbox"/> CREATED_BY
<input checked="" type="checkbox"/> Preference: REQUEST_TYPE_ID_LIST	<input type="checkbox"/> REQUEST_TYPE_ID_LIST

1
 2
 3

Add Data Mapping Delete All

Done Cancel

Close Window X

hp Close Window X

Edit Drilldown: DEMO - Pie Chart

The following lists the portlets drilled-to by this hyperlink. You may add portlets to the list or remove them as well as edit the drilldown mappings for each portlet. The drilldown mappings of the selected portlet can be viewed in the table below.

Drill-to Portlets

DEMO - Request List Portlet - 1
 DEMO - Request List Portlet - 2

▲
▼

Add Remove

Drill-To Preference Values (DEMO - Request List Portlet - 2)

Preferences of the Drill-From portlet have been automatically mapped to preferences with the same name in the Drill-To portlet. To create additional mappings, click Add Data Mapping. In the Add Data Mapping window, use the data source column or preference of the drill-from portlet or enter text to define the mapping.

Map From	Map To
<input checked="" type="checkbox"/> Source Column: COLUMN_HIDDEN	<input type="checkbox"/> PTP_RL_PRIORITY
<input checked="" type="checkbox"/> Preference: REQUEST_TYPE_ID_LIST	<input type="checkbox"/> REQUEST_TYPE_ID_LIST
<input checked="" type="checkbox"/> Preference: CREATED_BY	<input type="checkbox"/> CREATED_BY

1
 3
 2

Add Data Mapping Delete All

Done Cancel

Close Window X

DEMO - Request List Portlet - 1

This is one of the drill-to portlets and its various components.

Preferences:			
Request # Δ	Request Type	Description	Priority
30145	Enhancement Request	Update New Employee Health Care Assignment	Low
30167	Telco Generic	are there required fields?	Low
30210	Gap	Software doesn't support multi-currency	High
30301	System Change Request	New Period Close Reporting for Finance	Normal
30303	System Change Request	Need daily MRP run to start at 23:00 instead of 22:00 to accomodate for longer run times.	Low

Showing 1 to 5 of 200 [Prev](#) [Next](#) [Maximize](#)

Data Source

The screenshot shows the configuration window for a data source. The title bar reads "Data Source : DEMO - Request List Portlet - 1". The "Data Source Name" is "DEMO - Request List Portlet - 1" and the "Time-out" is set to "20" seconds. The "Reference Code" is "DEMO__REQUEST_LIST_PORTLET__1". The "Description" field is empty. The "Enabled" checkbox is checked, with "Yes" selected. Below this are tabs for "Data Source", "Filter Fields", "Portlet Definitions", and "Ownership". The "Full Query for the Data Source" field contains the following SQL query:

```
SELECT PRIORITY_MEANING MY_PRIORITY, request_id MY_REQUEST_NO
FROM KCRT_REQUESTS_V
WHERE 1=1
AND batch_number = 1
```

At the bottom, there are buttons for "Edit Query", "Verify", "OK", "Save", and "Cancel". A status message at the very bottom says "Save Successful."

Data Source : DEMO - Request List Portlet - 1

Data Source Name: DEMO - Request List Portlet - 1 Time-out Use Default 20 Seconds

Reference Code: DEMO_REQUEST_LIST_PORTLET__1

Description:

Enabled: Yes No

Data Source Filter Fields Portlet Definitions Ownership

Seq	Name	Token	Validation	Required	Enabled
1	Created By	CREATED_BY	IPM - User Names - Enabled	N	Y
2	Request Type(s)	REQUEST_TYPE_ID_LIST	IRT - Request Types - Enabled	N	Y
3	Priority	RTP_RL_PRIORITY	DEM Filter - Priority - Enabled (with blank)	N	Y

↑↓ New Edit Remove

Verify OK Save Cancel

*Save Successful.

Configure Portlet Definition: DEMO - Request List Portlet - 1

Portlet Type: List **Data Source:** DEMO - Request List Portlet - 1
Created By: **Last Modified By:** **Last Modification Date:** Aug 3, 2006

Name:

Category:

Description:

Default Width: Wide

Enabled: Yes No In use by 0 user(s), 0 module(s), and 1 hyperlink(s).

Display Columns

Columns may be displayed in the portlet by Default (in the user's initial view) or in the Maximized view only. Columns may be made optionally available for the user's selection.

Click on a column to select User Sortable

Columns Displayed by Default:

<input type="button" value="v"/>	<input type="button" value="^"/>	Priority	<input type="button" value="^"/>	My Priority	<input type="button" value="v"/>
<input type="button" value="v"/>	<input type="button" value="^"/>	Request #	<input type="button" value="^"/>	My Request No	<input type="button" value="v"/>

Columns Displayed by Default in Maximized View Only:

Columns Available for Display:

Arrange Data

Default Sort By:
 Ascending
 Descending

Default Rows Displayed: In Normal View
 In Maximized View

DEMO - Request List Portlet - 2

This is the other drill-to portlet and its various components.

Preferences:			
Request # Δ	Request Type	Description	Priority
30145	Enhancement Request	Update New Employee Health Care Assignment	Low
30167	Telco Generic	are there required fields?	Low
30210	Gap	Software doesn't support multi-currency	High
30301	System Change Request	New Period Close Reporting for Finance	Normal
30303	System Change Request	Need daily MRP run to start at 23:00 instead of 22:00 to accomodate for longer run times.	Low

Showing 1 to 5 of 200 [Prev](#) [Next](#) [Maximize](#)

Data Source

The screenshot shows a configuration window titled "Data Source : DEMO - Request List Portlet - 2". The window contains the following fields and options:

- Data Source Name:** DEMO - Request List Portlet - 2
- Time-out:** Use Default (dropdown), 20 (input), Seconds
- Reference Code:** DEMO__REQUEST_LIST_PORTLET__2
- Description:** (empty text box)
- Enabled:** Yes No
- Full Query for the Data Source:**

```
SELECT PRIORITY_MEANING MY_PRIORITY, request_id MY_REQUEST_NO, DESCRIPTION MY_DESCRIPTION,
REQUEST_TYPE_NAME MY_REQUEST_TYPE_NAME
FROM KCRT_REQUESTS_V
WHERE 1=1
AND batch_number = 1
```
- Use Bind Variables?:** Yes No
- Buttons:** Edit Query, Verify, OK, Save, Cancel

Save Successful.

Data Source : DEMO - Request List Portlet - 2

Data Source Name: DEMO - Request List Portlet - 2 Time-out Use Default 20 Seconds

Reference Code: DEMO_REQUEST_LIST_PORTLET__2

Description:

Enabled: Yes No

Data Source Filter Fields Portlet Definitions Ownership

Seq	Name	Filter	Validation	Required	Enabled
1	Created By	CREATED_BY	PPM - User Names - Enabled	N	Y
2	Request Type(s)	REQUEST_TYPE_ID_LIST	CRT - Request Types - Enabled	N	Y
3	Priority	PRT_PRL_PRIORITY	DEM Filter - Priority - Enabled (with blank)	N	Y

↑ ↓ New Edit Remove

Verify OK Save Cancel

Ready

Portlet Definition

Configure Portlet Definition: DEMO - Request List Portlet - 2

[Preview](#) [Save](#) [Done](#) [Cancel](#)

Portlet Type: List **Data Source:** DEMO - Request List Portlet - 2

Created By: **Last Modified By:** **Last Modification Date:** Aug 3, 2006

Name: DEMO - Request List Portlet - 2

Category: [Manage Categories](#)

Description:

Default Width: Wide

Enabled: Yes No In use by 0 user(s), 0 module(s), and 1 hyperlink(s). [View Usage](#) [Copy](#) [Delete](#)

[Display](#) [Preference Fields](#) [Access](#) [User Help](#)
Display Columns

Columns may be displayed in the portlet by Default (in the user's initial view) or in the Maximized view only. Columns may be made optionally available for the user's selection.

[Add Column](#) [Edit](#) [Delete](#)

Click on a column to select User Sortable

Columns Displayed by Default:

<input type="checkbox"/>	<input type="checkbox"/>	Request #	<input type="checkbox"/>	My Request No	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	Request Type	<input type="checkbox"/>	My Request Type Name	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	Description	<input type="checkbox"/>	My Description	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	Priority	<input type="checkbox"/>	My Priority	<input type="checkbox"/>

Columns Displayed by Default in Maximized View Only:

Columns Available for Display:

Arrange Data

Default Sort By: Request # Ascending Descending

Default Rows Displayed: 5 In Normal View
50 In Maximized View

[Preview](#) [Save](#) [Done](#) [Cancel](#)


Defining a Portlet Event

The following procedure describes how to define a portlet event. These instructions are applicable to the third step of the Portlet Definition wizard.

To define a portlet event for a column:

1. On the Set up Display Options step of the Create Portlet Definition (<Portlet Type>) page, from the Hyperlink Options section, select **Portlet Event**.
2. Click **Edit**.

The Edit Portlet Event Properties dialog box appears.



3. Provide an event topic. Use the auto-complete button to provide an existing event topic or click Manage event topics to add a new topic or delete an existing topic.

4. Click **Add Event Property**.

The Add Event Property dialog box appears.

5. Provide the event property details using the information from the following table.

Field Name (*Required)	Description
*Property Key	<p>Select the desired preference from the portlet definition. Choices are limited to the preference fields in the portlet definition.</p> <p>Or, provide an alphanumeric string up to 200 characters in length.</p>
*Property Value	<p>Indicate the data to use.</p> <p>Choices include:</p> <ul style="list-style-type: none"> • Data Source Column. Select a column. Choices are limited to the columns available in your data source. • Portlet source preference. Select the desired preference for the portlet. • Text. Provide an alphanumeric string up to 200 characters in length.

6. Click **Add**.

The information is added to the Edit Portlet Event Properties dialog box and the Add Event Property dialog box disappears.

7. (Optional) To delete an event property:

- Click the **Delete** icon next to the unwanted event property.
- Click **Delete All** to remove all the event properties at one time.

8. Once the event properties are correctly defined, click **Done**.

The Edit Portlet Event Properties dialog box disappears.

Continue with the configuration (and sharing) of your portlet as you normally would.

Managing Portlet Categories

Managing categories is an optional step when creating or maintaining portlet definitions.


Portlet categories define an entity, such as a request or a task. Portlet categories can also define functional groups, such as Development or Test. Adding one or more categories to a portlet can make a portlet easier to find.

Adding Portlet Categories

To add a portlet category:

1. Click **Manage Categories**, on either the:
 - Enter Portlet Information step of the Create Portlet Definition (<Portlet Type>) page
 - Configure Portlet Definition: <Portlet Definition> page

The Manage Categories dialog box appears.



2. Type a new category name in the **New Category** field.
3. Click **Add**.

The new category is added to the list.

4. Click **Done**.

The Manage Categories dialog box is closed.

Deleting Portlet Categories

To delete a portlet category:



HP-supplied portlet categories cannot be deleted. Also, you cannot delete a portlet category containing one or more portlet definition, and any such categories do not include a **Delete** icon.

1. Click **Manage Categories**, on either the:
 - Enter Portlet Information step of the Create Portlet Definition (<Portlet Type>) page
 - Configure Portlet Definition: <Portlet Definition> page

The Manage Categories dialog box appears.

2. Click the **Delete** icon next to the portlet category.

The portlet category is deleted.

3. Click **Done**.

The Manage Categories dialog box is closed.

Supplemental Details for the Set Up Display Option Step

This section provides relevant details for the Set up Display options for the various portlet types. This information is used in [step 7 on page 56](#).

List Portlet

Figure 3-4. Set up Display Options for list portlets

Create Portlet Definition (List)

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. **Set up Display Options** ▶ 4. Define Preferences
5. Configure Portlet Communication ▶ 6. Configure Access ▶ 7. Add User Help

Display Columns

Columns may be displayed in the portlet by Default (in the user's initial view) or in the Maximized view only. Columns may be made optionally available for the user's selection.

Add Column **Edit** **Delete**

Click on a column to select User Sortable

Columns Displayed by Default:

▲	Tasks	▲	OPEN_TASKS
---	-------	---	------------

Columns Displayed by Default in Maximized View Only:

▲	
---	--

Columns Available for Display:

Arrange Data

Default Sort By: Ascending Descending

*Default Rows Displayed: In Normal View
 In Maximized View

Cancel **Back** **Next**

Table 3-1. Set up Display Options field descriptions for list portlets (page 1 of 2)

Field Name (*Required)	Description
Display Columns section	
Add Column	Click to add a new column. See Adding Columns for details.
Edit	Select a column, then click to make changes to that column. See Editing Columns on page 106 for details.
Delete	Select a column, then click to remove that column. See Deleting Columns on page 107 for details.
Columns Displayed by Default	Use the up- and down-pointers to rearrange the order of the columns. Double-click on a column to edit it. Choices include the columns whose Display value is set to either By Default - Shown in user's initial view or Always - Cannot be removed by user .
Columns Displayed by Default in Maximized View Only	Use the up- and down-pointers to rearrange the order of the columns. Double-click on a column to edit it. Choices include the columns whose Display value is set to In Maximized View Only - Shown by default in Maximized View .
Columns Available for Display	Use the up- and down-pointers to rearrange the order of the columns. Double-click on a column to edit it. Choices include the columns whose Display value is set to Optional - Available for display by user .
Arrange Data section	
Default Sort By	Select the default column used to sort the data. Choices include the columns whose User Sortable value is set to Yes .

Table 3-1. Set up Display Options field descriptions for list portlets (page 2 of 2)

Field Name (*Required)	Description
Ascending/Descending	Indicate whether to sort the data in Ascending and Descending order.
*Default Rows Displayed in Normal View	Specify the default number of records displayed in a normal view portlet. Type any integer greater than zero.
*Default Rows Displayed in Maximized View	Specify the default number of records displayed in a maximized portlet. Type any integer greater than zero.

Adding Columns

To add a new column to a list portlet:

1. Click **Add Column**.

The Add Display Column dialog box opens.

Add Display Column

*Column Title:

*Column Type:

*Column Value: Visible Text Source:

Calculated:

Source contains HTML

Column Width:

Truncate after: Characters Show Full Text in Tooltip

Tooltip Value: Tooltip Source:

Calculated:

Source contains HTML

User Sortable: Yes No

Display: Optional - Available for display by user
 By Default - Shown in user's initial view
 In Maximized View Only - Shown by default in Maximized View
 Always - Cannot be removed by user

Hyperlink Options: No Hyperlink
 Hyperlink Source:
 Drilldown to Portlet: (None)
 Portlet Event:

2. Provide the column details using the information from the following table.



Many fields are dependent on the value for **Column Type** and the applicable fields may be described in multiple sections of the following table.

Field Name (*Required)	Description
All Column Types	
*Column Title	<p>Specify the column title to be displayed in the portlet.</p> <p>Type any alphanumeric string (up to 200 characters in length).</p> <p>Note: While the column title may be up to 200 characters in length, the PPM Dashboard, by default, displays only the first 20 characters. To increase (or decrease) the number of characters displayed by the PPM Dashboard, set the <code>dashboard.List-Column-Header-Size</code> parameter in the <code>server.conf</code> file. See the <i>Installation and Administration Guide</i> for more information about setting <code>server.conf</code> parameters.</p>
*Column Type	<p>Select the column type.</p> <p>Choices include:</p> <ul style="list-style-type: none">• Text• Text with Icon• Icon• Progress Bar

Field Name (*Required)	Description
Tooltip Value	<p>Specify the content that appears when a user's cursor hovers over an item. If the content contains HTML, select the Source contains HTML checkbox.</p> <ul style="list-style-type: none"> • Tooltip Source. Select the data column that contains the information to display in the tooltip. Choices are limited to those columns in the data source that are configured for this portlet definition on your PPM Center instance. • Calculated. Specify the content to display using Javascript to calculate the desired value (if a data column does not return the desired value or the desired value cannot be calculated using SQL). • Source contains HTML. Select to enable HTML support for Tooltip Value.
User Sortable	<p>Indicate whether or not the current column can be used for sorting purposes.</p>
Display	<p>Select how the column should be displayed. Choices include:</p> <ul style="list-style-type: none"> • Optional. Make the column available to the user in the portlet's edit page (Available Column). • By Default. Make the column visible in the portlet (Displayed Column). • In Maximized View Only. Make the column visible in the portlet's Maximized View only (Additional Columns Displayed in Maximized View). • Always. Make the column visible in the portlet (Displayed Column with asterisk).

Field Name (*Required)	Description
Hyperlink Options	<p>Specify whether the column can be linked to another page or portlet, or updates the other portlets on this page.</p> <p>Choices include:</p> <ul style="list-style-type: none"> ● No Hyperlink. Links to other pages are not allowed. ● Hyperlink Source. Link to the selected column. ● Drilldown to Portlet. Drill down to the selected portlet. See Defining a Drill-down Page on page 78 for details. ● Portlet Event. Update the portlets on this page. See Defining a Portlet Event on page 94 for details.
Column Type: Text and Text with Icon	
*Column Value	<p>Specify the content to display in the portlet. If the content contains HTML, select the Source contains HTML checkbox.</p> <ul style="list-style-type: none"> ● Visible Text Source. The content displayed is the value from the data column. Select from those columns in the data source that are configured for this portlet definition on your PPM Center instance. ● Calculated. Specify the content to display using Javascript to calculate the desired value (if a data column does not return the desired value or the desired value cannot be calculated using SQL). ● Source contains HTML. Select to enable HTML support for Column Value.
Column Width	<p>Select the width of the column relative to the other columns.</p> <p>Choices include:</p> <ul style="list-style-type: none"> ● Small ● Medium ● Large

Field Name (*Required)	Description
Truncate after <X> Characters	When the Source contains HTML checkbox for Column Value is selected, specify the number of characters to show in the column. Type any integer greater than zero.
Show Full Text in Tooltip	When a value is supplied for Truncate after <X> Characters , select to show the full text in the tooltip.
Column Type: Icon or Text with Icon	
*Column Value	<p>Select the icon to display in the portlet.</p> <ul style="list-style-type: none"> • Icon Source. The icon displayed is the value from the data column. Select from those columns in the data source that are configured for this portlet definition on your PPM Center instance or a column predefined with icon URLs. • Calculated. Specify the content to display using Javascript to calculate the desired value (if a data column does not return the desired value or the desired value cannot be calculated using SQL).
Column Type: Progress Bar	
*Column Value	<p>Select the percentage data to display in the portlet.</p> <ul style="list-style-type: none"> • Percentage Source. The percentage displayed is the value from the data column. Select from those columns in the data source that are configured for this portlet definition on your PPM Center instance or a column predefined with percentage information. • Calculated. Specify the content to display using Javascript to calculate the desired value (if a data column does not return the desired value or the desired value cannot be calculated using SQL).

Field Name (*Required)	Description
Color Value	<p>Select a color map to use.</p> <ul style="list-style-type: none"> • Color Source. Select the color map's data column. Select from those columns in the data source that are configured for this portlet definition on your PPM Center instance. • Calculated. Specify the content to display using Javascript to calculate the desired value (if a data column does not return the desired value or the desired value cannot be calculated using SQL). <p>See Selecting Portlet Colors on page 131 for details.</p>

The following are examples of **Calculated** values.

If you want the content to display a percentage as a whole number but the data column returns a decimal number, specify the following in the dialog to calculate the percentage:

```
var return_value=<DATA_COLUMN>*100;
```

To calculate a project's status based on the number of unassigned tasks, specify the following in the dialog to calculate status values. This example is for Column Type **Icon** or **Text with Icon** and sets the icon status to green if there are no unassigned tasks, yellow if there are less than five unassigned tasks, and red if there are five or more unassigned tasks.

```
var numTasks = "<DATA_COLUMN_UnassignedTasks>";
var image;

if (numTasks == 0)
    image = "images/green.gif";
else if (numTasks < 5)
    image = "images/yellow.gif";
else
    image = "images/red.gif";

return_value=image;
```

3. Click **Done**.

The Add Display Column dialog box closes and the new column is added to the Create Portlet Definition (List) page.

Editing Columns

To modify an existing column in a list portlet:

1. Select the column to be modified and click Edit (or double-click the column).

The Edit Display Column: *<Column Title>* dialog box opens.

HP logo Close Window X

Edit Display Column: Status

*Column Title: Status

*Column Type: Text

*Visible Text Source: STATUS Source contains HTML

Column Width: Small

Truncate after: Characters Show Full Text in Tooltip

Tooltip Source: Source contains HTML

User Sortable: Yes No

Display: Optional - Available for display by user
By Default - Shown in user's initial view
in Maximized View Only - Shown by default in Maximized View
Always - Cannot be removed by user

Hyperlink Options: No Hyperlink
Hyperlink Source: COPY_URL
Drilldown to Portlet: TMG - Total Hrs by Work Item Edit

Done Cancel

Copyright © 2004 Mercury Close Window X

2. Make the desired changes using the information from the table in [step 2 on page 101](#) as a guideline.



Many fields are dependent on the value for **Column Type** and the applicable fields may be described in multiple sections of that table.

3. Click **Done**.

The Edit Display Column: *<Column Title>* dialog box closes and any applicable changes are noted on the Create Portlet Definition (List) page.

Deleting Columns

To delete an existing column from a list portlet:

1. Select the column to be removed.
2. Click **Delete**.

The column is deleted from the Create Portlet Definition (List) page.

Pivot Table Portlet

Figure 3-5. Set up Display Options for pivot table portlets

Create Portlet Definition (Pivot Table)

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. Set up Display Options ▶ 4. Define Preferences
5. Configure Portlet Communication ▶ 6. Configure Access ▶ 7. Add User Help

Dimension

Data columns may be displayed in the pivot row, column dimensions or used as paging filters.

[Add Column](#) [Add Measurement](#) [Edit](#) [Delete](#)

Click on a column to select, double-click to edit

Data columns displayed in the pivot Row Dimension

[▲](#)
[▼](#)

Data columns displayed in the pivot Column Dimension

[▲](#)
[▼](#)

Data columns used as pivot paging filters

[▲](#)
[▼](#)

Data columns used as pivot measurements

[▲](#)
[▼](#)

Display Options

Enable aggregation configuration Aggregation function: ▼
 Display empty cells Totals aggregation function: ▼
 Display row/column totals
 Display subtotals

Hyperlink Options: No Hyperlink
 Drilldown to Portlet: (None) [Edit](#)
 Portlet Event: [Edit](#)

[Cancel](#) [◀ Back](#) [Next ▶](#)

Table 3-2. Set up Display Options field descriptions for pivot table portlets
(page 1 of 3)

Field Name (*Required)	Description
Dimension section	
Add Column	Click to add a new data column. See Adding a Pivot Table Row, Column, or Paging Filter Data Column for details.
Add Measurement	Click to add a new measurement data column. See Adding a Pivot Table Measurement Data Column for details.
Edit	Select a data column, then click to make changes to that data column. You can also double-click on a specific data column to edit that data column.
Delete	Select a data column, then click to remove that column.
Data columns displayed in the pivot row dimension	Use the up- and down-pointers to rearrange the order of the data columns. Double-click on a data column to edit it. This data is displayed one row per category.
Data columns displayed in the pivot column dimension	Use the up- and down-pointers to rearrange the order of the data columns. Double-click on a data column to edit it. This data is displayed one column per category.
Data columns used as pivot paging filters	Use the up- and down-pointers to rearrange the order of the data columns. Double-click on a data column to edit it. This data is displayed one table per category.

Table 3-2. Set up Display Options field descriptions for pivot table portlets
(page 2 of 3)

Field Name (*Required)	Description
Data columns used as pivot measurements	Use the up- and down-pointers to rearrange the order of the data columns. Double-click on a data column to edit it. This is the data that is summarized in the table.
Display Options section	
Enable aggregation configuration	By default, aggregation is enabled. Aggregation configuration is the calculation of values based on the selected Totals aggregation function . Disable aggregation if the data source aggregates the data.
Aggregation function	Select a function to determine how to calculate a value if the data source contains more than one value for a distinct data column.
Display empty cells	If the data source does not contain any data, the row or column is not displayed. Select this checkbox to display empty cells.
Totals aggregation function	Select a function to determine how to calculate the totals for the displayed values.

Table 3-2. Set up Display Options field descriptions for pivot table portlets
(page 3 of 3)

Field Name (*Required)	Description
Display row/column totals	Select to display totals for all rows and columns. The value is calculated using the selected Totals aggregation function .
Display subtotals	Select to display subtotals for each row or column. The value is calculated using the selected Totals aggregation function .
Hyperlink Options	Specify whether the column can be linked to another page or portlet, or updates the other portlets on this page. Choices include: <ul style="list-style-type: none"> • No Hyperlink. Links to other pages are not allowed. • Drilldown to Portlet. Drill down to the selected portlet. See Defining a Drill-down Page on page 78 for details. • Portlet Event. Update the portlets on this page. See Defining a Portlet Event on page 94 for details.

Adding a Pivot Table Row, Column, or Paging Filter Data Column

To add a new data column (row, column, or paging filter) to a pivot table portlet:

1. Click **Add Column**.

The Add Pivot Column dialog box opens.

2. Provide the column details using the information from the following table.

Field Name (*Required)	Description
*Column Title	Specify the column title to display in the portlet. Type any alphanumeric string (up to 200 characters in length).
*Data Source Column	Select a source column for the information to display in the pivot table column.
Dimension	<p>Select the dimension of the data. Choices include:</p> <ul style="list-style-type: none"> • Add this column to the pivot rows dimension. Data is displayed one row per category. Categories are determined by the values from the data source. • Add this column to the pivot columns dimension. Data is displayed one column per category. Categories are determined by the values from the data source. • Add this column as a pivot paging filter. Data is displayed one table per category. Categories are determined by the values from the data source.

3. Click **Done**.

The Add Pivot Column dialog box closes and a new data column is added to the Create Portlet Definition (Pivot Table) page.

Adding a Pivot Table Measurement Data Column

To add a new measurement data column to a pivot table portlet:

1. Click **Add Measurement**.

The Add Measurement dialog box opens.

The screenshot shows the 'Add Measurement' dialog box with the following fields and options:

- *Column Title:** A text input field.
- *Data Source Column:** A dropdown menu with 'EFFORT_HOVER' selected.
- Symbol:** Three radio buttons: 'None' (selected), '%', and 'Currency Symbol'. A text input field is next to the 'Currency Symbol' option.
- *Number Precision:** A text input field with '0' and the text 'digits following the decimal point'.

Buttons: Done, Cancel

2. Provide the column details using the information from the following table.

Field Name (*Required)	Description
*Column Title	Specify the column title to display in the portlet. Type any alphanumeric string (up to 200 characters in length).
*Data Source Column	Select a source column for the information to display in the pivot table.
Symbol	Select the symbol to display for the measurement. Choices include: <ul style="list-style-type: none">• None. Do not display a symbol.• %. Display the percentage symbol.• Currency Symbol. Select the currency symbol to display.
*Number Precision	Specify the number of decimal places to display.

3. Click **Done**.

The Add Measurement dialog box closes and a new measurement data column is added to the Create Portlet Definition (Pivot Table) page.

Figure 3-6. Set up Display Options for bar chart portlets




Table 3-3. Set up Display Options field descriptions for bar chart portlets (page 1 of 2)

Field Name (*Required)	Description
Chart Title	Specify a name for the chart. Type any alphanumeric string (up to 200 characters in length).
*Bar Source	Select a source column for the information to be displayed on the bar axis. Choices are limited to those columns available in your portlet data source.
Bar Axis Label	Specify the label for the bar axis. Type any alphanumeric string (up to 200 characters in length.)
*Bar Value Source	Select a <i>numeric</i> source column for the information to be displayed on the value axis (the length of each bar). Choices are limited to those columns available in your portlet data source.

Table 3-3. Set up Display Options field descriptions for bar chart portlets
(page 2 of 2)

Field Name (*Required)	Description
Value Axis Label	Specify the label for the value axis. Type any alphanumeric string (up to 200 characters in length.)
Orientation	Indicate the orientation of the bars. Choices include: <ul style="list-style-type: none"> • Horizontal • Vertical
Color Source	Select the source for the color. See Selecting Portlet Colors on page 131 for details.
Tooltip Source	Select the source column for the tooltip to be displayed when the cursor hovers over an item. Choices are limited to those columns available in your portlet data source.
Hyperlink Options	Specify whether the column can be linked to another page or portlet, or updates the other portlets on this page. Choices include: <ul style="list-style-type: none"> • No Hyperlink. Links to other pages are not allowed. • Hyperlink Source. Link to the selected column. • Drilldown to Portlet. Drill down to the selected portlet. See Defining a Drill-down Page on page 78 for details. • Portlet Event. Update the portlets on this page. See Defining a Portlet Event on page 94 for details.

Clustered Bar Chart Portlet

Figure 3-7. Set up Display Options for clustered bar chart portlets




Table 3-4. Set up Display Options field descriptions for clustered bar chart portlets (page 1 of 3)

Field Name (*Required)	Description
Chart Title	Specify a name for the chart. Type any alphanumeric string (up to 200 characters in length).
*Cluster Source	Select a source column for the information to be displayed in the cluster. Choices are limited to those columns available in your portlet data source.
Cluster Axis Label	Specify the label for the cluster axis. Type any alphanumeric string (up to 200 characters in length.)
*Bar Source	Select a source column for the information to be displayed for the bars. Choices are limited to those columns available in your portlet data source.

Table 3-4. Set up Display Options field descriptions for clustered bar chart portlets (page 2 of 3)

Field Name (*Required)	Description
Bar Label	Specify the label for the legend. Type any alphanumeric string (up to 200 characters in length.)
*Bar Value Source	Select a <i>numeric</i> source column for the information to be displayed on the value axis (the length of each bar). Choices are limited to those columns available in your portlet data source.
Value Axis Label	Specify the label for the value axis. Type any alphanumeric string (up to 200 characters in length.)
Orientation	Indicate the orientation of the bars. Choices include: <ul style="list-style-type: none"> • Horizontal • Vertical

Table 3-4. Set up Display Options field descriptions for clustered bar chart portlets (page 3 of 3)

Field Name (*Required)	Description
Color Source	<p>Select the source for the color.</p> <p>See Selecting Portlet Colors on page 131 for details.</p>
Tooltip Source	<p>Select the source column for the tooltip to be displayed when the cursor hovers over an item. Choices are limited to those columns available in your portlet data source.</p>
Hyperlink Options	<p>Specify whether the column can be linked to another page or portlet, or updates the other portlets on this page.</p> <p>Choices include:</p> <ul style="list-style-type: none"> • No Hyperlink. Links to other pages are not allowed. • Hyperlink Source. Link to the selected column. • Drilldown to Portlet. Drill down to the selected portlet. See Defining a Drill-down Page on page 78 for details. • Portlet Event. Update the portlets on this page. See Defining a Portlet Event on page 94 for details.

Stacked Bar Chart Portlet

Figure 3-8. Set up Display Options for stacked bar chart portlets




Table 3-5. Set up Display Options field descriptions for stacked bar chart portlets (page 1 of 2)

Field Name (*Required)	Description
Chart Title	Specify a name for the chart. Type any alphanumeric string (up to 200 characters in length).
*Bar Source	Select a source column for the information to be displayed on the bar axis. Choices are limited to those columns available in your portlet data source.
Bar Axis Label	Specify the label for the bar axis. Type any alphanumeric string (up to 200 characters in length).
*Bar Division Source	Select the source column for the bar divisions. Choices are limited to those columns available in your portlet data source.
Bar Division Label	Specify the label for the bar divisions.

Table 3-5. Set up Display Options field descriptions for stacked bar chart portlets (page 2 of 2)

Field Name (*Required)	Description
*Bar Division Value Source	Select a <i>numeric</i> source column for the information to be displayed on the value axis (the length of each bar). Choices are limited to those columns available in your portlet data source.
Value Axis Label	Specify the label for the value axis. Type any alphanumeric string (up to 200 characters in length.)
Orientation	Indicate the orientation of the bars. Choices include: <ul style="list-style-type: none"> • Horizontal • Vertical
Color Source	Select the source for the color. See Selecting Portlet Colors on page 131 for details.
Tooltip Source	Select the source column for the tooltip to be displayed when the cursor hovers over an item. Choices are limited to those columns available in your portlet data source.
Hyperlink Options	Specify whether the column can be linked to another page or portlet, or updates the other portlets on this page. Choices include: <ul style="list-style-type: none"> • No Hyperlink. Links to other pages are not allowed. • Hyperlink Source. Link to the selected column. • Drilldown to Portlet. Drill down to the selected portlet. See Defining a Drill-down Page on page 78 for details. • Portlet Event. Update the portlets on this page. See Defining a Portlet Event on page 94 for details.

Figure 3-9. Set up Display Options for pie chart portlets




Table 3-6. Set up Display Options field descriptions for pie chart portlets (page 1 of 2)

Field Name (*Required)	Description
Chart Title	Specify a name for the chart. Type any alphanumeric string (up to 200 characters in length).
*Wedge Source	Select the source column for the wedge (pie slice). Choices are limited to those columns available in your portlet data source.
*Wedge Size Source	Select the <i>numeric</i> source column which determines the size of each wedge. Choices are limited to those columns available in your portlet data source.
Wedge Label	Specify a label for the wedges. Type any alphanumeric string (up to 200 characters in length).

Table 3-6. Set up Display Options field descriptions for pie chart portlets
(page 2 of 2)

Field Name (*Required)	Description
Color Source	<p>Select the source for the color.</p> <p>See Selecting Portlet Colors on page 131 for details.</p>
Tooltip Source	<p>Select the source column for the tooltip to be displayed when the cursor hovers over an item. Choices are limited to those columns available in your portlet data source.</p>
Hyperlink Options	<p>Specify whether the column can be linked to another page or portlet, or updates the other portlets on this page.</p> <p>Choices include:</p> <ul style="list-style-type: none"> • No Hyperlink. Links to other pages are not allowed. • Hyperlink Source. Link to the selected column. • Drilldown to Portlet. Drill down to the selected portlet. See Defining a Drill-down Page on page 78 for details. • Portlet Event. Update the portlets on this page. See Defining a Portlet Event on page 94 for details.

Figure 3-10. Set up Display Options for line chart portlets




Table 3-7. Set up Display Options field descriptions for line chart portlets (page 1 of 2)

Field Name (*Required)	Description
Chart Title	Specify a name for the chart. Type any alphanumeric string (up to 200 characters in length).
Chart Subtype	Select Line to set up display options for this portlet.
*X-Axis Source	Select the source column for the x-axis. Choices are limited to those columns available in your portlet data source.
X-Axis Scale	Select a scale for the x-axis. Choices include ordinal (an ordered sequence or ranking) and numeric .
X-Axis Label	Specify a label for the x-axis. Type any alphanumeric string (up to 200 characters in length).

Table 3-7. Set up Display Options field descriptions for line chart portlets
(page 2 of 2)

Field Name (*Required)	Description
*Y-Axis Source	Select the <i>numeric</i> source column for the y-axis. Choices are limited to those columns available in your portlet data source.
Y-Axis Label	Specify a label for the y-axis. Type any alphanumeric string (up to 200 characters in length).
*Line Source	Select the source column for each line. Choices are limited to those columns available in your portlet data source.
Line Label	Specify a label for the legend. Type any alphanumeric string (up to 200 characters in length).
Color Source	Select the source for the color. See Selecting Portlet Colors on page 131 for details.
Tooltip Source	Select the source column for the tooltip to be displayed when the cursor hovers over an item. Choices are limited to those columns available in your portlet data source.
Hyperlink Options	Specify whether the column can be linked to another page or portlet, or updates the other portlets on this page. Choices include: <ul style="list-style-type: none"> • No Hyperlink. Links to other pages are not allowed. • Hyperlink Source. Link to the selected column. • Drilldown to Portlet. Drill down to the selected portlet. See Defining a Drill-down Page on page 78 for details. • Portlet Event. Update the portlets on this page. See Defining a Portlet Event on page 94 for details.

XY (Scatter) Line Chart Portlet

Select an XY line chart to display data points without connecting lines.

Figure 3-11. Set up Display Options for XY (scatter) line chart portlets

Create Portlet Definition (Line Chart)

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. **Set up Display Options** ▶ 4. Define Preferences
5. Configure Portlet Communication ▶ 6. Configure Access ▶ 7. Add User Help


Data Source Mapping to Chart

Select a data source column to map to each chart property:

Chart Title:

Chart Subtype: XY (Scatter) ▼

* X-Axis Source: ASSIGNED_TO_EMAIL ▼

X-Axis Scale: Ordinal ▼ 

X-Axis Label: ASSIGNED_TO_EMAIL

* Y-Axis Source: ASSIGNED_TO_EMAIL ▼

Y-Axis Label: ASSIGNED_TO_EMAIL

* Series Source: ASSIGNED_TO_EMAIL ▼

Series Label: ASSIGNED_TO_EMAIL

Color Source:

Tooltip Source:

Hyperlink Options:

No Hyperlink

Hyperlink Source: ASSIGNED_TO_EMAIL ▼


Drilldown to Portlet: (None)

Portlet Event:

Sample XY Chart

Chart Title

Y-Axis Label



(Y Value) n

n

n

n

n

(X Value) n

n

n

n

n

X-Axis Label

Series Label

Series G Series H Series I

Series J Series K

Table 3-8. Set up Display Options field descriptions for XY (scatter) line chart portlets (page 1 of 3)

Field Name (*Required)	Description
Chart Title	Specify a name for the chart. Type any alphanumeric string (up to 200 characters in length).
Chart Subtype	Select XY (Scatter) to set up display options for this portlet.
*X-Axis Source	Select the source column for the x-axis. Choices are limited to those columns available in your portlet data source.
X-Axis Scale	Select a scale for the x-axis. Choices include ordinal (an ordered sequence or ranking) and numeric .

Table 3-8. Set up Display Options field descriptions for XY (scatter) line chart portlets (page 2 of 3)

Field Name (*Required)	Description
X-Axis Label	Specify a label for the x-axis. Type any alphanumeric string (up to 200 characters in length).
*Y-Axis Source	Select the <i>numeric</i> source column for the y-axis. Choices are limited to those columns available in your portlet data source.
Y-Axis Label	Specify a label for the y-axis. Type any alphanumeric string (up to 200 characters in length).
*Series Source	Select the source column for each series. Choices are limited to those columns available in your portlet data source.
Series Label	Specify a label for the legend. Type any alphanumeric string (up to 200 characters in length).

Table 3-8. Set up Display Options field descriptions for XY (scatter) line chart portlets (page 3 of 3)

Field Name (*Required)	Description
Color Source	<p>Select the source for the color.</p> <p>See Selecting Portlet Colors on page 131 for details.</p>
Tooltip Source	<p>Select the source column for the tooltip to be displayed when the cursor hovers over an item. Choices are limited to those columns available in your portlet data source.</p>
Hyperlink Options	<p>Specify whether the column can be linked to another page or portlet, or updates the other portlets on this page.</p> <p>Choices include:</p> <ul style="list-style-type: none"> • No Hyperlink. Links to other pages are not allowed. • Hyperlink Source. Link to the selected column. • Drilldown to Portlet. Drill down to the selected portlet. See Defining a Drill-down Page on page 78 for details. • Portlet Event. Update the portlets on this page. See Defining a Portlet Event on page 94 for details.

Radar (Spider) Line Chart Portlet

Select a radar line chart to display cyclic data or data that has no natural order. This chart uses the polar coordinate system.

Figure 3-12. Set up Display Options for radar (spider) line chart portlets

Create Portlet Definition (Line Chart)

1. Choose Portlet Type ▶ 2. Enter Portlet Information ▶ 3. Set up Display Options ▶ 4. Define Preferences
5. Configure Portlet Communication ▶ 6. Configure Access ▶ 7. Add User Help


Data Source Mapping to Chart

Select a data source column to map to each chart property.

Chart Title:

Chart Subtype: Radar (Spider) ▼

* **Category Source:** ASSIGNED_TO_EMAIL ▼

Category Scale: Ordinal ▼ 

* **Distance Source:** ASSIGNED_TO_EMAIL ▼

* **Line Source:** ASSIGNED_TO_EMAIL ▼

Line Label:

Color Source:

Tooltip Source:

Hyperlink Options:

No Hyperlink

Hyperlink Source: ▼

Drilldown to Portlet: (None)

Portlet Event:

Sample Radar Chart




Table 3-9. Set up Display Options field descriptions for radar (spider) line chart portlets (page 1 of 2)

Field Name (*Required)	Description
Chart Title	Specify a name for the chart. Type any alphanumeric string (up to 200 characters in length).
Chart Subtype	Select Radar (Spider) to set up display options for this portlet.
*Line Source	Select the source column for each line. Choices are limited to those columns available in your portlet data source.
Line Label	Specify a label for the legend. Type any alphanumeric string (up to 200 characters in length).

Table 3-9. Set up Display Options field descriptions for radar (spider) line chart portlets (page 2 of 2)

Field Name (*Required)	Description
*Category Source	Select the source column for each category on the angular coordinate. Choices are limited to those columns available in your portlet data source.
Category Scale	Select a scale for the category. Choices include ordinal (an ordered sequence or ranking) and numeric .
*Distance Source	Select the source column for each radial coordinate (distance from the center pole). Choices are limited to those columns available in your portlet data source.
Color Source	Select the source for the color. See Selecting Portlet Colors on page 131 for details.
Tooltip Source	Select the source column for the tooltip to be displayed when the cursor hovers over an item. Choices are limited to those columns available in your portlet data source.
Hyperlink Options	Specify whether the column can be linked to another page or portlet, or updates the other portlets on this page. Choices include: <ul style="list-style-type: none"> • No Hyperlink. Links to other pages are not allowed. • Hyperlink Source. Link to the selected column. • Drilldown to Portlet. Drill down to the selected portlet. See Defining a Drill-down Page on page 78 for details. • Portlet Event. Update the portlets on this page. See Defining a Portlet Event on page 94 for details.

Bubble Chart Portlet

Figure 3-13. Set up Display Options for bubble chart portlets




Table 3-10. Set up Display Options field descriptions for bubble chart portlets (page 1 of 2)

Field Name (*Required)	Description
Chart Title	Specify a name for the chart. Type any alphanumeric string (up to 200 characters in length).
*X-Axis Source	Select the source column for the x-axis. Choices are limited to those columns available in your portlet data source.
X-Axis Label	Specify a label for the x-axis. Type any alphanumeric string (up to 200 characters in length).
*Y-Axis Source	Select the <i>numeric</i> source column for the y-axis. Choices are limited to those columns available in your portlet data source.

Table 3-10. Set up Display Options field descriptions for bubble chart portlets
(page 2 of 2)

Field Name (*Required)	Description
Y-Axis Label	Specify a label for the y-axis. Type any alphanumeric string (up to 200 characters in length).
*Bubble Size Source	Select the source column for the size of the bubble. Choices are limited to those columns available in your portlet data source.
Bubble Size Label	Specify the label for the bubble size. Type any alphanumeric string (up to 200 characters in length).
Color Source	Select the source for the color. See Selecting Portlet Colors for details.
Color Label Source	Select the source for the labels associated with the colors.
Color Label	Specify the label for the legend. Type any alphanumeric string (up to 200 characters in length).
Tooltip Source	Select the source column for the tooltip to be displayed when the cursor hovers over an item. Choices are limited to those columns available in your portlet data source.
Hyperlink Options	Specify whether the column can be linked to another page or portlet, or updates the other portlets on this page. Choices include: <ul style="list-style-type: none"> • No Hyperlink. Links to other pages are not allowed. • Hyperlink Source. Link to the selected column. • Drilldown to Portlet. Drill down to the selected portlet. • Portlet Event. Update the portlets on this page. See Defining a Portlet Event on page 94 for details.



You can limit the number of bubbles displayed in the bubble chart by setting the `MAX_BUBBLE_CHART_RESULT` parameter. By default, up to 500 bubbles are displayed. See the *Installation and Administration Guide* for more information about setting this parameter.

Setting the Displayed Color Label Length for a Bubble Chart

If the legend of a bubble chart contains many color labels, the labels may be truncated. You can extend the displayed color label length by doing the following:

1. Edit the `<PPM_Home>/server/<PPM_Server_Name>/deploy/dashboard.war/static/app/portlet/css/BubbleChart.css` file:
 - a. Find the `maxLegendItemLength` key and increase its value. The value is in pixels. About 1,000 pixels is equal to the 200 character color label length limit.
 - b. Save the file.
2. Repeat [step 1](#) for all nodes in a cluster.
3. Restart the PPM Server.

Selecting Portlet Colors

Most of the portlet types include the option to specify particular colors for a portlet. Unlike the default color map that selects and changes the colors seemingly at random, the colors you specify will always be used when the portlet is displayed.

To specify color mappings for a portlet requires configuration of the:

- Portlet data source
- Portlet definition

Defining Color Maps in the Portlet Data Source

To specify a color map for a portlet, refer to [Chapter 2, *Creating and Maintaining Portlet Data Sources*](#), on page 17. In the section [Completing the Data Source Tab](#) on page 25, you will need to add (or modify) columns to specify the color map.

In general, color mappings:

- Should correspond to the column used in the Order By clause
- Can be indicated for one or more of the Order By values
- Color can be specified by:
 - Name (such as LemonChiffon)
 - Hexadecimal code (for example, #FFFACD)

Names or codes are case-insensitive. That is, DarkGoldenRod is the same as DARKgoldenROD and #B8860B is the same as #b8860b.

[Appendix A, *Color Names*, on page 153](#), provides a comprehensive list of color names and some recommendations about their use.



Specific colors can also be specified based on portlet field labels; however, these settings are instance-wide. This can be especially helpful for making colors consistent for field labels such as High, Medium, or Low. See the *Customizing the Standard Interface* guide for details.

[Figure 3-14](#) shows examples of these settings in the **Select** section of the Select/From tab of the Query Definition window (see [Chapter 2, *Creating and Maintaining Portlet Data Sources*, on page 17](#) for details about this window).


- The values for priority_code column include the priorities associated with a request (of the type being displayed in this portlet):
 - Normal
 - Low
 - High
 - Critical
 - None
- The Display_Order column ranks the values of the priority codes
- The Order By clause specifies the use of the Display_Order column

- The Color column specifies the relationship of the colors to the display order as follows:
 - Wheat (by hexadecimal code) for Normal
 - MistyRose for Low
 - The default color for High (which means the color is subject to change)
 - CadetBlue for Critical
 - Tomato for None



The colors shown in this example, as well as the choice of portlet are probably unrealistic. You probably want to select colors that are meaningful to your organization and more practical than those selected for this example.

Figure 3-14. Color map in the portlet data source




Specifying the Color Map in the Portlet Definition

Once a portlet data source includes a color map, you can specify its use in a color specification–enabled portlet.

Figure 3-15 shows a preview of a pie chart that uses the default color map.


As shown in *Figure 3-17* on page 135, specifying a color map can help establish consistency of the portlet coloration and, potentially, its interpretation.

Figure 3-15. Default color map




To specify use of a color map available in a portlet's data source, select the color map's column for the **Color Source** as shown in *Figure 3-16*.

Figure 3-16. Set up Display Options with color specification



The resulting preview is shown in *Figure 3-17*.

Figure 3-17. Selected color mappings



4 Creating and Maintaining PPM Dashboard Pages and Modules

About PPM Dashboard Pages and Modules

Modules are either provided by HP or application administrators and can be supplied to users as either preconfigured Dashboard pages or “shared.” Modules must have a unique name and can contain one or more Dashboard pages, each with one or more portlets.

Preconfigured Dashboard Pages

Preconfigured Dashboard pages are modules that users can add to their Private pages folder. These pages are useful in situations where users routinely use the same (basic) page setup. These preconfigured Dashboard pages can be edited and personalized by users to increase their usefulness. Preconfigured Dashboard pages are provided by either HP or application administrators.

HP-Provided Preconfigured Pages

Preconfigured Dashboard pages that are provided by HP are added using the **Add preconfigured pages** drop-down menu item located on the Personalize Dashboard page (see *Figure 4-1*). Once clicked, the Add Preconfigured Pages to Dashboard dialog box opens (see *Figure 4-2*).

Application Administrator-Provided Preconfigured Pages

Preconfigured Dashboard pages that are provided by application administrators appear in the Shared pages folder on the Personalize Dashboard page (such as Sample, shown in *Figure 4-1*). Once moved to the Private pages folder (using **Copy** and **Paste** functionality) the module can be personalized by the user; modules appearing in the Shared pages folder cannot be edited.

Figure 4-1. Personalize Dashboard page





Figure 4-2. Add Preconfigured Pages to Dashboard dialog box



Shared Dashboard Pages

Shared Dashboard pages are modules that are created by application administrators and users find these in their Shared pages folder. Shared modules can be configured such that users can copy them to the Private pages folder and edit them (therefore behaving much like preconfigured Dashboard pages), or shared modules can be made uneditable—these type of modules are especially useful when application administrators want to share specific details and status with their stakeholders.

Landing Page (Default PPM Dashboard Page)

The landing page is the default PPM Dashboard page that displays when a user logs on to PPM Center. This page can be configured by the application administrator.

If the user does not have access to the module that contains the landing page, the user's first private page is used as the default PPM Dashboard page. If the user also does not have any private pages configured, the first shared page is used as the default PPM Dashboard page.

For information on how to configure this page, see *Configuring the Landing Page (Default PPM Dashboard Page)* on page 150.

Searching for Modules

To search for an existing module:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Modules > Configure Modules**.

The Configure Modules page appears.

Configure Modules

Search for a Module to Configure Reset Form

Name starts with:

Created By:

Last Updated From: To:

Available to Users: Groups: Org-Units:

Status:

Sort By: Ascending Descending Results Displayed Per Page:

Search

3. Provide the search criteria using the information from the following table.

Field Name (*Required)	Description
Name starts with	Specify a string. The search results display all modules whose name starts with the specified string. Type any alphanumeric string (up to 255 characters in length).
Created By	Select the user who created the module.
Last Updated From <Date> To <Date>	Select the date range when the module was last updated.
Available to Users	Select one or more users who have access to the module.
Groups	Select one or more groups who have access to the module.

Field Name (*Required)	Description
Org-Units	Select one or more groups who have access to the module.
Status	Select the status criteria: Choices include: <ul style="list-style-type: none"> • All • Enabled • Disabled
Sort By	Select the sort criteria. Choices include: <ul style="list-style-type: none"> • Name • Last Updated On • Status
Ascending/Descending	Indicate the sorting sequence.
*Results Displayed Per Page	Specify the maximum number of search results to display on a page. Type any integer, including zero.



Click **Reset Form** if you would like to clear your current search criteria.

4. Click **Search**.

The Configure Modules page is updated to include the search results which are displayed in the **Select a Module to Configure** section. If the list of results is long, click **Prev** and **Next** to navigate the list.

The screenshot displays the 'Configure Modules' interface. At the top, it states: 'These Modules are maintained only by Administrators. Users that wish to personalize module pages must copy the pages to their private dashboard area.' Below this is a table titled 'Select a Module to Configure' with columns for Name, Description, Last Updated On, and Status. The table lists several modules, each with a checkbox and a delete icon. Below the table are buttons for 'Configure Modules', 'All', and 'None'. Underneath is a search form titled 'Search for a Module to Configure' with fields for Name starts with, Created By, Last Updated From, To, Available to Users, Groups, Org-Units, Status, and Sort By. A 'Search' button is located at the bottom right of the search form.

Name	Description	Last Updated On	Status
<input type="checkbox"/> AH - TEMP	just a test. should be deleted	March 12, 2007	Enabled
<input type="checkbox"/> AH - test 2		March 12, 2007	Enabled
<input type="checkbox"/> Capital Exposure	Dashboard to display the state of capitalized costs in the current portfolio broken down by project.	March 12, 2007	Enabled
<input type="checkbox"/> Demand Manager	Contains the default set of portlets for an organization's Demand Manager.	March 12, 2007	Enabled
<input type="checkbox"/> New Module	dsmplr	March 12, 2007	Enabled
<input type="checkbox"/> Portfolio Manager	Contains the default set of portlets for a Portfolio Manager.	March 12, 2007	Enabled
<input type="checkbox"/> Program Manager	Contains a list of portlets useful to a Program Manager.	March 12, 2007	Enabled
<input type="checkbox"/> Standard PPM Dashboard	Standard PPM Dashboard	March 12, 2007	Enabled
<input type="checkbox"/> Team Manager	Contains the default set of portlets for a manager of a team's demand.	March 12, 2007	Enabled
<input type="checkbox"/> Time Management	Contains portlets for a new Time Management user.	March 12, 2007	Enabled

From the Configure Modules page you can:

- **Select a module.** In the **Select a Module to Configure** section, either select the checkbox associated with the desired module or click the link for the module.
- **Delete a module.** In the **Select a Module to Configure** section, click the delete icon next to the module you want to delete.
- **Sort the modules.** In the **Select a Module to Configure** section, click on a column header to change the sort criteria or sequence.
- **Refine your search.** In the **Search for a Module to Configure** section, provide the search criteria detailed in [step 3](#).

Creating Modules

To create a module:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Modules > Create a Module**.

The Create Module page appears.

Create Module

Create

Header

Module Name:

Description:

Enabled: Yes No

Create



If you are already in the Personalize Dashboard page, you can highlight **Modules** and select **New Module** from the drop-down menu to create a new module.

3. In the **Module Name** field, type the name of the module.
4. (Optional, although highly recommended) In the **Description** field, type a brief description of the module.
5. (Optional) Select the desired **Enabled** option.

6. Click **Create**.

The Personalize Dashboard page appears and includes the Configure: *<Module_Name>* display.

The screenshot shows a web browser window titled "Configure: New Module 0". On the left is a tree view with "Modules", "New Module 0", and "New Page". The main content area has a "Save" button in the top right. It is divided into three sections: "Header" with fields for "Created By", "Last Modified By", "Last Modification Date", "Module Name", "Description", and "Enabled"; "Administrator Comments" with an "Add Comment" text box and a "View Comments" button; and "Configure Access" with "Read-Only Access" and "Administrator Access" subsections.



The contents of the page may differ depending on the module chosen.

7. (Optional) In the **Header** section, update the data in the appropriate fields.
8. (Optional, although highly recommended) In the **Administrator Comments** section, add comments as desired.



Click **Save** before clicking **View Comments** to view the comments you just added.


9. In the **Configure Access** section, specify to whom, and the type of, access of the module should be granted.

10. Add Dashboard pages and portlets as desired.

a. To add a page, either:

- Select the **New Page** file from the folder containing the new module
- Select the module from the Modules folder and select either **Add > Add New Page** or **Add > Add user pages** (following a right-click).

The Personalize Dashboard page appears and includes the Edit page display.




b. (Optional) Rename the page.

c. (Optional) Set the page refresh rate.

d. Click **Add Portlets**.

The Add Portlets dialog box appears.



e. Search for portlets to add.

- To list all the portlets, click **Find Portlets**. The **Select Portlets to Add** section is added to the Add Portlets dialog. The **Select Portlets to Add** section lists all the portlets.

- To list specific portlets:
 - i. In **Category**, select the portlet's category from the drop-down list.
 - ii. In **Portlet Name**, provide all or part of the portlet's name.
 - iii. Click **Find Portlets**.

The **Select Portlets to Add** section is added to the Add Portlets dialog. The **Select Portlets to Add** section lists all of the portlets matching the search criteria.

- f. In the **Select Portlets to Add** section, select one or more portlets and click **Add**.
 - g. (Optional) Click **Preview** to review the results.
11. Repeat [step 10](#) until the module is configured as desired.



If your PPM Center instance supports multiple languages, any module you create is defined in the language you selected at logon (your session language). After the module is created, it can be modified only in its definition language. For more information, see *Multilingual User Interface Guide*.

Sharing Modules

To share a module:

1. Select the module name from the Modules folder.
2. In the Header section, select the **Yes** option for **Enabled**.
3. In the Configure Access section, select the **Allow access to all users** and **Enable users to copy this module pages to their private dashboard** checkboxes.
4. Click **Save**.

Copying Modules

To copy an existing module and use it as the basis for a new module:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Modules > Configure Modules**.

The Configure Modules page appears, as shown in [step 2 on page 140](#).

3. Search for and select a module.

For complete information on how to search for and select modules, see [Searching for Modules on page 140](#).

The Personalize Dashboard page appears, as shown in [step 6 on page 144](#).

4. Select the name of the module from the Modules folder.
5. Click the **Clone** icon (or right-click the module name and select **Clone**).

An advisory dialog box appears.

6. Click **OK**.

A copy of the module will appear in the Modules folder.

7. Select the name of the copied module.
8. Change the settings of the copied module using the steps detailed in [Creating Modules on page 143](#).



Remember to enable the module once the settings are updated.

9. Click **Save**.

Modifying Modules

To change an existing module:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Modules > Configure Modules**.

The Configure Modules page appears, as shown in [step 2 on page 140](#).

3. Search for and select a module.

For detailed instructions on how to search for and select modules, see [Searching for Modules on page 140](#).

The Personalize Dashboard page appears, as shown in [step 6 on page 144](#).

4. From this page, you can do the following:
 - Change the contents or accessibility of a module, see [Creating Modules on page 143](#).
 - Copy the module, see [Copying Modules on page 147](#).
 - Remove the module, see [Deleting Modules](#).



If your PPM Center instance supports multiple languages and the module is defined in a language other than your session language, you cannot modify the module. For more information click **here** in the header or see [Multilingual User Interface Guide](#).

Deleting Modules

To delete an existing module:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Modules > Configure Modules**.

The Configure Modules page appears, as shown in [step 2 on page 140](#).

3. Search for and select a module.

For complete information on how to search for and select modules, see [Searching for Modules on page 140](#).

The Personalize Dashboard page appears, as shown in [step 6 on page 144](#).

4. Select the name of the module from the Modules folder.
5. Click the **Delete** icon (or right-click the module name and select **Delete**).

A confirmation dialog box opens.

6. Click **OK**.

Configuring the Landing Page (Default PPM Dashboard Page)

The landing page is the default PPM Dashboard page that is configured to display when a user logs on to PPM Center. This page is configured by the application administrator to meet the business requirements of users or security groups.



If a default PPM Dashboard page is not configured, the first private page listed in the Private pages folder becomes the default page. If no private pages have been configured, the first shared page listed in the Shared pages folder becomes the default page.

To configure the default PPM Dashboard page you must set the landing page and configure the module's access:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Modules > Configure Default Dashboard Page**.

The Set Landing page appears.

3. Select the **Enable default Landing page** checkbox.
4. Select the name of the module that contains the default landing page.
5. Select the name of the page.
6. Click **Save**.

The message The Landing page has been successfully configured. In order to set the Landing Page users' access, configure the parent module's access appears above the Configure Landing Page section.

7. Click **configure the parent module's access**.

The Configure: *<module_name>* page appears.

8. Expand the Configure Access section and add read-only access for all users or selected users.
9. Click **Save**.

Changing the Landing Page

Changing the landing page is changing the default PPM Dashboard page that displays when a user logs on to PPM Center. For information on how to modify or edit the contents of the landing page, see the *Getting Started* Guide.

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Modules > Configure Default Dashboard Page**.

The Set Landing page appears.

3. Select the name of the module that contains the default landing page.
4. Select the name of the page.
5. Click **Save**.

The message `The Landing page has been successfully configured. In order to set the Landing Page users' access, configure the parent module's access appears above the Configure Landing Page section.`

6. Click **configure the parent module's access**.

The Configure: `<module_name>` page appears.

7. Expand the Configure Access section and add read-only access for all users or selected users.
8. Click **Save**.

Disabling the Landing Page

You can disable the landing page by either disabling the feature or by disabling the module's access. When the landing page is disabled, the first page listed in the Private pages folder becomes the default PPM Dashboard page. If no private pages are configured, the first page listed in the Shared pages folder becomes the default PPM Dashboard page.

To disable the landing page without changing the module's access:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Modules > Configure Default Dashboard Page**. The Set Landing page appears.
3. Unselect the **Enable default Landing page** checkbox.
4. Click **Save**.

To disable the landing page by disabling the module's access:

1. Log on to PPM Center.
2. From the menu bar, select **Open > Administration > Modules > Configure Default Dashboard Page**. The Set Landing page appears.
3. Click **Save**.

The message `The Landing page has been successfully configured. In order to set the Landing Page users' access, configure the parent module's access` appears above the **Configure Landing Page** section.

4. Click **configure the parent module's access**.

The **Configure: <module_name>** page appears.

5. Expand the **Configure Access** section and remove read-only access for all users or selected users.
6. Click **Save**.

A Color Names

This appendix provides the table of color names that are supported by most browsers. These are the color names referenced in *Selecting Portlet Colors* on page 131.

It is important to note that only 16 color names are supported in the W3C HTML 4.0 standard (aqua, black, blue, fuchsia, gray, green, lime, maroon, navy, olive, purple, red, silver, teal, white, and yellow). If you have concerns about browser compatibility, or are planning to export the portlet, you should use the hexadecimal values rather than the color names.

To view the colors themselves, go to www.w3.org/TR/css3-color/#html4 and locate the section documenting SVG color keywords.

Table A-1. Color names (page 1 of 7)

Color Name	Hex Value
AliceBlue	#F0F8FF
AntiqueWhite	#FAEBD7
Aqua	#00FFFF
Aquamarine	#7FFFD4
Azure	#F0FFFF
Beige	#F5F5DC
Bisque	#FFE4C4
Black	#000000
BlanchedAlmond	#FFEBCD

Table A-1. Color names (page 2 of 7)

Color Name	Hex Value
Blue	#0000FF
BlueViolet	#8A2BE2
Brown	#A52A2A
BurlyWood	#DEB887
CadetBlue	#5F9EA0
Chartreuse	#7FFF00
Chocolate	#D2691E
Coral	#FF7F50
CornflowerBlue	#6495ED
Cornsilk	#FFF8DC
Crimson	#DC143C
Cyan	#00FFFF
DarkBlue	#00008B
DarkCyan	#008B8B
DarkGoldenrod	#B8860B
DarkGray	#A9A9A9
DarkGreen	#006400
DarkKhaki	#BDB76B
DarkMagenta	#8B008B
DarkOliveGreen	#556B2F
DarkOrange	#FF8C00
DarkOrchid	#9932CC
DarkRed	#8B0000
DarkSalmon	#E9967A

Table A-1. Color names (page 3 of 7)

Color Name	Hex Value
DarkSeaGreen	#8FBC8F
DarkSlateBlue	#483D8B
DarkSlateGray	#2F4F4F
DarkTurquoise	#00CED1
DarkViolet	#9400D3
DeepPink	#FF1493
DeepSkyBlue	#00BFFF
DimGray	#696969
DodgerBlue	#1E90FF
Feldspar	#D19275
FireBrick	#B22222
FloralWhite	#FFFAF0
ForestGreen	#228B22
Fuchsia	#FF00FF
Gainsboro	#DCDCDC
GhostWhite	#F8F8FF
Gold	#FFD700
GoldenRod	#DAA520
Gray	#808080
Green	#008000
GreenYellow	#ADFF2F
HoneyDew	#F0FFF0
HotPink	#FF69B4
IndianRed	#CD5C5C

Table A-1. Color names (page 4 of 7)

Color Name	Hex Value
Indigo	#4B0082
Ivory	#FFFFFF0
Khaki	#F0E68C
Lavender	#E6E6FA
LavenderBlush	#FFF0F5
LawnGreen	#7CFC00
LemonChiffon	#FFFACD
LightBlue	#ADD8E6
LightCoral	#F08080
LightCyan	#E0FFFF
LightGoldenrodYellow	#FAFAD2
LightGrey	#D3D3D3
LightGreen	#90EE90
LightPink	#FFB6C1
LightSalmon	#FFA07A
LightSeaGreen	#20B2AA
LightSkyBlue	#87CEFA
LightSlateBlue	#8470FF
LightSlateGray	#778899
LightSteelBlue	#B0C4DE
LightYellow	#FFFFE0
Lime	#00FF00
LimeGreen	#32CD32
Linen	#FAF0E6

Table A-1. Color names (page 5 of 7)

Color Name	Hex Value
Magenta	#FF00FF
Maroon	#800000
MediumAquaMarine	#66CDAA
MediumBlue	#0000CD
MediumOrchid	#BA55D3
MediumPurple	#9370D8
MediumSeaGreen	#3CB371
MediumSlateBlue	#7B68EE
MediumSpringGreen	#00FA9A
MediumTurquoise	#48D1CC
MediumVioletRed	#C71585
MidnightBlue	#191970
MintCream	#F5FFFA
MistyRose	#FFE4E1
Moccasin	#FFE4B5
NavajoWhite	#FFDEAD
Navy	#000080
OldLace	#FDF5E6
Olive	#808000
OliveDrab	#6B8E23
Orange	#FFA500
OrangeRed	#FF4500
Orchid	#DA70D6
PaleGoldenrod	#EEE8AA

Table A-1. Color names (page 6 of 7)

Color Name	Hex Value
PaleGreen	#98FB98
PaleTurquoise	#AFEEEE
PaleVioletRed	#D87093
PapayaWhip	#FFEFD5
PeachPuff	#FFDAB9
Peru	#CD853F
Pink	#FFC0CB
Plum	#DDA0DD
PowderBlue	#B0E0E6
Purple	#800080
Red	#FF0000
RosyBrown	#BC8F8F
RoyalBlue	#4169E1
SaddleBrown	#8B4513
Salmon	#FA8072
SandyBrown	#F4A460
SeaGreen	#2E8B57
SeaShell	#FFF5EE
Sienna	#A0522D
Silver	#C0C0C0
SkyBlue	#87CEEB
SlateBlue	#6A5ACD
SlateGray	#708090
Snow	#FFFAFA

Table A-1. Color names (page 7 of 7)

Color Name	Hex Value
SpringGreen	#00FF7F
SteelBlue	#4682B4
Tan	#D2B48C
Teal	#008080
Thistle	#D8BFD8
Tomato	#FF6347
Turquoise	#40E0D0
Violet	#EE82EE
VioletRed	#D02090
Wheat	#F5DEB3
White	#FFFFFF
WhiteSmoke	#F5F5F5
Yellow	#FFFF00
YellowGreen	#9ACD32

Index

- A**
 - access grants
 - Edit Portlet Definition, [36](#)
 - Ownership Override, [36](#)
 - adding
 - list portlet columns, [100](#)
 - pivot table portlet data columns, [110](#), [112](#)
 - portlet categories, [96](#)
 - application administrator-provided
 - preconfigured Dashboard pages, [138](#)
- B**
 - bar chart portlet, [113](#)
 - display options, [113](#)
 - bind variables, [25](#)
 - bubble chart portlet, [129](#)
 - display options, [129](#)
 - builder portlets, [47](#), [49](#)
- C**
 - changing
 - default Dashboard page, [151](#)
 - landing Dashboard page, [151](#)
 - clustered bar chart portlet, [115](#)
 - display options, [115](#)
 - color map
 - defining in portlet data sources, [131](#)
 - selecting in portlet definitions, [134](#)
- colors
 - hexadecimal values, [153](#)
 - names, [153](#)
- configuring
 - default Dashboard page, [150](#)
 - landing Dashboard page, [150](#)
- copying
 - modules, [147](#)
 - portlet data sources, [37](#)
 - portlet definitions, [64](#)
- Create Portlet Definition wizard, [53](#)
- creating
 - modules, [143](#)
 - portlet data sources, [21](#)
 - portlet definitions, [53](#)
 - portlets, [15](#)
- D**
 - Dashboard, [13](#)
 - Dashboard pages, [13](#)
 - administrator-provided, [138](#)
 - changing the default, [151](#)
 - configuring a default, [150](#)
 - default, [139](#)
 - disabling the default, [152](#)
 - HP-provided, [137](#)
 - landing, [139](#)
 - preconfigured, [137](#)
 - shared, [139](#)

- Data Source tab
 - portlet data sources, [25](#)
- default Dashboard page, [139](#)
 - changing, [151](#)
 - configuring, [150](#)
 - disabling, [152](#)
- defining
 - drill-down pages, [78](#), [80](#)
 - portlet data source color map, [131](#)
 - portlet events, [94](#)
- deleting
 - list portlet columns, [107](#)
 - modules, [149](#)
 - portlet categories, [97](#)
 - portlet data sources, [39](#)
 - portlet definitions, [68](#)
- disabling
 - default Dashboard page, [152](#)
 - landing Dashboard page, [152](#)
- display options
 - bar chart portlet, [113](#)
 - bubble chart portlet, [129](#)
 - clustered bar chart portlet, [115](#)
 - line chart portlet, [122](#)
 - list portlet, [99](#)
 - pie chart portlet, [120](#)
 - pivot table portlet, [108](#)
 - radar line chart portlet, [127](#)
 - scatter line chart portlet, [124](#)
 - spider line chart portlet, [127](#)
 - stacked bar chart portlet, [118](#)
 - XY line chart portlet, [124](#)
- drill-down pages
 - defining, [78](#), [80](#)

E

- editing
 - list portlet columns, [106](#)

F

- Filter clause, [29](#)
- Filter Fields tab
 - portlet data sources, [33](#)
- From clause, [27](#)

G

- Group By clause, [32](#)

H

- Having clause, [33](#)
- HP-provided preconfigured Dashboard pages, [137](#)

I

- Import Portlet Definition wizard, [69](#), [73](#)
- importing
 - Java portlet definitions, [69](#)
 - WSRP portlet definitions, [73](#)

J

- Java portlet definitions, [49](#), [69](#)
- Java portlets, [14](#), [47](#)

L

- landing Dashboard page, [139](#)
 - changing, [151](#)
 - configuring, [150](#)
 - disabling, [152](#)
- line chart portlets, [122](#)
 - display options, [122](#)
 - display options for radar, [127](#)
 - display options for scatter, [124](#)
 - display options for spider, [127](#)
 - display options for XY, [124](#)
 - radar, [127](#)
 - scatter, [124](#)
 - spider, [127](#)
 - XY, [124](#)

- list portlet, **98**
 - adding columns, **100**
 - deleting columns, **107**
 - display options, **99**
 - editing columns, **106**

M

- managing
 - portlet categories, **96**
- migrating
 - portlet definitions, **77**
- modifying
 - modules, **148**
 - portlet definitions, **65**
- modules, **13, 137**
 - copying, **147**
 - creating, **143**
 - deleting, **149**
 - modifying, **148**
 - searching, **140**
 - sharing, **146**

O

- opening
 - Create Portlet Definition wizard, **53**
 - Import Portlet Definition wizard, **69**
- Order By clause, **32**
- Ownership tab
 - portlet data sources, **36**

P

- pie chart portlet, **120**
 - display options, **120**
- pivot table portlet, **107**
 - adding data columns, **110, 112**
 - display options, **108**
- portlet categories
 - adding, **96**
 - deleting, **97**
 - managing, **96**

- portlet data sources, **14**
 - color map, **131**
 - column types, **41**
 - components, **17**
 - copying, **37**
 - creating, **21**
 - currency column type, **45**
 - Data Source tab, **25**
 - deleting, **39**
 - Filter clause, **29**
 - Filter Fields tab, **33**
 - From clause, **27**
 - general information section, **24**
 - Group By clause, **32**
 - Group By/Order By tab, **32**
 - Having clause, **33**
 - hyperlink column type, **43**
 - Order By clause, **32**
 - overview of, **17**
 - Ownership tab, **36**
 - relationship to portlet definitions, **18**
 - searching for, **19**
 - Select statement, **27**
 - Select/From tab, **27**
 - text-based column type, **41**
 - viewing, **19**
 - Where clause, **29**
 - Where/Filter tab, **29**
- portlet definitions, **14, 47**
 - builder portlets, **49**
 - color map, **134**
 - configuring access, **61**
 - copying, **64**
 - Create Portlet Definition wizard, **53**
 - creating, **53**
 - deleting, **68**
 - display options, **56**
 - drill-down pages, **78**
 - HP-imported, **49**
 - HP-supplied, **48**
 - Import Portlet Definition wizard, **69, 73**
 - importing Java portlets, **69**
 - importing WSRP portlets, **73**
 - Java portlets, **49**

- migrating, [77](#)
- modifying, [65](#)
- portlet communication, [60](#)
- portlet information, [54](#)
- portlet types, [53](#)
- preferences, [57](#)
- relationship to portlet data sources, [18](#)
- searching for, [50](#)
- standard, [49](#)
- user help, [63](#)
- viewing, [40](#)
- WSRP portlets, [49](#)

portlet types

- bar chart portlet, [113](#)
- bubble chart portlet, [129](#)
- clustered bar chart portlet, [115](#)
- line chart portlet, [122](#)
- list portlet, [98](#)
- pie chart portlet, [120](#)
- pivot table portlet, [107](#)
- portlet definitions, [53](#)
- radar line chart portlet, [127](#)
- scatter line chart portlet, [124](#)
- spider line chart portlet, [127](#)
- stacked bar chart portlet, [118](#)
- XY line chart portlet, [124](#)

portlets, [13](#)

- See also* portlet categories.
- See also* portlet data sources.
- See also* portlet definitions.
- See also* portlet types.
- builder, [47](#)
- creating, [15](#)
- Java, [14](#), [47](#)
- selecting colors, [131](#)
- support, [14](#)
- WSRP, [14](#), [47](#)

preconfigured Dashboard pages, [137](#)

- administrator-provided, [138](#)
- HP-provided, [137](#)

S

- searching
 - for modules, [140](#)
 - for portlet data sources, [19](#)
 - for portlet definitions, [50](#)
- Select statement, [27](#)
- selecting
 - portlet colors, [131](#)
 - portlet definition color map, [134](#)
- shared Dashboard pages, [139](#)
- sharing
 - modules, [146](#)
- stacked bar chart portlet, [118](#)
 - display options, [118](#)
- standard portlet definitions, [49](#)

V

- variables, bind, [25](#)
- viewing
 - portlet data sources, [19](#)
 - portlet definitions, [40](#)

W

- Where clause, [29](#)
- wizards
 - Create Portlet Definition, [53](#)
 - Import Portlet Definition, [69](#), [73](#)
- WSRP portlet definitions, [49](#), [73](#)
- WSRP portlets, [14](#), [47](#)